




Quick Connectors



Climate Control
Electromechanical
Filtration
Fluid & Gas Handling
Hydraulics
Process Control
Sealing & Shielding



VFK
Advanced Fluid Control

Contents

91C Series



01

91F Series



08

91V Series



12


91C Series

Features

- Maximum working pressure: 3000 psig (207 bar)
- Working temperatures:
 - 10°F to 400°F (-23°C to 204°C) with Fluorocarbon FKM seal
 - 10°F to 250°F (-23°C to 121°C) with Buna N seal
- Materials: stainless steel or brass
- Reliable, leak-tight O-ring seal for vacuum or pressure systems.
- Interchangeable with other main brands.


Single-end Shutoff (SESO)

SESO stem + body




Double-end Shutoff (DESO)

DESO stem + body



Full-flow Quick-connects

SESO stem + full-flow body



Pressure-Temperature Ratings

Temperature °F (°C)	Stainless Steel with FKM O-ring			Brass with Buna N O-ring		
	91C4	91C6	91C8	91C4	91C6	91C8
	pressure rating, psig (bar)					
70 (20)	3000 (207)	1500 (103)	750 (51.6)	2000 (137)	1000 (68.9)	500 (34.4)
250 (121)	—			250 (17.2)		
400 (204)	250 (17.2)			—		

Insertion Depth and Maximum Flow Rate

Series	Insertion Depth		Max. Flow Rate at 70°F (20°C)	
	SESO	DESO		
	in. (mm)	in. (mm)	U.S. gal/min	L/min
91C4	1.09 (27.7)	1.15 (29.2)	4.0	15.0
91C6	1.18 (30.0)	1.30 (33.0)	6.0	22.0
91C8	1.48 (37.6)	1.68 (42.7)	10.0	37.0


In order to measure overall length in the coupled position, the insertion depth should be deducted from any overall stem and body combination length.

Cautions:

- Do not uncouple single-end shutoff quick-connects under pressure.
- Do not insert foreign object into uncoupled stems and bodies.
- Re-lubricate stem seal O-ring periodically.


SESO Stems

Tube Fitting




Tube Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
in.			in.	in. (mm)
1/8	-91C4-FX2-S	0.08	5/8	2.32 (58.9)
1/4	-91C4-FX4-S	0.3	5/8	2.36 (59.9)
3/8	-91C6-FX6-S	1.0	3/4	2.52 (64.0)
1/2	-91C8-FX8-S	2.4	15/16	2.96 (75.2)
mm			mm	mm (in.)
6	-91C4-MX6-S	0.3	16	59.9 (2.36)
10	-91C6-MX10-S	1.0	19	67.3 (2.65)
12	-91C8-MX12-S	2.4	24	75.2 (2.96)

Male NPT




NPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/8	-91C4-N2-S	0.3	5/8	2.07 (52.6)
1/4	-91C4-N4-S	0.3	5/8	2.22 (56.4)
1/4	-91C6-N4-S	0.8	3/4	2.32 (58.9)
3/8	-91C6-N6-S	0.8	3/4	2.35 (59.7)
1/2	-91C8-N8-S	2.0	15/16	2.84 (72.1)

Female NPT




NPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/8	-91C4-FN2-S	0.3	5/8	2.01 (51.1)
1/4	-91C4-FN4-S	0.3	3/4	2.26 (57.4)
1/4	-91C6-FN4-S	0.8	3/4	2.35 (59.7)
3/8	-91C6-FN6-S	0.8	7/8	2.35 (59.7)
1/2	-91C8-FN8-S	2.0	1 1/16	2.82 (71.6)

Male BSPT




BSPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/8	-91C4-R2-S	0.3	5/8	2.07 (52.6)
1/4	-91C4-R4-S	0.3	5/8	2.22 (56.4)
1/4	-91C6-R4-S	0.8	3/4	2.32 (58.9)
3/8	-91C6-R6-S	0.8	3/4	2.35 (59.7)
1/2	-91C8-R8-S	2.0	15/16	2.84 (72.1)

Female BSPT



BSPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/8	-91C4-FR2-S	0.3	5/8	2.01 (51.1)
1/4	-91C4-FR4-S	0.3	3/4	2.26 (57.4)
1/4	-91C6-FR4-S	0.8	3/4	2.35 (59.7)
3/8	-91C6-FR6-S	0.8	7/8	2.35 (59.7)
1/2	-91C8-FR8-S	2.0	1 1/16	2.82 (71.6)


Male JIC(AN) 37° Flare



AN Tube Flare Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
in.			in.	in. (mm)
1/4	-91C4-AN4-S	0.2	5/8	2.23 (56.6)
3/8	-91C6-AN6-S	1.0	3/4	2.35 (59.7)
1/2	-91C8-AN8-S	2.4	15/16	2.79 (70.9)


SESO Stems

Hose Connector



Hose Size in.	Basic Ordering Number	Flow Coefficient (Cv)	F in.	L in. (mm)
1/4	-91C4-HC4-S	0.2	5/8	2.47 (62.7)
3/8	-91C6-HC6-S	1.0	3/4	2.66 (67.6)
1/2	-91C8-HC8-S	2.4	15/16	3.07 (78.0)


Bulkhead Tube Fitting



Tube Size in.	Basic Ordering Number	Flow Coefficient (Cv)	F in.	L in. (mm)	Min. Panel Hole in. (mm)	Max. Panel Thickness in. (mm)
1/4	-91C4-FX4-SS	0.3	5/8	2.74 (69.6)	0.47 (11.9)	0.25 (6.4)
3/8	-91C6-FX6-SS	1.0	3/4	2.92 (74.2)	0.60 (15.2)	0.27 (6.9)
1/2	-91C8-FX8-SS	2.4	15/16	3.43 (87.1)	0.78 (19.8)	0.26 (6.6)
mm	——	——	mm	mm (in.)	mm (in.)	mm (in.)
6	-91C4-MX6-SS	0.3	16	69.6 (2.74)	11.7 (0.46)	6.4 (0.25)
10	-91C6-MX10-SS	1.0	22	77.7 (3.06)	16.8 (0.66)	6.9 (0.27)
12	-91C8-MX12-SS	2.4	24	87.1 (3.43)	19.6 (0.77)	6.6 (0.26)


DESO Stems

Tube Fitting




Tube Size in.	Basic Ordering Number	Flow Coefficient (Cv)	F in.	L in. (mm)
1/8	-91C4-FX2-D	0.08	5/8	2.77 (70.4)
1/4	-91C4-FX4-D	0.2	5/8	2.42 (61.5)
3/8	-91C6-FX6-D	0.5	3/4	2.64 (67.1)
1/2	-91C8-FX8-D	1.5	15/16	3.16 (80.3)
mm	——	——	mm	mm (in.)
6	-91C4-MX6-D	0.2	16	61.5 (2.42)
10	-91C6-MX10-D	0.5	19	70.4 (2.77)
12	-91C8-MX12-D	1.5	24	80.3 (3.16)

Male NPT



NPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F in.	L in.(mm)
1/8	-91C4-N2-D	0.2	5/8	2.13 (54.1)
1/4	-91C4-N4-D	0.2	5/8	2.28 (57.8)
1/4	-91C6-N4-D	0.5	3/4	2.44 (61.9)
3/8	-91C6-N6-D	0.5	3/4	2.47 (62.7)
1/2	-91C8-N8-D	1.3	15/16	3.04 (77.2)


Female NPT



NPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F in.	L in. (mm)
1/8	-91C4-FN2-D	0.2	5/8	2.07 (52.6)
1/4	-91C4-FN4-D	0.2	3/4	2.32 (58.9)
1/4	-91C6-FN4-D	0.5	3/4	2.47 (62.7)
3/8	-91C6-FN6-D	0.5	7/8	2.47 (62.7)
1/2	-91C8-FN8-D	1.3	1 1/16	3.04 (77.2)


DESO Stems

Male BSPT




BSPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/8	-91C4-R2-D	0.2	5/8	2.13 (54.1)
1/4	-914-R4-D	0.2	5/8	2.28 (57.8)
1/4	-916-R4-D	0.5	3/4	2.44 (61.9)
3/8	-916-R6-D	0.5	3/4	2.47 (62.7)
1/2	-918-R8-D	1.3	15/16	3.04 (77.2)

Female BSPT




BSPT Size	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/8	-91C4-FR2-D	0.2	5/8	2.07 (52.6)
1/4	-91C4-FR4-D	0.2	3/4	2.32 (58.9)
1/4	-91C6-FR4-D	0.5	3/4	2.47 (62.7)
3/8	-91C6-FR6-D	0.5	7/8	2.47 (62.7)
1/2	-91C8-FR8-D	1.3	1 1/16	3.04 (77.2)

Male JIC(AN) 37° Flare




AN Tube Flare Size in.	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/4	-91C4-AN4-D	0.2	5/8	2.29 (58.2)
3/8	-91C6-AN6-D	0.5	3/4	2.47 (62.7)
1/2	-91C8-AN8-D	1.5	15/16	2.99 (75.9)

Hose Connector



Hose Size in.	Basic Ordering Number	Flow Coefficient (Cv)	F	L
			in.	in. (mm)
1/4	-91C4-HC4-D	0.2	5/8	2.53 (64.3)
3/8	-91C6-HC6-D	0.5	3/4	2.78 (70.6)
1/2	-91C8-HC8-D	1.5	15/16	3.27 (83.1)


Bulkhead Tube Fitting



Tube Size in.	Basic Ordering Number	Flow Coefficient (Cv)	F	L	Min. Panel Hole in. (mm)	Max. Panel Thickness in. (mm)
			in.	in. (mm)		
1/4	-91C4-FX4-DS	0.2	5/8	2.80 (71.1)	0.47 (11.9)	0.25 (6.4)
3/8	-91C6-FX6-DS	0.5	3/4	3.07 (78.0)	0.60 (15.2)	0.27 (6.9)
1/2	-91C8-FX8-DS	1.5	15/16	3.63 (92.2)	0.78 (19.8)	0.26 (6.6)
mm			mm	mm (in.)	mm (in.)	mm (in.)
6	-91C4-MX6-DS	0.2	16	71.1 (2.80)	11.7 (0.46)	6.4 (0.25)
10	-91C6-MX10-DS	0.5	22	78.7 (3.10)	16.8 (0.66)	6.9 (0.27)
12	-91C8-MX12-DS	1.5	24	92.2 (3.63)	19.6 (0.77)	6.6 (0.26)


Bodies

Tube Fitting




Tube Size	Basic Ordering Number	H	L
in.		in. (mm)	in. (mm)
1/8	-91C4-FX2-B	0.91 (23.1)	2.26 (57.4)
1/4	-91C4-FX4-B	0.91 (23.1)	2.30 (58.4)
3/8	-91C6-FX6-B	1.03 (26.2)	2.58 (65.5)
1/2	-91C8-FX8-B	1.21 (30.7)	3.09 (78.5)
mm		mm (in.)	mm (in.)
6	-91C4-MX6-B	23.1 (0.91)	58.4 (2.30)
10	-91C6-MX10-B	26.2 (1.03)	68.1 (2.68)
12	-91C8-MX12-B	30.7 (1.21)	78.5 (3.09)

Male NPT




NPT Size	Basic Ordering Number	H	L
		in. (mm)	in. (mm)
1/8	-91C4-N2-B	0.91 (23.1)	2.01 (51.1)
1/4	-91C4-N4-B	0.91 (23.1)	2.16 (54.9)
1/4	-91C6-N4-B	1.03 (26.2)	2.38 (60.5)
3/8	-91C6-N6-B	1.03 (26.2)	2.38 (60.5)
1/2	-91C8-N8-B	1.21 (30.7)	2.97 (75.4)

Female NPT




NPT Size	Basic Ordering Number	H	L
		in. (mm)	in. (mm)
1/8	-91C4-FN2-B	0.91 (23.1)	2.16 (54.9)
1/4	-91C4-FN4-B	0.91 (23.1)	2.42 (61.5)
1/4	-91C6-FN4-B	1.03 (26.2)	2.54 (65.4)
3/8	-91C6-FN6-B	1.03 (26.2)	2.57 (65.3)
1/2	-91C8-FN8-B	1.21 (30.7)	3.22 (81.8)

Male BSPT




BSPT Size	Basic Ordering Number	H	L
		in. (mm)	in. (mm)
1/8	-91C4-R2-B	0.91 (23.1)	2.01 (51.1)
1/4	-91C4-R4-B	0.91 (23.1)	2.16 (54.9)
1/4	-91C6-R4-B	1.03 (26.2)	2.38 (60.5)
3/8	-91C6-R6-B	1.03 (26.2)	2.38 (60.5)
1/2	-91C8-R8-B	1.21 (30.7)	2.97 (75.4)

Female BSPT



BSPT Size	Basic Ordering Number	H	L
		in. (mm)	in. (mm)
1/8	-91C4-FR2-B	0.91 (23.1)	2.16 (54.9)
1/4	-91C4-FR4-B	0.91 (23.1)	2.42 (61.5)
1/4	-91C6-FR4-B	1.03 (26.2)	2.54 (65.4)
3/8	-91C6-FR6-B	1.03 (26.2)	2.57 (65.3)
1/2	-91C8-FR8-B	1.21 (30.7)	3.22 (81.8)


Male JIC (AN) 37° Flare



AN Tube Flare Size	Basic Ordering Number	H	L
in.		in. (mm)	in. (mm)
1/4	-91C4-AN4-B	0.91 (23.1)	2.17 (55.1)
3/8	-91C6-AN6-B	1.03 (26.2)	2.41 (61.2)
1/2	-91C8-AN8-B	1.21 (30.7)	2.92 (74.2)


Bodies

Hose Connector



Hose Size in.	Basic Ordering Number	Flow Coefficient (Cv)	H in. (mm)	L in. (mm)
1/4	-91C4-HC4-B	0.3	0.91 (23.1)	2.41 (61.2)
3/8	-91C6-HC6-B	1.5	1.03 (26.2)	2.72 (69.1)
1/2	-91C8-HC8-B	3.3	1.21 (30.7)	3.20 (81.3)

Bulkhead Tube Fitting



Tube Size in.	Basic Ordering Number	Flow Coefficient (Cv)	H in. (mm)	L in. (mm)	Min. Panel Hole in. (mm)	Max. Panel Thickness in. (mm)
1/4	-91C4-FX4-BS	0.4	0.91 (23.1)	2.67 (67.8)	0.47 (11.9)	0.25 (6.4)
3/8	-91C6-FX6-BS	1.5	1.03 (26.2)	2.98 (75.7)	0.60 (15.2)	0.27 (6.9)
1/2	-91C8-FX8-BS	3.3	1.21 (30.7)	3.56 (90.4)	0.78 (19.8)	0.26 (6.6)
mm			mm (in.)	mm (in.)	mm (in.)	mm (in.)
6	-91C4-MX6-BS	0.4	23.1 (0.91)	67.8 (2.67)	11.7 (0.46)	6.4 (0.25)
10	-91C6-MX10-BS	1.5	26.2 (1.03)	75.9 (2.99)	16.8 (0.66)	6.9 (0.27)
12	-91C8-MX12-BS	3.3	30.7 (1.21)	90.4 (3.56)	19.6 (0.77)	6.6 (0.26)


Keyed QC Series

VFK keyed quick-connects provide a positive mechanical lockout system to prevent accidental intermixing of different lines in multifluid or multipressure systems.

QC Series Key Numbers and Sleeve Outside Diameters


Key Number and Color	QC4		QC6		QC8	
	Body Sleeve	Stem Sleeve	Body Sleeve	Stem Sleeve	Body Sleeve	Stem Sleeve
	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)	in. (mm)
K1 black	0.96 (24.4)	0.82 (20.8)	1.13 (28.7)	0.99 (25.1)	1.26 (32.0)	1.10 (27.9)
K2 orange	0.99 (25.1)	0.85 (21.6)	1.16 (29.5)	1.02 (25.9)	1.29 (32.8)	1.14 (29.0)
K3 green	1.02 (25.9)	0.88 (22.4)	1.19 (30.2)	1.05 (26.7)	1.32 (33.5)	1.17 (29.7)
K4 yellow	1.05 (26.7)	0.91 (23.1)	1.22 (31.0)	1.08 (27.4)	1.35 (34.3)	1.20 (30.5)
K5 blue	1.08 (27.4)	0.94 (23.9)	1.24 (31.5)	1.11 (28.2)	1.38 (35.1)	1.23 (31.2)
K6 white	1.11 (28.2)	0.97 (24.6)	1.28 (32.5)	1.14 (29.0)	1.41 (35.8)	1.26 (32.0)
K7 purple	1.14 (29.0)	1.00 (25.4)	1.31 (33.3)	1.17 (29.7)	1.44 (36.6)	1.29 (32.8)
K8 brown	1.17 (29.7)	1.03 (26.2)	1.34 (34.0)	1.20 (30.5)	1.47 (37.3)	1.32 (33.5)

Stem Protector



Series	Basic Ordering Number
91C4	-91C4-SP
91C6	-91C6-SP
91C8	-91C8-SP

Body Protector



Series	Basic Ordering Number
91C4	-91C4-BP
91C6	-91C6-BP
91C8	-91C8-BP

- To order a protector, add material designator (SS for stainless steel or B for brass) as a prefix to the basic ordering number.
Example: SS91C4-BP
- To order a keyed protector, add material designator (SS for stainless steel or B for brass) as a prefix and key designator from the table below as a suffix to the ordering number.
Example: SS91C4-BP-K2


91 Series How to Order

SS — 91C4 — FX4 — S — K1

Material	Series	Size	End Connection Type	End Connection Size	Stem or Body	Key number and color
SS 316SS	91C	4 1/4" (6.4 mm)	FN Female NPT	4 1/4 (in.)	S Stem without valve remains open when uncoupled	K1 Black
B Brass		6 3/8" (9.5 mm)	N Male NPT	6 3/8 (in.) or 6 mm	D Stem with valve shuts off when uncoupled	K2 Orange
S4 304SS		8 1/2" (12.7 mm)	FR Female BSPT	8 1/2 (in.) or 8 mm	B Body with valve shuts off when uncoupled	K3 Green
CS Carbon Steel			R Male BSPT	10 5/8 (in.) or 10 mm	BF Full-flow body	K4 Yellow
			FM Female ISO (for RP)	12 3/4 (in.) or 12 mm		K5 Blue
			M Male ISO (for RG)	14 M14 x 1.5		K6 White
			FX Fractional Tube Fitting	16 1 (in.) or 16 mm		K7 Purple
			MX Metric Tube Fitting	18 M18 x 1.5		K8 Brown
			FT Fractional Tube Adapter	20 M20 x 1.5		
			MT Metric Tube Adapter			
			AN Male JIC 37° Flare			

- Sizes and types listed are standard. Other sizes and types are available on request.
- Dimensions are for reference only and are subject to change.

91F Series



Features

- Full flow
- Quick, easy operation
- Maximum working pressure: 6000 psig (414 bar)
- Materials: stainless steel, carbon steel, and brass
- Smooth, open bores without valving on either end to minimize pressure drop and allow easy cleaning.

Pressure-Temperature Ratings

Temperature °F (°C)	Stainless Steel with FKM O-ring				Brass with Buna N O-ring				Carbon Steel with Buna N O-ring			
	91F4	91F8	91F12	91F16	91F4	91F8	91F12	91F16	91F4	91F8	91F12	91F16
	pressure rating, psig (bar)											
70 (20)	6000 (414)		4000 (275)		4000 (275)	3000 (207)	2000 (137)		4000 (275)	3000 (207)		
250 (121)	—				100 (6.9)				100 (6.9)			
400 (204)	100 (6.9)				—				—			


Insert Depth

Series	Insert Depth in. (mm)
91F4	0.78 (19.8)
91F8	0.81 (20.6)
91F12	0.90 (22.9)
91F16	0.94 (23.9)

In order to measure overall length in the coupled position, insertion depth should be deducted from any overall stem and body combination length.

Stems

Tube Fitting




Tube Size in.	Basic Ordering Number	Flow Coefficient (Cv)	E in. (mm)	F in.	L in. (mm)
1/4	-91F4-FX4-S	2.2	0.19 (4.8)	9/16	1.77 (45.0)
3/8	-91F4-FX6-S	2.8	0.24 (6.1)	11/16	1.77 (45.0)
3/8	-91F8-FX6-S	2.8	0.28 (7.1)	7/8	1.88 (47.8)
1/2	-91F8-FX8-S	13.0	0.41 (10.4)	7/8	1.99 (50.5)
3/4	-91F12-FX12-S	26.0	0.62 (15.7)	1 1/16	2.15 (54.6)
1	-91F16-FX16-S	45.0	0.88 (22.4)	1 3/8	2.45 (62.2)
mm	—	—	(mm) in.	mm	(mm) in.
6	-91F4-MX6-S	2.2	4.8 (0.19)	15	45.0 (1.77)
10	-91F8-MX10-S	2.8	7.1 (0.28)	22	48.5 (1.91)
12	-91F8-MX12-S	13.0	9.5 (0.37)	22	51.3 (2.02)
20	-91F12-MX20-S	26.0	15.7 (0.62)	30	54.6 (2.15)
25	-91F16-MX25-S	45.0	22.4 (0.88)	36	63.5 (2.50)

Cautions:

- Do not uncouple under pressure.
- Do not insert foreign object into uncoupled stems and bodies.
- Re-lubricate stem seal O-ring periodically.


Stems

Male NPT




NPT Size	Basic Ordering Number	Flow Coefficient (Cv)	E	F	L
			in. (mm)	in.	in. (mm)
1/4	-91F4-N4-S	1.7	0.24 (6.1)	9/16	1.59 (40.4)
3/8	-91F4-N6-S	1.7	0.24 (6.1)	11/16	1.59 (40.4)
3/8	-91F8-N6-S	7.1	0.41 (10.4)	7/8	1.65 (41.9)
1/2	-91F8-N8-S	11.5	0.50 (12.7)	7/8	1.84 (46.7)
3/4	-91F12-N12-S	23.6	0.72 (18.3)	1 1/16	2.03 (51.6)
1	-91F16-N16-S	39.0	0.88 (22.4)	1 3/8	2.35 (59.7)

Female NPT




NPT Size	Basic Ordering Number	Flow Coefficient (Cv)	E	F	L
			in. (mm)	in.	in. (mm)
1/4	-91F4-FN4-S	1.7	0.24 (6.1)	3/4	1.60 (40.6)
3/8	-91F4-FN6-S	1.7	0.24 (6.1)	7/8	1.67 (42.4)
3/8	-91F8-FN6-S	7.1	0.41 (10.4)	1 1/16	1.59 (40.4)
1/2	-91F8-FN8-S	11.5	0.50 (12.7)	1 1/16	1.82 (46.2)
3/4	-91F12-FN12-S	23.6	0.72 (18.3)	1 5/16	2.08 (52.8)
1	-91F16-FN16-S	39.0	0.88 (22.4)	1 5/8	2.49 (63.2)

Male BSPT



BSPT Size	Basic Ordering Number	Flow Coefficient (Cv)	E	F	L
			in. (mm)	in.	in. (mm)
1/4	-91F4-R4-S	1.7	0.24 (6.1)	9/16	1.59 (40.4)
3/8	-91F4-R6-S	1.7	0.24 (6.1)	11/16	1.59 (40.4)
3/8	-91F8-R6-S	7.1	0.41 (10.4)	7/8	1.65 (41.9)
1/2	-91F8-R8-S	11.5	0.50 (12.7)	7/8	1.84 (46.7)
3/4	-91F12-R12-S	23.6	0.72 (18.3)	1 1/16	2.03 (51.6)
1	-91F16-R16-S	39.0	0.88 (22.4)	1 3/8	2.35 (59.7)


Female BSPT




BSPT Size	Basic Ordering Number	Flow Coefficient (Cv)	E	F	L
			in. (mm)	in.	in. (mm)
1/4	-91F4-FR4-S	1.7	0.24 (6.1)	3/4	1.60 (40.6)
3/8	-91F4-FR6-S	1.7	0.24 (6.1)	7/8	1.67 (42.4)
3/8	-91F8-FR6-S	7.1	0.41 (10.4)	1 1/16	1.59 (40.4)
1/2	-91F8-FR8-S	11.5	0.50 (12.7)	1 1/16	1.82 (46.2)
3/4	-91F12-FR12-S	23.6	0.72 (18.3)	1 5/16	2.08 (52.8)
1	-91F16-FR16-S	39.0	0.88 (22.4)	1 5/8	2.49 (63.2)

Bodies


Tube Fitting




Male NPT




Female NPT



Male BSPT



Female BSPT



Tube Size	Basic Ordering Number	E	F	H	L
in.		in. (mm)	in.	in. (mm)	in. (mm)
1/4	-91F4-FX4-B	0.19 (4.8)	11/16	0.87 (22.1)	1.80 (45.7)
3/8	-91F4-FX6-B	0.28 (7.1)	11/16	0.87 (22.1)	1.81 (46.0)
3/8	-91F8-FX6-B	0.28 (7.1)	1 1/16	1.30 (33.0)	2.17 (55.1)
1/2	-91F8-FX8-B	0.47 (11.9)	1 1/16	1.30 (33.0)	2.23 (56.6)
3/4	-91F12-FX12-B	0.62 (15.7)	1 1/2	1.66 (42.2)	2.45 (62.2)
1	-91F16-FX16-B	0.88 (22.4)	1 11/16	1.88 (47.8)	2.75 (69.9)
mm		(mm) in.	mm	(mm) in.	(mm) in.
6	-91F4-MX6-B	4.8 (0.19)	18	22.1 (0.87)	45.7 (1.80)
10	-91F8-MX10-B	7.1 (0.28)	27	33.0 (1.30)	55.9 (2.20)
12	-91F8-MX12-B	10.4 (0.41)	27	33.0 (1.30)	57.4 (2.26)
22	-91F12-MX20-B	15.9 (0.63)	38	42.2 (1.66)	63.5 (2.50)
25	-91F16-MX25-B	21.8 (0.86)	46	47.8 (1.88)	70.0 (2.76)

NPT Size	Basic Ordering Number	E	F	H	L
		in. (mm)	in.	in. (mm)	in. (mm)
1/4	-91F4-N4-B	0.25 (6.4)	11/16	0.87 (22.1)	1.57 (39.9)
3/8	-91F4-N6-B	0.37 (9.4)	11/16	0.87 (22.1)	1.57 (39.9)
3/8	-91F8-N6-B	0.41 (10.4)	1 1/16	1.30 (33.0)	1.83 (46.5)
1/2	-91F8-N8-B	0.50 (12.7)	1 1/16	1.30 (33.0)	2.08 (52.8)
3/4	-91F12-N12-B	0.72 (18.3)	1 1/2	1.66 (42.2)	2.33 (59.2)
1	-91F16-N16-B	0.88 (22.4)	1 11/16	1.88 (47.8)	2.65 (67.3)


NPT Size	Basic Ordering Number	E	F	H	L
		in. (mm)	in.	in. (mm)	in. (mm)
1/4	-91F4-FN4-B	0.38 (9.7)	3/4	0.87 (22.1)	1.50 (38.1)
3/8	-91F4-FN6-B	0.38 (9.7)	7/8	0.87 (22.1)	1.63 (41.4)
3/8	-91F8-FN6-B	0.59 (15.0)	1 1/16	1.30 (33.0)	1.73 (43.9)
1/2	-91F8-FN8-B	0.63 (16.0)	1 1/16	1.30 (33.0)	1.73 (43.9)
3/4	-91F12-FN12-B	0.88 (22.4)	1 1/2	1.66 (42.2)	1.89 (48.0)
1	-91F16-FN16-B	1.06 (26.9)	1 11/16	1.88 (47.8)	2.12 (53.8)

BSPT Size	Basic Ordering Number	E	F	H	L
		in. (mm)	in.	in. (mm)	in. (mm)
1/4	-91F4-R4-B	0.25 (6.4)	11/16	0.87 (22.1)	1.57 (39.9)
3/8	-91F4-R6-B	0.37 (9.4)	11/16	0.87 (22.1)	1.57 (39.9)
3/8	-91F8-R6-B	0.41 (10.4)	1 1/16	1.30 (33.0)	1.83 (46.5)
1/2	-91F8-R8-B	0.50 (12.7)	1 1/16	1.30 (33.0)	2.08 (52.8)
3/4	-91F12-R12-B	0.72 (18.3)	1 1/2	1.66 (42.2)	2.33 (59.2)
1	-91F16-R16-B	0.88 (22.4)	1 11/16	1.88 (47.8)	2.65 (67.3)

BSPT Size	Basic Ordering Number	E	F	H	L
		in. (mm)	in.	in. (mm)	in. (mm)
1/4	-91F4-FR4-B	0.38 (9.7)	3/4	0.87 (22.1)	1.50 (38.1)
3/8	-91F4-FR6-B	0.38 (9.7)	7/8	0.87 (22.1)	1.63 (41.4)
3/8	-91F8-FR6-B	0.59 (15.0)	1 1/16	1.30 (33.0)	1.73 (43.9)
1/2	-91F8-FR8-B	0.63 (16.0)	1 1/16	1.30 (33.0)	1.73 (43.9)
3/4	-91F12-FR12-B	0.88 (22.4)	1 1/2	1.66 (42.2)	1.89 (48.0)
1	-91F16-FR16-B	1.06 (26.9)	1 11/16	1.88 (47.8)	2.12 (53.8)


Protectors

Stem Protector



Series	Basic Ordering Number
91F4	-91F4-SP
91F8	-91F8-SP
91F12	-91F12-SP
91F16	-91F16-SP

Body Protector



Series	Basic Ordering Number
91F4	-91F4-BP
91F8	-91F8-BP
91F12	-91F12-BP
91F16	-91F16-BP

© To order a protector, add material designator (SS for stainless steel or B for brass) as a prefix to the basic ordering number.

Example: SS91F4-BP

Ordering Information

SS 91F4 – Fx4 – S

Material

Series

Size

End Connection Type

End Connection Size

Stem or Body

SS

316SS

B

Brass

S4

304SS

CS

Carbon Steel

91F

4

1/4" (6.4 mm)

8

1/2" (12.7 mm)

12

3/4" (19.0 mm)

16

1" (25.4 mm)

FN

Female NPT

N

Male NPT

FR

Female BSPT

R

Male BSPT

FM

Female ISO (for RP)

M

Male ISO (for RG)

FX

Fractional Tube Fitting

MX

Metric Tube Fitting

FT

Fractional Tube Adapter

MT

Metric Tube Adapter

AN

Male JIC 37° Flare

4

1/4 (in.)

6

3/8 (in.) or 6 mm

8

1/2 (in.) or 8 mm

10

5/8 (in.) or 10 mm

12

3/4 (in.) or 12 mm

14

M14 x 1.5

16

1 (in.) or 16 mm

18

M18 x 1.5

20

M20 x 1.5

S

Stem without valve remains open when uncoupled

B


Body without valve shuts off when uncoupled

1. Dimensions are for reference only and are subject to change.
2. Sizes and types listed are standard. Other sizes and types are available on request.

QV Series

Features

- ⦿ Large flow area and stem ensure high flow capacity.
- ⦿ Positive valve stop. The perch maintains valve alignment and provides metal to metal valve stop to ensure that the valves open fully.
- ⦿ Hardened nipples and sleeves and solid barstock construction make for a quality coupling with maximum resistance to damage from hydraulic and mechanical shock.
- ⦿ The seal is designed to withstand high pressure and provide reliable sealing.
- ⦿ Durable ball-locking mechanism assures reliable connection.



Pressure-Temperature Ratings

Body Material	Stainless Steel						Brass					
Series	91V2	91V4	91V6	91V8	91V12	91V16	91V2	91V4	91V6	91V8	91V12	91V16
O-ring	FKM						Buna N					
Temperature Range	-10°F to 400°F (-23°C to 204°C)						-10°F to 250°F (-23°C to 121°C)					
Working Pressue psig (bar)	2000 (137)		1500 (103)		1000 (68.9)		1000 (68.9)					

Insert Depth

Series	Insert Depth
	in. (mm)
91V2	0.71 (18.0)
91V4	0.81 (20.6)
91V6	0.89 (22.5)
91V8	1.01 (25.6)
91V12	1.26 (32.1)
91V16	1.42 (36.1)





In order to measure overall length in the coupled position, the insertion depth should be deducted from any overall stem and body combination length.

Cautions:

- ⦿ Do not uncouple under pressure.
- ⦿ Do not insert foreign object into uncoupled stems and bodies.
- ⦿ Re-lubricate stem seal O-ring periodically.



Stems





Female NPT

NPT Size	Basic Ordering Number	Flow coefficient (Cv)	A	F
			in. (mm)	in.
1/8	-91V2-FN2-D	0.8	1.16 (29.5)	9/16
1/4	-91V4-FN4-D	3.0	1.39 (35.3)	3/4
3/8	-91V6-FN6-D	6.0	1.50 (38.1)	7/8
1/2	-91V8-FN8-D	12.0	1.75 (44.5)	1 1/8
3/4	-91V12-FN12-D	28.0	2.16 (54.9)	1 3/8
1	-91V16-FN16-D	50.0	2.58 (65.5)	1 5/8

Female BSPT

BSPT Size	Basic Ordering Number	Flow coefficient (Cv)	A	F
			in. (mm)	in.
1/8	-91V2-FR2-D	0.8	1.16 (29.5)	9/16
1/4	-91V4-FR4-D	3.0	1.39 (35.3)	3/4
3/8	-91V6-FR6-D	6.0	1.50 (38.1)	7/8
1/2	-91V8-FR8-D	12.0	1.75 (44.5)	1 1/8
3/4	-91V12-FR12-D	28.0	2.16 (54.9)	1 3/8
1	-91V16-FR16-D	50.0	2.58 (65.5)	1 5/8

Bodies



Female NPT

NPT Size	Basic Ordering Number	A	B	C
		in. (mm)	in. (mm)	in. (mm)
1/8	-91V2-FN2-B	1.90 (48.3)	0.69 (17.5)	0.96 (24.4)
1/4	-91V4-FN4-B	2.26 (57.4)	0.81 (20.6)	1.14 (29.0)
3/8	-91V6-FN6-B	2.49 (63.2)	0.88 (22.2)	1.40 (35.6)
1/2	-91V8-FN8-B	2.87 (72.9)	1.13 (28.6)	1.77 (45.0)
3/4	-91V12-FN12-B	3.56 (90.4)	1.31 (33.3)	2.14 (54.4)
1	-91V16-FN16-B	4.18 (106.2)	1.63 (41.3)	2.52 (64.0)



VFK

VFK FLUID CONTROL CO.,LTD

Add: No.18 Danyan Road, Fenghuang Industrial Park, Danyang, Jiangsu, P.R. China

Tel: 0086-511-86197685

Fax: 0086-511-86535052

[Http://www.vfkgroup.com](http://www.vfkgroup.com)