

Find OIL & GAS
with Hydrocarbon Surveys

Copeland Remote Sensing, LLC
HydrocarbonSurveys.com



Patent Claim 1 - A detector system for detecting underground anomalies.....

Patent Claim 18 - The detector system of Claim 1, wherein the underground anomalies comprise at least one of hydrocarbon, **hydrocarbon bearing formations, faults, voids, or disturbances** underground.

A passive receiver system for detecting currently existing hydrocarbons in place, as well as faults, voids, or disturbances directly below each point of measurement.

C. Dave Copeland - 512.917.7260

(12) **United States Patent**
Copeland

(10) **Patent No.:** **US 10,761,237 B1**
(45) **Date of Patent:** **Sep. 1, 2020**

(54) **SYSTEM AND METHOD FOR DETECTING UNDERGROUND ANOMALIES**

(71) Applicant: **COPELAND RESOURCES, INC.**,
Austin, TX (US)

(72) Inventor: **Charles David Copeland**, Austin, TX
(US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/453,886**

(22) Filed: **Jun. 26, 2019**

(51) **Int. Cl.**
G01V 7/04 (2006.01)
G01V 7/08 (2006.01)
G01F 23/68 (2006.01)
G01F 23/72 (2006.01)
G05D 23/01 (2006.01)

(52) **U.S. Cl.**
CPC **G01V 7/04** (2013.01); **G01F 23/68** (2013.01); **G01F 23/72** (2013.01); **G01V 7/08** (2013.01); **G05D 23/015** (2013.01)

(58) **Field of Classification Search**
CPC **G01F 23/68; G01F 23/72; G01V 7/08; G01V 7/04**
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,899,826 A *	8/1959	La Coste	G01V 7/02 73/382 R
5,564,276 A *	10/1996	Abadilla	F25B 21/04 136/204
6,076,409 A *	6/2000	Bang	G01L 19/0038 73/756
6,526,825 B2	3/2003	Manson	

* cited by examiner

Primary Examiner — Paul M. West

(74) *Attorney, Agent, or Firm* — Hulsey P.C.

(57) **ABSTRACT**

Disclosed is a detector system for detecting underground anomalies comprising a detector device which includes a fluid chamber which is sealed; a float including a target, positioned within the fluid chamber; and a shielded phase shift proximity sensor configured to detect a distance between the target and proximity sensor, wherein a presence of an underground anomaly is determined based on the detected distance.

18 Claims, 13 Drawing Sheets
(4 of 13 Drawing Sheet(s) Filed in Color)