

# NATIONAL HIGHWAY INSTITUTE SOILS & FOUNDATIONS: SUBSURFACE EXPLORATIONS

Main Category:	Civil Engineering
Sub Category:	Geotechnical Engineering
Course #:	GEO-115
Course Content:	138 pgs
PDH/CE Hours:	11

# **OFFICIAL COURSE/EXAM** (SEE INSTRUCTIONS ON NEXT PAGE)

<u>WWW.ENGINEERING-PDH.COM</u> TOLL FREE (US & CA): 1-833-ENGR-PDH (1-833-364-7734) <u>SUPPORT@ENGINEERING-PDH.COM</u>

# **GEO-115 EXAM PREVIEW**

# - TAKE EXAM! -

# Instructions:

- At your convenience and own pace, review the course material below. When ready, click "Take Exam!" above to complete the live graded exam. (Note it may take a few seconds for the link to pull up the exam.) You will be able to re-take the exam as many times as needed to pass.
- Upon a satisfactory completion of the course exam, which is a score of 70% or better, you will be provided with your course completion certificate. Be sure to download and print your certificates to keep for your records.

# Exam Preview:

- 1. From Recommended process for developing subsurface model for engineering design (FHWA, 2002a), during Subsurface Exploration and Field Testing, the first step is to review available subsurface information and develop preliminary model of subsurface conditions.
  - a. True
  - b. False
- 2. From Recommended process for developing subsurface model for engineering design (FHWA, 2002a), The last major category is:
  - a. Laboratory Testing
  - b. Test Interpretation
  - c. Subsurface Exploration & Field Testing
  - d. Engineering Design
- 3. When preparing for subsurface exploration, basic sources of geotechnical information should be reviewed to determine landform boundaries and to provide a basis for outlining the project subsurface exploration program.
  - a. True
  - b. False
- 4. In general, rocks are classified as igneous, sedimentary, and metamorphic. Soils are a result of the weathering of rocks. Regardless of the type of rock, most weathering takes place below the ground surface.
  - a. True
  - b. False

- 5. A <u>landform</u> is one that was formed in its present location through weathering of the parent (or bed) rock. <u>tend</u> to be characterized by angular to subangular particles, mineralogy similar to parent rock, and the presence of large angular fragments within the overall soil mass.
  - a. residual soil
  - b. transformed soil
  - c. transferred soil
  - d. subsurface soil
- 6. A transported soil is one that was formed from rock weathering at one location and transported by some exterior agent to another location. Once a landform is identified, the geotechnical specialist can develop an \_\_\_\_\_ for exploration.
  - a. "area" concept
  - b. "plan" concept
  - c. "land" concept
  - d. "soil" concept
- 7. Several in-situ tests for sampling define the geostratigraphy and provide direct measurements of soil properties and geotechnical parameters. The common in-situ tests include: Standard Penetration Test (SPT), Cone Penetration Test (CPT), Piezocone Test (CPTu), Flat Plate Dilatometer Test (DMT), Pressuremeter Test (PMT), and Vane Shear Test (VST).
  - a. True
  - b. False
- 8. Geotechnical borings are a critical component of any subsurface exploration program. They are performed to satisfy several objectives including identifing the subsurface distribution of materials with distinctive properties, including the presence and thickness of distinct layers.
  - a. True
  - b. False
- 9. \_\_\_\_\_ is the systematic collection of local, detailed geologic data, and, for engineering purposes, is used to characterize and document the condition of a rock mass or outcrop.
  - a. Subsurface mapping
  - b. Geologic mapping
  - c. Strata mapping
  - d. Boring mapping

10. Recommendations for Sampling Depth Intervals in Soils - Some general recommendations for minimum sampling depth for preliminary screening, disturbed samples might be taken continuously in the upper 10 ft (3 m), at 5 ft (1.5 m) intervals up to 200 ft (30 m)

- a. True
- b. False



Publication No. FHWA NHI-06-088 December 2006

# NHI Course No. 132012

# **SOILS AND FOUNDATIONS**

# **Reference Manual – Volume I - Ch.3 SUBSURFACE**

# **EXPLORATIONS**





National Highway Institute

ENGINEERING-PDH.COM | GEO-115 |

### NOTICE

The contents of this report reflect the views of the authors, who are responsible for the facts and the accuracy of the data presented herein. The contents do not necessarily reflect policy of the Department of Transportation. This report does not constitute a standard, specification, or regulation. The United States Government does not endorse products or manufacturers. Trade or manufacturer's names appear herein only because they are considered essential to the objective of this document.

**Technical Report Documentation Page** 

	Item	neur report Documentation I ag	
1. Report No.	2. Government Accession No.   3	. Recipient's Catalog No.	
FHWA-NHI-06-088			
4. Title and Subtitle	5	. Report Date	
SOILS AND FOUND ATTOMS		December 2006	
REFERENCE MANUAL - Volur	me I	. Performing Organization Code	
$\frac{1}{7} \text{ Author(s)}$		Parforming Organization Papart No.	
		. Fertorning Organization Report No.	
Naresh C. Samtani <sup>*</sup> , PE, PhD and E	Edward A. Nowatzki*, PE, PhD		
Ryan R. Berg and Associates, Inc.	adress 1	U. WORK UNIT NO. (TRAIS)	
2190 Leyland Alcove, Woodbury,	, MN 55125		
* NCS GeoResources, LLC	1	1. Contract or Grant No.	
640 W Paseo Rio Grande, Tucso	on, AZ 85737	DTFH-61-02-T-63016	
12. Sponsoring Agency Name and Addre	ess 1	3. Type of Report and Period Covered	
National Highway Institute	n –		
Federal Highway Administration,	Washington, D.C. 20590	4. Sponsoring Agency Code	
15. Supplementary Notes			
FHWA COTR – Larry Jones			
FHWA Technical Review – Jer	rry A. DiMaggio, PE; Silas Nichols,	PE; Richard Cheney, PE;	
Be	enjamin Rivers, PE; Justin Henwood	, PE.	
Contractor Technical Review – Ry	Contractor Technical Review – Ryan R. Berg, PE; Robert C. Bachus, PhD, PE;		
This manual is an update of the 3 <sup>rd</sup> Edition prepared by Parsons Brinckerhoff Quade & Douglas, Inc, in 2000.			
Author: Richard Cheney, PE. The au	uthors of the $1^{st}$ and $2^{nd}$ editions prepare	ed by the FHWA in 1982 and 1993,	
respectively, were Richard Cheney, P	E ana Ronala Chassie, PE.		
The Reference Manual for Soils and Fo	bundations course is intended for design a stion of geotechnical features for surface	nd construction professionals involved transportation facilities The manual i	
geared towards practitioners who rout	inely deal with soils and foundations iss	ues but who may have little theoretica	
background in soil mechanics or found	dation engineering. The manual's conte	nt follows a project-oriented approach	
computation of settlement, allowable	e footing pressure, etc., to the constru	the boring request through design ction of approach embankments and	
foundations. Appendix A includes	an example bridge project where	such an approach is demonstrated	
Recommendations are presented on	how to layout borings efficiently, how	to minimize approach embankmen	
settlement, how to design the most	cost-effective pier and abutment foun	dations, and how to transmit design ject engineer so that the project can be	
constructed efficiently.	sective and/or contact with the pre-	jeet engineer so that the project can be	
The objective of this manual is to prese	ent recommended methods for the safe of	ost-effective design and construction o	
geotechnical features. Coordination	between geotechnical specialists and pr	oject team members at all phases of	
project is stressed. Readers are encount	raged to develop an appreciation of geot	echnical activities in all project phase	
17 Kay Words			
17. Key words 18. Distribution Statemen Subsurface exploration testing slope stability onbankments out slopes shallow			
foundations, driven piles, drilled shafts, earth retaining structures, construction.			
19. Security Classif. (of this report)	20. Security Classif. (of this page)	21. No. of Pages 22. Price	
UNCLASSIFIED	UNCLASSIFIED	462	
E DOT E 1700 7(0 70)			

Form DOT F 1700.7(8-72)

Reproduction of completed page authorized

[THIS PAGE INTENTIONALLY BLANK]

#### PREFACE

This update to the Reference Manual for the Soils and Foundations course was developed to incorporate the guidance available from the FHWA in various recent manuals and Geotechnical Engineering Circulars (GECs). The update has evolved from its first two versions prepared by Richard Cheney and Ronald Chassie in 1982 and 1993, and the third version prepared by Richard Cheney in 2000.

The updated edition of the FHWA Soils and Foundations manual contains an enormous amount of information ranging from methods for theoretically based analyses to "rules of thumb" solutions for a wide range of geotechnical and foundation design and construction issues. It is likely that this manual will be used nationwide for years to come by civil engineering generalists, geotechnical and foundation specialists, and others involved in transportation facilities. That being the case, the authors wish to caution against indiscriminate use of the manual's guidance and recommendations. The manual should be considered to represent the minimum standard of practice. The user must realize that there is no possible way to cover all the intricate aspects of any given project. Even though the material presented is theoretically correct and represents the current state-of-the-practice, engineering judgment based on local conditions and knowledge must be applied. This is true of most engineering disciplines, but it is especially true in the area of soils and foundation engineering and construction. For example, the theoretical and empirical concepts in the manual relating to the analysis and design of deep foundations apply to piles installed in the glacial tills of the northeast as well as to drilled shafts installed in the cemented soils of the southwest. The most important thing in both applications is that the values for the parameters to be used in the analysis and design be selected by a geotechnical specialist who is intimately familiar with the type of soil in that region and intimately knowledgeable about the regional construction procedures that are required for the proper installation of such foundations in local soils.

#### General conventions used in the manual

This manual addresses topics ranging from fundamental concepts in soil mechanics to the practical design of various geotechnical features ranging from earthworks (e.g., slopes) to foundations (e.g., spread footings, driven piles, drilled shafts and earth retaining structures). In the literature each of these topics has developed its own identity in terms of the terminology and symbols. Since most of the information presented in this manual appears in other FHWA publications, textbooks and publications, the authors faced a dilemma on the regarding terminology and symbols as well as other issues. Following is a brief discussion on such issues.

#### • Pressure versus Stress

The terms "pressure" and "stress" both have units of force per unit area (e.g., pounds per square foot). In soil mechanics "pressure" generally refers to an applied load distributed over an area or to the pressure due to the self-weight of the soil mass. "Stress," on the other hand, generally refers to the condition induced at a point within the soil mass by the application of an external load or pressure. For example, "overburden pressure," which is due to the self weight of the soil, induces "geostatic stresses" within the soil mass. Induced stresses cause strains which ultimately result in measurable deformations that may affect the behavior of the structural element that is applying the load or pressure. For example, in the case of a shallow foundation, depending upon the magnitude and direction of the applied loading and the geometry of the footing, the pressure distribution at the base of the footing can be uniform, linearly varying, or non-linearly varying. In order to avoid confusion, the terms "pressure" and "stress" will be used interchangeably in this manual. In cases where the distinction is important, clarification will be provided by use of the terms "applied" or "induced."

#### • Symbols

Some symbols represent more than one geotechnical parameter. For example, the symbol  $C_c$  is commonly used to identify the coefficient of curvature of a grain size distribution curve as well as the compression index derived from consolidation test results. Alternative symbols may be chosen, but then there is a risk of confusion and possible mistakes. To avoid the potential for confusion or mistakes, the Table of Contents contains a list of symbols for each chapter.

#### • Units

English units are the primary units in this manual. SI units are included in parenthesis in the text, except for equations whose constants have values based on a specific set of units, English or SI. In a few cases, where measurements are conventionally reported in SI units (e.g., aperture sizes in rock mapping), only SI units are reported. English units are used in example problems. Except where the units are related to equipment sizes (e.g., drill rods), all unit conversions are "soft," i.e., approximate. Thus, 10 ft is converted to 3 m rather than 3.05 m. The soft conversion for length in feet is rounded to the nearest 0.5 m. Thus, 15 ft is converted to 4.5 m not 4.57 m.

#### • Theoretical Details

Since the primary purpose of this manual is to provide a concise treatment of the fundamental concepts in soil mechanics and an introduction to the practical design of various geotechnical features related to highway construction, the details of the theory underlying the methods of analysis have been largely omitted in favor of discussions on the application of those theories to geotechnical problems. Some exceptions to this general approach were made. For example, the concepts of lateral earth pressure and bearing capacity rely too heavily on a basic understanding of the Mohr's circle for stress for a detailed presentation of the Mohr's circle theory to be omitted. However, so as not to encumber the text, the basic theory of the Mohr's circle is presented in Appendix B for the reader's convenience and as an aid for the deeper understanding of the concepts of earth pressure and bearing capacity.

#### • Standard Penetration Test (SPT) N-values

The SPT is described in Chapter 3 of this manual. The geotechnical engineering literature is replete with correlations based on SPT N-values. Many of the published correlations were developed based on SPT N-values obtained with cathead and drop hammer methods. The SPT N-values used in these correlations do not take in account the effect of equipment features that might influence the actual amount of energy imparted during the SPT. The cathead and drop hammer systems typically deliver energy at an estimated average efficiency of 60%. Today's automatic hammers deliver energy at a significantly higher efficiency (up to 90%). When published correlations based on SPT N-values are presented in this manual, they are noted as  $N_{60}$ -values and the measured SPT N-values should be corrected for energy before using the correlations.

Some researchers developed correction factors for use with their SPT N-value correlations to address the effects of overburden pressure. When published correlations presented in this manual are based upon values corrected for overburden they are noted as  $N1_{60}$ . Guidelines are provided as to when the  $N_{60}$ -values should be corrected for overburden.

#### • Allowable Stress Design (ASD) and Load and Resistance Factor Design (LRFD) Methods

The design methods to be used in the transportation industry are currently (2006) in a state of transition from ASD to LRFD. The FHWA recognizes this transition and has developed separate comprehensive training courses for this purpose. Regardless of whether the ASD or LRFD is used, it is important to realize that the fundamentals of soil mechanics, such as the

determination of the strength and deformation of geomaterials do not change. The only difference between the two methods is the way in which the uncertainties in loads and resistances are accounted for in design. Since this manual is geared towards the fundamental understanding of the behavior of soils and the design of foundations, ASD has been used because at this time most practitioners are familiar with that method of design. However, for those readers who are interested in the nuances of both design methods Appendix C provides a brief discussion on the background and application of the ASD and LRFD methods.

# ACKNOWLEDGEMENTS

The authors would like to acknowledge the following events and people that were instrumental in the development of this manual.

- Permission by the FHWA to adapt the August 2000 version of the Soils and Foundations Workshop Manual.
- Provision by the FHWA of the electronic files of the August 2000 manual as well as other FHWA publications.
- The support of Ryan R. Berg of Ryan R. Berg and Associates, Inc. (RRBA) in facilitating the preparation of this manual and coordinating reviews with the key players.
- The support provided by the staff of NCS Consultants, LLC, (NCS) Wolfgang Fritz, Juan Lopez and Randy Post (listed in alphabetical order of last names). They prepared some graphics, some example problems, reviewed selected data for accuracy with respect to original sources of information, compiled the Table of Contents, performed library searches for reference materials, and checked internal consistency in the numbering of chapter headings, figures, equations and tables.
- Discussions with Jim Scott (URS-Denver) on various topics and his willingness to share reference material are truly appreciated. Dov Leshchinsky of ADAMA Engineering provided copies of the ReSSA and FoSSA programs which were used to generate several figures in the manual as well as presentation slides associated with the course presentation. Robert Bachus of Geosyntec Consultants prepared Appendices D and E. Allen Marr of GeoComp Corporation provided photographs of some laboratory testing equipment. Pat Hannigan of GRL Engineers, Inc. reviewed the driven pile portion of Chapter 9. Shawn Steiner of ConeTec, Inc. and Salvatore Caronna of gINT Software prepared the Cone Penetration Test (CPT) and boring logs, respectively, shown in Chapter 3 and Appendix A. Robert (Bob) Meyers (NMDOT), Ted Buell (HDR-Tucson) and Randy Simpson (URS-Phoenix) provided comments on some sections (particularly Section 8.9).
- Finally, the technical reviews and recommendations provided by Jerry DiMaggio, Silas Nichols, Benjamin Rivers, Richard Cheney (retired) and Justin Henwood of the FHWA, Ryan Berg of RRBA, Robert Bachus of Geosyntec Consultants, Jim Scott of URS, and Barry Christopher of Christopher Consultants, Inc., are gratefully acknowledged.

## SPECIAL ACKNOWLEDGEMENTS

A special acknowledgement is due of the efforts of Richard Cheney and Ronald Chassie for their work in the preparation of the previous versions of this manual. It is their work that made this course one of the most popular FHWA courses. Their work in developing this course over the past 25 years is acknowledged.

With respect to this manual, the authors wish to especially acknowledge the in-depth review performed by Jerry DiMaggio and time he spent in direct discussions with the authors and other reviewers. Such discussions led to clarification of some existing guidance in other FHWA manuals as well as the introduction of new guidance in some chapters of this manual.

	SI CONVERSION FACTORS			
	APPROXIMA	<b>ATE CONVERSION</b>	S FROM SI UNITS	
Symbol	When You	Multiply By	To Find	Symbol
· ·	Know			·
		LENGTH		
mm	millimeters	0.039	inches	in
m	meters	3.28	feet	ft
m	meters	1.09	yards	yd
km	kilometers	0.621	miles	mi
	•	AREA	-	•
$mm^2$	square millimeters	0.0015	square inches	in <sup>2</sup>
m <sup>2</sup>	square meters	10.758	square feet	ft <sup>2</sup>
$m^2$	square meters	1.188	square yards	yd <sup>2</sup>
ha	hectares	2.47	acres	ac
km <sup>2</sup>	square kilometers	0.386	square miles	mi <sup>2</sup>
	•	VOLUME	• •	•
ml	milliliters	0.034	fluid ounces	floz
1	liters	0.264	gallons	gal
m <sup>3</sup>	cubic meters	35.29	cubic feet	ft <sup>3</sup>
m <sup>3</sup>	cubic meters	1.295	cubic yards	vd <sup>3</sup>
		MASS	<u>۲</u>	
g	grams	0.035	ounces	OZ
kg	kilograms	2.205	pounds	lb
tonnes	tonnes	1.103	US short tons	tons
		TEMPERATURE		
°C	Celsius	1.8°C + 32	Fahrenheit	°F
	•	WEIGHT DENSIT	Y	
kN/m <sup>3</sup>	kilonewtons / cubic	6.36	Pound force / cubic foot	pcf
	meter			
	FC	ORCE and PRESSURE or	STRESS	
Ν	newtons	0.225	pound force	lbf
kN	kilonewtons	225	pound force	lbf
kPa	kilopascals	0.145	pound force / square inch	psi
kPa	kilopascals	20.88	pound force / square foot	psf
	]	PERMEABILITY (VELO	DCITY)	
cm/sec	centimeter/second	1.9685	feet/minute	ft/min

[THIS PAGE INTENTIONALLY BLANK]

#### SOILS AND FOUNDATIONS VOLUME I

#### TABLE OF CONTENTS

LIST	OF FIG	URES .		ix
LIST	OF TA	BLES		xv
LIST	OF SYI	MBOLS		xviii
1.0	INTR	ODUCT	ION	1-1
	1.1	PURPO	SE AND SCOPE	1-1
	1.2	SOILS	AND FOUNDATIONS FOR HIGHWAY FACILITIES	1-5
	1.3	ORGAN	NIZATION OF MANUAL	1-10
	1.4	REFER	ENCES	1-12
		1.4.1	Primary FHWA References	1-12
		1.4.2	Other Primary References	1-13
2.0	STRE	SS AND	STRAIN IN SOILS	
	2.1	BASIC	WEIGHT-VOLUME RELATIONSHIPS	
		2.1.1	Volume Ratios	
		2.1.2	Weight Ratios	
		2.1.3	Weight-Volume Ratios (Unit Weights) and Specific Gravity	
		2.1.4	Determination and Use of Basic Weight-Volume Relations	
		2.1.5	Size of Grains in the Solid Phase	
		2.1.6	Shape of Grains in Solid Phase	2-13
			2.1.6.1 Bulky Shape	2-13
		/	2.1.6.2 Platy Shape	2-15
		2.1.7	Effect of Water on Physical States of Soils	2-15
	2.2	PRINC	PLE OF EFFECITVE STRESS	2-19
	2.3	OVERE	BURDEN PRESSURE	2-19
	2.4	VERTI	CAL STRESS DISTRIBUTION IN SOIL DUE TO EXTERNA	4L
		LOADI	NGS	2-22
		2.4.1	Uniformly Loaded Continuous (Strip) and Square Footings	2-24
		2.4.2	Approximate (2:1) Stress Distribution Concept	2-26
	2.5	REPRE	SENTATION OF IMPOSED PRESSURES ON	
		THE po	DIAGRAM	2-26
	2.6	LOAD-	DEFORMATION PROCESS IN SOILS	2-30
		2.6.1	Time Dependent Load-Deformation (Consolidation) Process .	2-31
		2.6.2	Comparison of Drainage Rates between Coarse-Grained and F	ine-
		(	Grained Soil	2-34
	2.7	LATER	AL STRESSES IN FOUNDATION SOILS	2-34
		2.7.1	Effect of Shear Strength of Soils on Lateral Pressures	2-36

	2.8	STRE	ENGTH OF SOILS TO RESIST IMPOSED STRESSES	2-38
		2.8.1	Basic Concept of Shearing Resistance and Shearing Strength	2-38
	2.9	STRE	NGTH OF SOILS RELATED TO LATERAL	
		EART	TH PRESSURES	2-42
		2.9.1	Distribution of Lateral Earth and Water Pressures	2-45
		2.9.2	Deformations Associated with Lateral Pressures	2-47
	2.10	UNSA	ATURATED SOIL MECHANICS	2-47
3.0	SUBS	SURFA	CE EXPLORATIONS	3-1
	3.01	Prima	rv References	
	3.1	PREP	PARING FOR SUBSURFACE EXPLORATION	
		3.1.1	Soil Formations and Landforms	3-6
			3.1.1.1 Residual Soils	3-7
			3.1.1.2 Transported Soils	3-9
			3.1.1.3 Area Concept of Explorations Based on Landforms	
	3.2	FIELI	D RECONNAISSANCE	3-13
	3.3	SUBS	SURFACE EXPLORATION PROGRAM	3-15
	3.4	SAMI	PLING TECHNIOUES AND TOOLS	3-17
	3.5	BORI	NG METHODS	
		3.5.1	Auger Borings	
		3.5.2	Wash-type Borings	
		3.5.3	Coring in Rocks	3-26
	3.6	SAMI	PLING METHODS	
		3.6.1	Disturbed Sampling of Soil	3-28
		3.6.2	Undisturbed Sampling of Soil	3-28
		3.6.3	Thin-Walled (Shelby) Tube Sampling	3-35
		3.6.4	Undisturbed Sampling of Rock (Rock Coring)	
			3.6.4.1 Core Barrels	
			3.6.4.2 Coring Bits	
			3.6.4.3 Drilling Fluid	
		3.6.5	Observations During Rock Core Drilling	
		01010	3.6.5.1 Drilling Rate/Time	
			3 6 5 2 Core Photographs	3-43
			3 6 5 3 Rock Classification	3-44
			3 6 5 4 Recovery	3-44
			3 6 5 5 Rock Quality Designation (ROD)	3-44
			3 6 5 6 Drilling Fluid Recovery	3-47
			3 6 5 7 Core Handling and Labeling	3-48
			3.6.5.8 Care and Preservation of Rock Samples	3-50
		366	Geologic Manning	3-50
	37	STAN	JDARD PENETRATION TEST (SPT)	3_51
	5.1	371	Energy Efficiency of Hammers	3-54
		372	Effect of Overburden Stress on N-values	
		373	Correlation of SPT N-Values with Basic Soil Characteristics	3_58
		5.1.5	3731 Applicability of SPTs in Gravelly Soils	3_58
		374	SPT Test Frrors	3_59
		J. / . f		

	3.8	LOG OF BOREHOLE INFORMATION ("BORING LOGS")	3-62
		3.8.1 Boring Log Format	3-62
		3.8.2 Duties of the Logger	3-62
	3.9	CONE PENETRATION TESTING (CPT)	3-67
		3.9.1 Equipment Description and Operation	3-68
		3.9.2 The Standard Cone Penetration Test (CPT)	3-69
		3.9.3 The Piezo-cone Penetration Test (CPTu)	3-71
		3.9.4 The Seismic Piezocone Penetration Test (SCPTu)	3-71
		3.9.5 Test Procedures	3-71
		3.9.6 CPT Profiles	3-72
		3.9.7 CPT Profile Interpretation	3-72
	3.10	DILATOMETER TEST (DMT)	3-75
	3.11	PRESSUREMETER TEST (PMT)	3-76
	3.12	VANE SHEAR TEST (VST)	3-77
	3.13	GROUNDWATER MEASUREMENTS	3-78
		3.13.1 Information on Existing Wells	3-78
		3.13.2 Open Borings	3-79
		3.13.3 Observation Wells	3-79
		3.13.4 Water Level Measurements	3-81
		3.13.4.1 Chalked Tape	3-81
		3.13.4.2 Tape with a Float	3-82
		3.13.4.3 Electric Water-Level Indicator	3-82
		3.13.4.4 Data Loggers	3-82
	3.14	GUIDELINES FOR MINIMUM SUBSURFACE EXPLORATION	3-83
		3.14.1 Recommendations for Sampling Depth Intervals in Soils	3-87
		3.14.2 Recommendations for Sampling Depth Intervals in Rocks	3-89
		3.14.3 Recommendations for Water Level Monitoring in Borings	3-89
	3.15	GEOPHYSICAL TESTS	3-90
		3.15.1 Types of Geophysical Tests	3-90
		3.15.2 Advantages and Disadvantages of Geophysical Tests	3-94
		3.15.2.1 Advantages of Geophysical Tests	3-94
		3.15.2.2 Disadvantages of Geophysical Tests	3-95
		3.15.3 Examples of Uses of Geophysical Tests	3-95
4.0	ENG	INEERING DESCRIPTION, CLASSIFICATION AND	
	CHA	RACTERISTICS OF SOILS AND ROCKS	4-1
	4.01	Primary References	4-3
	4.1	SOIL DESCRIPTION	
		4.1.1 Consistency and Apparent Density	
		4.1.2 Water Content (Moisture)	4-6
		4.1.3 Color	4-6
		4.1.4 Type of Soil	4-6
		4.1.4.1 Coarse-Grained Soils (Gravel and Sand)	4-7
		4.1.4.2 Fine-Grained Soils	4-9
		4.1.4.3 Highly Organic Soils	4-10
		4.1.4.4 Minor Soil Type(s)	4-11

		4.1.4.5 Inclusions	
		4.1.4.6 Other Descriptors	
		4.1.4.7 Layered Soils	
		4.1.4.8 Geological Name	
4.2	SOIL	CLASSIFICATION	
	4.2.1	Unified Soil Classification System (USCS)	
		4.2.1.1 Classification of Coarse-Grained Soils	
		4.2.1.2 Classification of Fine-Grained Soils	
	4.2.2	AASHTO Soil Classification System	
4.3	ENGI	NEERING CHARACTERISTICS OF SOILS	
	4.3.1	Engineering Characteristics of Coarse-Grained Soils (Sands	and
		Gravels)	
	4.3.2	Engineering Characteristics of Fine-Grained Soils	
		(Inorganic Clays)	
	4.3.3	Engineering Characteristics of Fine-Grained Soils	
		(Inorganic Silts)	
	4.3.4	Engineering Characteristics of Organic Soils	
4.4	PRAC	TICAL ASPECTS OF ENGINEERING CHARACTERISTIC	CS OF
	COAF	RSE-GRAINED SOILS	
4.5	PRAC	TICAL ASPECTS OF ENGINEERING CHARACTERISTI	CS OF
	FINE-	GRAINED SOILS	
4.6	DESC	RIPTION OF ROCK	
	4.6.1	Rock Type	
	4.6.2	Color	
	4.6.3	Grain Size and Shape	
	4.6.4	Stratification/Foliation	
	4.6.5	Mineral Composition	
	4.6.6	Weathering and Alteration	
	4.6.7	Strength	
	4.6.8	Hardness	
	4.6.9	Rock Discontinuity	
	4.6.10	Fracture Description	
	4.6.11	Rock Mass Classification	
4.7	SUBS	URFACE PROFILE DEVELOPMENT	
	4.7.1	Use of Historical Data in Development of Subsurface Profil	e 4-48
LAB	ORATO	ORY TESTING FOR GEOTECHNICAL DESIGN AND	
CON	STRUC	TION	
5.01	Prima	ry References	
5.1	QUAI	LITY ASSURANCE FOR LABORATORY TESTING	5-2
	5.1.1	Sample Tracking	5-2
	5.1.2	Sample Storage	5-2
	5.1.3	Sample Handling	5-4
	5.1.4	Effects of Sample Disturbance	5-4
	5.1.5	Specimen Selection	5-4
5.2	LABC	DRATORY TESTING FOR SOILS	

5.0

<ul> <li>5.3.1 General</li></ul>	5-10 5-10 5-11 5-12
<ul> <li>5.3.2 Moisture Content</li></ul>	5-10 5-11 5-12
<ul> <li>5.3.3 Unit Weight</li> <li>5.3.4 Particle Size Distribution</li></ul>	5-11
<ul> <li>5.3.4 Particle Size Distribution</li> <li>5.3.4.1 Sand Equivalent</li> <li>5.3.5 Atterberg Limits</li> </ul>	5-12
<ul><li>5.3.4.1 Sand Equivalent</li><li>5.3.5 Atterberg Limits</li></ul>	
5.3.5 Atterberg Limits	
	5-16
5.3.5.1 Significance of the "A-line" and "U-line" on	
Plasticity Chart	5-19
5.3.6 Specific Gravity	
5.3.7 Organic Content	
5.3.8 Electro Chemical Classification Tests	5-21
5.3.9 Laboratory Classification	5-21
5.4 CONSOLIDATION TESTING	5-22
5.4.1 Process of Consolidation	5-22
5.4.2 Consolidation Testing	5-23
5.4.3 Procedures	5-24
5.4.4 Presentation and Understanding the Consolidation Test Results	5-26
5.4.5 Comments on the Consolidation Tests	5-31
5.4.6 Useful Correlations between Consolidation Parameters and Index	X
Values	5-33
5.4.6.1 Compression Index, C <sub>c</sub>	
5.4.6.2 Recompression Index, Cr	5-35
5.4.6.3 Coefficient of Vertical Consolidation, cv	5-35
5.4.6.4 Coefficient of Secondary Compression, $C_{\alpha}$	5-37
5.5 SHEAR STRENGTH OF SOILS	5-38
5.5.1 Concept of Frictional and Cohesive Strengths	5-38
5.5.1.1 Strength Due to Friction	5-38
5.5.1.2 Strength Due to Cohesion	
5.5.1.3 Simplified Expression for Shear Strength of Soils	5-42
5.5.2 Strength Testing of Soils in the Laboratory	5-42
5.5.2.1 Unconfined Compression (UC) Tests	
5.5.2.2 Triaxial Tests	5-45
5.5.2.3 Direct Shear Tests	5-49
5.5.3 Factors Affecting Strength Testing Results	5-51
5.5.4 Comparison of Laboratory and Field Strengths	
5.5.5 Selection of Design Shear Strength	5-53
5.5.6 Correlations of Shear Strength Parameters with Index Parameters	3.5-53
5.5.6.1 Undrained Shear Strength of Cohesive Soils	5-53
5.5.6.2 Drained and Effective Shear Strength of Cohesive Soils	5-55
5.5.6.3 Shear Strength of Cohesionless Soils	5-56
5.6 PERMEABILITY	5-58
5.6.1 General	5-58
5.62 Equipment	5-58
5.6.2 Equipment	
5.6.3 Procedures	5-61

	5.7	VOLUME CHANGE PHENOMENA DUE TO LOADING AND	
		MOISTURE	5-65
		5.7.1 Swell Potential of Clays	5-65
		5.7.1.1 Evaluation of Expansion (Swell) Potential	5-67
		5.7.2 Collapse Potential of Soils	5-68
		5.7.3 Expansion of Soils due to Frost Action	5-70
	5.8	COMPACTION CHARACTERISTICS OF SOIL	5-72
		5.8.1 Concept of Compaction	5-72
		5.8.2 Test Procedures	5-73
		5.8.3 Implication of Laboratory Tests on Field	
		Compaction Specifications	5-76
		5.8.4 Engineering Characteristics of Compacted Soils	5-81
		5.8.4.1 Effect of Increase in Moisture Content on Shear Strength	
		of Compacted Soils	5-83
	5.9	ELASTIC PROPERTIES OF SOILS	5-83
	5.10	COMMON SENSE GUIDELINES FOR LABORATORY TESTING OF	7
		SOILS	5-84
	5.11	LABORATORY TESTS FOR ROCK	5-87
		5.11.1 Introduction	5-87
		5.11.2 Point-Load Strength Test	5-89
		5.11.3 Unconfined Compressive Strength of Intact Rock Core	5-91
		5.11.4 Elastic Modulus of Intact Rock Core	5-91
		5.11.5 Laboratory Direct Shear Test	5-92
	5.12	ELASTIC PROPERTIES OF ROCKS	5-94
		5.12.1 Elastic Modulus of Rock Mass	5-95
	5.13	COMMON SENSE GUIDELINES FOR LABORATORY TESTING OF	7
		ROCKS	5-96
	5.14	PRACTICAL ASPECTS FOR LABORATORY TESTING	5-98
	5.15	VARIABILITY OF MEASURED PROPERTIES	5-99
6.0	SLO	PE STABILITY	6-1
	6.01	Primary Reference	6-1
	6.1	EFFECTS OF WATER ON SLOPE STABILITY	6-3
	6.2	DESIGN FACTOR OF SAFETY	6-5
	6.3	INFINITE SLOPE ANALYSIS	6-5
		6.3.1 Infinite Slopes in Dry Cohesionless Soils	6-5
		6.3.2 Infinite Slopes in c-φ Soils with Parallel Seepage	6-6
	6.4	CIRCULAR ARC FAILURE	6-9
		6.4.1 Simple Rule of Thumb for Factor of Safety	6-10
		6.4.2 Stability Analysis Methods (General)	6-11
		6.4.3 Ordinary Method of Slices – Step-By-Step	
		Computation Procedure	6-13
		6.4.4 Recommended Stability Methods	6-20
		6.4.5 Remarks on Safety Factor	6-22
	6.5	CRITICAL FAILURE SURFACE	6-22
	6.6	DESIGN (STABILITY) CHARTS	6-24

		6.6.1 Historic	al Background	6-25
		6.6.2 Taylor's	s Stability Charts	6-25
		6.6.2.1	Determination of the Factor of Safety for a Slope	6-30
		6.6.3 Janbu's	Stability Charts	6-33
	6.7	SLIDING BLO	CK FAILURE	6-43
		6.7.1 Sliding	Block – Hand Method of Analysis	6-44
		6.7.1.1	Computation of Forces - Simple Sliding Block Analysis	6-45
		6.7.2 Comput	ation of Forces - Complicated Sliding Block Analysis	6-47
	6.8	SLOPE STABI	LITY ANALYSIS USING COMPUTER PROGRAMS	6-48
	6.9	IMPROVING 7	THE STABILITY OF EMBANKMENTS	6-50
		6.9.1 Embankm	nent Stability Design Solutions	6-50
		6.9.2 Design A	pproach for Reinforced Soil Slopes	6-50
		6.9.2.1	Preliminary Feasibility Design of RSS	6-53
	6.10	IMPROVING	THE STABILITY OF CUT SLOPES	6-57
		6.10.1 Deep Se	ated Failure	6-57
		6.10.2 Shallow	Surface Failures	6-58
		6.10.3 Factor of	f Safety - Cut Slopes	6-59
7.0	APPR	OACH ROAD	WAY DEFORMATIONS	7-1
	7.1	TYPICAL APP	PROACH ROADWAY DEFORMATION PROBLEMS	7-1
	7.2	INTERNAL D	ERFROMTION WITHIN EMBANKMENTS	7-6
		7.2.1 General	Considerations for Select Structural Backfill	7-6
		7.2.2 General	Considerations for Drainage Aggregate	7-6
		7.2.3 Use of (	Geosynthetics to Control Internal Deformations	7-10
	7.3	EXTERNAL D	EFORMATION IN FOUNDATION SOILS BELOW	
		EMBANKMEN	NTS	7-10
		7.3.1 Procedu	re for Estimating Stress Distribution in Foundation Soils	
		under F	ills	7-11
	7.4	COMPUTATIO	ON OF IMMEDIATE SETTLEMENT	7-15
		7.4.1 Modifie	ed Hough's Method for Estimating Immediate Settlements	s. 7-16
		7.4.1.1	Comments on the Computed Settlement of Embankments	. 7-19
	7.5	COMPUTATIO	ON OF CONSOLIDATION (LONG-TERM)	
		SETTLEMENT	۲S	7-19
		7.5.1 Correct	ion of Laboratory One-Dimensional Consolidation Curve	s 7-21
		7.5.2 Comput	ation of Primary Consolidation Settlements	7-24
		7.5.2.1	Normally Consolidated Soils	7-24
		7.5.2.2	Overconsolidated (Preconsolidated) Soils	7-26
		7.5.2.3	Underconsolidated Soils	7-27
		7.5.3 Consoli	dation Rates (Time Rate of Consolidation Settlement)	7-28
		7.5.3.1	Percent Consolidation	7-30
		7.5.3.2	Step-by-step Procedure to Determine Amount and Time	
		]	for Consolidation	7-33
		7.5.4 Seconda	ary Compression of Cohesive Soils	7-38
	7.6	LATERAL SQ	UEEZE OF FOUNDATION SOILS	7-40
		7.6.1 Thresho	old Condition for Lateral Squeeze	7-41
		7.6.2 Calcula	tion of the Safety Factor against Lateral Squeeze	7-42

	7.6.3	Estimation of Horizontal Movement of Abutments	
7.7	DESI	GN SOLUTIONS - DEFORMATION PROBLEMS	
	7.7.1	Reducing the Amount of Settlement	
		7.7.1.1 Category 1 - Increasing the Resistance	
		7.7.1.2 Category 2 - Reducing the Load	
	7.7.2	Reducing Settlement Time	
		7.7.2.1 Surcharge Treatment	
		7.7.2.2 Vertical Drains	
	7.7.3	Design Solutions to Prevent Abutment Tilting	
7.8	PRAC	TICAL ASPECTS OF EMBANKMENT SETTLEMENT	
7.9	CONS	TRUCTION MONITORING AND QUALITY ASSURANC	E 7-48
	7.9.1	Embankment Construction Monitoring by Instrumentation	
		7.9.1.1 Inspector's Visual Observation	
		7.9.1.2 Types of Instrumentation	
		7.9.1.3 Typical Locations for Instruments	

### LIST OF FIGURES

<u>Figure</u>	<u>Caption</u> <u>Page</u>
1-1	Aerial view of a pair of 3-span Interstate 10 (I-10) bridges over local
	roadway in Tucson, Arizona1-1
1-2	Example of 3-span roadway bridges over another roadway1-2
1-3	The "BIG I" stack interchange at the intersection of I-40 and I-25 in
	Albuquerque, New Mexico (Photo: Courtesy of Bob Meyers, NMDOT)
	(Note: A stack interchange is a free-flowing junction between two or more
	roadways that allows turning in all directions)1-2
1-4	A major multi-span bridge structure over water (George P. Coleman Bridge
	over the York River in Yorktown, Virginia)1-3
1-5	Example of a roadway bounded by cut slopes and wet lands in an
	environmentally sensitive area1-3
1-6	Combinations of sources of information required to solve geotechnical
	engineering issues 1-5
1-7	Geotechnical activity flow chart for a typical project using design-bid-build
	procurement process1-8
2 1	A unit of soil mass and its idealization
2 - 1	A unit of son mass and its idealization
2-2	distributions 2 11
22	Sample grain size distribution surves 2.12
2-3 2 A	Terminology used to describe shape of coarse grained soils (Mitchell 1076) 2.14
2- <del>4</del> 2 5	Conceptual changes in soil phases as a function of water content
2-3 2.6	Plasticity chart and significance of Atterberg Limits 2.18
2-0	Example calculation of a p_diagram
2-1 28	Schematic of vertical stress distribution under embankment loading. Graphic
2-0	generated by EoSSA (2003) program
20	Vertical stress contours (isobars) by Boussinesa's theory for continuous and
2-)	square footings (modified after Sowers 1070: AASHTO 2002) 2-25
2-10	Distribution of vertical stress by the 2:1 method
2-10	(after Perloff and Baron, 1976) 2-27
2-11	Combined plot of overburden pressures (total and effective) and pressure due
2-11	to imposed loads
2-12	Example calculation of <b>n</b> <sub>c</sub> with stress increments from strip load
212	$p_{\rm r}$ $p_{\rm r}$ $p_{\rm r}$ with stress merements from strip four $2_2$
2-13	Spring-piston analogy for the consolidation process of fine-grained soils 2-23
2-13 2-14	Comparison of excess pore water pressure dissipation in coarse-grained and
217	fine-grained soils
2-15	Schematic of effect of lateral stresses 2-35
2-15 2-16	Schematic of lateral stress increases beneath an embankment Graphic
2 10	generated by FoSSA (2003) 2-37
2-17	Basic concept of shearing resistance and strength (after Murthy 1980) 2-30
2-17 2-18	Graphical representation of shearing strength 2 41
2-10	Gruphear representation of shearing suchgui

2-19	Stress states on a soil element subjected only to body stresses: (a) In-situ geostatic effective vertical and horizontal stresses. (b) Insertion of	
	hypothetical infinitely rigid, infinitely thin frictionless wall and removal of	
	soil to left of wall, (c) Active condition of wall movement away from	
	retained soil, (d) Passive condition of wall movement into retained soil2-4	13
2-20	Development of Rankine active and passive failure zones for a smooth	
/	retaining wall	15
2-21	Failure surface, pressure distribution and forces	
	(a) active case, (b) passive case	16
2-22	General distribution of combined active earth pressure and water pressure 2-4	16
3-1	Recommended process for developing subsurface model for engineering	
	design (FHWA, 2002a)	-2
3-2	Typical weathering profile for metamorphic and igneous rocks (Deere and	
	Patton, 1971)	-8
3-3	Typical field reconnaissance form	14
3-4	Common in-situ tests for geotechnical site characterization of soils (FHWA, 2002b)	18
3-5	(a) Large diameter auger. (b) Small diameter continuous flight auger	21
3-6	(a) Solid stem auger and hollow stem auger (FHWA, 2002b), (b) Hollow	
00	stem auger components (ASTM D 4700), (c) Sizes of hollow stem auger	
	flights (FHWA, 2002b), (d) Outer and inner assembly of hollow stem auger	
	(FHWA, 2002b)	25
3-7	(a) Schematic of drilling rig for rotary wash methods (after Hyorsley, 1948).	
	(b) Typical drilling configuration. (c) Settling basin (mud tank)	27
3-8	Split barrel sampler	28
3-9	Schematic of thin-walled (Shelby) tube (after ASTM D 4700) and photo of	
	tube with end caps (FHWA, 2002b)	31
3-10	Stationary piston sampler schematic (after ASTM D 4700) and photo	
	(FHWA 2002b)	33
3-11	Denison sampler (FHWA, 1997)	33
3-12	Pitcher sampler (FHWA, 1997, 2002b)	34
3-13	Shelby tube sealing methods: (a) Microcrystalline Wax, (b) O-Ring packer.	
	(FHWA, 2002b)	38
3-14	(a) Single, (b) and (c) Double tube rock core barrels (FHWA, 1997)	39
3-15	Double tube core barrel. (a) Outer barrel assembly (b) Inner barrel assembly	
	(FHWA, 2002b)	10
3-16	Coring bits: Diamond (top left), Carbide (top right), and Sawtooth	
	(bottom center) (FHWA, 2001)	11
3-17	Modified core recovery as an index of rock mass quality (FHWA, 1997) 3-4	15
3-18	Length measurements for core RQD determination (FHWA, 1997)	16
3-19	Core box for storage of recovered rock and labeling	19
3-20	Sequence of driving split-barrel sampler during the Standard Penetration	
	Test (modified after FHWA, 2002b)	52
3-21	(a) Stainless steel and brass liners, (b) Sample catchers (FHWA, 2002b) 3-5	53
3-22	SPT hammer types, (a) Donut, (b) Safety, and (c) Automatic (FHWA, 2006). 3-5	54

3-23	SPT N-values from (a) Uncorrected data, and (b) Corrected to 60%	
	efficiency (Data modified after Robertson, et al. 1983)	3-56
3-24	Variation of overburden correction factor, $C_N$ , as a function of vertical	2 57
2 250	Example subsymptons and provide $\log (0, 25 \text{ ft depth})$	2 62
3-23a 2 25h	Example subsurface exploration log (0 - 55 ft depth)	3-05
2.26	Dreadynes and components of the Cone Departmention Test (EUWA 2002h)	2 60
2-20 2-27	Cone nonetrometer terminology (from Bohortson and Companella, 1080)	2 60
3-27	Cone and piezocone penetrometers (Note the Quarter for Scale)	5-09
3-28	(FHWA, 2002b)	3-70
3-29	Cone penetration testing from cone truck	3-71
3-30	Piezo-cone results for Apple Freeway Bridge	3-73
3-31	A commonly used simplified soil classification chart for standard electronic	
	friction cone (after Robertson, et al., 1986)	3-74
3-32	Dilatometer test equipment and procedure (FHWA, 2002b)	3-75
3-33	Pressuremeter test schematic (FHWA, 2002b)	3-76
3-34	Vane shear test equipment and procedure (after FHWA, 2002b)	3-77
3-35	Representative details of observation well installations. (a) Drilled-in place	
	stand-pipe piezometer, (b) Driven well point (FHWA, 1997)	3-80
4-1	Flow chart to determine the group symbol and group name for coarse-	
	grained soils (ASTM D 2488)	4-17
4-2	Evaluation of type of gradation for coarse-grained soils	4-20
4-3	Plasticity chart for Unified Soil Classification System (ASTM D 2488)	4-22
4-4a	Flow chart to determine the group symbol and group name for fine-grained soils (ASTM D 2488)	4-23
4-4b	Flow chart to determine the group symbol and group name for organic soils	
	(ASTM D 2488)	4-24
4-5	Range of liquid limit and plasticity index for soils in groups A-2, A-4, A-5,	
	A-6 and A-7 per AASHTO M 145 (or ASTM D 3282)	4-28
4-6	Comparison of the USCS with the AASHTO Soil Classification System	
	(after Utah DOT – Pavement Design and Management Manual, 2005)	4-29
4-7	Comparison of soil groups in the USCS with the AASHTO Soil	
	Classification Systems (Holtz and Kovacs, 1981)	4-30
4-8	Example boring location plan (FHWA, 2002a)	4-47
4-9	Example interpreted subsurface profile (FHWA, 2002a)	4-48
5 1	Seconda la la la constructione de la construct	
5-1	sample laboratory lest request form (Note: Only some lests are included in this sample form)	53
5_2	Example grain size distribution based on sieve analysis (Jumikis, 1962)	5_14
5-3	Grain size distribution curve based on data in Figure 5-2	5-14
5- <i>1</i>	Some of the equipment used for Atterberg Limits testing of soil	5-17
5- <u>-</u>	Location of clay minerals on the Casagrande Plasticity Chart and Activity	5-17
55	Index values (after Skempton 1953 Mitchell 1976 Holtz and	
	Kovacs (1981)	5-18
5-6	Schematic of a consolidation test	5_27/
5-0		5-24

5-7	(a) Components of consolidation test equipment, (b) Weighted lever arm –	
	incremental load consolidation apparatus, (c) Automatic load frame and	
	computerized consolidation apparatus	
	(Photo courtesy of GeoComp Corporation)	. 5-25
5-8	Consolidation test relationships (after NAVFAC, 1986a)	. 5-27
5-9	Empirical correlation between Compression Index and natural (in-situ) water	•
	content (from Terzaghi, et al., 1996)	. 5-34
5-10	Approximate correlations between c <sub>v</sub> and LL (NAVFAC, 1986a)	. 5-36
5-11	Correlation between $C_{\alpha e}$ and natural water content (NAVFAC, 1986a)	. 5-37
5-12	Potential contributions of various bonding mechanisms to cohesive strength	
	(Ingles, 1962)	. 5-41
5-13	Schematic of an unconfined compression test	. 5-44
5-14	Schematic of a triaxial compression test (Lambe and Whitman, 1979)	. 5-45
5-15	(a) Failure of a loose sand specimen in a triaxial cell; and (b) Load frame,	
	pressure panel, and computerized data acquisition system (Photograph	
	courtesy of GeoComp Corporation)	. 5-46
5-16	Typical stress-strain curves from CU test	. 5-48
5-17	Schematic of the Direct Shear Test	. 5-49
5-18	Direct shear testing box (Photograph courtesy of GeoComp Corporation)	. 5-50
5-19	Soil sample mounted in direct shear testing apparatus (Photograph courtesy	
	of GeoComp Corporation)	. 5-50
5-20	Relationship between the ratio of undrained shear strength to effective	
	overburden pressure and plasticity index for normally-consolidated and	
	overconsolidated clays (after Holtz and Kovacs, 1981)	. 5-54
5-21	Relationships between $\phi$ and PI (after Terzaghi, <i>et al.</i> , 1996)	. 5-56
5-22	Correlation between relative density, material classification and angle of	
	internal friction for coarse-grained soils (NAVFAC, 1986a)	. 5-57
5-23	Correlation between relative density and SPT resistance	
	(NAVFAC, 1986a)	. 5-57
5-24	Rigid wall permeameter (Photograph courtesy of GeoComp Corporation)	. 5-59
5-25	Flexible wall permeameter (Photograph courtesy of GeoComp Corporation).	. 5-60
5-26	The permeability of sands and gravels (after NAVFAC, 1986a)	. 5-64
5-27	Classification of swell potential for soils (after Seed, et al., 1962)	. 5-66
5-28	Chart for evaluation of collapsible soils (after Holtz and Hilf, 1961)	. 5-68
5-29	Approximate frost depth map for United States (Bowels, 1996)	. 5-71
5-30	Hammer and mold for laboratory compaction test (tape measure is for scale	
	purpose only	. 5-73
5-31	Compaction curves (after Holtz and Kovacs, 1981)	. 5-74
5-32	Compactors recommended for various types of soil and rock	
	(Schroeder, 1980)	. 5-77
5-33	Relative density, relative compaction and void ratio concepts	. 5-78
5-34	Example evaluation of economical field compaction conditions	
	(after Bowles, 1979)	. 5-81
5-35	Point load strength test equipment (Wyllie, 1999)	. 5-89
5-36	(a) Unconfined compression test on intact rock core, (b) Use of strain gage	

	on intact rock core sample for measurement of stress-strain characteristics	<b>z</b> 0 <b>2</b>
	(Geomechanical Laboratory, University of Arizona)	. 5-92
5-37	Laboratory direct shear testing equipment for rock (Wyllie, 1999)	. 5-93
6-1	Embankment failures: (a) Infinite slope failure in embankment fill,	
	(b) Circular arc failure in embankment fill and foundation soil,	
	(c) Sliding block failure in embankment fill and foundation soil, and	
	(d) Lateral squeeze of foundation soil	6-2
6-2	Effect of water content on cohesive strength of clay	6-4
6-3	Infinite slope failure in dry sand	6-6
6-4	Infinite slope failure in a c- $\phi$ soil with parallel seepage	6-7
6-5	Typical circular arc failure mechanism	6-9
6-6	Example proposed embankment	. 6-10
6-7	Geometry of Ordinary Method of Slices	. 6-12
6-8	Example of dividing the failure mass in slices	. 6-13
6-9	Forces on a slice without water effect	. 6-15
6-10	Forces on a slice with water effect	. 6-15
6-11a	Tabular form for computing weights of slices	. 6-18
6-11b	Tabular form for calculating factor of safety by Ordinary Method of Slices	. 6-19
6-12	Typical static forces acting on a slice of sliding mass without seepage	. 6-20
6-13	Location of critical circle by plotting contours of minimum safety factors	
	for various trial circles	. 6-23
6-14	Taylor's chart for soils with friction angle (after Taylor, 1948)	. 6-27
6-15	Taylor's chart for $\phi'=0$ conditions for slope angles ( $\beta$ ) less than 54° (after Taylor, 1948)	6 28
6 16	1001, 1940)	6 24
6 17	Stability charts for $\psi = 0$ solis (Jalibu, 1908)	. 0-34
0-1/	shorts for the 0 and the 0 and the 1068	6.26
c 10	charts for $\phi=0$ and $\phi > 0$ solis (Janbu, 1968)	. 0-30
0-18	Reduction factors to account for surcharge (upper) and submergence and/or	
	seepage (lower) to be used with stability charts for $\phi=0$ and $\phi > 0$ solis	   
C 10	(Janbu, 1908)	. 0-3/
6-19	Stability charts for $\phi > 0$ (Janbu, 1968)	. 0-39
6-20	Data for Example 6-2	. 0-41
6-21	Sliding block failure mechanism	. 0-43
6-22	Geometry and force components for sliding block analysis	. 6-44
0-25	Deduction of grade line to improve along stability	. 0-40
0-24	Lise of counterweight how to improve slope stability	. 0-32
6 26	Use of char key to improve slope stability	6 52
0-20 6 27	Eailure modes for Deinforced Soil Slopes	. 0-32 6 52
6 29	Chart solution for determining the rainforcement strength requirements	. 0-33
0-28	(Schwartmann, at al. 1987). The Tensor Corneration	6 55
6_20	Deep seated slope failure (left) and bench slope design (right) to provent	. 0-33
0-27	slope failure	6-57
6-30	Typical cut slope failure mechanism in clay soils	6-58
0-30	rypical cut slope famile meenamsin in clay solis	.0-30

7-1	(a) Elements of a bridge approach system, (b) Plan view of an approach system (modified after NCHRP, 1997) 7-2
7-2	Types of abutments (modified after NCHRP 1990) 7-3
7-3	Problems leading to the existence of a hump (modified after NCHRP 1997) 7-4
7-4	Suggested approach embankment details
7-5	Structural backfill placement limits for porous drainage aggregate
7-6	Pressure coefficients beneath the end of a fill (NYSDOT, 1970)
7-7	Bearing capacity index (C') values used in Modified Hough method for
	computing immediate settlements of embankments (AASHTO, 2004 with
	2006 Interims; modified after Hough, 1959)
7-8	Effect of sample disturbance on the shape of the one-dimensional
	consolidation curve (Reese, <i>et al.</i> , 2006)
7-9	Construction of field virgin consolidation relationships (adapted from
	USACE, 1994)
7-10	Typical consolidation curve for normally consolidated soil – (a) Void ratio
	versus vertical effective stress and (b) Vertical strain versus vertical
	effective stress
7-11	Typical consolidation curve for overconsolidated soil – (a) Void ratio versus
	vertical effective stress and (b) Vertical strain versus vertical effective stress. 7-26
7-12	Typical consolidation curve for under-consolidated soil – (a) Void ratio
	versus vertical effective stress and (b) Vertical strain versus vertical
	effective stress7-27
7-13	Diagram illustrating consolidation of a layer of clay between two pervious
	layers (modified after Terzaghi, et al., 1996)7-28
7-14	Typical settlement-time curve for clay under an embankment loading7-32
7-15	Logarithm-of-time method for determination of c <sub>v</sub>
7-16	Square-root-of-time method for determination of c <sub>v</sub>
7-17	Example time plot from one-dimensional consolidometer test for
	determination of secondary compression (USACE, 1994)7-39
7-18	Schematic of lateral squeeze phenomenon
7-19	Examples of abutment tilting due to lateral squeeze (FHWA, 2006a)
7-20	Definitions for calculating safety factor against later squeeze (after Silvestri, 1983)
7-21	Determination of surcharge time required to achieve desired settlement
7-22	Use of vertical drains to accelerate settlement
7-23	Typical locations for various types of monitoring instruments for an
	embankment constructed over soft ground
	-

### LIST OF TABLES

<u>No.</u>	Caption	<u>Page</u>
1-1	Geotechnical involvement in project phases	1-9
2-1	Summary of index properties and their application	2-8
2-2	Weight-volume relations (after Das, 1990)	2-8
2-3	U.S. standard sieve sizes and corresponding opening dimension	. 2-10
2-4	Concept of soil phase, soil strength and soil deformation based on Liquidity	
	Index	. 2-17
3-1	Sources of historical site data (after FHWA, 2002a)	3-4
3-2	Common landforms of transported soils and their engineering significance	. 3-10
3-3	Reference publications on in-situ testing (FHWA, 2002b)	. 3-19
3-4a	Soil and soft rock boring methods (FHWA, 2002a)	. 3-22
3-4b	Rock core drilling methods (FHWA, 2002a)	. 3-23
3-4c	Other exploratory techniques (FHWA, 2002a)	. 3-24
3-5a	Common samplers to retrieve disturbed soil samples	
	(modified after NAVFAC, 1986a)	. 3-29
3-5b	Common samplers to retrieve disturbed soil samples	
	(modified after NAVFAC, 1986a)	. 3-30
3-6	Nominally undisturbed soil samplers (modified after NAVFAC, 1986a)	. 3-32
3-7	Dimensions of core sizes (FHWA, 1997)	. 3-41
3-8	Advantages and disadvantages of the Standard Penetration Test (SPT)	. 3-51
3-9	Soil properties correlated with Standard Penetration Test values	
	(after Peck. <i>et al.</i> , 1974)	. 3-58
3-10	Factors affecting the SPT and SPT results (after Kulhawy and Mayne, 1990)	. 3-61
3-11	Advantages and disadvantages of the Cone Penetration Test (CPT)	
	(FHWA, 2002b)	. 3-67
3-12	Classification of Sensitivity Values (Mitchell, 1976)	.3-78
3-13	Guidelines for minimum number of exploration points and depth of	
	exploration (modified after FHWA, 2002a)	. 3-84
3-14	Geophysical testing techniques (modified after FHWA, 2002a)	. 3-91
4-1	Evaluation of the apparent density of coarse-grained soils	
	(after Peck, et al., 1974)	4-5
4-2	Evaluation of the consistency of fine-grained soils (after Peck, et al., 1974).	4-5
4-3	Adjectives to describe water content of soils (ASTM D 2488)	4-6
4-4	Particle size definition for gravels and sands (after ASTM D 2488)	4-7
4-5	Adjectives for describing size distribution for sands and gravels (after ASTM	I
-	D 2488)	4-8
4-6	Field methods to describe plasticity (FHWA, 2002b)	.4-10
4-7	Descriptive terms for layered soils (NAVFAC. 1986a)	. 4-13
4-8	Basic USCS soil designations based on percents passing No. 200 (0.075mm)	
-	Sieve (after ASTM D 2487; Holtz and Kovacs, 1981)	. 4-14

4-9	Soil classification chart (laboratory method) (after ASTM D 2487)	. 4-15
4-10	Gradation based on C <sub>u</sub> and C <sub>c</sub> parameters	. 4-19
4-11	Soil plasticity descriptors (based on Figures 4-3, 4-4a and 4-4b)	. 4-25
4-12	Examples of description of fine-grained soils (based on Figures 4-3, 4-4a and	l
	4-4b)	. 4-25
4-13	AASHTO soil classification system based on AASHTO M 145 (or	
	ASTM D 3282)	. 4-27
4-14	Example gradation limits of well-graded granular material (see Curve A in	
	Figure 4-2)	. 4-33
4-15	Example gradation limits of drainage materials (see Curve C in Figure 4-2)	. 4-33
4-16	Rock groups and types (FHWA, 1997)	. 4-35
4-17	Terms to describe grain size (typically for sedimentary rocks)	. 4-36
4-18	Terms to describe grain shape (for sedimentary rocks)	. 4-36
4-19	Terms to describe stratum thickness	. 4-37
4-20	Terms to describe rock weathering and alteration (ISRM, 1981)	. 4-38
4-21	Terms to describe rock strength (ISRM, 1981)	. 4-38
4-22	Terms to describe rock hardness (FHWA, 2002b)	. 4-39
4-23	Terms to describe discontinuities (after ISRM, 1981)	. 4-40
4-24	Terms to classify discontinuities based on aperture size (ISRM, 1981)	. 4-40
4-25	Geomechanics classification of rock masses (AASHTO 2004	
	with 2006 Interims)	. 4-43
4-26	Geomechanics rating adjustment for joint orientations (after AASHTO 2004	
	with 2006 Interims)	. 4-44
4-27	Geomechanics rock mass classes determined from total ratings (AASHTO	
	2004 with 2006 Interims)	. 4-44
5 1	Commente a formed to be active to the end of the FUNDA 2002-)	5 (
5-1 5-2	Mothe de fan in deu testing of goile (after FHWA, 2002a)	3-0
5-2 5-2	Methods for index testing of soils (after FHWA, 2002a)	)-/
5-5 5-1	Turical neutial sizes uniformity coefficients used ratios and unit weights	3-8
3-4	(from Kulhawa and Mayne, 1990)	5 12
5 5	Correlations for C (modified after Holtz and Koyacs, 1081)	5 22
5-5 5-6	Typical values of coefficient of vertical consolidation $c_{c}$ (after Carter and	. 5-55
5-0	Reptley 1991)	5-36
5_7	Typical values of $C_{-}/C_{-}$ (Terzaghi <i>et al.</i> 1996)	5_37
5-8	Summary of issues relevant to shear strength evaluation in support of the	. 5-57
5-0	design of typical geotechnical features (after FHWA 2002a)	5-39
5-9	Recommended maximum hydraulic gradient for permeability testing	5-61
5-10	Typical permeability values in soils (after Carter and Bentley 1991)	5-63
5-11	Typical permeability values for highway materials (after Krebs and	. 5 05
5-11	Walker 1971)	5-63
5-12	Qualitative assessment of collapse potential (after ASTM D 5333)	5-69
5-13	Characteristics of laboratory compaction tests	5-73
5-14	Some values of D <sub>c</sub> as a function of RC based on Modified and Standard	. 5 1 5
~ 1 1	Proctor Compaction Test	5-79
5-15	Average engineering properties of compacted inorganic soils	

	(after USBR, 1960)
5-16	Elastic constants of various soils (after AASHTO 2004 with 2006 Interims) 5-85
5-17	Rate of increase of soil modulus with depth $n_h$ (tsf/ft) for sand
	(AASHTO 2004 with 2006 Interims)
5-18	Common sense guidelines for laboratory testing of soils
5-19	Common rock tests performed in the laboratory
5-20	Summary information on rock laboratory test methods (FHWA, 2002a) 5-88
5-21	Summary of elastic moduli for intact rock (AASHTO 2004 with
	2006 Interims)
5-22	Summary of Poisson's Ratio for intact rock (AASHTO 2004 with
	2006 Interims)
5-23	Estimation of E <sub>m</sub> based on RQD (AASHTO 2004 with 2006 Interims)5-96
5-24	Common sense guidelines for laboratory testing of rocks
5-25	Values of coefficient of variation, V, for geotechnical properties and in-situ
	tests (after Duncan, 2000)
6-1	Slope stability guidelines for design
6-2	Practical design solutions to mitigate embankment stability problems
6-3	Typical design solutions to mitigate cut slope stability problems
7-1	General considerations for specification of select structural backfill7-9
7-2	Suggested gradation for drainage aggregate7-9
7-3	Reconstruction of virgin field consolidation (modified from USACE, 1994)7-23
7-4	Average degree of consolidation, U, versus time factor, $T_v$ , for uniform
	initial increase in pore water pressure7-32
7-5	Summary of abutment movements (Nicu, et al., 1971)7-43

### LIST OF SYMBOLS

#### Chapter 1

AASHTO	American Association of State Highway and Transportation Officials
AC	Asphaltic concrete
CMAR	Construction manager at risk
D-B	Design-build
FHWA	Federal Highway Administration
MSE	Mechanically stabilized earth
NHI	National Highway Institute
NMDOT	New Mexico Department of Transportation
PCC	Portland cement concrete
RCC	Reinforced cement concrete
RSS	Reinforced soil slope(s)
USDA	United States Department of Agriculture
USGS	Unites States Geological Survey

## Chapter 2

А	Overall contact area
AASHTO	American Association of State Highway and Transportation Officials
В	Width
с	Cohesion
c'	Effective cohesion
D <sub>r</sub>	Relative density
D <sub>s</sub> , DOSI	Depth of significant influence
e	Void ratio
e <sub>max</sub>	Maximum void ratio
e <sub>min</sub>	Minimum void ratio
Fa	Tangential force
F <sub>r</sub>	Shearing resistance
G	Specific gravity
Gs	Specific gravity of the solid phase
h	Embankment height
$h_w$	Depth to water table
Κ	Value of proportionality constant; coefficient of lateral earth pressure
Ka	Coefficient of active earth pressure
Ko	Coefficient of lateral earth pressure "at rest"
K <sub>p</sub>	Coefficient of passive earth pressure
K <sub>w</sub>	Coefficient of lateral earth pressure for water
L	Length
LI	Liquidity index
LL	Liquid limit
n	Porosity
Р	Load applied
pa	Active lateral pressure

<b>p</b> <sub>f</sub>	Final stress = effective overburden pressure + pressure increment due to
-	external loads
$\mathbf{p}_{\mathrm{h}}$	Lateral stress
PI	Plasticity index
PL	Plastic limit
P <sub>n</sub>	Normal force
po	Effective overburden pressure
p <sub>p</sub>	Passive lateral pressure
$p_t$	Total overburden pressure
Q	Load
$q, q_o$	Unit load of embankment
S	Degree of saturation
SI	Shrinking index
SL	Shrinkage limit
t	time
u	Porewater pressure
USCS	Unified Soil Classification System
V	Volume of the total soils mass
Va	Volume of air phase
$V_s$	Volume of solid phase
$V_{v}$	Volume of total voids
$V_{w}$	Volume of water phase
W	Gravimetric water or moisture content
W	Weight of the total soil mass
$\mathbf{W}_{\mathrm{a}}$	Weight of air phase
$\mathbf{W}_{\mathbf{s}}$	Weight of solid phase
$\mathbf{W}_{\mathrm{v}}$	Weight of total voids
$W_{w}$	Weight of water phase
Z	Depth
Zw	Depth below water table
δ	Angle of interface friction
$\delta_a$	active translation
$\delta_b$	passive translation
Δp	Pressure due to external loads
Δu	Excess pore water pressure
γ	Total unit weight
γ'	Effective unit weight
$\gamma_b$	Buoyant unit weight (same as effective unit weight)
$\gamma_d$	Dry unit weight
$\gamma_{s}$	Unit weight of the solid phase
$\gamma_{sat}$	Saturated unit weight
$\gamma_{\rm T}$ or $\gamma_{\rm t}$	Total unit weight
γ <sub>w</sub>	Unit weight of water
φ	Angle of friction
ф'	Effective angle of internal friction
	U

ν	Poisson's ratio
θ	Angle of obliquity
$\theta_{\rm m}$	Maximum angle of obliquity
σ	Total stress
σ'	Effective stress
$\sigma_{n}$	Normal stress
$\sigma_n'$	Effective normal stress
τ	Shearing strength
τ'	Effective shear stress (strength)
Chapter 3	
AASHTO	American Association of State Highway and Transportation Officials
AR	Area ratio
ASTM	American Society for Testing and Materials
BPT	Becker (Hammer) penetration test
C <sub>N</sub>	Overburden correction factor or stress normalization parameter
CPT	Cone penetration test
CPTu PCPT	Piezocone penetration test
d	Displacement
	Displacement
D	Diameter of sampler cutting tin
D <sub>e</sub>	Inside diameter of the sampling tube
$D_1$	Flat plate dilatometer
D	Outside diameter of the sampling tube
	Department of Transportation
DOI	Energy officiency
Ef	Energy enficiency
EK	Energy ratio
FEMA	Federal Emergency Management Agency
FHWA	Federal Highway Administration
I <sub>s</sub>	Sleeve friction
g	Gravitational constant
GPR	Ground penetrating radar
h	Drop height
1	Inclination
ICR	Inside clearance ratio
ID	Inside Diameter
ISRM	International Society of Rock Mechanics
KE	Kinetic energy
LPT	Large penetration test
m	Mass
Ν	SPT blows per foot
N1 <sub>60</sub>	Overburden-normalized energy-corrected blowcount
N <sub>60</sub>	Energy-corrected SPT-N value adjusted to 60% efficiency
NAVFAC	Naval Facilities Engineering Command
NCR	No core recovery

N <sub>meas</sub>	N-Value measured in the field
OD	Outside diameter
PE	Potential energy
PMT	Pressuremeter test
po	Vertical effective pressure at the depth where the SPT is performed
PVC	Polyvinyl chloride
q <sub>c</sub>	Cone tip resistance
$q_t$	Tip resistance
$R_{\mathrm{f}}$	Friction ratio
RQD	Rock quality designation
$\mathbf{S}_{\mathbf{t}}$	Sensitivity
SASW	Spectral analysis of surface waves
SBT	Soil behavioral type
SCPTu	Seismic cone piezocone penetration test
SPT	Standard Penetration Test
SWPPP	Storm Water Pollution Prevention Plan
ts	Shear wave time
u <sub>m</sub>	Pore water pressure
USCS	Unified Soil Classification System
USEPA	United States Environmental Protection Agency
USGS	Unites States Geological Survey
V	Impact velocity
VST	Vane shear test
W	Work

#### Chapter 4

AASHTO	American Association of State Highway and Transportation Officials			
ASTM	American Society for Testing and Materials			
Cc	Coefficient of curvature			
Cu	Coefficient of uniformity			
D <sub>10</sub>	Diameter of soil particles of which 10% of the soil is finer			
D <sub>30</sub>	Diameter of soil particles of which 30% of the soil is finer			
D <sub>60</sub>	Diameter of soil particles of which 60% of the soil is finer			
DOT	Department of Transportation			
EGS	Effective grain size			
F	Percent passing No. 200 sieve			
FHWA	Federal Highway Administration			
GI	Group index			
GIS	Geographic information system			
GSD	Grain size distribution			
IGM	Intermediate geomaterial			
Is	Point load index			
ISRM	International Society of Rock Mechanics			
LI	Liquid index			
LL	Liquid limit			
Ν	SPT blows per foot			
N <sub>60</sub>	Energy-corrected SPT-N value adjusted to 60% efficiency			
----------------------	--	--	--	--
NAVFAC	Naval Facilities Engineering Command			
PI	Plasticity index			
PL	Plastic limit			
RMR	Rock mass rating			
RQD	Rock quality designation			
SPT	Standard penetration test			
U.S.	United States			
USCS	Unified Soil Classification System			
USDA	United States Department of Agriculture			
Chapter 5				
A	Activity index			
А	Area			
AASHTO	American Association of State Highway and Transportation Officials			
ASTM	American Society for Testing and Materials			
В	Bulk modulus			
с	Cohesion			
С	Permeability coefficient			
$C_{\alpha}$	Coefficient of secondary compression			
c'	Effective stress cohesion intercept			
c' <sub>cu</sub>	Effective stress cohesion from CU test			
CBR	California Bearing Ratio			
C <sub>c</sub>	Compression index			
C <sub>ce</sub>	Modified compression index			
CD	Consolidated drained triaxial test			
CF	Clay fraction			
c <sub>h</sub>	Coefficient of horizontal consolidation			
co	Compacted cohesion			
СР	Collapse potential			
Cr	Recompression index			
C <sub>rε</sub>	Modified recompression index			
c <sub>sat</sub>	Saturated cohesion			
CU	Consolidated undrained triaxial test			
c <sub>u</sub>	Apparent cohesion			
c <sub>v</sub>	Coefficient of consolidation			
c <sub>v</sub>	Coefficient of vertical consolidation			
$C_{\alpha}$	Secondary compression index			
$C_{\alpha\epsilon}$	Modified secondary compression index			
D	Distance between contact points of platens			
D	Vane diameter			
D <sub>10</sub>	Diameter of soil particles of which 10% of the soil is finer			
D <sub>60</sub>	Diameter of soil particles of which 60% of the soil is finer			
De	Equivalent core diameter			
D <sub>max</sub>	Maximum diameter of soil particle			
$D_{min}$	Minimum diameter soil particles			

D <sub>r</sub>	Relative density		
ds	Equivalent diameter		
e	Void ratio		
e <sub>max</sub>	Maximum void ratio		
e <sub>min</sub>	Minimum void ratio		
Е	Young modulus		
Ei	Elastic modulus of intact rock		
Em	Elastic modulus of rock mass		
e <sub>max</sub>	Maximum void ratio		
e <sub>min</sub>	Minimum void ratio		
eo	Initial void ratio		
E or E <sub>s</sub>	Elastic modulus		
FHWA	Federal Highway Administration		
g	Gravitational constant		
Ğ	Shear modulus		
Gs	Specific gravity		
Н	Height of vane		
Н	Soil layer thickness		
H/D	Height to diameter ratio		
H <sub>o</sub>	Initial height of specimen		
iB	Angle of taper at the bottom of the vane		
ĨĹ	Incremental load		
Is	Point load strength index		
$I_{s(50)}$	Size-corrected point load strength index		
i <sub>T</sub>	Angle of taper at the top of the vane		
k	Hydraulic conductivity		
k <sub>PLT</sub>	Size correction factor		
LI	Liquid index		
LIR	Load increment ratio		
LL	Liquid limit		
LVDT	Linear variable differential transducer		
md	Man-days		
MPC	Modified Proctor compaction		
Ms	Mass of solid component of sample		
M <sub>t</sub>	Total mass		
Ν	Normal stress		
Ν	SPT blows per foot		
N1 <sub>60</sub>	Overburden-normalized energy-corrected blowcount		
N <sub>60</sub>	Energy-corrected SPT-N value adjusted to 60% efficiency		
NAVFAC	Naval Facilities Engineering Command		
NC	Normally consolidated		
n <sub>h</sub>	Rate of increase of soil modulus with depth		
OC	Over consolidated		
OCR	Overconsolidation ratio		
OMC	Optimum moisture content		
Р	Breaking load		

pc	Maximum past effective stress
p <sub>c</sub>	Preconsolidation pressure
PI	Plasticity index
PL	Plastic limit
$\mathbf{p}_{\mathbf{o}}$	Effective overburden pressure
$p_t$	Total vertical stress
$q_c$	Cone tip resistance
$q_{u}$	Unconfined compression stress
RC	Relative compaction
RMR	Rock mass rating
RQD	Rock quality designation
S	Degree of saturation
S, S <sub>t</sub>	Sensitivity
S <sub>collapse</sub>	Collapse settlement
SL	Shrinkage limit
SPC	Standard Proctor compaction
SPT	Standard penetration test
s <sub>r, VST</sub>	Remolded undrained shear strength (obtained by using VST data)
St, VST	Sensitivity (obtained by using VST data)
Su	Undrained shear strength
S <sub>u, VST</sub>	Undrained shear strength (obtained by using VST data)
$s_u/p_o$	Undrained strength ratio
Т	Tangential (shear) force
Т	Torque (related to VST)
t	Vane edge thickness
t <sub>100</sub>	Time corresponding to 100% of primary consolidation
$T_{max}$	Maximum torque (related to VST)
T <sub>net</sub>	Difference between T <sub>max</sub> and T <sub>rod</sub>
$T_{rod}$	Rod friction (related to VST)
u	Pore water pressure
UC	Unconfined compression test
U.S.	United States
USBR	United States Bureau of Reclamation
USCS	Unified Soil Classification System
UU	Unconsolidated undrained triaxial test
V	Coefficient of variation
$V_s$	Volume of soil solids
VST	Vane shear test
$\mathbf{V}_{\mathrm{t}}$	Total volume
W	Specimen width
W	Water content
Wn	Natural moisture content
Wopt	Optimum moisture content
$\mathbf{W}_{\mathbf{s}}$	Weight of solid component of soil
$\mathbf{W}_{t}$	Total weight
Z	Depth below ground surface

Δe	Change in void ratio
$\Delta H_c$	Change in height upon wetting
$\Delta \sigma$	Incremental stress
3	Strain
γ	Unit weight
γ'	Effective unit weight
$\gamma_b$	Buoyant unit weight (same as effective unit weight)
$\gamma_{d field}$	Field dry unit weight
$\gamma_{\rm d}$ or $\gamma_{\rm dry}$	Dry unit weight
γ <sub>d-max</sub>	Maximum dry unit weight
$\gamma_{s}$	Unit weight of solid particles in the soil mass
$\gamma_{sat}$	Saturated unit weight
$\gamma_t$ or $\gamma_{tot}$	Total unit weight
$\gamma_t$	Moist unit weight of compacted soil
$\gamma_{\rm w}$	Unit weight of water
φ	Angle of internal friction
φ'	Effective friction angle
φ	Friction
φ'	Peak effective stress friction angle
φ' <sub>cu</sub>	Effective friction angle from CU test
φ'r	Residual effective stress friction angle
μ	Coefficient of friction
ν	Poisson ratio
ρ	Density
$\rho_d \text{ or } \rho_{dry}$	Dry mass density
$\rho_t \text{ or } \rho_{tot}$	Total mass density
$\rho_t$	Moist (total) mass density
σ'	Effective normal stress
$\sigma_{c}$	Uniaxial compressive strength
$\sigma_n$	Normal stress
$\sigma'_p$	Preconsolidation stress
$\sigma_{vo}$	Total vertical stress
τ	Shear stress
%C	Percent collapse

Chapter 6	
AASHTO	American Association of State Highway and Transportation Officials
b	Unit width
b	Width of slice
с	Cohesion
с	Cohesion component of shear strength
с	Unit cohesion
c'	Effective cohesion
CD	Consolidated drained triaxial test
Cd	Developed cohesion
ČU	Consolidated undrained triaxial test
d	Depth factor
D	Depth ratio
- F <sub>c</sub>	Average factor of safety with respect to cohesion
FHWA	Federal Highway Administration
FS or FOS	Factor of safety
F <sub>+</sub>	Average factor of safety with respect to friction angle
-Ψ h	Depth less than or equal to the depth of saturation
Н	Height
Н	Height of soil layer in active wedge
h	Slope depth
Н	Slope height
H'w	Height of water within the slope
H <sub>Fill</sub>	Fill height
h;	Height of laver at center of slice
H <sub>t</sub>	Tension crack height
hw	Depth from groundwater surface to the centroid point on the circle
	Depth of water outside the slope
H <sub>zone</sub>	Height of zone
I <sub>N</sub>	Interslice normal (horizontal) force
Is	Interslice shear (vertical) force
Ка	Coefficient of active earth pressure
K <sub>n</sub>	Coefficient of passive earth pressure
1	Arc length of slice base
Ls	Radius of circle
Lw	Level arm distance to the center of rotation
Ň	Normal force component or total normal force
N	Number of reinforcement layers
N'	Effective normal force component
N <sub>ef</sub>	Critical stability number
N <sub>o</sub>	Stability number
N <sub>a</sub>	Stability number
P <sub>a</sub>	Active force (driving)
- a Do	In-situ vertical effective overburden pressure
ru P.	Passive force (resisting)
• p	Surcharge load
Ч	Surenui 5e Iouu

R	Moment arm
R <sub>c</sub>	Coverage ratio of the reinforcement
RSS	Reinforced soil slope
S	Frictional force along failure plane
S	Shear strength along failure plane
SPT	Standard penetration test
$S_v$	Vertical spacing of reinforcement
Т	Tangential force component
Ta	Sum of available tensile force per width of reinforcement for all reinforcement layers
tan ø	Coefficient of friction along failure surface
T <sub>MAX</sub>	Maximum design tension
T <sub>S-MAX</sub>	Maximum tensile force
T <sub>zone</sub>	Maximum reinforced tension required for each zone
U	Pore water force
u	Water pressure on slice base
u	Water uplift pressure against failure surface
UU	Unconsolidated undrained triaxial test
W	Weight of slice
Wi	Partial weight
W <sub>T</sub>	Total slice weight
α	Angle between vertical and line drawn from circle center to midpoint of slice base
$\alpha_{\rm w}$	Slope of water table from horizontal
$\gamma_{\rm Fill}$	Fill soil unit weight
μ' <sub>w</sub>	Seepage correction factor
$\mu_q$	Surcharge correction factor
$\mu_t$	Tension crack correction factor
$\mu_{\rm w}$	Submergence correction factor
σ	The total normal stress against the failure surface slice base due to the weight of soil and water above the failure surface
$\Sigma W_i$	Total weight of slice
β	Angle of slope
β	Inclination of the slope
φ	Angle of internal friction
φ'	Effective angle of internal friction
Φd	Developed angle of internal friction
γ	Unit weight of soil
γ	Unit weight of soil in the active wedge
γ <sub>i</sub>	Unit weight of layer i
γ	Effective unit weight
γ	Moist unit weight
v m V	Saturated unit weight
I sat	Total soil unit weight
Ϋ́t	I Utal SOIL UIIIT WEIGHT
$\gamma_{ m w}$	Unit weight of water

$\sigma'_n$	Effective stress between soil grains
τ	Frictional shearing resistance
τ	Total shear strength
$\tau_d$	Developed shear strength

## Chapter 7

AASHTO	American Association of State Highway and Transportation Officials
C′	Bearing capacity index
$C_c$	Compression index
$C_{c\epsilon}$	Modified compression index
Cr	Mean slope of the rebound laboratory curve
Cre	Modified recompression index
C <sub>v</sub>	Coefficient of consolidation
$C_{\alpha}$	Coefficient of secondary consolidation (determined from lab consolidation test)
Car	Modified secondary compression index
$D_{S}$	Depth of soft soil beneath the toe of the end slope of the embankment
e	Void ratio
eo	Initial void ratio at $p_0$
FHWA	Federal Highway Administration
FS <sub>SO</sub>	Safety factor against failure by squeezing
H	Height of the fill
Н	Thickness of soil layer considered
$H_d$	Distance to the drainage boundary
h <sub>f</sub>	Fill height
H <sub>o</sub>	Layer thickness
ID	Inner Diameter
N1 <sub>60</sub>	Number of blows per foot corrected for overburden and hammer efficiency
NCHRP	National Cooperative of Highway Research Program
OCR	Over consolidation ratio
p <sub>c</sub>	Maximum past effective stress
p <sub>c</sub>	Maximum past vertical pressure (preconsolidation)
$p_{\rm f}$	Final effective vertical stress at the center of layer n
$p_{\rm f}$	Final pressure applied to the foundation subsoil
$p_{\rm f}$	Final stress
$p_{\rm f}$	Total embanklment pressure
PI	Plasticity index
po	Effective overburden pressure
po	Existing effective overburden pressure
po	Initial effective vertical stress at the center of layer n
RSS	Reinforced soil slope
S	Degree of saturation
S	Settlement
S <sub>c</sub>	Settlement due to primary consolidation
SPT N	Number of blows per foot (blow/0.3m)
SPT	Standard penetration test

XXVIII ENGINEERING-PDH.COM | GEO-115 |

S <sub>s</sub> Settlement due to secondary compression				
S <sub>t</sub> Settlement at time t				
s <sub>u</sub> Undrained shear strength of soft soil beneath e	mbankment			
Sultimate Settlement at end of primary consolidation	Settlement at end of primary consolidation			
t Time				
t <sub>1 lab</sub> Time when secondary compression begins				
t <sub>1</sub> Time when approximately 90% of primary con	npression has occurred			
t <sub>100</sub> Time for 100% of primary consolidation				
t <sub>2 lab</sub> Arbitrary time on the curve				
t <sub>2</sub> The service life of the structure or any time of	interest			
t <sub>90</sub> Time for 90% of primary consolidation				
T <sub>v</sub> Time factor				
U Average degree of consolidation				
u <sub>s</sub> Hydrostatic pore water pressure at any depth				
u <sub>s</sub> Initial hydrostatic pore water pressure				
USACE United States Army Corps of Engineers				
u <sub>sb</sub> Hydrostatic pore water pressure at bottom of la	nyer			
u <sub>st</sub> Hydrostatic pore water pressure at top of layer				
ut Total pore water pressure at any depth after tim	ne t			
Z <sub>I</sub> Zone of influence				
$\Delta e$ Change in void ratio				
ΔH Settlement				
$\Delta p$ Distributed embankment pressure				
Δp Load increment				
$\Delta p$ Stress increase				
Δp <sub>o</sub> Effective vertical stress increment				
Δpt Applied vertical stress increment				
$\Delta u$ Excess pore water pressure at any depth after t	ime t			
$\Delta u_i$ Initial excess pore water pressure				
$\varepsilon_{v}$ Vertical strain				
γ Unit weight of fill				
$\gamma'$ Effective unit weight				
$\gamma_{\rm b}$ Buoyant unit weight (same as effective unit we	eight)			
$\gamma_{\rm f}$ Fill unit weight				
A Angle of slope				

[THIS PAGE INTENTIONALLY BLANK]

#### CHAPTER 3.0 SUBSURFACE EXPLORATIONS

To perform properly, a structure must interact favorably with the soil on which it rests. The modern geotechnical specialist, who often must build in areas that were considered too poor to build upon a few years ago, must be well versed in the fundamentals of soil mechanics. This knowledge will be used in the design of structural foundations and earthworks to answer the following questions. Will settlements be excessive? Can the structure tolerate settlements? Will the proposed foundation type perform better than another type? Can the foundation soils safely support the imposed embankment or footing loads? Will the proposed cut or fill slopes have adequate stability? Are the foundation and earthwork designs cost-effective?

The engineer should have adequate knowledge of the subsurface conditions at a site before attempting to answer these questions. A site- and project-specific subsurface model must be developed for the cost-effective engineering design of a facility. Figure 3-1 shows a flow chart that identifies a recommended process for developing a subsurface model for engineering design. The investment of a few tens of thousands of dollars in a systematic approach as outlined in Figure 3-1 could result in design and construction savings of hundreds of thousands of dollars by preventing costly failures or overly conservative designs.

The process shown in Figure 3-1 is logical and is generally followed on many projects. In many cases, however, old "rules-of-thumb" and "status quo" approaches can result in an unconscious "by-passing" of critical steps. In particular, selection of the correct tests to determine the relevant engineering properties, the interpretation of the results of those tests, and summarization of data are often poorly performed. Rigorous attention to the rational process in Figure 3-1 is required to assure efficient and thorough exploration and testing programs, especially since many projects are fragmented to the extent that drilling, testing, and design are performed by different parties. This document provides guidance on all the items presented in Figure 3-1. The three major steps in the flow chart in Figure 3-1 and the applicable chapters in this document are as follows:

Step 1: Subsurface Exploration and Field Testing (this Chapter)

Step 2: Laboratory Testing and Test Interpretation (Chapters 4 and 5)

Step 3: Engineering Design (Chapters 6 to 10 and Appendix A)



Figure 3-1. Recommended process for developing subsurface model for engineering design (FHWA, 2002a).

3 – Subsurface Explorations December 2006

#### 3.01 Primary References

The primary references for this Chapter as well as Chapters 4 and 5 are as follows:

FHWA (2002a). *Geotechnical Engineering Circular 5 (GEC5) - Evaluation of Soil and Rock Properties*. Report No FHWA-IF-02-034. Authors: Sabatini, P.J, Bachus, R.C, Mayne, P.W., Schneider, J.A., Zettler, T.E., Federal Highway Administration, U.S. Department of Transportation.

FHWA (2002b). *Subsurface Investigations (Geotechnical Site Characterization)*. Report No. FHWA NHI-01-031, Authors: Mayne, P. W., Christopher, B. R., and DeJong, J., Federal Highway Administration, U.S. Department of Transportation.

AASHTO (2006). *Standard Specifications for Transportation Materials and Methods of Sampling and Testing*, Parts I and II, American Association of State Highway and Transportation Officials, Washington, D.C.

ASTM (2006). Annual Book of ASTM Standards – Sections 4.02, 4.08, 4.09 and 4.13. ASTM International, West Conshohocken, PA.

#### 3.1 PREPARING FOR SUBSURFACE EXPLORATION

The initial step in any highway project must include consideration of the soil or rock on which the highway embankment and structures are to be supported. The extent of the site exploration will depend on many factors, not the least of which will be the project scheduling, general subsurface conditions, and the nature of the loads to be supported. In any event, certain basic steps should be followed before exploration equipment is mobilized to the project site. The first step in the exploration is to collect and analyze all existing data. A review of available information prior to the field reconnaissance will help establish what to look for at the site. In the Eighth Rankine Lecture, Glossop (1968) stated the following truism regarding site exploration: "If you do not know what you should be looking for in a site investigation, you are not likely to find much of value." For a highway project, basic sources of geotechnical information should be reviewed to determine landform boundaries and to provide a basis for outlining the project subsurface exploration program. Those sources and functional uses are identified in Table 3-1.

~				
Source	Functional Use	Location	Examples	
Utility Maps	Identifies buried utility locations	Local agencies/utility	Power line identification prior to an intrusive	
	<ul> <li>Identifies access restrictions</li> </ul>	companies	exploration prevents extensive power outage,	
	Prevents damage to utilities		expensive repairs, and bodily harm	
	Identifies manmade structures	Local Soil Conservation	Evaluating a series of aerial photographs may show	
	• Identifies potential borrow source areas	Office, United States	an area on site which was filled during the time period	
Aerial	Provides geologic and hydrological	Geological Survey (USGS),	reviewed	
Photographs	information which can be used as a	local library, local & national		
	basis for site reconnaissance	aerial survey companies		
	Track site changes over time			
	Provides good index map of site area	USGS, State Geological	Engineer identifies access areas/restrictions, identifies	
	Allows for estimation of site	Survey	areas of potential slope instability; and can estimate	
<b>T</b> 11	topography		cut/fill capacity before visiting the site	
Topographic	• Identifies physical features in the site			
Maps	area			
	• Can be used to assess access			
	restrictions			
	• May provide information on nearby	USGS, United States	A five year old report for a nearby roadway widening	
	soil/rock type; strength parameters;	Environmental Protection	project provides geologic, hydrogeologic, and	
Existing Subsurface	hydrogeological issues; foundation	Agency (USEPA), State/local	geotechnical information for the area, reducing the	
Exploration Report	types previously used; environmental	agencies, developers, etc.	scope of the exploration	
	concerns			
	Provides information on nearby	USGS and State Geological	A twenty year old report on regional geology	
Geologic Reports and Maps	soil/rock type and characteristics;	Survey	identifies earth fissure rock types (including fracture	
	hydrogeological issues, environmental		and orientation data) and groundwater flow patterns	
	concerns			
	• Provide stratigraphy of the site and/or	State Geological	A boring log of a water supply well two miles from	
Water/Brine Well	regional area	Survey/Natural Resources,	the site area shows site stratigraphy facilitating	
Logs	• Varied quality from state to state	Department of water	evaluations of required depth of exploration	
	Groundwater levels	resources		

Table 3-1Sources of historical site data (after FHWA, 2002a)

Source	Functional Use	Location	Examples
Flood Insurance	<ul> <li>Identifies 100 and 500 yr floodplains near water bodies</li> <li>Caution against construction in a floodplain</li> </ul>	Federal Emergency Management Agency (FEMA), USGS, state/local	Prior to exploration, the flood map shows that the site is in a 100 yr floodplain and the proposed structure is moved to a new location
Maps	<ul> <li>Provide information for evaluation of scour potential</li> </ul>	agencies	
Soil Survey	<ul><li>Identifies site soil types</li><li>Permeability of site soils</li><li>Climatic and geologic information</li></ul>	Local Soil Conservation Service	The local soil survey provides information on near- surface soils to facilitate preliminary borrow source evaluation
Sanborn Fire Insurance Maps	<ul> <li>Useful in urban areas</li> <li>Maps for many cities are continuous for over 100 years.</li> <li>Identifies building locations and type</li> <li>Identifies business type at a location (e.g., chemical plant)</li> <li>May highlight potential environmental problems at an urban site</li> </ul>	State library/Sanborn Company (www.sanborncompany.com)	A 1929 Sanborn map of St. Louis shows that a lead smelter was on site for 10 years. This information prevents an exploration in a contaminated area.

Table 3-1 (Continued)Sources of historical site data (after FHWA, 2002a)

A necessary part involved in review of existing data is to identify the major geologic processes that occurred at the project site because this will permit the geotechnical specialist to develop an understanding of how the local soil and rock formations may have developed. The soil formation process and consideration of landforms in designs of geotechnical features is discussed briefly followed by discussions of subsurface exploration programs.

#### 3.1.1 Soil Formations and Landforms

Soils are a result of the weathering of rocks. In general, rocks are classified as igneous, sedimentary, and metamorphic. Igneous rocks are products of melts (magma) generated an unknown distance below the earth's surface. Sedimentary rocks are cemented and/or compressed materials derived from pre-existing sediments deposited in layers by water or by air. A metamorphic rock is any rock that originates by a process of change from what it was previously. Any former igneous, sedimentary, or metamorphic rock can be metamorphosed (changed) into a new metamorphic rock by an increase in temperature and/or pressure and/or by reaction with surrounding hot fluids and gases. Regardless of the type of rock, most weathering takes place near the ground surface. Rock weathering can occur due to mechanical (physical) and/or chemical processes as follows:

- Mechanical or physical process refers to the process whereby the intact rock breaks into smaller fragments. Physical weathering may be caused by expansion resulting from unloading (e.g., exfoliation or spalling off of the exterior surface of the exposed rock), abrasion, temperature changes (e.g., freeze/thaw), erosion by wind or rain, crystal growth (e.g., ice and other crystals such as salt crystals that form as the result of the capillary action of water containing salts in solution), and organic activity (e.g., forces exerted by growing plants and roots in voids and crevasses of rock).
- Chemical process refers to the process whereby the minerals in the rock are altered into new compounds. Chemical weathering is usually preceded by hydration and hydrolysis and may be caused by, oxidation (e.g., chemical reaction with rainwater), solution (e.g., dissolution of limestone) and/or leaching (e.g., dissolution of the cementing agent in the rock). Chemical weathering commonly occurs by fluids seeping into the fractures caused by mechanical (physical) weathering processes. These fluids are chiefly acids created as rainwater dissolves carbon dioxide from the atmosphere and more carbon dioxide and organic acids from the soil. Most chemical weathering processes result in an increase in volume (that causes an increase in stress within the rock mass), lower density materials (e.g., soils), smaller particle sizes (e.g., clay sizes), and more stable minerals (that may decrease the rate of chemical weathering).

The combined effects of the mechanical and chemical weathering processes vary considerably with climate and the mineralogy of the parent rock. The chemical reactions proceed most rapidly and completely in humid tropics and subtropics and least effectively in cold or arid climates (Goodman, 1993). Thus, in the Arctic regions and deserts, the mechanical processes of physical weathering act virtually alone to gradually breakup the rock into a fractured or rubbled mass whereas, in the tropics, the two weathering processes work together rapidly first to break up the rock and then to alter newly exposed rock surfaces during a project's life.

Once the intact rock is broken into fragments, the rate of weathering depends on the particle size and the climate. In general, small particles weather at a faster rate than large ones due to their larger surface area. The weathering processes can result in particle sizes that are not distinguishable by the naked eye (e.g., colloidal particle size) and can be identified only by equipment such as electron microscopes. Based on particle size, the principal terms used by civil engineers to describe soils are gravel, sand, silt and clay. These terms were discussed in Chapter 2 as a function of the particle sizes they represent and some of their physical characteristics. For example, silt and clay particles are finer than the No. 200 sieve (0.075 mm) and exhibit varying properties in presence of water.

Soils created by a particular geologic process assume characteristic topographic features, called **landforms**, which can be readily identified by the geotechnical specialist. A landform contains soils with generally similar engineering properties and typically extends irregularly over wide areas of a project alignment. Early identification of landforms can be used to optimize the subsurface exploration program. Landforms may be described according to the method of formation as **residual soil landforms** or **transported soil landforms**. Soils commonly associated with these two types of landforms are briefly described as follows:

#### 3.1.1.1 Residual Soils

A residual soil landform is one that was formed in its present location through weathering of the parent (or bed) rock. Residual soils tend to be characterized by angular to subangular particles, mineralogy similar to parent rock, and the presence of large angular fragments within the overall soil mass. Because residual soil weathers from parent bedrock, its profile with depth represents a history of the weathering process. Figure 3-2 shows a typical weathering profile for metamorphic and igneous rocks. In Figure 3-2, the weathering profile is divided into three zones: *residual soil, weathered rock,* and *unweathered rock.* Deere and Patton (1971) present 12 other weathering-profile classification systems proposed by workers from around the world. Regardless of the weathering-profile classification, the following are some of the properties for such profiles:



Figure 3-2. Typical weathering profile for metamorphic and igneous rocks (Deere and Patton, 1971).

FHWA NHI-06-088 Soils and Foundations – Volume I 3 – Subsurface Explorations December 2006

- The permeability and shear strength gradually change with depth. These two parameters control both the amount of rainfall infiltration and the location of the shear surface when external loads are applied on or in these soils.
- Soil profile thickness and properties depend upon parent bedrock, discontinuities, topography, and climate. Because these factors vary horizontally, the profile can vary significantly over relatively short horizontal distances.
- Deep profiles form in tropical regions where weathering agents are especially strong and advanced stages of chemical weathering form cemented soils called *laterites*. The technical literature often refers to residual soils as tropical soils.
- The material in the transitory zone between residual soil and unweathered rock is called *saprolite*. Saprolites are generally unsaturated, weakly bonded and heterogeneous soils with relict joint systems (Lambe, 1996). Saprolites have widely varying void ratios and widely varying mineralogy and shear strength (Vaughn, *et al.*, 1988).

#### **3.1.1.2 Transported Soils**

A transported soil is one that was formed from rock weathering at one location and transported by some exterior agent to another location. The transporting agent may be water (principal agent), a glacier, wind, and/or gravity. Often the deposits of transported soils are given names indicative of the mode of transportation causing the deposit, e.g., alluvial deposits, glacial till, etc. Transported soils are characterized by subrounded to rounded particles and a wide variety of particle sizes. Table 3-2 summarizes commonly encountered landforms composed of transported soils, their primary formational process, and their engineering significance.

#### 3.1.1.3 Area Concept for Explorations Based on Landforms

Knowledge of the landforms and the engineering properties of the soils and rocks enables the designer to determine the most economical location for a highway alignment and grade, to evaluate design problems for each type of soil or rock, and to determine sources of granular borrow material. Once a landform is identified, the geotechnical specialist can develop an **"area" concept** for exploration. In this concept, the lateral extents of landforms in the immediate vicinity of the footprint of the proposed facility are first identified. Then, a limited exploration program (e.g., geologic mapping, geophysical work and some preliminary cone penetration tests and borings) is implemented at strategic locations such that the general characteristics of the landforms are identified. The exploration program can then be refined to obtain specific information on soil types of interest with respect to the footprint of the proposed facility and the anticipated loadings.

	Common fanciorins of transported soils and their engineering significance				
Agent	Landform	Formational Process and General Engineering Significance for Study			
Water	Flood Plain	• Formed in valleys that are nearly flat and near the high water level of streams. At flood stage the valley is assortially a "flood plain" that is susceptible to widespread shallow flooding			
		essentially a flood plain that is susceptible to widespread shallow flooding.			
		• Generally poor construction site with fine-grained soils and water problems. Potential scour area. Spread footing			
		design below ground will probably require undercut, low foundation pressure and scour protection. Pile			
		Toundations probable. Additional shallow explorations required along footing length to determine buried			
		meandering channels. Historic high water levels should be used in design.			
	Coastal	<ul> <li>Formed similar to flood plain but in coastal areas.</li> </ul>			
	Plain	• Consider spread footings for moderate loads except for high water areas. Potential scour area. Soil "set-up"			
	possible for friction piles (see Chapter 9).				
	Terraces	• Formed when a stream or water body cuts into a previously deposited sediment or as the stream bed is lowered over			
		geological periods due to normal erosion or to crustal deformations. Terraces are also known as bajadas.			
		Consider spread footings for lightly loaded foundations.			
	Lakebed	Formed by sedimentation in lake (fresh water) environments. <i>Varves</i> are a particular type of lake deposit formed			
	(Lacustrine,	during glacial periods from seasonal ice melting, which temporarily increased the runoff velocity so that			
	Varves)	precipitated sand layers alternate with layers of precipitates such as silt or silt-clay made at low velocities.			
		• Suitable only for spread footings to support light loads and even then settlement may be expected. Pile foundation			
		probable and often deep. Obtain undisturbed tube samples for laboratory testing. Consider drilling with "mud"			
		rather than casing. Long-term water observations necessary to determine static water level due to impervious soil.			
	Potential scour area.				
	Deltas	• Formed by sediments precipitated at the mouths of rivers or streams into bays, oceans, or lakes.			
		• The use of spread footings must be carefully studied as poor soils often underlie deltaic sands and gravels. The			
		parent material is capable of sustaining high spread footing loads. Piles may be required to penetrate delta material			
		and poor soil. Use casing of adequate size to obtain undisturbed samples of poor soil. Potential scour area.			
	Alluvial	• Formed similar to delta deposits, but typically found in arid areas where mountain stream runoff flows into wide			
	Fans. Filled	valleys or on to the plains at the mouths of streams. In arid climates, alluvial fans can become cemented by salts left			
	Valleys	in the ground by evaporating water or by dropping groundwater. Cemented soils can be loose to dense (e.g.,			
	(Basin	caliche) or open-graded (collapsible).			
	Deposits)	• Consider spread footings for low to moderate loads except at lower elevation of alluvial fans where high water table			
		is possible. In case of collapsible soils, either treat the soils such that collapse potential is mitigated or use deep			
		foundations to bypass such soils. If the caliche is firm to hard, spread foundations can be used.			

 Table 3-2

 Common landforms of transported soils and their engineering significance

Agent	Landform	Formation and General Engineering Significance for Study			
Ice	Moraines	• Formed by soil deposits pushed into ridges around the periphery of a glacier. <i>Terminal moraines</i> are ridges of			
(Glacier)	(Terminal,	material scraped or bulldozed to the front of a glacier; lateral moraines develop along the sides of a glacier. The			
and	lateral)	moraine may not be a single nicely rolled ridge, but rather a highly serrated, above ground level, earth mass.			
meltwater		• Advisable to use spread footings for all foundation loads. Piles should not be used due to very difficult driving and			
associated		boulders. Core all rock to 10 ft (3.0 m) in case boulders are encountered.			
with ice	Glacial	• Glacial Till (also termed ground moraine or simply till) is the deposit of ice-suspended material through the bottom of			
	Till	the glacier. As glaciers melted, materials suspended in the ice precipitated onto the underlying soil or rock to form			
	(ground	glacial till. Till deposits are characterized by all sizes of particles with no obvious arrangement. Much of northern			
	US has glacial till.				
		• Where till is unsorted, dense and contains considerable sand and gravel, it is advisable to use spread footings for all			
	foundation loads. Piles should not be used due to difficult driving conditions and boulders. Core all rock encountered				
	to depth of 10 ft (3.0 m) as large boulders may be encountered. Long-term water observations necessary				
	static water level due to soil density.				
	• Sediments precipitated from glacial melts in the discontinuities between ridges in moraines. Small lakes may				
	temporarily form in depressions behind ridges, producing lacustrine (fresh water) sediments.				
	• Spread footing normally used to support moderate to heavy foundation loads. Piles, if required, will be short. Use				
	large diameter sample spoon to permit representative sample to be obtained as average particle size m				
	(35.3 mm) sample spoon. Standard penetration test may be erratically high due to large particle sizes				
	value as sand and gravel sources since the material often contains very little amount of fines, i.e., par				
		than No. 200 (0.075 mm) sieve.			
	Eskers	• Eskers are deposits (usually as ridges) formed by precipitation of water-suspended material flowing in ice tunnels.			
		• Advisable to use spread footings for all loads as soil contains much gravel and is dense. Piles not recommended.			
Large diameter sample spoon recommended as above for outwash. Commercial value as sand and g					
	<b>D</b> !!	since the material often contains very little amount of fines, i.e., particle size less than No. 200 (0.0/5 mm) sieve.			
	<ul> <li>Drumlins</li> <li>Drumlins are isolated mounds of glacial debris varying from about 35 (10 m) ft to 230 ft (70 m) high and m) to 2600 ft (800 m) long. Most drumlins are of the order of 100 ft (30 m) or less in height and 1000 ft (less in length. They often occur in groups called drumlin fields (several).</li> </ul>				
		• Suitable for spread footing design with moderate to heavy loads. Piles seldom used due to dense coarse nature of subscill. Commencial value as and and arrows lower since the material after containing the little arrows of finance of the sector of the se			
	subsoil. Commercial value as sand and gravel sources since the material often contains very little amour				
		i.e., particle size less than No. 200 (0.075 mm) sieve.			

## Table 3-2 (continued) Common landforms of transported soils and their engineering significance

Accent	Londform Equation and Consul Engineering Significance for Study				
Agent	Landform	Formation and General Engineering Significance for Study			
Wind	Loess	• Formed by wind blowing silt and clay with the deposit held together by a montmorillonite binder. Generally derived			
(Aeolian)		from glacial outwash in the US. Low density (often less than 90 pcf (14 kN/m <sup>3</sup> )), low wet strength (i.e., collapsible			
		upon water ingress), has the ability to stand on vertical cuts due to cementing agents between particles.			
		• Consider spread footings for low to moderate loads. Heavy loads should be pile supported with the bearing resistance			
		obtained below the loess deposit. Accurate ground water level determination important.			
	Sand Dune	• Formed by wind action blowing the sand. Transport occurs mainly along the ground until an obstruction is met,			
		whereupon a dune (or mound) forms. Later winds may demolish the dune and redeposit the material at a new location			
		further downwind. Dune sands tend to be well rounded from abrasion.			
		• Consider spread footings for small foundations not subject to vibratory loading. Heavy structural loads should be			
		supported on friction piles.			
Gravity	Colluvium	<ul> <li>Formed by physical and chemical weathering of bedrock. The fragmented particles, given sufficient topographic relief, tend to move down slopes under gravitational forces and accumulate as distinctive deposits along the lower portions of slopes, in topographic depressions, and especially at the base of cliffs.</li> <li>The characteristics of colluvial materials vary according to the characteristics of the bedrock sources and the climate under which the weathering and transport occur. From an engineering viewpoint, colluvium is weakly stratified and consists of a heterogeneous mixture of soil and rock fragments ranging in size from clay particles to rock more than 3 ft (1 m) in diameter. Because they are found along the lowest portions of valley sides, such deposits frequently need to be partially excavated to allow passage of transportation facilities. The resulting cut slopes are commonly unstable and require constant monitoring and maintenance. Colluvial soils are prone to creep (slow movement with time) and landslides are common in such soils.</li> </ul>			
	Talus (Scree)	<ul> <li>Talus is colluvium composed of predominantly large fragments. Talus fragments can be huge boulders tens of feet across; however, a lower size limit has not been well defined. With time, the coarse fragments may degrade or finer materials may be added by wind or water transport so that these deposits slowly become infilled with a matrix of fine-grained materials. The degree of infilling of these talus deposits may vary horizontally and vertically.</li> <li>Rock-supported talus is often inherently unstable and may be hazardous to even walk across. Furthermore, the open structure is porous. Talus deposits are not suitable for engineering structures. Talus deposits could be used to make riprap.</li> </ul>			

# Table 3-2 (continued) Common landforms of transported soils and their engineering significance

The area concept is a powerful tool, particularly for linear highway facilities, as it streamlines the subsurface exploration program costs and provides the planning engineer with useful data during the design and construction phases of a project. It also permits early identification of the type and extent of problem soils to be encountered during construction and therefore allows construction costs to be estimated more accurately.

#### 3.2 FIELD RECONNAISSANCE

Application of the area concept requires the use of proper subsurface exploration equipment and techniques. In particular the use of wide area exploration techniques such as remote sensing and geophysical techniques can provide insight of general subsurface conditions in the project area economically. An adequate site exploration can be accomplished only under the direction of a geotechnical specialist who knows the general limitations of the exploration equipment as well as the general demands of the project. A field reconnaissance, preferably with the bridge designer, roadway designer, and project manager, is recommended to assess subsurface conditions prior to establishing a subsurface exploration.

The field reconnaissance should include:

- 1. Inspection of nearby structures to determine their performance with the particular foundation type utilized. If settlement is suspected, the original structural plans should be reviewed and the structure surveyed by using the original benchmark.
- 2. For water crossings, inspection of structural footings and the stream banks up and down stream for evidence of scour. Take careful note of the stream bed material. Often large boulders exposed in the stream but not encountered in the borings, are an indication of potential subsurface obstructions to pile installation.
- 3. Recording the location, type, and depth of any existing structures or abandoned foundations that may infringe on the new highway facility.
- 4. Relating site conditions to the proposed boring operations. Record potential problems with utilities (overhead and underground), site access, private property, or obstructions.

Figure 3-3 is an example of a field reconnaissance form used to record data pertinent to the site. Upon completion of the site inspection, the geotechnical specialist should prepare a terrain reconnaissance report in which the general suitability of the site is assessed. The report should:

Field Reconnaissance Report Department of Transportation				
Project No: County	Sta. No			
Reported By:	Date			
1. Staking of Line Well Staked Poorly Staked (We can work) Request Division to Restake	8. Bridge Site - Continued Cut Section - m (ft) Fill Section - m (ft) If Stream Crossing:			
2. Bench Marks In Place: YesNo Distance from bridge - m (ft)	Can Cable Be Stretched Across Stream?			
3. Property Owners Granted Permission: Yes No Remarks on Back	How Long?         Is Outboard Motorboat Necessary?         Current:         Swift         Moderate         Describe Streambanks scour			
4. Utilities Will Drillers Encounter Underground or Overhead Utilities? YesNo MaybeAt Which Holes? What Type? Who to See for Definite Location	If Present Bridge Nearby: Type of Foundation Any Problems Evident in Old Bridge Including Scour (describe on back) Is Water Nearby for Wet Drilling - m (ft) Are Abandoned Foundations in Proposed Alignment?			
<ol> <li>Geologic Formation</li> <li>Surface Soils Sand Clay Sandy Clay Muck Silt Other</li> </ol>	9. Ground Water Table Close to Surface - m (ft) nearby Wells - Depth - m (ft) Intermediate Depth - m (ft) Artesian head - m (ft)			
7. General Site Description Topography Level Rolling Hillside Valley Swamp Gullied Groundcover Cleared Farmed Buildings Heavy Woods Light Woods Other Remarks on Back	10. Rock       Boulders Over Area? Yes No         Definite Outcrop? Yes No         (show sketch on back)         What kind?         11. Special Equipment Necessary			
8. Bridge Site Replacing Widening Relocation Check Appropriate Equipment	12. Remarks on Access (Describe any Problems on Access)			
Truck Mounted Drill Rig/Cone Rig Track Mounted Drill Rig/Cone Rig Failing 1500 Truck Mounted Skid Rig Skid Rig Rock Coring Rig Wash Boring Equipment Water Wagon Pump Hose m (ft)	13. Debris and Sanitary Dumps Stations Remarks  Reference: Modified from 1978 AASHTO Foundation Investigation Manual			

## Figure 3-3. Typical field reconnaissance form.

- 1. Flag major potential problems, which may preclude construction.
- 2. Recommend beneficial shifts in location.
- 3. Present a general discussion of expected subsurface conditions.
- 4. Present cost estimate for extraordinary geotechnical treatments.
- 5. Prepare an estimate of subsurface exploration quantities, costs, and time.

This information should be transmitted to all the groups involved with the project such as the project manager, roadway designer, and bridge designer.

#### 3.3 SUBSURFACE EXPLORATION PROGRAM

The procedures employed in any subsurface exploration program are dependent on a variety of factors that vary from site to site. The project design objectives and the expected subsurface conditions have the major influence on the subsurface explorations. Highway projects necessarily involve both earthwork and structural foundations. Typical boring programs for highways on new alignments are established such that basic information is first gathered along the entire highway alignment and subsequent detailed borings are taken as required at the locations of structures or in problem earthwork areas as disclosed by the initial basic program. Subsurface explorations for widening or improvements of existing highways generally are done in one stage as the location is predetermined.

**Consideration should be given, particularly for large or complex projects, to performing geologic mapping and geophysical explorations after the field reconnaissance and prior to any invasive explorations such as borings.** Geologic mapping and geophysical explorations can be quick and provide a much larger coverage of the project area as compared to invasive explorations. The information from field reconnaissance, geologic mapping and geophysical explorations explorations can then be used to setup the conventional subsurface exploration and testing program. Geophysical explorations are discussed in Section 3.15.

After the field reconnaissance and geophysical explorations are completed, "invasive" explorations using drilled borings and in-situ tests must be performed to obtain in-situ properties and physical samples for identification and testing. The sampling techniques and tools are discussed in Section 3.4 and other sections of this chapter. The objectives for such explorations are as follows:

- 1. Determine stratigraphy.
  - a. physical description and extent of each stratum.
  - b. thickness and elevation of top and bottom of each stratum.
- 2. For fine-grained soils (each stratum) determine:
  - a. natural moisture contents.
  - b. Atterberg limits.
  - c. stiffness.
  - d. presence of organic materials.
  - e. evidence of desiccation or previous soil disturbance, shearing, or slickensides.
  - f. swelling characteristics.
  - g. unconfined compressive strength typically estimated from Standard Penetration Tests or Cone Penetration Tests.
  - h. shear strength.
  - i. compressibility.
- 3. For coarse-grained soils (each stratum) determine:
  - a. in-situ density (average and range) typically determined from Standard Penetration Tests or Cone Penetration Tests.
  - b. grain-size distributions (gradation).
  - c. presence of organic materials.
- 4. Determine depth to ground water (for each aquifer if more than one is present).
  - a. piezometric surface over site area: existing, past, and probable range in future (observe at several times).
  - b. perched water table.
- 5. Determine depth to bedrock.
  - a. depth over entire site.
  - b. type of rock.
  - c. extent and character of weathering.
  - d. joints, including distribution, spacing, whether open or closed, and joint infilling.
  - e. faults.
  - f. solution effects in limestone or other soluble rocks.
  - g. core recovery and soundness (RQD).
  - h. hardness and strength.

#### 3.4 SAMPLING TECHNIQUES AND TOOLS

The purpose of this section is to provide information on various in-situ testing methods that are currently used to establish site-specific soil and rock properties for design and construction. The execution of a conventional subsurface exploration and testing program usually includes rotary drilling, Standard Penetration Testing (SPT), disturbed and undisturbed sample recovery, and laboratory testing. Although procedures for these commonly performed activities are described in AASHTO and ASTM standards and are well known to most geo-professionals, important testing details are sometimes overlooked that can result in data having marginal quality. This section discusses the importance of carefully selecting and properly conducting the appropriate field and/or laboratory testing method.

In-situ testing methods are increasingly being used on transportation projects, however testing procedures and test limitations are not as well understood as those of the more conventional methods of subsurface exploration and testing such as the use of drilled borings. In this chapter, procedures for various in-situ and laboratory testing methods are presented as they relate to obtaining high quality data for the evaluation of engineering properties of soils and rocks for transportation projects. Information on equipment calibration, measured test parameters, quality control, and the range of ground conditions that apply to each test is also presented.

Several in-situ tests define the geostratigraphy and provide direct measurements of soil properties and geotechnical parameters. The common in-situ tests include: Standard Penetration Test (SPT), Cone Penetration Test (CPT), Piezocone Test (CPTu), Flat Plate Dilatometer Test (DMT), Pressuremeter Test (PMT), and Vane Shear Test (VST). Although the load is applied differently in each test, the purpose of each test is to measure the corresponding response of the soil in an attempt to evaluate the soil's engineering properties, such as strength and/or stiffness. Figure 3-4 depicts these various devices and a graphical representation of how load is applied.

Some state DOTs perform these tests by using agency-owned equipment. In many cases however, the agency may retain an outside contractor for these services either directly or as part of an overall project development package. Several technical reports and manuals are available that describe these test methods. A brief list of these references is provided in Table 3-3. Agencies that perform or contract for these testing services are encouraged to obtain the references identified in Table 3-3. In this manual, only the SPT and the CPT tests will be discussed since they are the most commonly used.



Figure 3-4. Common in-situ tests for geotechnical site characterization of soils (FHWA, 2002b).

Boreholes are required for conducting the SPT and normal versions of the PMT and VST. Therefore a drill rig and crew are required for the performance of these tests. Boreholes are not required for the CPT, CPTu, and DMT; therefore these tests are called "direct-push" technologies. Although boreholes are not required for these tests, special mobilized equipment and data acquisition systems are required. Specialized versions of the PMT (i.e., full-displacement type) and VST can be conducted without boreholes. In such cases either standard drill rigs or mobile hydraulic systems (cone trucks) are used to push the probes to the required test depths. Obviously direct push test methods are not suitable in soil profiles that contain boulders, hard cemented layers and bedrock. For such profiles, borehole methods prevail as the testing device may be advanced through the hard layers by coring or non coring techniques. An advantage of direct-push soundings is that cuttings or spoil are not generated, however, this advantage is offset by a significant disadvantage, i.e., no soil sample is retrieved for classification or subsequent laboratory testing. Another advantage of the CPT and CPTu tests is that they provide a continuous record of soil response through the entire depth of the direct push. The other tests are performed at discrete intervals so that the soil's response is measure at specific depths only. In addition, important layers can be missed with any of the discrete interval test methods.

Test Method	AASHTO/ ASTM Designation	Reference	
SPT	AASHTO T206	FHWA (2002b). Subsurface Investigations (Geotechnical Site Characterization). Report No. FHWA NHI-01-031, Authors:	
	ASTM D 1586	Mayne, P. W., Christopher, B. R., and DeJong, J., Federal Highway Administration, U.S. Department of Transportation.	
CPT, CPTu, SCPTu	ASTM D 3341, D5778	FHWA (1992a). <i>The Cone Penetrometer Test</i> . Report No. FHWA NHI-91-043, Authors: Riaund J-L and Miran J., Federal Highway Administration, U.S. Department of Transportation.	
		Lunne, T., Robertson, P.K., and Powell, J.J.M. (1997) <i>Cone</i> <i>Penetration Testing in Geotechnical Practice</i> , E & F Spon.	
DMT	Suggested ASTM Method	FHWA (1992b). <i>The Flat Dilatometer Test</i> . Report No. FHWA NHI-91-044, Authors: Riaund J-L and Miran J., Federal Highway Administration, U.S. Department of Transportation.	
PMT	ASTM D 4719 FHWA (1989a). <i>The Pressuremeter Test for Highway</i> <i>Applications</i> . Report No. FHWA IP-89-008, Authors: Bi L, Federal Highway Administration, U.S. Department of Transportation.		
		Clarke, B.G. (1995) <i>Pressuremeters in Geotechnical Design</i> , Blackie Academic & Professional.	
VST	ASTM D 2573	ASTM (1988). Vane Shear Strength Testing in Soils: Field and Laboratory Studies, American Society for Testing and Materials, Committee D-18 on Soil and Rock for Engineering Purposes, Philadelphia, PA.	

Table 3-3Reference publications on in-situ testing (FHWA, 2002b)

#### 3.5 BORING METHODS

Geotechnical borings are a critical component of any subsurface exploration program. They are performed to satisfy several objectives including those listed below.

- identify the subsurface distribution of materials with distinctive properties, including the presence and thickness of distinct layers;
- retrieve samples of each layer for laboratory tests to determine engineering properties;
- determine depth to groundwater; and
- provide access for the introduction of in-situ testing devices.

There are many types of equipment used in current practice for advancing a soil or rock boring. Typical types of soil borings are listed in Table 3-4(a), rock coring methods in Table 3-4(b), and other exploratory techniques in Table 3-4(c). Detailed information on soil and rock boring procedures can be found in AASHTO (1988), FHWA (2002b), and ASTM D 4700. A brief description of typical soil boring methods is provided below (Day, 1999).

#### 3.5.1 Auger Borings

An auger is an apparatus with a helical shaft that can be manually or mechanically advanced to bore a hole into soil. Large and small diameter augers are shown in Figure 3-5. The practice of advancing a borehole with a mechanical auger consists of rotating the auger while applying a downward pressure on the auger to penetrate soil and possibly weak or weathered rock. The auger may be continuous, where the helix extends along the entire length of the shaft, or discontinuous when the auger helix is at the bottom of the drill stem.

• Discontinuous or single flight auger borings and bucket auger borings. There are basically two types of discontinuous augers: discontinuous flight augers and bucket augers. Commonly available discontinuous flight augers have diameters ranging from 0.25 to 3 ft (0.075 to 1 m) and bucket augers have diameters ranging from 1 to 8 ft (0.3 to 2.5 m). For discontinuous flight auger borings, the auger is periodically removed from the hole and the soil lodged in the grooves of the flight auger is removed. When a bucket auger is used, it too is periodically removed from the hole and the soil in the bucket removed. A casing is generally not used for discontinuous flight and bucket auger borings. Therefore, these methods are not recommended for boreholes deeper than 35 ft (10 m), or where the hole may cave-in during the

excavation of loose or soft soils, or when the boring is below the groundwater table. In firm stiff clays, discontinuous auger borings can be performed to depths in excess of 35 ft (10 m).

Continuous flight auger borings. As the name implies, continuous flight augers have the auger flights continuous along the entire length of the auger. As shown in Figure 3-6a, there are two types of continuous flight augers: solid stem and hollow stem. For both of these type augers the drill cuttings are returned to the ground surface via the auger flights. The solid stem auger must be removed from the borehole to allow access to the hole for insertion of sampling or testing devices. Because the auger must be periodically removed from the borehole, a solid stem auger is not appropriate in sands and soft soils or in soil deposits where groundwater is close to the surface. A hollow-stem auger has a circular hollow core that allows for sampling through the center of the auger. As shown in Figure 3-6c, hollow-stem augers come in a variety of diameters. The hollow-stem auger acts like a casing and allows for sampling in loose or soft soils or when the excavation is below the ground water table. A plug (Figure 3-6d) is necessary when hollow stem augers are advanced to prevent cuttings from migrating through the hollow stem. The plug is removed to permit SPT sampling. In loose sands and soft clays extending below the water table, drilling fluids are often used to minimize and mitigate disturbance effects and keep the hole open. The components of the hollow stem auger system are shown in Figure 3-6b.





(a) (b) Figure 3-5. (a) Large diameter auger, (b) Small diameter continuous flight auger.

FHWA NHI-06-088 Soils and Foundations – Volume I

Method	Procedure	Applications	Limitations / Remarks
Auger boring (ASTM D 1452)	Dry hole drilled with hand or power auger; samples recovered from auger flights	In soil and soft rock; to identify geologic units and water content above water table	Soil and rock stratification destroyed; sample mixed with water below the water table
Hollow-stem auger boring	Hole advanced by hollow-stem auger; soil sampled below auger as in auger boring above	Typically used in soils that would require casing to maintain an open hole for sampling	Sample limited by larger gravel; maintaining hydrostatic balance in hole below water table is difficult
Wash-type boring	Light chopping and strong jetting of soil; cuttings removed by circulating fluid and discharged into settling tub	Soft to stiff cohesive materials and fine to coarse granular soils	Coarse material tends to settle to bottom of hole; should not be used in boreholes above water table where undisturbed samples are desired.
Becker Hammer Penetration Test (BPT)	Hole advanced using double acting diesel hammer to drive a 6.6-in (168 mm) double-walled casing into the ground. Several sizes are available.	Typically used in soils with gravel and cobbles; casing is driven open-ended if sampling of materials is desired	Skin friction of casing difficult to account for; unsure as to the repeatability of test
Bucket Auger boring	A 2 to 4 ft (0.6 to 1.2 m) diameter drilling bucket with cutting teeth is rotated and advanced. At the completion of each advancement, the bucket is retrieved from the boring and soil is emptied on the ground.	Most soils above water table; can dig harder soils than above types and can penetrate soils with cobbles and boulders if equipped with a rock bucket	Not applicable in running sands; used for obtaining large volumes of disturbed samples and where it is necessary to enter a boring to make observations

# Table 3-4(a)Soil and soft rock boring methods (FHWA, 2002a)

Method	Procedure	Type of sample	Applications	Limitations / Remarks
Rotary coring of rock (ASTM D 2113; AASHTO T 225)	Outer tube with diamond (or tungsten carbide) bit on lower end rotated to cut annular hole in rock; core protected by stationary inner tube; cuttings flushed upward by drill fluid	Rock cylinder 1 in to 4 in (25 to 100 mm) in diameter and as long as 10 ft (3 m), depending on rock soundness. Standard coring size is 2- 1/8 in (54 mm) diameter.	To obtain continuous core in sound rock (percent of core recovered depends on fractures, rock variability, equipment, and driller skill)	Core lost in fracture or variable rock; blockage prevents drilling in badly fractured rock; dip of bedding and joint evident but not strike
Rotary coring of rock, wire line	Same as ASTM D 2113, but core and stationary inner tube retrieved from outer core barrel by lifting device or "overshot" suspended on thin cable (wire line) through special large- diameter drill rods and outer core barrel	Rock cylinder 1-1/8 in to 3-3/8 in (28 to 85 mm) wide and 5 ft to 10 ft (1.5 to 3 m) long	To recover core better in fractured rock which has less tendency for caving during core removal; to obtain much faster cycle of core recovery and resumption of drilling in deep holes	Core lost in fracture or variable rock; blockage prevents drilling in badly fractured rock; dip of bedding and joint evident but not strike
Rotary coring of swelling clay, soft rock	Similar to rotary coring of rock; swelling core retained by third inner plastic liner	Soil cylinder 1-1/8 in to 3-3/8 in (28 to 85 mm) wide and 2 ft to 5 ft (0.6 m to 1.5 m) long encased in plastic tube	In soils and soft rocks that swell or disintegrate rapidly in air (protected by plastic tube)	Sample smaller; equipment more complex than other soil sampling techniques

 Table 3-4(b)

 Pack core drilling methods (FHWA 2002s)

<sup>(1)</sup> See Section 3.6.4 for additional discussion on types of core barrels (i.e., single-, double-, or triple-tube).

Method	Procedure	Type of sample	Applications	Limitations / Remarks
Borehole camera	Inside of core hole viewed by circular photograph or scan	No sample, but a visual representation of the material	To examine stratification, fractures, and cavities in hole walls	Best above water table or when hole can be stabilized by clear water
Pits and Trenches	Pit or trench excavated to expose soils and rocks	Chunks cut from walls of trench; size not limited	To determine structure of complex formations; to obtain samples of thin critical seams such as failure surface	Moving excavation equipment to site, stabilizing excavation walls, and controlling groundwater may be difficult; useful in obtaining depth to shallow rock and for obtaining undisturbed samples on pit/trench sidewalls; pits need to be backfilled
Rotary or cable tool well drill	Toothed cutter rotated or chisel bit pounded and churned	Pulverized	To penetrate boulders, coarse gravel; to identify hardness from drilling rates	Identification of soils or rocks difficult
Percussive Method (jack hammer or air track)	Impact drill used; cuttings removed by compressed air	Rock dust	To locate rock, soft seams, or cavities in sound rock	Drill becomes plugged by wet soil

 Table 3-4(c)

 Other exploratory techniques (FHWA, 2002a)



(a)



(c)

(d)

(b)

Figure 3-6. (a) Solid stem auger and hollow stem auger, (FHWA, 2002b) (b) Hollow stem auger components (ASTM D 4700), (c) Sizes of hollow stem auger flights (FHWA, 2002b), (d) Outer and inner assembly of hollow stem auger (FHWA, 2002b).

#### 3.5.2 Wash-type Borings

Wash-type borings use circulating drilling fluid (e.g., water or mud) to remove cuttings from the borehole, Figure 3-7. Cuttings are created by the chopping, twisting, and jetting action of the drill bit that breaks the soil or rock into small fragments. Tri-cone bits are often used in dense soil or soft rock. If bentonite or a polymeric drilling mud cannot be used to maintain an open borehole, casings are often used to prevent cave-in of the borehole. The use of casing will require a significant amount of additional time and effort but will result in a protected borehole. When drilling mud is used during subsurface boring, it will be difficult to classify the soil from the auger cuttings because of contamination with the mud. Also, the outside of samples may become coated with drilling mud.

The properties of the drilling fluid and the quantity of water pumped through the drill bit will determine the size of particles that can be removed from the boring with the circulating fluid. In formations containing gravels, cobbles, or larger particles, coarse material may be left at the bottom of the boring. In these instances, cleaning the bottom of the boring with a larger diameter sampler (such as the 3 in (75 mm) OD split barrel sampler) may be needed to obtain a representative sample of the formation.

#### 3.5.3 Coring in Rocks

The previously described methods are typically used for soil exploration. The following methods are primarily used for rock exploration.

- <u>Rotary coring</u>. This type of coring equipment is most commonly used for rock exploration when an intact core of the rock is desired. Power rotation of the drilling bit is accompanied with introduction of a circulating fluid to remove cuttings from the hole. The drilling bits are specifically designed to core rock, and inner/outer tubes or casings are used to capture the intact core. Table 3-4(b) lists various types of rotary coring techniques for rock, although many of these techniques are also applicable to dense or stiff soil.
- <u>*Percussion drilling.*</u> This type of drilling equipment is often used to penetrate hard rock for subsurface exploration or for the purpose of drilling wells. The drill bit works much like a jackhammer, rising and falling to break up and crush the rock material. Air is commonly used to clean the hole and transport the cuttings to the ground surface. Table 3-4(c) includes a description on the use of the percussion drilling techniques.





(b)

(c)



FHWA NHI-06-088 Soils and Foundations – Volume I

(a)

3 - 27 Engineering-pdh.com | geo-115 | 3 – Subsurface Explorations December 2006
#### 3.6 SAMPLING METHODS

# 3.6.1 Disturbed Sampling of Soil

Disturbed sampling of soil provides a means to evaluate stratigraphy by visual examination and to obtain soil specimens for laboratory index testing. Disturbed samples are usually collected using split-barrel samplers (Figure 3-8; AASHTO T 206, ASTM D 1586), although several other techniques are available for disturbed sample collection in boreholes (see Table 3-5(a) and 3-5(b)). Shallow disturbed samples can also be obtained by using hand augers and test pits. Direct push methods, such as GeoProbe sampling, can be used to obtain continuous disturbed samples but these methods have limitations in sampling depth similar to those of solid stem and bucket augers (i.e., generally good for depths less than 33 feet (10 meter) unless in firm to stiff clays). Samples obtained via disturbed sampling methods are generally used for index property testing in the laboratory. They should <u>not</u> be used to prepare specimens for consolidation and strength tests.



Figure 3-8. Split barrel sampler.

# 3.6.2 Undisturbed Sampling of Soil

Undisturbed soil samples are required for performing laboratory strength and consolidation tests on cohesive soils having consistencies ranging from soft to stiff. High-quality samples for such tests are particularly important for approach embankments and for structural foundations and wall systems that may stress compressible strata. In reality, it is impossible to retrieve truly undisturbed samples since changes in the state of stress in the sample occur upon sampling and removal of the sample from depth. The goal of high-quality undisturbed sampling is to minimize the potential for: (1) alteration of the soil structure; (2) changes in moisture content or void ratio; and (3) changes in chemical composition of the soil. Due to cost and ease of use, the thin-walled Shelby tube (Figure 3-9) is the most commonly used sampler for obtaining relatively undisturbed samples of soft to stiff fine-grained soils.

Sampler	Typical Dimensions	Soils that Give Best	Method of	Cause of Low	Remarks
Sumptor		Results	Penetration	Recovery	
Split Barrel	Standard is 2 in (50 mm) outside diameter (OD) and 1-3/8 in (35 mm) inside diameter (ID)	All soils finer than gravel size particles that allow sampler to be driven; gravels invalidate drive data; A soil retainer may be required in granular soils.	140 lb (64 kg) hammer driven	Gravel may block sampler	A SPT is performed using a standard penetrometer and hammer (see text); samples are extremely disturbed
Continuous helical- flight auger	Diameters range 3 in to 16 in (75 to 400 mm; penetrations to depths exceeding 50 ft (15 m)	Most soils above water table; will not penetrate hard soils or those containing cobbles or boulders	Rotation	Hard soils, cobbles, boulders	Method of determining soil profile, bag samples can be obtained; log and sample depths must account for lag time between penetration of bit and arrival of sample at surface, to minimize errors in estimated sample depths

 Table 3-5(a)

 Common samplers to retrieve disturbed soil samples (modified after NAVFAC, 1986a)

Samplar	Typical Dimonsions	Soils that Cive Post	Mothod of	Cauco of Low	Domoniza
Sampler	Typical Dimensions	Sons that Give Dest	Niethou of	Cause of Low	Kemarks
		Results	Penetration	Recovery	
Disc auger	Up to 3.5 ft (1 m)	Most soils above water	Rotation	Hard soils, cobbles,	Method of determining
	diameter; usually has	table; will not penetrate		boulders	soil profile, bag samples
	maximum penetration	hard soils or those			can be obtained; log and
	depth of 25 ft (8 m)	containing cobbles or			sample depths must
		boulders			account for lag time
					between penetration of bit
					and arrival of sample at
					surface, to minimize errors
					in estimated sample depths
Bucket auger	Up to 4 ft (1.2 m)	Most soils above water	Rotation	Soil too hard to	Several bucket types
	diameter common;	table; can penetrate		penetrate	available, including those
	larger sizes available;	harder soils than above			with ripper teeth and
	with extensions, depth	types and can penetrate			chopping tools; progress is
	over 80 ft (25 m) are	soils with cobbles and			slow when extensions are
	possible	boulders if equipped			used
	*	with a rock bucket			
Test boring of large	2 in to 3 in (50 to 75	In sandy to gravelly	Up to 350 lb	Large gravel,	Sample is intact but very
samples,	mm) ID and 2.5 in to	soils	(160 kg) 350 lb	cobbles, and	disturbed; A resistance can
Large Penetration	3.5 in (63 mm to 89		hammer driven	boulders may block	be recorded during
Test (LPT)	mm) OD samplers			sampler	penetration, but is <u>not</u>
	(examples, Converse				equivalent to the SPT N-
	sampler, California				value and is more variable
	Sampler)				due to no standard
					equipment and methods

Table 3-5(b)
Common samplers to retrieve disturbed soil samples (modified after NAVFAC, 1986a)



# Figure 3-9. Schematic of thin-walled (Shelby) tube (after ASTM D 4700) and photo of tube with end caps (FHWA, 2002b).

Thin walled Shelby tube sampling is discussed in Section 3.5.3. Depending upon the in-situ condition of the fine-grained soil (e.g., stiffness and whether significant granular material is in the soil matrix), alternative sampling devices may be used to obtain nominally undisturbed soil samples. These alternative samplers include:

- Stationary piston sampler (Figure 3-10);
- Denison sampler (Figure 3-11);
- Pitcher samplers (Figure 3-12);
- Hydraulic piston sampler (Osterberg Sampler).

Summary information on these samplers is provided in Table 3-6 and detailed procedures for these sampling techniques are provided in FHWA (1997, 2002b). Although not common for typical transportation-related projects, a variety of special samplers are available to obtain samples of soil and soft rocks. These specialty samplers include the retractable plug sampler, the Sherbrooke sampler, and the Laval sampler.

Sampler	Typical Dimensions	Soils that Give Best	Method of	Cause of Disturbance	Remarks
		Results	Penetration	or Low Recovery	
Shelby tube (ASTM D 1587; AASHTO T 207)	3 in (76 mm) OD and 2-7/8 in (73 mm) ID most common; available from 2 in to 5 in (50 to 127 mm) OD; 30 in (760 mm) sampler length standard	Cohesive fine-grained or soft soils; gravelly and very stiff soils will crimp tube	Pressing with relatively rapid, smooth stroke; can be carefully hammer driven but this will induce additional disturbance	Erratic pressure applied during sampling, hammering, gravel particles, crimping of tube edge, improper soil types for sampler, pressing tube greater than 80% of tube length	Simplest device for undisturbed samples; boring should be clean before sampler is lowered; little waste area in sampler; not suitable for hard, dense or gravelly soils
Stationary piston	3 in (76 mm) OD most common; available from 2 in to 5 in (50 to 127 mm) OD; 30 in (760 mm) sampler length standard	Soft to medium clays and fine silts; not for sandy soils	Pressing with continuous, steady stroke	Erratic pressure during sampling, allowing piston rod to move during press, improper soil types for sampler	Piston at end of sampler prevents entry of fluid and contaminating material requires heavy drill rig with hydraulic drill head; samples generally less disturbed compared with Shelby tube; not suitable for hard, dense, or gravelly soil
Hydraulic piston (Osterberg)	3 in (76 mm) OD is most common; available from 2 in to 4 in (50 to 100 mm) OD; 36 in (910 mm) sampler length standard	Silts and clays, some sandy soils	Hydraulic or compressed air pressure	Inadequate clamping of drill rods, erratic pressure	Needs only standard drill rods; requires adequate hydraulic or air capacity to activate sampler; samples generally less disturbed compared with Shelby tube; not suitable for hard, dense, or gravelly soil
Denison	3.5 in to 7 in (89 to 177 mm) OD, producing samples 2-3/8 in 6.3 in (60 to 160 mm); 24 in (610mm) sampler length	Stiff to hard clay, silt, and sands with some cementation, soft rock	Rotation and hydraulic pressure	Improper operation of sampler; poor drilling procedures	Inner tube face projects beyond outer tube, which rotates; amount of projection can be adjusted; generally takes good samples; not suitable for loose sands and soft clays
Pitcher sampler	4 in (100 mm) OD; uses 3 in (76-mm) diameter Shelby tubes; sample length 24 in (610 mm)	Same as Denison	Same as Denison	Same as Denison	Differs from Denison in that inner tube projection is spring controlled; often ineffective in cohesionless soils
Foil Sampler	Continuous samples 2 in (50 mm) wide and as long as 65 ft (20 m)	Fine grained soils including soft sensitive clays, silts, and varved clays	Pushed into the ground with steady stroke; Pauses occur to add segments to sample barrel	Samplers should not be used in soils containing fragments or shells	Samples surrounded by thin strips of stainless steel, stored above cutter, to prevent contact of soil with tube as it is forced into soil

 Table 3-6

 Nominally undisturbed soil samplers (modified after NAVFAC, 1986a)



Figure 3-10. Stationary piston sampler schematic (after ASTM D 4700) and photo (FHWA, 2002b).





Figure 3-12. Pitcher sampler (FHWA, 1997, 2002b).

FHWA NHI-06-088 Soils and Foundations – Volume I 3 – Subsurface Explorations December 2006 When dealing with relatively shallow soils that are very stiff, brittle, partially cemented, or that contain coarse gravel or stones, the best method to obtain large relatively undisturbed samples is by block sampling. Block sampling involves isolating a soil column, encasing it in paraffin wax, and covering it with an open-ended box or tube (usually about 12 in (300 mm) square). The bottom is cut, sealed and covered, and the sample is transported to the laboratory. This sampling technique is generally difficult to implement at depths greater than approximately 10 ft (3 m).

#### 3.6.3 Thin-Walled (Shelby) Tube Sampling

The importance of appropriate sampling practice using Shelby tubes cannot be overemphasized. Poor sampling practices, exposure to extreme temperatures, and careless handling of samples can cause sample disturbance that may result in misleading test results that can lead to uneconomical or unsafe designs.

• <u>Geometry of a Thin-Walled Tube</u>: The area ratio (AR) and the inside clearance ratio (ICR) are parameters that are used to evaluate the disturbance potential for different types of soil samplers. These parameters are defined as follows:

$$AR = \frac{D_0^2 - D_i^2}{D_i^2} \times 100 \text{ percent}$$
 3-1a

$$ICR = \frac{D_i - D_e}{D_e}$$
 3-1b

where  $D_e$  = diameter at the sampler cutting tip,  $D_i$  = inside diameter of the sampling tube, and  $D_o$  = outside diameter of the sampling tube. For a sample to be considered undisturbed, the ICR should be approximately 1 percent and the AR should be 10 percent or less. Using a tube with this ICR value minimizes the friction buildup between the soil sample and the sampler during the advancement of the sampler. Using a tube with an AR value less than 10 percent enables the sampler to cut into the soil with minimal displacement of the soil. Thin-walled tubes (e.g., Shelby tubes) are typically manufactured to meet these specifications, but a thicker walled tube with an ICR of zero is commonly used in the Gulf states (e.g., Texas, Louisiana) to sample very stiff overconsolidated clays. The use of the thicker walled tube minimizes buckling of the sampler in the stiff deposits, and the ICR of zero minimizes sample expansion within the

FHWA NHI-06-088 Soils and Foundations – Volume I tube. Additional information on suitable geometry for thin-walled tubes is provided in ASTM D 1587.

- <u>Sample Tube Inspection and Storage</u>: Tubes received from the manufacturer should be inspected to assure that no damage has occurred to the ends of the tubes. Plastic end caps, which will later be used to facilitate securing of the sample, should be placed on the ends of the tube at this time.
- Cleaning Borehole Prior to Sampling: Depending upon the methods used, drilling and ٠ sampling procedures will cause some disturbance in the vicinity of the advancing face of a borehole. This is especially the case if a sample is overpushed, if casing is advanced ahead of the borehole, or during continuous sampling operations. It is recommended that a borehole be advanced and cleaned to two to three diameters below the bottom of the previous sample to minimize disturbance. Additionally, after advancement of the borehole, caving may occur at the bottom of the hole. Thus, the bottom of the borehole should be cleaned out thoroughly before the sampling device is advanced. Improper cleaning will lead to severe disturbance of the upper material (accumulated settled material), and possibly disturbance of the entire sample. Cleaning is usually performed by washing materials out of the hole. It should be ensured that the jet holes are not directed downward, for this will erode soft or granular materials to an unknown depth. All settled material should be removed to the edge of the casing. In deep or wide borings, special cleaning augers may be used to decrease time for cleaning and produce a cleaner hole.
- <u>Tube Advancement and Retrieval</u>: Tubes should be advanced without rotation in a smooth and relatively rapid manner. The length of the sampler advancement should be limited to 24 in (600 mm) for a 30 in (760 mm) long tube to minimize friction along the wall of the sampler and allow for loose material in the hole. The amount of recovery should be compared to the advanced length of the sampler to assess whether material has been lost, the sample has swelled, or some caved material has been collected at the top of the tube. The possible presence of caved material should be noted at the top of the tube so that no laboratory moisture content or performance tests are performed on that material. After advancing to the target depth, the drill rod should be rotated one full turn to shear off the bottom of the sample. Prior to shearing, a waiting period of 5 to 15 minutes is recommended for tubes in soft soils to permit the sample to reach equilibrium inside the tube and prevent the sample from falling out the bottom of the tube during retrieval. This waiting period may be reduced for stiffer soils.

Preparation for Shipment: Upon removal of the sample from the borehole, the ends • should be capped with the plastic end caps and the tube should be labeled. The label should be written directly on the tube with a permanent marking pen, and include: (1) tube and boring identification number; (2) sample depth; (3) top and bottom of sample; (4) length of recovery; (5) sampling date; (6) job name and/or number; and (7) sample description. Tube samples that are intended for laboratory performance testing (i.e., strength, consolidation, hydraulic conductivity) should never be extruded from the tube in the field and stored in alternative containers. Samples should be extruded only in the laboratory under controlled conditions. After a thin-walled tube sample has been taken, slough or cuttings from the upper end of the tube should be removed by use of a cleanout tool. The length of sample recovered should be measured and the soil classified for the log. About 1 in (25 mm) of material at the bottom end of the tube should be removed and the cuttings placed in a properly labeled storage jar. Both ends of the tube should then be sealed with at least a 1 in (25 mm) thick layer of microcrystalline (non-shrinking) was after a plastic disk has been placed to protect the ends of the sample (Figure 3-13a). The use of relatively low temperature wax will minimize shrinkage and potential moisture migration within the sample. The remaining void above the top of the sample should be filled with moist sand. Plastic end caps should then be placed over both ends of the tube and electrician's tape wrapped over the joint between the collar of the cap and the tube and over the screw holes. The capped ends of the tubes are then dipped in molten wax. Alternatively, O-ring packers can be inserted into the sample ends and then sealed (Figure 3-13b). This method of sealing the sample may be preferable as it is cleaner and more rapid than waxing. In both cases, the sample must be sealed to ensure proper preservation of the sample. The tube should be kept vertical, with the top of the sample in the upright position. If the sample needs to be inverted for purposes such as sealing, care should be taken to ensure the sample does not slide within the tube. Samples must be stored upright in a protected environment to prevent freezing, desiccation, and alteration of the moisture content (ASTM D 4220).

<u>Shipment</u>: Sample tubes must to be packed **upright** in accordance with guidelines provided in ASTM D 4220, or in an equivalent sample box. Tubes should be isolated from other sample tubes, and fit snugly in the case to protect against vibration or shock. The cushioning material between the samples should be at least 1 in (25 mm) thick, and the cushioning on the container floor should be at least 2 in (50 mm) thick. The samples should not be exposed to extreme heat or cold. If possible, the geotechnical specialist should deliver the samples to the laboratory or use a special delivery service provider who offers shipping of fragile items (e.g., FedEx) to ship samples. The use of a chain of custody form for sample traceability records is encouraged.

FHWA NHI-06-088 Soils and Foundations – Volume I



Figure 3-13. Shelby tube sealing methods, (a) Microcrystalline Wax, (b) O-Ring packer (FHWA, 2002b).

## 3.6.4 Undisturbed Sampling of Rock (Rock Coring)

When equipment for rock coring is being considered, the dimensions, type of core barrel, type of coring bit, and drilling fluid are important variables. The minimum depth of rock coring should be determined based on the local geology of the site and the type of structure to be constructed. Coring should also be performed to a depth that assures that refusal is not encountered on a boulder. A brief description of issues related to rock coring is provided in this document. Additional information on drilling rigs, methods of circulating drill cuttings (i.e., fluid or air), hole diameters, and casings is provided in ASTM D 2113.

#### 3.6.4.1 Core Barrels

Four different types of core barrels are described in ASTM D 2113 including:

- 1) Single Tube Figure 3-14(a);
- 2) Rigid Double Tube Figure 3-14(b);
- 3) Swivel Double Tube Figure 3-14(c); and
- 4) Triple Tube.



Figure 3-14. (a) Single, (b) and (c) Double tube rock core barrels (FHWA, 1997).

Since the double core barrel isolates the rock from the drilling fluid stream to yield better recovery, it is the minimum standard of core barrel that should be used in practice when an intact core is required for testing. Figure 3-15 shows the outer and inner assembly for a double-tube core barrel. The inner tube of a swivel-type core barrel does not rotate during drilling, which results in less disturbance and better recovery in weak and fractured rock. Rigid type double tube core barrels should not be used where core recovery is a concern. Triple tube swivel-type core barrels will produce better recovery and less core breakage than a double tube barrel.

Most rock coring today is done by use of the wireline method, which was introduced in the 1960s. In this method, an inner tube containing the core is detached from the core barrel assembly when the core barrel is full or a blockage occurs. The tube and core contained in it are pulled to the surface by wire dropped down the string of drill rods. A latch or "overshot assembly," which snaps on to the top of the inner tube, is used for this purpose. The inner

tube is then rapidly hoisted to surface within the string of drill rods. After the core is removed, the inner tube is dropped down into the outer core barrel and drilling resumes. Thus, the core is retrieved without having to pull all of the rods and production rates, particularly for deep cores, are therefore greater than those for conventional techniques.

Table 3-7 lists the available core sizes. The standard size rock core, NX, has a diameter of 2-1/8 in (54 mm). Generally larger core sizes will lead to less mechanical breakage and yield greater recovery, but the associated cost for drilling will be much higher. Since the size of the core will affect the percent recovery, the core barrel size should be clearly recorded on the log. Additionally, the core barrel length can increase recovery in fractured and weathered rock zones. In these zones a core barrel length of 5 ft (1.5 m) is recommended. Core barrel lengths should not be greater than 10 ft (3 m) under any conditions because of the potential for damage to the long cores.



(a) (b) Figure 3-15. Double tube core barrel. (a) Outer barrel assembly (b) Inner barrel assembly (FHWA, 2002b).

#### 3.6.4.2 Coring Bits

The coring bit is the bottommost component of the core barrel assembly. It is the grinding action of this component that cuts the core from the rock mass. The following three basic categories of bits are in use: diamond, carbide and sawtooth (Figure 3-16).

Coring bits are generally selected by the driller and are often approved by the geotechnical specialist. Bit selection should be based on a general knowledge of drill bit performance for the expected formations and the proposed drilling fluid.

Size	Diameter of Core	Diameter of Borehole
	mm (in)	mm (in)
EX,EXM	21.5 (0.846)	37.7 (1.484)
EWD3	21.2 (0.835)	37.7 (1.484)
AX	30.1 (1.185)	48.0 (1.890)
AWD4, AWD3	28.9 (1.138)	48.0 (1.890)
AWM	30.1 (1.185)	48.0 (1.890)
AQ Wireline, AV	27.1 (1.067)	48.0 (1.890)
BX	42.0 (1.654)	59.9 (2.358)
BWD4, BWD3	41.0 (1.614)	59.9 (2.358)
BXB Wireline, BWC3	36.4 (1.433)	59.9 (2.358)
BQ Wireline, BV	36.4 (1.433)	59.9 (2.358)
NX	54.7 (2.154)	75.7 (2.980)
NWD4,NWD3	52.3 (2.059)	75.7 (2.980)
NXB Wireline, NWC3	47.6 (1.874)	75.7 (2.980)
NQ Wireline, NV	47.6 (1.874)	75.7 (2.980)
HWD4,HXB Wireline,	61.1 (2.406)	92.7 (3.650)
HQ Wireline	63.5 (2.500)	96.3 (3.791)
CP, PQ Wireline	85.0 (3.346)	122.6 (4.827)

Table 3-7Dimensions of core sizes (FHWA, 1997)



Figure 3-16. Coring bits: Diamond (top left), Carbide (top right), and Sawtooth (bottom center) (FHWA, 2002b).

Diamond coring bits, such as surface set or impregnated-diamond types, are the most versatile since they can produce high-quality cores in soft to extremely hard rock materials (see Figure 3-10, top left). Compared to other types, diamond bits in general permit more rapid coring and, as noted by Hvorslev (1948), exert lower torsional stresses on the core. Lower torsional stresses permit the retrieval of longer cores and cores of smaller diameter. The wide variation in the hardness, abrasiveness, and degree of fracturing encountered in rock has led to the design of bits to meet specific conditions known to exist or expected to be encountered at given sites. Thus, wide variations in the quality, size, and spacing of diamonds, in the composition of the metal matrix, in the face contour, and in the type and number of waterways are found in bits of this type. Similarly, the diamond content and the composition of the metal matrix of impregnated bits are varied to meet differing rock conditions.

Carbide bits use tungsten carbide in lieu of diamonds. There are of several types of carbide bits. The standard type carbide bit is shown in Figure 3-16, top right. Bits of this type are used to core soft to medium hard rock. They are less expensive than diamond bits. However, the rate of drilling is slower than with diamond bits.

Sawtooth bits consist of teeth cut into the bottom of the bit (see Figure 3-10, bottom center). The teeth are faced and tipped with a hard metal alloy such as tungsten carbide to provide water resistance and thereby to increase the life of the bit. Although these bits are less expensive than diamond bits, they do not provide as high a rate of coring and do not have a salvage value. The saw tooth bit is used primarily to core overburden and very soft rock.

An important feature in all bits is the type of waterways provided in the bits for the passage of drilling fluid. Bits are available with so-called "conventional" waterways, which are passages cut on the interior face of the bit, or with bottom discharge waterways, which are internal passages that discharge at the bottom face of the bit behind a metal skirt separating the core from the discharge fluid. Bottom discharge bits should be used when soft rock or rock having soil-filled joints is cored to prevent erosion of the core by the drilling fluid before the core enters the core barrel.

Bit selection is based on the anticipated rock formation as well as the expected drilling fluid. Diamond bits are applicable in all rock types. They permit greater rates of coring than other types of bits. Carbide bits are less expensive than diamond bits and can be used in soft to medium-hard rock. Sawtooth bits are the least expensive of the three, however they have no salvage value. They lead to slower coring and are typically used only in soft rock.

## 3.6.4.3 Drilling Fluid

In many instances, clear water is used as the drilling fluid in rock coring. If drilling mud is required to stabilize collapsing holes or to seal zones when there is loss of drill water, the geotechnical specialist should be notified to confirm that the type of drilling mud is acceptable. Drilling mud will clog open joints and fractures, which adversely affects permeability measurements and piezometer installations. Drilling fluid should be contained in a settling basin to remove drill cuttings and to allow recirculation of the fluid. Generally, drilling fluids can be discharged onto the ground surface. However, special precautions or handling may be required if the material is contaminated with oil or other substances. Such fluids may require disposal off site. Water flow over the ground surface should be avoided as much as possible. Local environmental agencies should be contacted for permits because some drilling fluids may have adverse effects on local surface and subsurface environments. Certain local agencies may also require implementation of a Storm Water Pollution Prevention Plan (SWPPP).

# 3.6.5 Observations During Rock Core Drilling

# **3.6.5.1 Drilling Rate/Time**

The drilling rate should be monitored and recorded on the boring log in the units of minutes per 1 ft (0.3 m). Only time spent advancing the boring should be used to determine the drilling rate.

# **3.6.5.2** Core Photographs

Cores in the split core barrel should be photographed immediately upon removal from the borehole. A label should be included in the photograph to identify the borehole, the depth interval and the number of the core run. It may be desirable to get a "close-up" of interesting features in the core. Wetting the surface of the recovered core by using a spray bottle and/or sponge prior to photographing will often enhance the color contrasts of the core.

A tape measure or ruler should be placed across the top or bottom edge of the core box to provide a scale in the photograph. The tape or ruler should be at least 3 ft (1 m) long, and it should have relatively large, high contrast markings to be visible in the photograph.

A color bar chart is often desirable in the photograph to provide indications of the effects of variation in film age, film processing, and the ambient light source. The photographer should strive to maintain uniform light conditions from day to day, and those lighting conditions should be compatible with the type of film selected for the project. The use of a digital camera is a convenient way to circumvent some of the problems associated with the use of film cameras for photographing rock cores.

## 3.6.5.3 Rock Classification

The rock type and its inherent discontinuities, joints, seams, and other facets should be documented. See Chapter 4 for a discussion of rock description and classification.

## 3.6.5.4 Recovery

The core recovery is the length of rock core recovered from a core run. The recovery ratio is the ratio of the length of core recovered to the total length of the core drilled on a given run, expressed as either a fraction or a percentage. Core length should be measured along the core centerline. When the recovery is less than the length of the core run, the non-recovered section should be assumed to be at the end of the run unless there is reason to suspect otherwise (e.g., weathered zone, drop of rods, plugging during drilling, loss of fluid, and rolled or re-cut pieces of core). Non-recovery should be marked as NCR (no core recovery) on the boring log, and entries should not be made for bedding, fracturing, or weathering in that interval.

Recoveries greater than 100 percent may occur if core that was not recovered during a run is subsequently recovered in the next run. Recoveries greater than 100 percent should be recorded and adjustments to data should not be made in the field.

# 3.6.5.5 Rock Quality Designation (RQD)

The RQD is a quantitative measure that represents a modified core recovery percentage. By definition the RQD is the sum of the lengths of all pieces of sound core over 4 in (100 mm) long divided by the length of the core run (Deere, 1963). The correct procedure for measuring RQD is illustrated in Figure 3-17. The RQD is an index of rock quality. Problematic rock that is highly weathered, soft, fractured, sheared, and jointed typically yields lower RQD values than more intact rock. Thus, RQD is simply a measurement of the percentage of "good" rock recovered from an interval of a borehole.

It should be noted that the original definition of RQD reported by Deere (1963) was based on measurements made on NX-size core. Experience in recent years reported by Deere and Deere (1989) indicates that cores with diameters both slightly larger and smaller than NX may be used for computing RQD. The wire line cores using NQ, HQ, and PQ are also considered acceptable. Use of RQD for the smaller BQ and BX sizes is discouraged because of a greater potential for core breakage and loss that would result in a smaller value of RQD.





FHWA NHI-06-088 Soils and Foundations – Volume I

3 - 45 engineering-pdh.com | ged-115 | 3 – Subsurface Explorations December 2006

#### Length Measurements of Core Pieces

The same piece of core could be measured three ways: along the centerline, from tip to tip, or along the fully circular barrel section (Figure 3-18). The recommended procedure is to measure the core length along the centerline. This method is advocated by the International Society for Rock Mechanics (ISRM), Commission on Standardization of Laboratory and Field Tests (ISRM, 1981). The centerline measurement is preferred because: (1) it results in a standardized RQD not dependent on the core diameter, and (2) it avoids unduly penalizing the rock quality for cases where fractures run parallel to the borehole and are cut by a second set of fractures.



Figure 3-18. Length measurements for core RQD determination (FHWA, 1997).

#### Assessment of Soundness

Pieces of core which are not "hard and sound" should not be counted for the RQD even though they possess the requisite 4 in (100 mm) length. The purpose of the soundness requirement is to downgrade the rock quality where the rock has been altered and weakened either by agents of surface weathering or by hydrothermal activity. Obviously, in many instances a judgment decision must be made as to whether or not the degree of chemical alteration is sufficient to reject the core piece.

One commonly used procedure is not to count a piece of core if there is any doubt about its meeting the soundness requirement as evidenced by discolored or bleached grains, heavy staining, pitting, or weak grain boundaries. This procedure may unduly penalize the rock quality, but it errs on the side of conservatism. A second procedure that is occasionally used includes the altered rock within the RQD summed percentage, but indicates by means of an asterisk (RQD\*) that the soundness requirements have not been met. The advantage of this method is that the RQD\* will provide some indication of the rock quality with respect to the degree of fracturing, while also noting its lack of soundness.

Core breaks caused by the drilling process should be fitted together and counted as one piece. Drilling breaks are usually evidenced by rough fresh surfaces. For schistose and laminated rocks, it is often difficult to discern the difference between natural breaks and drilling breaks. When in doubt about a break, it should be considered as natural in order to be conservative in the calculation of RQD for most uses. Obviously, this practice would not be conservative when the RQD is used as part of a ripping or dredging estimate.

# **3.6.5.6 Drilling Fluid Recovery**

The loss of drilling fluid during the advancement of a boring can be indicative of the presence of open joints, fracture zones or voids in the rock mass being drilled. Therefore, the volumes of fluid losses and the intervals over which they occur should be recorded. For example, "no fluid loss" means that no fluid was lost except through spillage and filling the hole. "Partial fluid loss" means that a return was achieved, but the amount of return was significantly less than the amount being pumped in. "Complete water loss" means that no fluid returned to the surface during the pumping operation. A combination of opinions from the field personnel and the driller on this matter will result in the best estimate.

#### 3.6.5.7 Core Handling and Labeling

Rock cores from geotechnical explorations should be stored in structurally sound core boxes made of wood or corrugated waxed cardboard (Figure 3-19). Wooden boxes should be provided with hinged lids, with the hinges on the upper side of the box and a latch to secure the lid in a closed position.

Cores should be handled carefully during transfer from barrel to box to preserve mating across fractures and fracture-filling materials. Breaks in core that occur during or after the core is transferred to the core box should be refitted and marked with three short parallel lines across the fracture trace to indicate a mechanical break. Breaks made to fit the core into the core box and breaks made to examine an inner core surface should be marked as such. These deliberate breaks should be avoided unless absolutely necessary. Cores should be placed in the boxes from left to right, top to bottom. When the upper compartment of the box is filled, the next lower (or adjoining) compartment should be filled beginning at the lefthand side, and so on the same way until the box is filled. The depths of the top and bottom of the core and each noticeable gap in the formation should be marked by a clearly labeled wooden spacer block.

If there is less than 100 percent core recovery for a run, a cardboard tube spacer of the same length as the core loss should be placed in the core box either at the depth of core loss, if known, or at the bottom of the run. The depth of core loss, if known, or length of core loss should be marked on the spacer with a black permanent marker. The core box labels should be completed using an indelible black marking pen. An example of recommended core box markings is shown in Figure 3-19. The core box lid should have identical markings both inside and out, and both exterior ends of the box should be marked as shown in Figure 3-19. For angled borings, depths marked on core boxes and boring logs should be noted on the core box and the boring. The angle and orientation of the boring should be noted on the core box and the boring log.



Subcontract No. Boring No. Runs Depth from to	Run #         Depths         Rec (mm)         RQD (mm)	Box #of Date Sketch of Location of Core within the Core Box
Subcontract No. Boring No.	Run Nos. Box Depths	
	Core Box Front and Back Face	/
		Subcontract No. Run Nos. Boring No. Depths Box #of

Figure 3-19. Core box for storage of recovered rock and labeling.

#### 3.6.5.8 Care and Preservation of Rock Samples

A detailed discussion of sample preservation and transportation is presented in ASTM D 5079. Four levels of sample protection are identified as follows:

- a) routine care,
- b) special care,
- c) soil-like care, and
- d) critical care.

Routine care in placing rock core in core boxes will be used for most geotechnical explorations. ASTM D 5079 suggests enclosing the core in a loose-fitting polyethylene sleeve prior to placing the core in the core box.

Special care is considered appropriate if the moisture state of the rock core (especially shale, claystone and siltstone) and the corresponding properties of the core may be affected by exposure. Special care can also be applied if it is important to maintain fluids other than water in the sample. Critical care is needed to protect samples against shock and vibration or variations in temperature, or both. For soil-like care, samples should be treated as indicated in ASTM D 4220.

# **3.6.6 Geologic Mapping**

Geologic mapping is the systematic collection of local, detailed geologic data, and, for engineering purposes, is used to characterize and document the condition of a rock mass or outcrop. The data derived from geologic mapping are a portion of the data required for the design of a cut slope or for the stabilization of an existing slope. Geologic mapping can often provide more extensive and less costly information than drilling. Soil and soil-like materials, although occasionally mapped, are not considered in this section. For a detailed discussion of geologic mapping, the reader is referred to the FHWA manual on rock slopes (FHWA, 1998a).

# 3.7 STANDARD PENETRATION TEST (SPT)

The standard penetration test (SPT) is performed during the advancement of a soil boring to obtain a disturbed drive sample (split barrel type) of the soil being penetrated and an approximate measure of its dynamic resistance. The test was introduced by the Raymond Pile Company in 1902 and remains today as the most common in-situ test performed worldwide. The procedures for the SPT are detailed in ASTM D 1586 and AASHTO T 206. A summary of the important features of the test follows.

The SPT involves the driving of a hollow thick-walled tube into the ground and measuring the number of blows to advance the split-barrel sampler having standard dimensions of 2 in (50 mm) outside diameter (OD) and 1-3/8 in (35 mm) inside diameter (ID) a vertical distance of 1 ft (300 mm), see Figure 3-20. A 140 pound (63.5 kilogram) hammer is repeatedly dropped from a height of 30 in (0.76 m) to achieve three successive 6 in (150 mm) increments of penetration. The first recorded increment is considered as a "seating" penetration, while the number of blows to advance the second and third increments are summed to give the N-value ("blow count") or SPT-resistance (reported in blows per foot (0.3 m)).

The SPT can be halted when a total of 100 blows have been counted or if the number of blows exceeds 50 in any given 6 in (150 mm) increment, or if the sampler fails to advance during 10 consecutive blows. SPT refusal is defined by penetration resistances exceeding 100 blows per 2 in (50 mm), although ASTM D 1586 has re-defined this limit at 50 blows per 1 in (25 mm). If bedrock, or an obstacle such as a boulder, is encountered, the boring may be advanced further by using diamond core drilling or non-core rotary methods (ASTM D 2113; AASHTO T 225) at the discretion of the geotechnical specialist. In certain cases, this SPT criterion may be utilized to define the top of bedrock within a particular geologic setting where boulders are not of concern or not of great impact on the project requirements. The advantages and disadvantages of the SPT are listed in Table 3-8.

	Advantages and disadvantages of the Standard Penetration Test (SPT)				
Advantages		Disadvantages			
•	Obtain both a sample and an N-value	•	Disturbed sample (index tests only)		
•	Simple and rugged	٠	N-value is a crude number for analysis		
•	Suitable in many soil types	•	Not applicable in soft clays & loose silts		
•	Can be performed in weak rocks	•	High variability and uncertainty		
•	Readily available throughout the U.S.	•	Unreliable in gravelly soils		

 Table 3-8

 Advantages and disadvantages of the Standard Penetration Test (SPT)

FHWA NHI-06-088 Soils and Foundations – Volume I



# Figure 3-20. Sequence of driving split-barrel sampler during the Standard Penetration Test (modified after FHWA, 2002b).

The SPT is conducted at the bottom of a soil boring that has been advanced by use of either flight augers or rotary wash drilling methods. The borehole can be cased or uncased. At regular depth intervals, the drilling process is interrupted to perform the SPT. Generally, at depths shallower than 10 ft (3 m) the SPT is performed continuously or at intervals of 2.5 ft (0.75 m). Below a depth of 10 ft (3 m) the SPT is generally performed at intervals of 5 ft (1.5 m) to the planned end of the boring or refusal. If the borehole extends below the groundwater table, the head of water in the borehole must be maintained at or above the ambient groundwater level to avoid inflow of water and borehole instability.

Liners may be placed inside the split-barrel sampler with the same inside diameter as the cutting shoe, see Figure 3-21a. This allows samples to remain intact during transport to the laboratory. The liners may be arranged in a set of 1-inch (25 mm) high rings in which case "ring" samples of pre-determined height may be obtained. In U.S. practice, it is normal to omit the liner. The resistance of the sampler to driving is altered depending upon whether or not a liner is used (Skempton 1986, Kulhawy and Mayne, 1990). Therefore, **when the liners are used, their use should be clearly mentioned in the boring logs.** 

Steel or plastic sampler "catchers" are often required to keep samples of clean granular soils in the split-barrel sampler. Figure 3-21 shows a variety of catchers. They are inserted inside the sampler between the cutting shoe and the sample barrel to help retain loose or flowing materials. These catchers permit the soil to enter the sampler during driving but upon withdrawal they close and thereby retain the sample. **Use of sample catchers should be noted on the boring log.** 



(a)



(b)



FHWA NHI-06-088 Soils and Foundations – Volume I

3 - 53 Engineering-pdh.com | ged-115 | 3 – Subsurface Explorations December 2006

#### 3.7.1 Energy Efficiency of Hammers

In current U.S. practice, three types of drop hammers and four types of drill rods are used in performing the SPT. Drop hammer types are typically donut, safety, and automatic (see Figure 3-22). Typical drill rod sizes are N or A (see Figure 3-20 for sizes). The test results are highly dependent upon the type of equipment used and the experience of the operator performing the test. One of the more important factors for obtaining useful data from the test is the energy efficiency of the system. The theoretical energy of a free-fall system with the specified mass and drop height is 350 ft-lb (48 kg-m), but the actual energy is less due to a number of factors including frictional losses and eccentric loading that are specific to the hammer drop. The energy efficiency of the rotating cathead and rope system commonly used in the past depends on numerous factors including: type of hammer, number of rope turns, conditions of the sheaves and rotating cathead (e.g., lubricated, rusted, bent, new, old), age of the rope, actual drop height, vertical plumbness, weather and moisture conditions (e.g., wet, dry, freezing), and other variables (see for example Skempton, 1986). In the recent past the trend has been towards the use of automated systems for lifting and dropping the mass in order to minimize these factors. Automated systems provide more reliable and more reproducible results than the rotating cathead and rope system used in the past.



Figure 3-22. SPT hammer types, (a) Donut, (b) Safety, and (c) Automatic (FHWA, 2006a).

A calibration of energy efficiency for a specific drill rig and operator is recommended by ASTM D 4633. Instrumented strain gages and accelerometer measurements are used for these calibrations in an attempt to standardize the energy levels. The standard of practice for energy efficiency varies from about 35% to 85% with cathead systems using donut or safety hammers. The average for cathead systems in the United States is approximately 60%. The newer automatic trip-hammers can deliver between 80 to 100% efficiency, depending upon the type of commercial system being used.

If energy efficiency ( $E_f$ ) is measured, then the energy-corrected SPT N-value adjusted to 60% efficiency ( $N_{60}$ ) is given by:

$$N_{60} = (E_f/60) N_{meas}$$
 3-2

where  $N_{meas}$  is the N-value measured in the field during the test. N-values measured in the field should be corrected to  $N_{60}$  for all soils, if possible. The relative magnitudes of corrections for energy efficiency, sampler lining, rod lengths, and borehole diameter are given by Skempton (1986) and Kulhawy and Mayne (1990), but only as general guidelines. Theoretically it is mandatory to measure  $E_f$  to get the proper correction to  $N_{60}$ . In absence of data, AASHTO (2004 with 2006 Interims) recommends  $E_f = 60$  for rope and cathead systems, i.e., donut and safety hammers and  $E_f = 80$  for automatic hammer systems.

The efficiency may be obtained by comparing either the work done (W = F.d = force times displacement) or the kinetic energy (KE =  $\frac{1}{2}mv^2$ ) with the potential energy of the system (PE = mgh), where m = mass, v = impact velocity, g = 32.2 ft/s<sup>2</sup> = 9.8 m/s<sup>2</sup>= gravitational constant, and h = drop height. Thus, the energy ratio (ER) is defined as W/PE, or ER = KE/PE. It is important to note that geotechnical foundation practice and engineering usage based on SPT correlations have been developed on the basis of the standard-of-practice, corresponding to an average ER  $\approx 60$  %. Thus, it is recommended to adjust measured N-values (N<sub>meas</sub>) to N<sub>60</sub> values.

Figure 3-23 exemplifies the need for correcting measured N-values to a reference energy level where the successive SPTs were conducted by alternating the use of donut and safety hammers in the same borehole. The energy ratios were measured for each test and gave 34 < ER < 56 for the donut hammer (average = 45%) and 55 < ER < 69 for the safety hammer (average = 60%) at this site. The individual trends for the measured N-values from donut and safety hammers are quite apparent in Figure 3-23(a), whereas a consistent profile is obtained in Figure 3-23(b) once the data have been corrected to ER = 60%.



Figure 3-23. SPT N-values from (a) Uncorrected data, and (b) Corrected to 60% efficiency (Data modified after Robertson and Campanella, 1983).

#### 3.7.2 Effect of Overburden Stress on N-values

Since N-values of similar materials increase with increasing effective overburden stress, the corrected blow count ( $N_{60}$ ) is often normalized to 1-atmosphere (1 tsf or about 100 kPa) effective overburden stress by using overburden normalization schemes. The energy-corrected blow count normalized for overburden is referred to as  $N1_{60}$ , and is equal to:

$$N1_{60} = C_N N_{60}$$
 3-3

where  $C_N$  is the overburden correction factor (or stress normalization parameter) calculated as (Peck, *et al.*, 1974):

$$C_N = [0.77 \log_{10} (20/p_o)]$$
, and  $C_N < 2.0$   
 $p_o =$  vertical effective pressure at the depth where the SPT test is performed (tsf)  
 $N_{60} =$  SPT blow count corrected for hammer efficiency (blows/ft) – refer to Equation 3-2

Note that the constants in Equation 3-3 are unit dependent therefore the units of  $p_0$  must be tsf. Figure 3-24 presents the overburden correction factor as a function of vertical effective stress.



Figure 3-24. Variation of overburden correction factor, C<sub>N</sub>, as a function of vertical effective stress.

Caution should be exercised in applying the overburden correction factor to indurated cemented soils, e.g., hard caliche soils encountered in the desert southwest. In such soils, the overburden pressure may not be a direct function of the depth of the soil. Therefore, the overburden correction is not recommended for such soils since it may lead to overly conservative designs.

#### 3.7.3 Correlation of SPT N-Values with Basic Soil Characteristics

SPT N-values are an indication of the relative density of cohesionless soils and the consistency of cohesive soil. Table 3-9 shows N-value ranges correlated to the relative density of sands and the consistency of fine-grained soils. It is emphasized that these correlations are unreliable for gravels, silts and clays and should serve only as crude estimates for these materials.

Soil properties correlated with Standard Penetration Test values (after Peck, <i>et al.</i> , 1974)					
Sands (Reliable)		Silts and Clays (Unreliable)			
N <sub>60</sub>	Relative Density	N <sub>60</sub>	Consistency		
0-4	Very loose	Below 2	Very soft		
5-10	Loose	2-4	Soft		
11-30	Medium Dense	5-8	Medium		
31-50	Dense	9-15	Stiff		
Over 50	Very dense	16-30	Very stiff		
		Over 30	Hard		

 Table 3-9

 Soil properties correlated with Standard Penetration Test values (after Peck. *et al.*, 1974)

## 3.7.3.1 Applicability of SPTs in Gravelly Soils

The SPT can be performed in a wide variety of soil types as well as weak rocks, however the SPT is not particularly useful in the characterization of gravely soils. Since the split-spoon inside diameter is  $1-\frac{3}{8}$  in (35 mm), gravel sizes larger than  $1-\frac{3}{8}$  in (35 mm) will not enter the spoon. Therefore, soil descriptions may not reflect actual gravel content of the deposit. Also, gravel pieces may plug the end of the spoon and cause the SPT blow count to be erroneously large. Thus, the SPT in such cases produces refusal blow counts (i.e., > 50 blows per 1 in (25) mm)) that are misleading and lead to unconservative designs. In this case, "Large Penetration Tests" (LPTs), such as the Becker Penetration Test (BPT), are more suitable. The LPTs consist of driving a pipe (casing) larger than the standard split spoon sampler into the ground with a pile-driving hammer. While the pipe is being driven, the driving resistance or blow count/ft of penetration is recorded. Unlike the SPT, the LPT blow count is nonstandardized and is a function of the drill rod size, pipe (sampler) size, hammer type, and hammer efficiency. Careful energy calibrations are required to correlate the LPT blow counts to SPT N-values However, this effort may be worthwhile considering that the results of SPT in gravelly soils are unreliable and misleading. Daniel, et al. (2003) present methods for evaluating LPT blow counts.

Since the gravel content cannot be measured by the SPT, it is recommended that consideration be given to obtaining bulk samples by drilling large diameter borings with

augers similar to the one shown in Figure 3-5a. The bulk samples obtained from such borings will also help evaluate whether the soil deposit is indeed a gravel deposit or gravels are larger particles floating in a softer soil matrix. The bulk samples will also permit an accurate determination of the Unified Soil Classification System (USCS) designation (see Chapter 4), which will be useful from design as well as constructability considerations.

## 3.7.4 SPT Test Errors

Although the procedures for conducting the SPT test have been standardized, several errors can creep into the test. The most common errors are:

- 1. Effect of overburden pressure. Soils of the same density will give smaller blow counts near the ground surface. The overburden stress normalization parameter  $(C_N)$  can be used to correct for this factor.
- 2. Variations in the 30 in (770 mm) free fall of the drive weight. The drop height is often gauged by eye with the older rotating cathead and rope system Newer hammer systems automatically release the weight at a height of 30 inches. The energy correction factor accounts for this factor.
- 3. Interference with the free fall of the drive weight by the guides or the hoist rope required in the rotating cathead and rope system. Newer automatic hammer systems eliminate rope interference. The energy correction factor accounts for this factor.
- 4. Use of a drive shoe that is damaged or worn from too many "refusal" blow counts  $(N_{meas} \ge 100 \text{ blows/foot}).$
- 5. Failure to seat the sampler properly on undisturbed material in the bottom of the boring.
- 6. Inadequate cleaning of loosened material (slough) from the bottom of the boring.
- 7. Failure to maintain sufficient hydrostatic pressure in the borehole during drilling below the groundwater table. Unbalanced hydrostatic pressures between the borehole drill water and the groundwater table can cause the test zone to become "quick." This can happen when a continuous-flight auger is used with the end plugged and with a water level in the hollow stem below that in the hole.
- 8. Effect of gravel size as discussed in Section 3.7.3.1.

- 9. Samples retrieved from dilatant soils (fine sands, sandy silts) that exhibit unusually high blow counts should be examined in the field to determine if the sampler drive shoe is plugged. Poor sample recovery is usually an indication of plugging.
- 10. Careless work on the part of the drill crew.

# The use of qualified and experienced drillers cannot be overemphasized. Agencies that maintain their own drilling personnel and equipment generally achieve much more reliable and consistent results than those that routinely let boring contracts to the lowest bidder.

Soil type, density, and overburden pressure are the most significant factors affecting SPT N-values (assuming good workmanship and equipment). Table 3-10 lists factors affecting the SPT and SPT results.

Regardless of the impressive list of shortcomings, the SPT is not likely to be abandoned for several reasons:

- 1. The test is very economical in terms of cost per unit of information.
- 2. The test results provides soil samples, which can be tested for index properties and visually examined.
- 3. Long service life of the enormous amount of equipment in use.
- 4. The accumulation of a large SPT database that is continually expanding.
- 5. The results of the SPT have been correlated with a number of soil properties to provide estimates of the values of those properties. The estimated values are often used for preliminary designs in lieu of values obtained from tests run specifically to determine those properties.
- 6. The fact that other methods can be readily used to supplement the SPT when the borings indicate more refinement in sample/data collection.

i actors arrecting the SI i t	ind of Tresults (after Kunnuwy and Mu	yne, 1770)
Cause	Effects	Influence on SPT N-value
Inadequate cleaning of hole	SPT is performed in loose slough.	Increases
1 C	Therefore soil may become trapped in	
	sampler and may be compressed as	
	sampler is driven, reducing recovery	
Failure to maintain adequate	Bottom of borehole may become	Decreases
head of water in borehole when	"quick"	
test is performed below		
groundwater level		
Careless measure of hammer	Hammer energy varies (generally	Increases
drop	variations cluster on low side)	
Hammer weight inaccurate	Hammer energy varies (driller supplies	Increases or
	weight; variations of 5 - 7 percent are	decreases
	common)	
Hammer strikes drill rod collar	Hammer energy reduced	Increases
eccentrically		
Lack of hammer free fall	Hammer energy reduced	Increases
because of ungreased sheaves,		
new stiff rope on weight, more		
than two turns on cathead,		
incomplete release of rope each		
drop		
Sampler driven above bottom	Sampler driven in disturbed, artificially	Increases
of casing	densified soil	greatly
Careless counting of hammer	Inaccurate results	Increases or
blows		decreases
Use of non-standard sampler	Correlations with SPT sampler invalid	Increases or
		decreases
Coarse gravel or cobbles in soil	Sampler becomes clogged or impeded	Increases
Use of bent drill rods	Inhibited transfer of energy of sampler	Increases

 Table 3-10

 Factors affecting the SPT and SPT results (after Kulhawy and Mayne, 1990)

# 3.8 LOG OF BOREHOLE INFORMATION ("BORING LOGS")

The importance of accurate field notes and good logging of boreholes cannot be overemphasized. The logger must realize that a good field description must be recorded. The field-boring log is the major portion of the factual data used in the analysis of foundation conditions.

The boring log is a record that should contain all of the information obtained from a boring whether or not it may seem important at the time of drilling. It is important to record the maximum amount of information accurately. This record is the "field" boring log, as opposed to the "finished" boring log used in the preparation of the geotechnical data report. The finished log is drawn from the data presented in the field log supplemented by the results of visual identifications of samples and classification tests made in the laboratory. A typical boring log form is shown on Figures 3-25. The form presented in Figures 3-25 can be used for recording *field* data as well.

#### 3.8.1 Boring Log Format

A wide variety of boring log forms are used by various agencies. The specific log to be used for a given type of boring will depend on local practice. The log in Figures 3-25 is just one example of a log used by geotechnical specialists. For detailed information on boring logs, the reader can refer to FHWA (1997, 2002b). The boring log shown in Figures 3-25 is used in this document simply to present the reader with an idea of the basic information that should be included in a boring log. Specific projects will likely require more detailed logs. Often separate logs are used for logging information from borings in soils and rocks unlike the log shown in Figures 3-25, which combines this information.

#### 3.8.2 Duties of the Logger

The technical background and experience of the person who logs the field information will vary by organization. Some organizations will have a geotechnical engineer, an engineering geologist, a geologist, or a trained technician to accompany the drill crew, while others may train the drill crew foreman to log the borehole. In order to obtain the maximum amount of accurate data, the logger should work closely with the driller and be alert for changes in materials and operations while drilling is being performed. The logger is generally responsible for recording the following basic information on the field boring log:



Figure 3-25a. Example subsurface exploration log (0 – 35 ft depth).

FHWA NHI-06-088 Soils and Foundations – Volume I
REGION	REGION 3 SUBSURFACE EXPLORATION LOG HOLE_BAF-2												
COUNTY	COUNTY_Orange							LINE_Baseline					
PROJEC	PROJECT Interstate 0							STA. <u>92+00</u>					
DATE ST	DATE START 5/4/92					2	HAN	AMMER FALL-CASING_18" OFFSET_50' Lt	OFFSET 50' Lt				
DATE FIN	DATE FINISH 5/6/92						HAN	HAMMER FALL-SAMPLER 30" SURF. ELEV. 996.2					
CASING	CASING O.D I.D WE				1/4"		WE	EIGHT OF HAMMER-CASING 300 LBS.					
SAMPLE	R O.D.	2"	I.D	1-:	3/8"		WE	EIGHT OF HAMMER-SAMPLER 140 LBS. TIME 4:00 pm 8:00 am					
<b>RIG TYP</b>	E Acke	er B-40						DATE 5/4/92 5/6/92					
CORE BA	CORE BARREL Double Tube DEPTH TO WATER 10' 10'												
HAR	BLOWS ON	SAMPLE NO.	BLOWS ON SAMPLER		El les								
						COVI	DESCRIPTION OF SOIL AND ROCK	MOIST					
N N							CONT 96						
	62	J13	1	2	4	-	16						
	63												
	72							MOIST - PLASTIC					
-	71							39'					
<u>40</u>	89	-	20		05	-	-						
<u>-</u>	91	-	30	20	35								
	104			-				4 +					
· · ·	120							GR SANDY GRAVEL					
	140							MOIST - NON PLASTIC					
	110							(Cored Boulder 42.5' to 45' recovered 12"-7 pieces: used boulder buster)					
	136												
-	166												
-	191	-	-	-									
<u>50</u>	482	-		-				TOP OF ROCK 50°					
-	-		-	-	-		-	HARD UNWEATHERED BASALT					
-	-							Bun 1 50 55'					
								RQD = 80% 55'					
-	-												
-		-	-	-			_	HARD UNWEATHERED BASALT					
			-	-	-	-	-						
-	-	-	-	-	-		-	Run 2 55 - 60'					
60 -		1						- RQD = 75%					
								4 4					
		-						4 -					
	-	-	-	-	-			4					
								4 +					
								j ł					
<u>70</u>								] [					
100													
	THE SUBSURFACE INFORMATION SHOWN HERE WAS OBTAINED FOR STATE DESIGN AND ESTIMATE PURPOSES. IT IS MADE AVAILABLE TO AUTHORIZED USERS ONLY THAT THEY MAY HAVE ACCESS TO THE SAME INFORMATION AVAILABLE TO THE STATE. IT IS PRESENTED IN GOOD FAITH, BUT IS NOT INTENDED AS A SUBSTITUTE FOR INVESTIGATION, INTERPRETATION OR JUDGMENT OF SUCH AUTHORIZED USERS.					on Sh Iate Sers Iatio Th, Bi On, II Zed U	iowi Purf Onl' N AV JT IS NTER JSER	VN HERE WAS OBTAINED       DRILL RIG OPERATOR Klinedinst         XPOSES. IT IS MADE       DRILL RIG OPERATOR Klinedinst         XPOSES. IT IS MADE       SOIL & ROCK DESCRIP. Chassie         LY THAT THEY MAY HAVE       SOIL & ROCK DESCRIP. Chassie         VAILABLE TO THE STATE.       REGIONAL SOILS ENGR. Cheney         S NOT INTENDED AS A       SHEET 2 OF 2         RPRETATION OR       STRUCTURE NAME/NO. Apple Freeway #2					
CONTR	CONTRACTOR ACME Drilling, Inc. SM					SM		HOLE_BAF-2					

Figure 3-25b. Example subsurface exploration log (35 - 60 ft depth).

1. General description of each soil and rock stratum, and the depth to the top and bottom of each stratum. As noted before, the log demonstrated in Figure 3-25 is intended to be a field log. On the final log, the description of the soil should be much more detailed and follow a specified soil classification system. Soils in the geotechnical engineering community are most often classified according to the Unified Soil Classification System (USCS). For example, the soils between depths 15 ft to 39 ft have been simply described in the field as "GR. SILTY CLAY, MOIST-PLASTIC." The full classification as per USCS on the final log may read as follows (the detailed description and classification of soils and the USCS are discussed in Chapter 4):

Soft, wet, gray, high plasticity CLAY, with Silt; Fat CLAY (CH); (Alluvium)

- 2. The depth to groundwater at the time it is first encountered and afterwards at the end of each day, at completion of boring, and, if possible, at least 24 hours after completion of the boring.
- 3. The depth at which each sample is taken, the type of sample taken, its number, and any loss of samples taken during extraction from the hole.
- 4. The depths at which field tests are made and the results of the test.
- 5. Information generally required by the log format, such as:
  - Boring number and location.
  - Date of start and finish of the hole.
  - Name of driller (and of logger, if applicable).
  - Elevation at top of hole.
  - Depth of hole and reason for termination.
  - Diameter of any casing used.
  - Size of hammer and free fall used on casing (if driven).
  - Blows per foot to advance casing (if driven).
  - Description and size of sampler.
  - Size of drive hammer and free fall used on sampler in dynamic field tests.
  - Blow count for each 6 in (150 mm) to drive sampler. (Sampler should be driven three 6 in (150 mm) increments or to a total of 100 blows).
  - Type of drilling rig used.

- Type and size of core barrel used.
- Length of time to drill each core run or foot of core run.
- Length of each core run and amount of core per run.
- Recovery of sample in inches and RQD of rock core.
- Project identification.
- 6. Notes regarding any other pertinent information and remarks on miscellaneous conditions encountered, such as:
  - Depth of observed groundwater, elapsed time from completion of drilling, conditions under which observations were made, and comparison with the elevation noted during reconnaissance (if any).
  - Artesian water pressure.
  - Obstructions encountered.
  - Difficulties in drilling (caving, coring boulders, surging or rise of sands in casing, caverns, etc.).
  - Loss of circulating water and addition of extra drilling water.
  - Drilling mud and casing as needed and why.
  - Odor of recovered sample.
  - Sampler plugged.
  - Poor recovery.
- 7. Any other information the collection of which may be required by agency policy (e.g., names and associations of visitors to the site, etc.).

# 3.9 CONE PENETRATION TESTING (CPT)

The history of field cone penetrometers began with a design by the Netherlands Department of Public Works in 1930. This "Dutch" cone penetrometer was a mechanical operation using a manometer to read loads. Paired sets of inner and outer rods are pushed into the ground in 8 in (200 mm) intervals. In 1948, electric cones permitted continuous measurements to be taken downhole. In 1965, the addition of sleeve friction measurement devices allowed an indirect means for identifying soil types. Later, in 1974, the electric cone was combined with a piezoprobe to form the first piezocone penetrometer. Most recently, additional sensors have been added to form specialized devices such as the resistivity cone, acoustic cone, seismic cone, vibrocone, cone pressuremeter, and lateral stress cone.

The cone penetration test (CPT) was first introduced in the U.S. in 1965. Since that time, the CPT has developed into one of the most popular in-situ testing methods because it is fast, economical, and provides continuous profiling of the geostratigraphy and allows for continuous in-situ evaluation of soil properties. Depending upon equipment capability as well as soil conditions, 330 to 1150 ft (100 to 350 m) of penetration testing may be completed in one day.

As shown in Figure 3-26, the CPT involves the hydraulic push of an instrumented steel probe into the soil at a constant rate to obtain continuous vertical profiles of stresses and/or other measurements. No borehole, cuttings, or spoil are produced by this test. Testing is conducted in accordance with ASTM D 5778.

The CPT can be used in very soft clays to dense sands. It is not suitable for use in highly indurated or cemented soils or in soils containing significant amounts of gravel and boulders. The advantages and disadvantages of the CPT are listed in Table 3-11.

Auvantages and disauvantages of the cone reneuration rest (CI I) (FIIWA, 2002b)					
Advantages	Disadvantages				
• Fast and continuous profiling	• High capital investment				
Economical and productive	• Requires skilled operator to run				
• Results not operator-dependent	• Electronic drift, noise, and calibration				
• Strong theoretical basis in interpretation	• No soil samples are obtained				
• Particularly suitable for soft soils	• Unsuitable for gravel/boulder deposits*				
*Note: Except where special rigs are provided and/or additional drilling support is available.					

 Table 3-11

 Advantages and disadvantages of the Cone Penetration Test (CPT) (FHWA, 2002b)



Figure 3-26. Procedures and components of the Cone Penetration Test (FHWA, 2002b).

Although the test provides continuous logging of the in-situ response of the soil, which can lead to more accurate and reliable analyses, no soil samples are available for laboratory testing. For that reason the CPT provides an excellent complement to the more conventional soil test boring with SPT measurements and subsequent laboratory testing on retrieved samples.

# 3.9.1 Equipment Description and Operation

Electronic cones are now the dominant cone type used in cone penetration testing. Therefore, mechanical cones are not discussed in this document. Electronic cones may be further divided into three primary types: (a) the standard friction cone (CPT), (b) the piezo-cone (PCPT or more commonly CPTu), and (c) the seismic cone piezo-cone (SCPTu). Each of these cones is briefly described here. To assist in following the brief descriptions, the standard terminology regarding the cone penetrometer is shown in Figure 3-27.



Figure 3-27. Cone penetrometer terminology (from Robertson and Campanella, 1989).

#### **3.9.2** The Standard Cone Penetration Test (CPT)

The equipment necessary for performing a standard CPT includes a penetrometer, cone rod or drill rod, an electrical cable, a data acquisition system, and a hydraulic actuator attached to equipment that has sufficient reaction mass to advance the penetrometer. The equipment that provides the reaction mass can be a conventional drilling rig, however, a dedicated CPT truck commonly weighing 20 to 25 tons (200 to 250 kN) is more commonly used.

A standard cone penetrometer is a 1.4 in (35.7 mm) diameter cylindrical probe with a  $60^{\circ}$  conical apex at the tip. The tip has a projected area of 1.6 in<sup>2</sup> (10 cm<sup>2</sup>). The surface area of the sleeve above the cone is 23.3 in<sup>2</sup> (150 cm<sup>2</sup>). More robust penetrometers are available with a 1.7 in (44 mm) diameter body, a 2.3 in<sup>2</sup> (15 cm<sup>2</sup>) projected tip area, and a 31 to 35 in<sup>2</sup> (200 to 225 cm<sup>2</sup>) sleeve surface area. A penetrometer having a projected cone area of 2.3 in<sup>2</sup> (15 cm<sup>2</sup>) will generally provide the same response as one having a projected cone area of 1.6 in<sup>2</sup> (10 cm<sup>2</sup>). The "size" of a cone is defined by its projected tip area, e.g. a 1.6 in<sup>2</sup> (10 cm<sup>2</sup>) cone or a 2.3 in<sup>2</sup> (15 cm<sup>2</sup>) cone. Figure 3-28 shows a number of different cone penetrometers and piezocones.



Figure 3-28. Cone and piezocone penetrometers (note the quarter for scale) (FHWA, 2002b).

A section of standard cone rod is typically 3.3 ft (1 m) in length with a 1.4 in (35.7 mm) outer diameter and a 0.9 in (22 mm) inner diameter. Alternatively, the penetrometer can be pushed with standard AW drill rod (1<sup>3</sup>/<sub>4</sub> in (44.4 mm) OD; 1<sup>1</sup>/<sub>4</sub> in (31.8mm) ID) or EW drill rod (1<sup>3</sup>/<sub>8</sub> in (34.9 mm) OD; 15/16 in (23.8 mm) ID).

The cone cable runs through the hollow cone/drill rods and attaches to an electronic data acquisition system at the ground surface. The data acquisition system generally consists of an analog signal conditioner, an analog to digital (A-D) converter, and a computer processor. Current data acquisition systems are attached to one or two computer monitors so the operator and engineer can observe data recorded during the sounding in real time. Real time monitoring allows for decisions to be made in the field with respect to the sounding. This is helpful if auxiliary tests, such as a pore pressure dissipation test, are to be performed in certain soil layers, or if the test is to be terminated once a certain layer is encountered. Printers can be attached to the computer processor to obtain a real-time printout of the data. Printed data are a good backup in case an unforeseen incident causes the computer to crash resulting in the loss of the electronically stored data. Data are typically recorded every <sup>3</sup>/<sub>4</sub> to 2 in (20 to 50 mm) of vertical penetration.

The test procedure for the standard cone penetration test and the nature of the data acquired during the test are described in Sections 3.9.5 and 3.9.6, respectively.

# 3.9.3 The Piezo-cone Penetration Test (CPTu)

The piezo-cone (CPTu) is essentially the same as the standard electronic friction cone except that it includes porous filter piezo-elements that may be located at the cone tip, on the cone face, behind the cone tip, or behind the friction sleeve. These porous filter elements are used to measure pore water pressure during penetration. Saturation of the porous element and cavity is essential to obtain reliable pore water pressure measurements.

# 3.9.4 The Seismic Piezocone Penetration Test (SCPTu)

For the seismic piezocone test (SCPTu), a geophone is located approximately 1.6 feet (500 millimeters) uphole from the cone tip. The geophone detects shear waves generated at the ground surface at intervals of approximately 3 or 5 ft (1 or 1.5 m), corresponding to successive rod additions. If necessary, adjustments should be made if AW or EW rods are used to advance the cone since they typically come in longer lengths.

# 3.9.5 Test Procedures

The test procedure for the CPT consists of hydraulically pushing the cone at a rate of 0.8 in/s (20 mm/s) in accordance with ASTM D 5778 by using either a standard drill rig or a specialized cone truck as the reaction mass (see Figure 3-29). The advance of the probe requires the successive addition of rods at approximately 3 or 5 ft (1 or 1.5 m) intervals. Readings of tip resistance ( $q_t$ ), sleeve friction ( $f_s$ ), inclination (*i*), and pore water pressure ( $u_m$ ) are taken at least every 2 in (50 mm) (i.e., at approximately 2.5-sec intervals). For the seismic cone test, shear wave arrival times ( $t_s$ ) are typically recorded at rod breaks corresponding to 3 or 5 ft (1 or 1.5 m) intervals.



Figure 3-29. Cone penetration testing from cone truck.

FHWA NHI-06-088 Soils and Foundations – Volume I

#### 3.9.6 CPT Profiles

The results of the individual channels of a piezocone penetration test are plotted with depth, as illustrated in a typical plot shown in Figure 3-30. Since soil samples are not obtained with the CPT, an indirect assessment of Soil Behavioral Type (SBT) is inferred by an examination of the readings. The numbers can be processed for use in empirical chart classification systems, or the raw readings can be easily interpreted for soil strata changes. A simplified soil classification chart for a standard electric friction cone is presented in Figure 3-31. The sleeve friction, often expressed in terms of a friction ratio  $R_f = f_s/q_t$ , also is a general indicator of soil type. For example, in sands, usually  $0.5\% < R_f < 1.5\%$ ; and in clays, normally  $3\% < R_f < 10\%$ . In the lower half of the Figure 3-31, the center column shows an approximate relationship between the SPT N-value and the cone tip resistance,  $q_c$ . The SPT N-value obtained from this relationship should be considered to be equivalent to N1<sub>60</sub>.

#### **3.9.7** CPT Profile Interpretation

The CPT sounding shown in Figure 3-30 was taken in the immediate vicinity of the boring recorded in the boring log shown in Figures 3-25. These two logs permit an interesting comparison to be made of the SPT and CPT procedures. In the sounding shown in Figure 3-30, a clayey and sandy stratum (clay, clayey silt, silt, silty sand and sandy silt) occurs from the ground surface to a depth of 10 ft (3 m). These strata are underlain by a thick layer of sand and sandy silt to depth of approximately 20 ft (6 m), which in turn is underlain by a clay layer extending down to a depth of approximately 45 ft (14 m). Finally, a dense gravelly sand layer is encountered, which the cone penetrometer could not penetrate. The SPT tests could however be performed in this dense layer since it was possible to drill into this layer.

Figure 3-30 is a good example that demonstrates the advantage of continuous sounding compared to the samples obtained at discrete intervals using SPT procedures. For example, depending on the sampling interval in the SPT test, the silt layer within the clay layer may not have been undetected. Even if it had been detected, it would not have been possible to estimate its thickness accurately between the locations of the SPT samples because the SPT samples are commonly retrieved at 5 ft (1.5 m) intervals. The implications of this shortcoming can be significant in design. For example, silt consolidates faster than clay. If the designer is not aware of the silt layer, then he/she might design a wick drain surcharge system that, based on a clay layer 25 ft (7.5 m) thick, will take longer to consolidate than what might actually be the case. In fact, the CPT profile in Figure 3-30 shows that only the 15 ft (4.5 m) portion of the clay layer below the silt layer has excess pore pressures, which suggests that it will be the primary source of consolidation settlements.



Figure 3-30. Piezo-cone results for Apple Freeway Bridge.

It is important for the reader to understand that CPT procedures do not allow retrieval of physical samples that can be tested in the laboratory to characterize various phenomena such as consolidation and shear strength. Thus, it is most beneficial to use the CPT with another method, such as the boring technique used in the SPT, that allows the retrieval of physical samples for laboratory testing. Performing the CPT before sampling in borings will permit identification of the specific depths where disturbed and undisturbed physical samples should be obtained for laboratory tests.



# Figure 3-31. A commonly used simplified soil classification chart for standard electronic friction cone (after Robertson, *et al.*, 1986).

FHWA NHI-06-088 Soils and Foundations – Volume I

3 - 74 Engineering-pdh.com | ged-115 | 3 – Subsurface Explorations December 2006

#### 3.10 DILATOMETER TEST (DMT)

The dilatometer is an in-situ testing device that was developed in Italy in the early 1970s and first introduced in the U.S. in 1979. Like the cone penetrometer, the dilatometer is generally hydraulically pushed into the ground although it may also be driven. When the dilatometer can be pushed into the ground with tests conducted at 8 in (200 mm) increments, 100 to 130 ft (30 to 40 m) of soundings may be completed in a day. The primary utilization of the dilatometer test (DMT) in pile foundation design is the delineation of subsurface stratigraphy and interpreted soil properties. However, it would appear that the CPT/CPTu is generally better suited to this task than the DMT. The DMT may be a potentially useful test for the design of piles subjected to lateral loads. Design methods in this area show promise, but are still in the development stage. For design of axially loaded piles, the DMT has limited direct value. A picture of the DMT equipment is presented in Figure 3-32.



Figure 3-32. Dilatometer test equipment and procedure (FHWA 2002b).

FHWA NHI-06-088 Soils and Foundations – Volume I

3 - 75 engineering-pdh.com | geo-115 | 3 – Subsurface Explorations December 2006

#### 3.11 PRESSUREMETER TEST (PMT)

The pressuremeter is an in-situ device used to evaluate soil and rock properties. The pressuremeter has been used in Europe for many years and was introduced into the U.S. in the mid 1970s. The pressuremeter imparts lateral pressures to the soil, and the soil shear strength and compressibility are determined by interpretation of a pressure-volume relationship. The pressuremeter test (PMT) allows a determination of the load-deformation characteristics of soil in axisymmetric conditions. Deposits such as soft clays, fissured clays, sands, gravels and soft rock can be tested with pressuremeters. A pressuremeter test produces information on the elastic modulus of the soil as well as the at rest horizontal earth pressure, the creep pressure, and the soil limit pressure. A schematic of the pressuremeter test is presented in Figure 3-33.



Figure 3-33. Pressuremeter test schematic (FHWA, 2002b).

The utilization of test results is based upon semi-empirical correlations from a large number of tests and observations on actual structures. For piles subjected to lateral loads, the pressuremeter test is a useful design tool and can be used for determination of p-y curves. For design of vertically loaded piles, the pressuremeter test has limited value. Pile design procedures using pressuremeter data have been developed and may be found in FHWA (1989a). Details on test procedures may be found in ASTM D 4719.

FHWA NHI-06-088 Soils and Foundations – Volume I

#### 3.12 VANE SHEAR TEST (VST)

The vane shear test is an in-situ test for determining the undrained shear strength of soft to medium clays. Figure 3-34 is a schematic drawing of the essential components and test procedure. The test consists of forcing a four-bladed vane into undisturbed soil and rotating it until the soil shears. Two shear strengths are usually recorded, the peak shearing strength and the remolded shearing strength. These measurements are used to determine the **sensitivity of clay**, which is defined as the ratio of the peak undrained shearing strength to the remolded undrained shearing strength. Sensitivity, S<sub>t</sub>, allows analysis of the soil resistance to be overcome during pile driving in clays which is useful for pile driveability analyses. It is necessary to measure skin friction along the steel connector rods which must be subtracted to determine the actual shear strength. The VST generally provides the most accurate undrained shear strength values for clays with undrained shear strengths less than 1 ksf (50 kPa). The test procedure has been standardized in AASHTO T 223-74 and ASTM D 2573.

It should be noted that the sensitivity of a clay determined from a vane shear test provides insight into the set-up potential of the clay deposit. However, the sensitivity value is a qualitative and not a quantitative indicator of soil set-up. Classification of clayey soils based on sensitivity values is presented in Table 3-12.



Figure 3-34. Vane shear test equipment and procedure (after FHWA, 2002b).

FHWA NHI-06-088 Soils and Foundations – Volume I

3 - 77 Engineering-pdh.com | geo-115 | 3 – Subsurface Explorations December 2006

clussification of Schold any	values (ivitieneity 1270)
Classification	Sensitivity, S <sub>t</sub>
Insensitive	~ 1.0
Slightly sensitive clays	1-2
Medium sensitive clays	2-4
Very sensitive clays	4-8
Slightly quick clays	8 – 16
Medium quick clays	16 - 32
Very quick clays	32-64
Extra quick clays	> 64

Table 3-12Classification of Sensitivity Values (Mitchell, 1976)

# 3.13 GROUNDWATER MEASUREMENTS

Observations of the groundwater level and pore water pressure are an important part of all geotechnical explorations. The identification of groundwater conditions should receive the same level of care given to soil descriptions and samples. Measurements of water entry during drilling and measurements of the groundwater level at least once following drilling should be considered a minimum effort to obtain water level data, unless alternate methods, such as installation of observation wells, are defined by the geotechnical specialist. Detailed information regarding groundwater observations can be obtained from ASTM D 4750 and ASTM D 5092.

#### 3.13.1 Information on Existing Wells

Many states require the drillers of water wells to file logs of the wells they have drilled. These are good sources of information of the materials encountered and water levels recorded during well installation. The well owners, both public and private, may have records of the water levels after installation, which may provide extensive information on fluctuations of the water level. This information may be available at state agencies regulating the drilling and installation of water wells, such as the Department of Transportation, the Department of Natural Resources, State Geologist, Hydrology Department, Department of Environmental Quality, and Division of Water Resources.

# 3.13.2 Open Borings

The water level in open borings should be measured after any prolonged interruption in drilling, at the completion of each boring, and at least 12 hours (preferably 24 hours) after completion of drilling. Additional water level measurements should be made at the completion of the field exploration and at other times designated by the engineer. The date and time of each observation should be recorded.

If the borehole has caved, the depth to the collapsed region should be recorded on the boring record as the collapse may have been caused by groundwater conditions. The elevations of the caved depths of certain borings may be consistent with groundwater table elevations at the site. This consistency may become apparent once the subsurface profile is constructed (see Chapters 4 and 11).

Drilling mud obscures observations of the groundwater level owing to filter cake action and the greater specific gravity of the drilling mud compared to that of the water. If drilling fluids are used to advance borings, the drill crew should be instructed to bail the hole prior to making groundwater observations.

#### 3.13.3 Observation Wells

The observation well, also referred to as a piezometer, is the fundamental means for measuring water head in an aquifer and for evaluating the performance of dewatering systems. In theory, a "piezometer" measures the water pressure in a confined aquifer or at a specific horizon of the geologic profile, while an "observation well" measures the level of a water table in an aquifer (Powers, 1992). In practice, however, the two terms are often used interchangeably to describe any device for determining static water head.

The term "observation well" is applied to any well or drilled hole used for the purpose of long-term studies of groundwater levels and pressures. Existing wells and bore holes in which casing is left in place are often used to observe groundwater levels. These, however, are not considered to be as satisfactory as wells constructed specifically for the purpose of measuring groundwater conditions. The latter may consist of a standpipe installed in a previously drilled exploratory hole or a hole drilled solely for use as an observation well.

Details of typical observation well installations are shown in Figure 3-35. The simplest type of observation well is formed by a small-diameter polyvinyl chloride (PVC) pipe set in an open hole. The bottom of the pipe is slotted and capped, and the annular space around the

slotted pipe is backfilled with clean sand. The area above the sand is sealed with bentonite, and the remaining annulus is filled with grout, concrete, or soil cuttings. A surface seal, which is sloped away from the pipe, is commonly formed with concrete in order to prevent the entrance of surface water. The top of the pipe should also be capped to prevent the entrance of foreign material; there should be a small vent hole in the top of the removable cap. In some localities, regulatory agencies may stipulate the manner for installation and closure of observation wells.





FHWA NHI-06-088 Soils and Foundations – Volume I

3 - 80 engineering-pdh.com | ged-115 | 3 – Subsurface Explorations December 2006 Driven or pushed-in well points are another common type of observation well for use in granular soil formations and very soft clay (Figure 3-35b). The well is formed by a stainless steel or brass well point threaded to a galvanized steel pipe. In granular soils, an open boring or rotary wash boring is advanced to a point several inches above the measurement depth and the well point is driven to the desired depth. A seal is commonly required in the boring above the well point with a surface seal at the ground surface. Note that observation wells may require development (see ASTM D 5092) to minimize the effects of installation, drilling fluids, etc. Minimum pipe diameters should allow introduction of a bailer or other pumping apparatus to remove fine-grained materials in the well to improve the response time.

Local jurisdictions may impose specific requirements on "permanent" observation wells, including closure and reporting of the location and construction that must be considered in the planning and installation. Licensed drillers and special fees may be required.

Piezometers are available in a number of designs. Commonly used piezometers are of the pneumatic and the vibrating wire type. Interested readers are directed to Dunnicliff (1988) and FHWA (1997) for a detailed discussion of the various types of piezometers.

#### 3.13.4 Water Level Measurements

A number of devices have been developed for sensing or measuring the water level in observation wells. Following is a brief presentation of three methods that are commonly used to measure the depth to groundwater. In general, common practice is to measure the depth to the water surface by using the top of the casing as a reference, with the reference point at a common orientation (often north) marked or notched on the well casing.

#### 3.13.4.1 Chalked Tape

In this method a short section at the lower end of a metal tape is chalked. The tape with a weight attached to its end is then lowered until the chalked section has passed slightly below the water surface. The depth to the water is determined by subtracting the depth of penetration of the line into water, as measured by the water line in the chalked section, from the total depth from the top of casing. This is probably the most accurate method, and the accuracy is useful in pump tests where very small drawdowns are significant. The method is cumbersome, however, when a series of rapid readings is taken since the tape must be fully removed each time. An enameled tape is not suitable unless it is roughened with sandpaper so it will accept chalk. The weight on the end of the tape should be small in volume so it does not displace enough water to create an error in the water level.

FHWA NHI-06-088 Soils and Foundations – Volume I

# 3.13.4.2 Tape with a Float

In this method, a tape with a flat-bottomed float attached to its end is lowered until the float hits the water surface and the tape goes slack. The tape is then lifted until the float is felt to touch the water surface and the tape is just taut; the depth to the water surface is then measured. With practice this method can give rough measurements, but its accuracy is poor. A refinement is to mount a heavy whistle, open at the bottom, on a tape. When it sinks in the water, the whistle will give an audible beep as the air within it is displaced.

# 3.13.4.3 Electric Water-Level Indicator

This battery operated indicator consists of a weighted electric probe attached to the lower end of a length of electrical cable that is marked at intervals to indicate the depth. When the probe reaches the water a circuit is completed. This condition is registered by a meter mounted on the cable reel. Various manufacturers produce the instrument, utilizing a neon lamp, a horn, or an ammeter as the signaling device. The electric indicator has the advantage that it may be used in extremely small holes.

The instrument should be ruggedly built, since some degree of rough handling can be expected. The distance markings must be securely fastened to the cable. Some models are available in which the cable itself is manufactured as a measuring tape. The sensing probe should be shielded to prevent shorting out against metal risers. When the water is highly conductive, erratic readings can develop in the moist air above the actual water level. Sometimes careful attention to the intensity of the neon lamp or the pitch of the horn will enable the reader to distinguish the true level. A sensitivity adjustment on the instrument can be useful. If oil or iron sludge has accumulated in the observation well, the electric probe will give unreliable readings.

# 3.13.4.4 Data Loggers

When timed and frequent water level measurements are required, as for a pump test or slug test, data loggers are useful. Data loggers are in the form of an electric transducer near the bottom of the well that senses changes in water level as changes in pressure. A data acquisition system is used to acquire and store the readings. A data logger can eliminate the need for onsite technicians on night shifts during extended field permeability testing. A further significant saving is in the technician's time back in the office. The preferred models of the data logger not only record the water level readings but permit the data to be downloaded into a personal computer and, with appropriate software, to be quickly reduced

and plotted. These devices are also extremely useful for cases where measurement of artesian pressures is required or where data for tidal corrections during field permeability tests are necessary.

#### 3.14 GUIDELINES FOR MINIMUM SUBSURFACE EXPLORATION

In regard to the scope of the subsurface exploration program for a structure or a geotechnical feature, one must consider the small cost of the borings in relation to the foundation costs. The knowledge gained from a thorough subsurface exploration program will allow the geotechnical specialist to evaluate various candidate foundation schemes and provide recommendations for those that can be built most efficiently and economically on the project site. Without an adequate subsurface exploration program, the result is generally an extremely conservative foundation recommendation.

Planning a subsurface exploration program should include determining the location and depth of borings, test pits, or other procedures to be used and establishing the methods of soil sampling and testing to be employed. Usually, the extent of the work is estimated based on available geological studies, earlier explorations, or records of existing structures. The number of borings and their locations in a site area will depend on the proposed structure, design parameters, access issues, geologic constraints, and expected stratigraphy.

Although no rigid rules apply universally to geotechnical explorations, certain general principles are usually followed in practice. Recommended guidelines for the minimum number of exploration points and their spacing are provided in Table 3-13. This table was developed based on a number of FHWA documents. This table should be used only as a first step in estimating the minimum number of borings for a particular design, as actual boring spacings will be dependent upon the project type and geologic environment. In all cases, it is recommended that the depth of the exploration should be such that the depth of significant influence (DOSI) is explored. For a given configuration of loading, the DOSI may exceed the minimum guidelines in Table 3-13 in which case the depth of exploration should be increased accordingly. Some other general guidance in addition to that in Table 3-13 is as follows:

• In areas underlain by heterogeneous soil deposits and/or rock formations, it will probably be necessary to exceed the minimum guidelines presented in Table 3-13 to capture variations in soil and/or rock type and to assess consistency across the site.

	Minimum Number of Exploration Points		
Application	and Location of Exploration Points	Minimum Depth of Exploration	
Retaining walls	(1) A minimum of one exploration point for each retaining wall.	<ul><li>(1) Investigate to a depth below bottom of wall between 1 and 2 times the wall height or a minimum of 10 ft (3 m) into bedrock.</li></ul>	
	(2) For retaining walls more than 100 ft (30 m) in length,	(2) Exploration depth should be great enough to fully penetrate soft	
	exploration points spaced every 100 to 200 ft (30 to 60 m)	highly compressible soils (e.g. peat, organic silt, soft fine grained	
	with locations alternating from in front of the wall to	soils) into competent material of suitable bearing capacity (e.g.,	
	behind the wall.	stiff to hard cohesive soil, compact dense cohesionless soil, or	
	(3) For anchored walls, additional exploration points in the angle $x = 100 \text{ tr} (20 \text{ tr} (0 \text{ m}))$	bedrock).	
	anchorage zone spaced at 100 to 200 ft (30 to 60 m).		
	(4) For son-nan wans, additional exploration points at a distance of 1.0 to 1.5 times the height of the wall behind		
	the wall spaced at 100 to 200 ft (30 to 60 m)		
Embankment	(1) A minimum of one exploration point every 200 ft (60 m)	(1) Exploration depth should be, at a minimum, equal to twice the	
Foundations	(erratic conditions) to 400 ft (120 m) (uniform conditions)	embankment height unless a hard stratum is encountered above	
	of embankment length along the centerline of the	this depth.	
	embankment.	(2) If soft strata are encountered extending to a depth greater than	
	(2) At critical locations, (e.g., maximum embankment heights,	twice the embankment height, the exploration depth should be	
	maximum depths of soft strata) a minimum of three	great enough to fully penetrate the soft strata into competent	
	exploration points in the transverse direction to define the	material (e.g., stiff to hard cohesive soil, compact to dense	
	existing subsurface conditions for stability analyses.	cohesionless soil, or bedrock).	
	(3) For bridge approach embankments, at least one exploration		
Cut Slopes	(1) A minimum of one exploration point every 200 ft (60 m)	(1) Exploration donth should be at a minimum $15 \text{ ft} (4.5 \text{ m})$ holow	
Cut Slopes	(1) A minimum of one exploration point every 200 ft (60 m) (erratic conditions) to 400 ft (120 m) (uniform conditions)	(1) Exploration deput should be, at a minimum, 15 ft (4.5 m) below the minimum elevation of the cut unless a hard stratum is	
	of slope length	encountered below the minimum elevation of the cut	
	(2) At critical locations (e.g., maximum cut depths, maximum	(2) Exploration depth should be great enough to fully penetrate	
	depths of soft strata) a minimum of three exploration points	through soft strata into competent material (e.g., stiff to hard	
	in the transverse direction to define the existing subsurface	cohesive soil, compact to dense cohesionless soil, or bedrock).	
	conditions for stability analyses.	(3) In locations where the base of cut is below ground-water level,	
	(3) For cut slopes in rock, perform geologic mapping along the	increase depth of exploration as needed to determine the depth of	
	length of the cut slope.	underlying pervious strata.	

 Table 3-13

 Guidelines for minimum number of exploration points and depth of exploration (modified after FHWA, 2002a)

# Table 3-13 (Continued) Guidelines for minimum number of exploration points and depth of exploration (after FHWA, 2002a)

Application	Minimum Number of Exploration Points and Location of Exploration Points	Minimum Depth of Exploration
Shallow Foundations	<ol> <li>For substructure (e.g., piers or abutments) widths less than or equal to 100 ft (30 m), a minimum of one exploration point per substructure.</li> <li>For substructure widths greater than 100 ft (30 m), a minimum of two exploration points per substructure.</li> <li>Additional exploration points should be provided if erratic subsurface conditions or sloping rock surfaces are encountered.</li> </ol>	<ul> <li>Depth of exploration should be:</li> <li>(1) great enough to fully penetrate unsuitable foundation soils (e.g., peat, organic silt, soft fine grained soils) into competent material of suitable bearing capacity (e.g. stiff to hard cohesive soil, compact to dense cohesionless soil or bedrock); and</li> <li>(2) at least to a depth where stress increase due to estimated footing load is less than 10% of the applied stress at the base of the footing; and</li> <li>(3) in terms of the width of the footing: at least 2 times for axisymmetric case and 4 times for strip footing (interpolate for intermediate cases); and</li> <li>(4) if bedrock is encountered before the depth required by item (2) above is achieved, exploration depth should be great enough to penetrate a minimum of 10 ft (3 m) into the bedrock, but rock exploration should be sufficient to characterize compressibility of infill material of near-horizontal to horizontal discontinuities.</li> </ul>
Deep Foundations	<ol> <li>For substructure (e.g., bridge piers or abutments) widths less than or equal to 100 ft (30 m), a minimum of one exploration point per substructure.</li> <li>For substructure widths greater than 100 ft (30 m), a minimum of two exploration points per substructure.</li> <li>Additional exploration points should be provided if erratic subsurface conditions are encountered.</li> <li>Due to large expense associated with construction of rock-socketed shafts, conditions should be confirmed at each shaft location.</li> </ol>	<ol> <li>In soil, depth of exploration should extend below the anticipated pile or shaft tip elevation a minimum of 20 ft (6 m), or a minimum of two times the maximum pile group dimension, whichever is deeper. All borings should extend through unsuitable strata such as unconsolidated fill, peat, highly organic materials, soft fine-grained soils, and loose coarse-grained soils to reach hard or dense materials.</li> <li>For piles bearing on rock, a minimum of 10 ft (3 m) of rock core shall be obtained at each exploration point location to verify that the boring has not terminated on a boulder.</li> <li>For shafts supported on or extending into rock, a minimum of 10 ft (3 m) of rock core, or a length of rock core equal to at least three times the shaft diameter for isolated shafts or two times the maximum shaft group dimension, whichever is greater, shall be extended below the anticipated shaft tip elevation to determine the physical characteristics of rock within the zone of foundation influence.</li> </ol>

- In the case of embankments, the guidance provided in Table 3-13 for the depth of exploration is the minimum recommended for any transportation facility, i.e., 2 times the height of the embankment. The minimum guidance may not be the same as the DOSI, which is a function of the geometry (crest width, height, configuration of side slopes, and the base width) of the embankment. For the same height of embankment, the DOSI increases as the base width of an embankment increases, and may vary from 4 to 6 times the height of the embankment. An example of this is shown in Figures 2-8 in Chapter 2, which shows that the DOSI can extend to depths much deeper than 2 times the height of the embankment. This may be particularly critical in cases where there are soft soils in the subsurface. Thus, for such situations, the geotechnical specialist should use tools such as the FoSSA program or published elastic solutions (Poulos and Davis, 1974) to determine the depth of exploration.
- For situations where large-diameter rock-socketed shafts will be used or where drilled shafts are being installed in karstic formations, it may be necessary to advance a boring at the location of each shaft.
- In a laterally homogeneous area, drilling or advancing a large number of borings may be redundant, since each sample tested would exhibit similar strength and compressibility properties.
- In all cases, it is necessary to understand how the design and construction of the geotechnical feature will affect the soil and/or rock mass in order to optimize the exploration.

During exploration, each exploration point (e.g., drill hole or CPT sounding) should be designated by a unique identification number to prevent duplication during subsequent explorations. For example, it is not unusual to find projects where borehole numbering was done by only single numbers so that the same designations were used during one or more subsequent explorations. A suggested method to avoid duplication is to designate that all bridge holes begin with the letter "B," followed by the initials of the highway or river being crossed and finally a sequential number. For example, the first boring for a structure on Apple Freeway would be designated DH-BAF-1, where the DH means a "drill hole" where SPTs were performed as opposed to CPT-BAF-1, where the CPT refers to the first CPT sounding performed for a bridge structure on Apple Freeway.

The geotechnical specialist should plot the proposed boring locations on a site topographic map prior to initiation of drilling. Notes taken during the site visit should be reviewed before boring locations are selected so that site access restrictions can be considered. Boring locations should never be selected arbitrarily or randomly. Alternate boring locations should be considered and a contingency plan should be developed in case a boring needs to be relocated due to access restrictions or unexpected geologic conditions (e.g., locate a replacement boring within a maximum of 15 ft (4.5 m) from the location of a boring that could not be drilled at a particular location). Field personnel unfamiliar with the objectives and rationale behind the planning of the site exploration should maintain contact with the person in responsible charge of the field exploration during field activities and discuss issues such as the relocation of a boring relocation, confusion, and wasted time in the field. Final boring locations should be surveyed and recorded as part of the permanent project record. Elevations and northing and easting should be provided for each boring.

# 3.14.1 Recommendations for Sampling Depth Intervals in Soils

It is difficult to establish a prescriptive drilling, sampling, and testing protocol that is applicable to all sites. To be most effective the geotechnical specialist should:

- (1) apply conventional guidelines with project-specific requirements and constraints;
- (2) recognize the advantages and limitations of the available sampling devices and in-situ testing methods.

Some general recommendations for minimum sampling depth intervals are as follows:

- For preliminary screening, disturbed samples might be taken continuously in the upper 10 ft (3 m), at 5 ft (1.5 m) intervals up to 100 ft (30 m), and possibly every 10 ft (3 m) at depths greater than 100 ft (30 m).
- Disturbed samples should be taken at every abrupt change in stratum as indicated by a noticeable change in the drilling pressure.
- Where footings are to be placed on natural soil, continuous spoon samples are recommended for a depth equal to 15 ft (4.5 m) or 1.5 times the width of the footing, whichever is greater, as measured below the anticipated footing base elevation.

- For characterization and assessment of design properties in fine-grained soils, a minimum of one undisturbed sample should be taken in each stratum, with additional samples taken at 10- to 20-ft (3 to 6 m) intervals with depth.
- Undisturbed Shelby tube samples should be obtained at 5 ft (1.5 m) intervals in at least one boring in cohesive soils. For cohesive deposits greater than 30 ft (9 m) in depth, the tube sample interval can be increased to 10 ft (3 m). Undisturbed samples may not need to be taken in each boring if the deposit is relatively homogeneous within closely spaced borings.

These minimum guidelines and intervals may need to be increased depending upon the project requirements and site geologic conditions. The sampling interval may need to be increased when soil/rock conditions change frequently with depth; however, these changes need to be considered in the context of the design. Therefore, ongoing communication between field personnel and the office/design engineer is absolutely essential. Once the site stratigraphy has been established, it may not be necessary to sample every time there is a change in stratigraphy if the changes have no impact on design. For example, it may not be necessary to sample alternating layers of coarse-grained deposits where settlement is of concern, and for designs concerned with bearing capacity. Similarly, although samples below the anticipated extent of the area influenced by the load may be reduced, samples should be obtained in case the type of foundation changes between preliminary and final design.

The sampling interval will vary between individual projects and regional geologies. If soils are anticipated to be difficult to sample or trim in the laboratory due to defects (e.g., bent tubes, improper handling, etc.), the frequency of sample collection should be greater than average to offset the number of samples that may be unusable in the laboratory for performance property evaluation (e.g., shear strength). When borings are widely spaced, it may be appropriate to retrieve undisturbed samples in each boring. For closely spaced borings or in deposits of lateral uniformity, undisturbed samples may be needed only in select borings. If a thin clay seam is encountered during drilling and not sampled, the boring may need to be offset and re-drilled to obtain a sample.

It is often quite helpful to combine in-situ soundings with conventional disturbed/undisturbed sampling. For example, by performing CPT or CPTu soundings prior to conventional drilling and sampling, it may be possible to target representative and/or critical areas where samples can be obtained later. This concept was illustrated previously by the discussion in Section 3.9.7 and Figure 3-30. The use of precursor soundings may reduce some of the potential drilling redundancy in heterogeneous environments. Geophysical methods can also

be used to provide useful information on conditions between and even beyond boring locations.

# 3.14.2 Recommendations for Sampling Depth Intervals in Rocks

For explorations for slopes and foundations within rock, it is important to consider structural geology in addition to the information obtained as part of a rock-coring program. For example, the orientation and characteristics of a clay-filled discontinuity are critical since they can be used to judge whether a rock slope will be stable or unstable or whether a structural foundation will undergo minor or significant settlement. A detailed structural geologic assessment may provide enough information to limit the scope of a rock-coring program significantly or even preclude such a program. For example, drilling and coring may not be required where applied loads are significantly less than the bearing capacity of the rock, where there is no possibility of sliding instability in a rock slope, or where there are extensive rock outcrops from which information can be obtained to establish the subsurface conditions confidently for design and constructability assessments (Wyllie, 1999).

# 3.14.3 Recommendations for Water Level Monitoring in Borings

The water level in each boring should be observed and the depth below the top of hole recorded on the drill log with the date and time of the reading for each of the following situations:

- a) Water seepage or artesian pressure encountered during drilling. Artesian pressure may be measured by extending drill casing above the ground until flow stops. Report the pressure as the number of ft (m) of head above ground.
- b) Water level at the end of each day and at completion of boring.
- c) Water level 24 hours (minimum) after hole completion. Long term readings may require installation of a perforated plastic tube before abandoning the hole.

A false indication of water level may be obtained when water is used in drilling and adequate time is not permitted after the boring is completed for the water level to stabilize. In low permeability soils, such as clays, more than one week may be required to obtain accurate readings. Proper safety precautions should be taken if a hole is allowed to remain open for such an extended period of time.

# 3.15 GEOPHYSICAL TESTS

As indicated in Section 3.3, geophysical testing can be used as part of the initial site exploration to provide supplementary information to data collected by other means (i.e., borings, test pits, geologic surveys, etc.). Geophysical testing can be used for establishing stratification of subsurface materials, the profile of the top of bedrock, the depth to groundwater, the boundaries of various types of soil deposits, the rippability of hard soil and rock, and the presence and depth of voids, buried pipes, and existing foundations. Data from geophysical testing should always be correlated with information from the direct methods of exploration discussed previously.

# **3.15.1** Types of Geophysical Tests

There are a number of different types of geophysical in-situ tests that can be used to obtain stratigraphic information from which engineering properties can be estimated. Table 3-14 provides a summary of the various geophysical methods that are currently available in U.S. practice. Further information on the procedures used for these methods is provided in FHWA (2003). Additional general discussion regarding the major test methods listed in Table 3-14 is presented below, with particular emphasis on potential applications to highway engineering.

- 1. Seismic Methods: These methods are becoming increasingly popular for geotechnical engineering practice because they have the potential to provide data regarding the compression and shear wave velocities of the subsurface materials. The shear wave velocity is directly related to small-strain material stiffness, which, in turn, is often correlated to compressive strength and soil/rock type. These techniques are often used for assessing the vertical stiffness profile in a soil deposit and for assessing the location at depth of the interface between soil and rock. Seismic refraction method involves measurement of time of arrival of the initial ground motion generated by the energy source while the seismic reflection method involves measurement of the initial ground motion.
- 2. Electrical Methods: These methods are usually used to locate voids or locally distinct materials. With regards to highway applications, these procedures may be used to assess the potential for karst activity along a planned transportation corridor, or for locating large underground voids and/or specific underground anomalies such as storage drums and/or tanks. Electrical methods provide qualitative information only and are usually part of a two- or three-phased exploration program.

Method	Basic Field Procedures	Applications	Limitations
SEISMIC METI	HODS		
Seismic Refraction	Impact load is applied to the ground surface. Seismic energy refracts off soil/rock layer interfaces and the <i>time of arrival</i> is recorded on the ground surface using several dozen geophones positioned along a line or performing repeated events using a single geophone.	<ul> <li>depth to bedrock</li> <li>depth to water table</li> <li>thickness and relative stiffness soil/rock layers</li> </ul>	<ul> <li>does not work if stiffness decreases with depth or if soft layer underlies stiff layer</li> <li>works best when sharp stiffness discontinuity is present</li> </ul>
Spectral- Analysis-of- Surface-Waves (SASW)	Impact load is applied to the ground surface. Surface waves propagate along ground surface and are recorded on the ground surface with two geophones positioned along a line.	<ul> <li>depth to bedrock</li> <li>measurement of shear wave velocity</li> <li>thickness and stiffness of surface pavement layer</li> <li>qualitative indicator of cracking in pavement</li> </ul>	<ul> <li>resolution decreases significantly with increasing depth</li> <li>accurate interpretation may require a significant amount of expertise</li> <li>interpretation is difficult if a stiff layer overlies a soft layer and soft layer properties are desired</li> </ul>
ELECTRICAL N	<b>IETHODS</b>		· · ·
DC Resistivity	DC current is applied to the ground by electrodes. Voltages are measured at different points on the ground surface with other electrodes positioned along a line.	<ul> <li>depth to water table</li> <li>inorganic groundwater contamination</li> <li>groundwater salinity</li> <li>soil layer thickness</li> <li>delineation of certain vertical features (e.g., sinkholes, contamination plumes, waste trenches)</li> </ul>	<ul> <li>slow; must install electrodes directly in the ground</li> <li>resolution decreases significantly with increasing depth</li> <li>resolution is difficult in highly heterogeneous deposits</li> </ul>
Electromagnetics	Electrical coils are held over the ground. Current passing through the coils induces a magnetic field in the ground, which is measured with receiver coils.	<ul> <li>groundwater salinity</li> <li>inorganic groundwater contamination</li> <li>detection of buried metal objects</li> <li>delineation of certain vertical features (e.g., sinkholes, contamination plumes, waste trenches)</li> </ul>	<ul> <li>extra effort is required to characterize depth of target</li> <li>resolution decreases significantly with increasing depth</li> </ul>
Ground Penetrating Radar (GPR)	Electromagnetic energy is pulsed into the ground. This energy reflects off boundaries between different soil layers and is measured at the ground surface.	<ul> <li>depth to water table</li> <li>identification of buried objects</li> <li>thickness of pavement layers</li> <li>void detection</li> </ul>	<ul> <li>not effective below the water table or in clay</li> <li>depth of penetration is limited to about 30 ft (10 m)</li> </ul>

Table 3-14Geophysical testing techniques (modified after FHWA, 2002a)

Method	Basic Field Procedures	Applications	Limitations			
GRAVITY AND MAGNETIC METHODS						
Gravity	The Earth's gravitational field is measured at the ground surface.	<ul> <li>identification of large subsurface voids</li> <li>identification of large objects possessing unusually high or low densities</li> </ul>	<ul> <li>results are non-unique (i.e. more than one subsurface condition can give the same result)</li> <li>primarily, large-scale reconnaissance tool; applications in highway engineering are limited</li> </ul>			
Magnetics	The Earth's magnetic field is measured at the ground surface.	<ul> <li>identification of ferrous materials</li> <li>identification of soil/rock containing large amounts of magnetic minerals</li> </ul>	<ul> <li>results are non-unique (i.e. more than one subsurface condition can give the same results)</li> <li>primarily a large-scale reconnaissance tool; applications in highway engineering are limited</li> </ul>			
NEAR-SURFACE	NUCLEAR METHODS					
Neutron Moisture Content	Instrument is placed on the ground surface and neutrons are emitted into the ground. Energy of returning neutrons is related to the moisture content in the ground (hydrogen atoms decrease the energy of the neutrons detected at the sensor).	<ul> <li>estimate of water content in compacted soil</li> <li>estimate of asphalt content in asphalt concrete</li> <li>can be quantitative if properly calibrated to site conditions</li> </ul>	<ul> <li>limited exploration depth (a few inches)</li> <li>possible health and safety hazard if operators not properly trained</li> <li>will detect hydrogen ion (i.e. gas, clay) in non-water bearing stratum</li> </ul>			
Gamma Density	Instrument is placed on the ground surface and gamma radiation is emitted into the ground. Returning gamma energy is a function of material density (denser materials absorb more gamma energy so less is detected at the sensor)	• estimate of density of soil or asphalt concrete	<ul> <li>limited exploration depth (less than one foot);</li> <li>exploration depth further limited to a few inches if ground cannot be penetrated</li> <li>possible health and safety hazard if operators not properly trained</li> </ul>			

Table 3-14Geophysical testing techniques (modified after FHWA, 2002a)

Method	Basic Field Procedures	Applications	Limitations			
BOREHOLE METHODS						
Crosshole/ Downhole	Energy sources and geophones are placed in boreholes and/or on ground surface; interval travel times are converted into seismic wave velocity as a function of depth in the borehole.	<ul> <li>measurement of wave velocities for seismic site response analysis</li> <li>depth to water table</li> <li>correlation of lithologic units with surface seismic</li> <li>identification of thin layers at depth</li> </ul>	• requires one or more boreholes and significant support field equipment			
Suspension Logger	Field instrument is placed in a fluid-filled borehole and used to measure P- (compression) and S-(shear) wave velocities in surrounding soil or rock.	<ul> <li>measurement of wave velocities for seismic site response analysis</li> <li>correlation of lithologic units with surface seismic</li> <li>identification of thin layers at depth</li> </ul>	<ul> <li>requires borehole and significant support field equipment, which is expensive</li> <li>borehole must be fluid-filled</li> </ul>			
Electrical Logging	Field instrument is placed in a borehole. Electrical fields are directly applied or electromagnetically induced into surrounding soil or rock and electrical resistivity is measured.	<ul> <li>estimate of soil/rock permeability or porosity</li> <li>identification of inorganic contaminant plumes or saltwater intrusion</li> <li>identification of thin layers at depth</li> </ul>	<ul> <li>requires borehole and significant support field equipment, which is expensive</li> <li>generally cannot operate in a cased borehole</li> <li>may require fluid-filled borehole</li> <li>results may be dependent upon drilling mud salinity</li> </ul>			
Nuclear Logging	Field instrument is placed in a borehole. Surrounding soil or rock is irradiated with neutrons particles and/or gamma energy. Energy and neutrons returning to the instrument are measured and related to rock density, porosity and pore fluid type.	<ul> <li>estimate of soil/rock type, density, porosity, and pore fluid density</li> <li>identification of thin layers at depth</li> </ul>	<ul> <li>requires borehole and significant support field equipment, which is expensive</li> <li>possible health and safety hazard if operators are not properly trained</li> </ul>			
Lithology Logging	Field instrument is placed in a borehole; naturally occurring electrical fields and radiation levels are related to soil or rock type.	<ul> <li>classification of soil or rock type</li> <li>identification of thin layers at depth</li> </ul>	<ul> <li>requires borehole and significant support field equipment, which is expensive</li> <li>may require fluid-filled borehole</li> <li>results are dependent upon site-specific conditions and/or borehole fluid salinity</li> </ul>			

# Table 3-14 (continued)Geophysical testing techniques (modified after FHWA, 2002a)

- 3. **Gravity and Magnetic Methods**: These methods are similar to electrical methods, except that they rely on correlations between the potential gravitational and/or magnetic influence of voids and subsurface anomalies and measured differences in the earth's micro-gravitational and/or magnetic fields, rather than on changes in electrical fields. These methods provide measurements at specific points unlike seismic and electrical methods that provide measurements over large areas.
- 4. **Near-surface nuclear methods**: These methods have been used for several years for compaction control of fills in the field. Through careful calibration, it is possible to assess the moisture content and density of compacted soils reliably. These methods have been widely adopted as reliable quantitative methods.
- 5. **Borehole Methods**: Downhole geophysical methods provide reliable indications of a wide range of soil properties. For example, downhole/crosshole methods provide reliable measures of shear wave velocity. As indicated previously, shear wave velocity is directly related to small-strain stiffness and is correlated to strength and soil/rock type. Although downhole logging methods have seen little use in highway construction, they have been the mainstay for deep geologic characterization in oil exploration. The principal advantage of downhole logging is the ability to obtain several different geophysical tests/indicators by "stringing" these tools together in a deep borehole.

# 3.15.2 Advantages and Disadvantages of Geophysical Tests

As with the other methods of exploration, geophysical testing offers some advantages and some disadvantages that should be considered before these techniques are recommended for a specific application. These are summarized as follows:

#### 3.15.2.1 Advantages of Geophysical Tests

- 1. Many geophysical tests are non-invasive. Therefore such tests offer significant benefits in cases where conventional drilling, testing, and sampling are difficult (e.g., deposits of gravel, talus deposits, etc.) or where potentially contaminated soils may occur in the subsurface.
- 2. In general, geophysical testing can cover a relatively large geographical area thereby providing the opportunity to characterize large areas with relatively few tests. Geophysical testing is particularly well-suited to projects that have large longitudinal extent such as new highway construction.

- 3. Geophysical measurements are used to assess the properties of soil and rock at very small strains, typically on the order of 0.001 percent, thereby providing information on truly elastic properties.
- 4. For the purpose of obtaining information on the subsurface, geophysical methods are relatively inexpensive considering the large area over which they provide information.

# 3.15.2.2 Disadvantages of Geophysical Tests

- 1. Most methods work best for situations in which there is a large difference in the property being measured between adjacent subsurface units. In seismic methods, it is difficult to develop good stratigraphic profiling if the general stratigraphy consists of hard material overlying soft material.
- 2. Each geophysical method has limitations that may be associated with equipment, signal noise, unfavorable site and subsurface conditions, and processing constraints.
- 3. Results can be non-unique and are generally interpreted qualitatively. Therefore useful results can be obtained only through analyses performed by a geotechnical specialist experienced with the particular testing method.
- 4. Specialized and more electronically sophisticated equipment is required as compared to the more conventional subsurface exploration tools.

#### **3.15.3** Examples of Uses of Geophysical Tests

The following are a few examples where geophysical testing could be used on highway projects to compliment conventional exploration.

1. <u>Highly Variable Subsurface Conditions</u>: In several geologic settings, the subsurface conditions along a transportation corridor may be expected to be variable. This variability could be from underlying karst development above limestone; alluvial deposits, including buried terrace gravels, across a wide floodplain; buried boulders in a talus slope, etc. For these cases, conventional exploration techniques may be very difficult and if "refusal" is encountered at one depth, there is a strong likelihood that different materials could underlie the region. Development of a preliminary subsurface characterization profile by using geophysical testing could prove advantageous in designing future focused explorations.

- 2. <u>Regional Studies</u>: Along a transportation corridor it may be necessary to assess the depth to (and through) rippable rock or highly cemented caliche. Alternative alignments may or may not be possible, but the cost implications may be significant. Therefore, it is important to obtain a profile related to rock/soil stiffness. Geophysical testing is a logical consideration for this application as a precursor to invasive explorations.
- 3. <u>Settlement Sensitive Structures</u>: The prior two examples related to cases where the geophysical testing served as the front-end of a multi-phase project. In the case where a settlement-sensitive structure is to be founded on deposits of sands, knowledge of the in-situ modulus of the sand deposit is critical. After the characteristics of the site are assessed, it may be helpful to quantify the deformation modulus by the use of geophysical testing at the specific foundation site.

These examples demonstrate that geophysical testing can play a potentially important role in the subsurface characterization of soils and rocks. As with the other investigative "tools" described in this document, the particular selection of the appropriate technology is very much a function of the site conditions and the goals of the characterization program.