



A Steel fixing set in concrete
(or similar solid foundations/hardstanding)
to manufactures specification, which
allows both the wheel and frame to be
locked securely.

7FT X 5FT TONGUE AND GROOVE TIMBER SHED.
DIP TREATED SOFTWOOD. STERLING BOARD
ROOF AND FLOOR. SHED TO HAVE A MINIMUM
INTERNAL AREA OF 2.5M2. WHEN PROVIDING
CYCLE STORAGE IN A SHED A MINIMUM OF
1SQM IS REQUIRED FOR GARDEN TOOLS.
SHED TO BE SET ON CONCRETE BASE WITH
A STEEL FIXING FOR A BIKE TO SECURE BOTH
WHEEL AND FRAME. TO HAVE SECURE LOCK
TO BS3621:2004.

REV.	DESCRIPTION	DATE
CLIENT		
Obsidian Developments		
DRAWING TITLE		
Timber Shed		
SCALE	DATE	DRAWN BY
1:25@A3	April '25	HA Ltd
DRAWING NO.	REVISION	TYPE
2445-SH1	.	PLN



10 Gold Tops
Newport
NP20 4PH

t. 01633 844970
e. info@hammond-ltd.co.uk

www.hammond-ltd.co.uk

© Hammond Architectural Limited 2025
Figured dimensions must be taken in preference to scaled dimensions and any
discrepancies are to be referred to Hammond Architectural Ltd. Contractors,
subcontractors and suppliers must verify all dimensions on site before
commencing any work or making any workshop drawings.