



A Steel fixing set in concrete (or similar solid foundations/hardstanding) to manufactures specification, which allows both the wheel and frame to be locked securely.

7FT X 5FT TONGUE AND GROOVE TIMBER SHED. DIP TREATED SOFTWOOD. STERLING BOARD ROOF AND FLOOR. 2 PERPEX WINDOWS. SHED TO HAVE A MINIMUM INTERNAL STORAGE AREA OF 2.5M2. WHEN PROVIDING CYCLE STORAGE IN A SHED A MINIMUM OF 1SQM IS REQUIRED FOR GARDEN TOOLS. SHED TO BE SET ON CONCRETE BASE WITH A STEEL FIXING FOR A BIKE TO SECURE BOTH WHEEL AND FRAME. TO HAVE SECURE LOCK TO BS3621:2004.

REV.	DESCRIPTION	DATE
CLIENT Wales & West HA		
JOB TITLE New Mill Road		
DRAWING TITLE Timber Shed Detail		
SCALE @ A3 1:25	DATE Jul '23	DRAWN BY PC
JOB NO. 2316	DRAWING NO. SHED-01	REVISION -



10 Gold Tops
Newport
NP20 4PH
t. 01633 844970
e. info@hammond-ltd.co.uk

www.hammond-ltd.co.uk

© Hammond Architectural Limited 2021
Figured dimensions must be taken in preference to scaled dimensions and any discrepancies are to be referred to Hammond Architectural Ltd. Contractors, subcontractors and suppliers must verify all dimensions on site before commencing any work or making any workshop drawings.