



PRODUCT IDENTIFIER: URETHANE CEMENT SL 160 PART A
DATE AND VERSION: 1 APRIL 2019 VERSION 1.0

SAFETY DATA SHEET (SDS)

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT IDENTIFIER: URETHANE CEMENT SL 160™
OTHER MEAN OF IDENTIFICATION: URETHANE CEMENT SL 160™ PART A
RECOMMENDED USE: SELF LEVELING URETHANE CEMENT FOR CONCRETE SUBSTRATES, SEE PRODUCT TDS
MANUFACTURED FOR: MVP COATINGS, INC.
5913 E WASHINGTON BLVD
LOS ANGELES, CA 90040
E-MAIL ADDRESS: SERVICE@MVPCOATINGS.COM
TELEPHONE NUMBER: (833) 326-2848
FAX NUMBER: (323) 484-5540

EMERGENCY TELEPHONE NUMBER:

24-HOUR EMERGENCY TELEPHONE NUMBER: CHEM-TREC 800-424-9300

SECTION 2: HAZARDOUS IDENTIFICATION

CLASSIFICATION OF THE SUBSTANCE OR MIXTURE:

SPECIFIC TARGET ORGAN TOXICITY - SINGLE EXPOSURE (RESPIRATORY TRACT IRRITATION) - CATEGORY 3
SPECIFIC TARGET ORGAN TOXICITY - REPEATED EXPOSURE - CATEGORY 2
SKIN IRRITATION - CATEGORY 2
RESPIRATORY SENSITIZER (SOLID/LIQUID) - CATEGORY 1
SKIN SENSITIZER - CATEGORY 1
CARCINOGENICITY - CATEGORY 2
EYE IRRITATION - CATEGORY 2
ACUTE TOXICITY ORAL CATEGORY 5

LABEL ELEMENTS: PICTOGRAM



SIGNAL WORD: DANGER

HAZARD STATEMENTS:

H335 - MAY CAUSE RESPIRATORY IRRITATION
H373 - MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE. H315 - CAUSES SKIN IRRITATION
H334 - MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED H317 - MAY CAUSE AN ALLERGIC SKIN REACTION
H351 - SUSPECTED OF CAUSING CANCER.
H319 - CAUSES SERIOUS EYE IRRITATION
H303 - MAY BE HARMFUL IF SWALLOWED

PRECAUTIONARY STATEMENTS - GENERAL:

P260 DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY
P284 IN CASE OF INADEQUATE VENTILATION WEAR RESPIRATORY PROTECTION
P280 WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION
P304+P340 IF INHALED: REMOVE VICTIM TO FRESH AIR AND KEEP AT REST IN A POSITION COMFORTABLE FOR BREATHING
P302+P352 IF ON SKIN: WASH WITH PLENTY OF WATER
P333+P313 IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION
P403+P233 STORE IN A WELL-VENTILATED PLACE. KEEP CONTAINER TIGHTLY CLOSED
P501 DISPOSE OF CONTENTS/CONTAINER IN ACCORDANCE WITH LOCAL/REGIONAL/NATIONAL/INTERNATIONAL REGULATIONS

HAZARD DESCRIPTION:

P101 - IF MEDICAL ADVICE IS NEEDED, HAVE PRODUCT CONTAINER OR LABEL AT HAND.
P102 - KEEP OUT OF REACH OF CHILDREN.
P103 - READ LABEL BEFORE USE.



SAFETY DATA SHEET (SDS)

PRECAUTIONARY STATEMENTS – PREVENTION

P261 - AVOID BREATHING DUST/FUME/GAS/MIST/VAPORS/SPRAY. P271 - USE ONLY OUTDOORS OR IN A WELL-VENTILATED AREA.
P233 - KEEP CONTAINER TIGHTLY CLOSED.
P260 - DO NOT BREATHE DUST/FUME/GAS/MIST/VAPORS/SPRAY. P264 - WASH THOROUGHLY AFTER HANDLING.
P280 - WEAR PROTECTIVE GLOVES/PROTECTIVE CLOTHING/EYE PROTECTION/FACE PROTECTION.
P284 - [IN CASE OF INADEQUATE VENTILATION] WEAR RESPIRATORY PROTECTION.
P272 - CONTAMINATED WORK CLOTHING SHOULD NOT BE ALLOWED OUT OF THE WORKPLACE.
P201 - OBTAIN SPECIAL INSTRUCTIONS BEFORE USE.
P202 - DO NOT HANDLE UNTIL ALL SAFETY PRECAUTIONS HAVE BEEN READ AND UNDERSTOOD.

PRECAUTIONARY STATEMENTS – RESPONSE:

P304 + P340 - IF INHALED: REMOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING.
P312 - CALL A POISON CENTER/DOCTOR IF YOU FEEL UNWELL.
P314 - GET MEDICAL ADVICE/ATTENTION IF YOU FEEL UNWELL.
P302 + P352 - IF ON SKIN: WASH WITH PLENTY OF WATER.
P321 - SPECIFIC TREATMENT (SEE SECTION 4 ON THIS SDS).
P332 + P313 - IF SKIN IRRITATION OCCURS: GET MEDICAL ADVICE/ATTENTION.
P362 + P364 - TAKE OFF CONTAMINATED CLOTHING. AND WASH IT BEFORE REUSE.
P342 + P311 - IF EXPERIENCING RESPIRATORY SYMPTOMS: CALL A POISON CENTER/DOCTOR.
P333 + P313 - IF SKIN IRRITATION OR A RASH OCCURS: GET MEDICAL ADVICE/ATTENTION.
P308 + P313 - IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.
P305 + P351 + P338 - IF IN EYES: RINSE CAUTIOUSLY WITH WATER FOR SEVERAL MINUTES. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING.
P337 + P313 - IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

PRECAUTIONARY STATEMENTS – STORAGE

P403 + P405 - STORE IN A WELL-VENTILATED PLACE. STORE LOCKED UP.
P405 - STORE LOCKED UP.

PRECAUTIONARY STATEMENTS – DISPOSAL:

P501 - DISPOSE OF CONTENTS/ CONTAINER TO AN APPROVED WASTE DISPOSAL PLANT.

SECTION 3: CHEMICAL COMPOSITION

CAS NUMBER	CONTENT WEIGHT	CHEMICAL NAME
0000101-68-8	64% - 100%	4,4'-METHYLENEDIPHENYL DISOCYANATE
0026447-40-5	1.7% - 3%	MDI (MONOMER)
THE SPECIFIC CHEMICAL IDENTITY AND/OR EXACT PERCENTAGE (CONCENTRATION) OF COMPOSITION HAS BEEN WITHHELD TO PROTECT CONFIDENTIALITY.		

SECTION 4: FIRST AID MEASURES

GENERAL ADVICE:

REMOVE CONTAMINATED CLOTHING

IF INHALED:

REMOVE SOURCE OF EXPOSURE OR MOVE PERSON TO FRESH AIR AND KEEP COMFORTABLE FOR BREATHING. IF EXPERIENCING RESPIRATORY SYMPTOMS: CALL A POISON CENTER/DOCTOR. IF BREATHING IS DIFFICULT, TRAINED PERSONNEL SHOULD ADMINISTER EMERGENCY OXYGEN IF ADVISED TO DO SO BY THE POISON CENTER/DOCTOR.

IF EXPOSED/FEEL UNWELL/CONCERNED: CALL A POISON CENTER/DOCTOR.

ELIMINATE ALL IGNITION SOURCES IF SAFE TO DO SO.



SAFETY DATA SHEET (SDS)

IF ON THE SKIN:

TAKE OFF CONTAMINATED CLOTHING, SHOES AND LEATHER GOODS (E.G. WATCHBANDS, BELTS). GENTLY BLOT OR BRUSH AWAY EXCESS PRODUCT. WASH WITH PLENTY OF LUKEWARM, GENTLY FLOWING WATER FOR A DURATION OF 15-20 MINUTES. IF SKIN IRRITATION OR RASH OCCURS: GET MEDICAL ADVICE/ATTENTION. WASH CONTAMINATED CLOTHING BEFORE RE-USE OR DISCARD. IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

IF IN THE EYES:

RINSE EYES CAUTIOUSLY WITH LUKEWARM, GENTLY FLOWING WATER FOR SEVERAL MINUTES, WHILE HOLDING THE EYELIDS OPEN. REMOVE CONTACT LENSES, IF PRESENT AND EASY TO DO. CONTINUE RINSING FOR 15-20 MINUTES. TAKE CARE NOT TO RINSE CONTAMINATED WATER INTO THE UNAFFECTED EYE OR ONTO THE FACE. IF EYE IRRITATION PERSISTS: GET MEDICAL ADVICE/ATTENTION.

IF SWALLOWED:

RINSE MOUTH. DO NOT INDUCE VOMITING. GIVE 1 OR 2 GLASSES OF MILK OR WATER TO DRINK AND GET MEDICAL ATTENTION/ADVICE. IF EXPOSED OR CONCERNED: GET MEDICAL ADVICE/ATTENTION.

SECTION 5: FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA:

DRY CHEMICAL, FOAM, CARBON DIOXIDE IS RECOMMENDED. WATER SPRAY IS RECOMMENDED TO COOL OR PROTECT EXPOSED MATERIALS OR STRUCTURES. CARBON DIOXIDE CAN DISPLACE OXYGEN. USE CAUTION WHEN APPLYING CARBON DIOXIDE IN CONFINED SPACES. SIMULTANEOUS USE OF FOAM AND WATER ON THE SAME SURFACE IS TO BE AVOIDED AS WATER DESTROYS THE FOAM. SAND OR EARTH MAY BE USED FOR SMALL FIRES ONLY.

UNSUITABLE EXTINGUISHING MEDIA:

IF WATER IS USED, USE VERY LARGE QUANTITIES OF COLD WATER. THE REACTION BETWEEN WATER AND HOT ISOCYANATE MAY BE VIGOROUS.

HAZARDS DURING FIRE-FIGHTING:

EXCESSIVE PRESSURE OR TEMPERATURE MAY CAUSE EXPLOSIVE RUPTURE OF CONTAINERS.

WATER CONTAMINATION WILL PRODUCE CARBON DIOXIDE. DO NOT RESEAL CONTAMINATED CONTAINERS AS PRESSURE BUILDUP MAY RUPTURE THEM.

ADVICE FOR FIRE-FIGHTERS:

ISOLATE IMMEDIATE HAZARD AREA AND KEEP UNAUTHORIZED PERSONNEL OUT. STOP SPILL/RELEASE IF IT CAN BE DONE SAFELY. MOVE UNDAMAGED CONTAINERS FROM IMMEDIATE HAZARD AREA IF IT CAN BE DONE SAFELY. WATER SPRAY MAY BE USEFUL IN MINIMIZING OR DISPERSING VAPORS AND TO PROTECT PERSONNEL. WATER MAY BE INEFFECTIVE BUT CAN BE USED TO COOL CONTAINERS EXPOSED TO HEAT OR FLAME. CAUTION SHOULD BE EXERCISED WHEN USING WATER OR FOAM AS FROTHING MAY OCCUR, ESPECIALLY IF SPRAYED INTO CONTAINERS OF HOT, BURNING LIQUID.

DISPOSE OF FIRE DEBRIS AND CONTAMINATED EXTINGUISHING WATER IN ACCORDANCE WITH OFFICIAL REGULATIONS.

SPECIAL PROTECTIVE ACTIONS:

WEAR NIOSH APPROVED SELF-CONTAINED BREATHING APPARATUS IN POSITIVE PRESSURE MODE WITH FULL-FACE PIECE. BOOTS, GLOVES (NEOPRENE), GOOGLES, AND FULL PROTECTIVE CLOTHING ARE ALSO REQUIRED.

CARE SHOULD ALWAYS BE EXERCISED IN DUST/MIST AREAS.

SECTION 6: ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES:

ELIMINATE ALL IGNITION SOURCES (NO SMOKING, FLARES, SPARKS OR FLAMES IN IMMEDIATE AREA).

DO NOT TOUCH OR WALK THROUGH SPILLED MATERIAL.

ISOLATE HAZARD AREA AND KEEP UNNECESSARY PEOPLE AWAY. REMOVE ALL POSSIBLE SOURCES OF IGNITION IN THE SURROUNDING AREA. NOTIFY AUTHORITIES IF ANY EXPOSURE TO THE GENERAL PUBLIC OR THE ENVIRONMENT OCCURS OR IS LIKELY TO OCCUR.

IF SPILLED MATERIAL IS CLEANED UP USING A REGULATED SOLVENT, THE RESULTING WASTE MIXTURE MAY BE REGULATED.



PRODUCT IDENTIFIER: URETHANE CEMENT SL 160 PART A
DATE AND VERSION: 1 APRIL 2019 VERSION 1.0

SAFETY DATA SHEET (SDS)

RECOMMENDED EQUIPMENT:

APPROPRIATE DUST OR FACE MASK TO ELIMINATE BREATHING FOAM DUST PARTICULATES.

PERSONAL PRECAUTIONS:

AVOID BREATHING VAPORS. AVOID CONTACT WITH SKIN, EYES OR CLOTHING. DO NOT TOUCH DAMAGED CONTAINERS OR SPILLED MATERIALS UNLESS WEARING APPROPRIATE PROTECTIVE CLOTHING.

ENVIRONMENTAL PRECAUTIONS:

STOP SPILL/RELEASE IF IT CAN BE DONE SAFELY. PREVENT SPILLED MATERIAL FROM ENTERING SEWERS, STORM DRAINS, OTHER UNAUTHORIZED DRAINAGE SYSTEMS AND NATURAL WATERWAYS BY USING SAND, EARTH, OR OTHER APPROPRIATE BARRIERS.

METHODS AND MATERIAL FOR CONTAINMENT AND CLEANUP:

COVER CONTAINER, BUT DO NOT SEAL, AND REMOVE FROM WORK AREA. PREPARE A DECONTAMINATION SOLUTION OF 2.0% LIQUID DETERGENT AND 3-8% CONCENTRATED AMMONIUM HYDROXIDE IN WATER (5-10% SODIUM CARBONATE MAY BE SUBSTITUTED FOR THE AMMONIUM HYDROXIDE). FOLLOW THE PRECAUTIONS ON THE SUPPLIER'S SAFETY DATA SHEETS.

TREAT THE SPILL AREA WITH THE DECONTAMINATION SOLUTION, USING ABOUT 10 PARTS OF THE SOLUTION FOR EACH PART OF THE SPILL, AND ALLOW IT TO REACT FOR AT LEAST 15 MINUTES. CARBON DIOXIDE WILL BE EVOLVED, LEAVING INSOLUBLE POLYUREAS. RESIDUES FROM SPILL CLEANUP, EVEN WHEN TREATED AS DESCRIBED MAY CONTINUE TO BE REGULATED UNDER PROVISIONS OF RCRA AND REQUIRE STORAGE AND DISPOSAL AS HAZARDOUS WASTE.

SLOWLY STIR THE ISOCYANATE WASTE INTO THE DECONTAMINATION SOLUTION DESCRIBED ABOVE. LET STAND FOR 48 HOURS, ALLOWING THE EVOLVED CARBON DIOXIDE TO VENT AWAY, RESIDUES MAY STILL BE SUBJECT TO RCRA STORAGE AND DISPOSAL REQUIREMENTS. DISPOSE OFF IN COMPLIANCE WITH ALL RELEVANT LOCAL, STATE, AND FEDERAL LAWS AND REGULATIONS REGARDING TREATMENT.

SECTION 7: HANDLING AND STORAGE

PRECAUTIONS FOR SAFE HANDLING:

WASH HANDS AFTER USE.

DO NOT GET IN EYES, ON SKIN OR ON CLOTHING.

DO NOT BREATHE VAPORS OR MISTS.

USE GOOD PERSONAL HYGIENE PRACTICES.

EATING, DRINKING AND SMOKING IN WORK AREAS IS PROHIBITED.

REMOVE CONTAMINATED CLOTHING AND PROTECTIVE EQUIPMENT BEFORE ENTERING EATING AREAS.

EYEWASH STATIONS AND SHOWERS SHOULD BE AVAILABLE IN AREAS WHERE THIS MATERIAL IS USED AND STORED.

VENTILATION REQUIREMENTS:

USE ONLY WITH ADEQUATE VENTILATION TO CONTROL AIR CONTAMINANTS TO THEIR EXPOSURE LIMITS. THE USE OF LOCAL VENTILATION IS RECOMMENDED TO CONTROL EMISSIONS NEAR THE SOURCE.

CONDITIONS FOR SAFE STORAGE:

KEEP CONTAINER(S) TIGHTLY CLOSED AND PROPERLY LABELED. STORE IN COOL, DRY, WELL-VENTILATED AREAS AWAY FROM HEAT, DIRECT SUNLIGHT, STRONG OXIDIZERS AND ANY INCOMPATIBILITIES. STORE IN APPROVED CONTAINERS AND PROTECT AGAINST PHYSICAL DAMAGE. KEEP CONTAINERS SECURELY SEALED WHEN NOT IN USE. INDOOR STORAGE SHOULD MEET OSHA STANDARDS AND APPROPRIATE FIRE CODES. CONTAINERS THAT HAVE BEEN OPENED MUST BE CAREFULLY RESEALED TO PREVENT LEAKAGE. EMPTY CONTAINER RETAIN RESIDUE AND MAY BE DANGEROUS.

USE NON-SPARKING VENTILATION SYSTEMS, APPROVED EXPLOSION-PROOF EQUIPMENT AND INTRINSICALLY SAFE ELECTRICAL SYSTEMS IN AREAS WHERE THIS PRODUCT IS USED AND STORED.

KEEP LIQUID AND VAPORS AWAY FROM SPARKS AND FLAME, STORE IN CONTAINERS ABOVE GROUND AND SURROUNDED BY DIKES TO CONTAIN SPILLS OR LEAKS. DO NOT CUT, DRILL, GRIND, WELD, OR PERFORM SIMILAR OPERATIONS ON OR NEAR CONTAINERS.

SECTION 8: EXPOSURE CONTROLS AND PERSONAL PROTECTION

EYE PROTECTION:

WEAR EYE PROTECTION WITH SIDE SHIELDS OR GOGGLES. WEAR INDIRECT-VENT, IMPACT AND SPLASH RESISTANT GOGGLES WHEN WORKING WITH LIQUIDS. IF ADDITIONAL PROTECTION IS NEEDED FOR ENTIRE FACE, USE IN COMBINATION WITH A FACE SHIELD.



SAFETY DATA SHEET (SDS)

SKIN PROTECTION:

USE OF GLOVES APPROVED TO RELEVANT STANDARDS MADE FROM THE FOLLOWING MATERIALS MAY PROVIDE SUITABLE CHEMICAL PROTECTION: PVC, NEOPRENE OR NITRILE RUBBER GLOVES. SUITABILITY AND DURABILITY OF A GLOVE IS DEPENDENT ON USAGE, E.G. FREQUENCY AND DURATION OF CONTACT, CHEMICAL RESISTANCE OF GLOVE MATERIAL, GLOVE THICKNESS, DEXTERITY. ALWAYS SEEK ADVICE FROM GLOVE SUPPLIERS. CONTAMINATED GLOVES SHOULD BE REPLACED. USE OF AN APRON AND OVER-BOOTS OF CHEMICALLY IMPERVIOUS MATERIALS SUCH AS NEOPRENE OR NITRILE RUBBER IS RECOMMENDED TO AVOID SKIN SENSITIZATION. THE TYPE OF PROTECTIVE EQUIPMENT MUST BE SELECTED ACCORDING TO THE CONCENTRATION AND AMOUNT OF THE DANGEROUS SUBSTANCE AT THE SPECIFIC WORKPLACE. LAUNDER SOILED CLOTHES OR PROPERLY DISPOSED OF CONTAMINATED MATERIAL, WHICH CANNOT BE DECONTAMINATED.

RESPIRATORY PROTECTION:

IF AIRBORNE CONCENTRATIONS EXCEED OR ARE EXPECTED TO EXCEED THE TLV, USE MSHA/NIOSH APPROVED POSITIVE PRESSURE SUPPLIED PRESSURE AIR RESPIRATORY WITH A FULL FACE PIECE OR AN AIR SUPPLIED HOOD. FOR EMERGENCIES, USE A POSITIVE PRESSURE SELF-CONTAINED BREATHING APPARATUS. AIR PURIFYING (CARTRIDGE TYPE) RESPIRATORS ARE NOT APPROVED FOR PROTECTION AGAINST ISOCYANATES.

APPROPRIATE ENGINEERING CONTROLS:

PROVIDE EXHAUST VENTILATION OR OTHER ENGINEERING CONTROLS TO KEEP THE AIRBORNE CONCENTRATIONS OF VAPORS BELOW THEIR RESPECTIVE THRESHOLD LIMIT VALUE.

Chemical Name	OSHA TWA (ppm)	OSHA TWA (mg/m3)	OSHA STEL (ppm)	OSHA STEL (mg/m3)	OSHA Tables (Z1, Z2, Z3)	OSHA Carcinogen	OSHA Skin designation	NIOSH TWA (ppm)	NIOSH TWA (mg/m3)	NIOSH STEL (ppm)	NIOSH STEL (mg/m3)	NIOSH Carcinogen
4,4'- METHYLENEDIPHEN- YL DIISOCYANATE	0.02 CEILING	0.2 CEILING			1			0.005		0.050		

CHEMICAL NAME	ACGIH TWA (ppm)	ACGIH TWA (mg/m3)	ACGIH STEL (ppm)	ACGIH STEL (mg/m3)
4,4'- METHYLENEDIPHEN- YL DIISOCYANATE	0.005	0.051		

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

DENSITY:	10.16 LB/GAL
SPECIFIC GRAVITY:	1.22
VOC REGULATORY:	0.00 LB/GAL
VOC PART A & B COMBINED:	N/A
APPEARANCE:	LIQUID
ODOR THRESHOLD:	N/A
ODOR DESCRIPTION:	MILD AROMATIC
PH:	N/A
SOLUBILITY IN WATER:	REACTS WITH WATER
FLAMMABILITY:	N/A
FLASH POINT SYMBOL:	N/A
FLASH POINT:	150° C
VISCOSITY:	N/A
LOWER EXPLOSION LEVEL:	N/A
UPPER EXPLOSION LEVEL:	N/A



SAFETY DATA SHEET (SDS)

VAPOR PRESSURE:	N/A
FREEZING POINT:	N/A
MELTING POINT:	N/A
LOW BOILING POINT:	200° C
HIGH BOILING POINT:	N/A
AUTO IGNITION TEMP:	N/A
DECOMPOSITION POINT:	N/A
EVAPORATION RATE:	SLOWER THAN ETHER
COEFFICIENT WATER/OIL:	N/A

SECTION 10: STABILITY AND REACTIVITY

STABILITY: MATERIAL IS STABLE AT STANDARD TEMPERATURE AND PRESSURE.

MATERIALS TO AVOID: THIS PRODUCT WILL REACT WITH ANY MATERIAL CONTAINING ACTIVE HYDROGENS, SUCH AS WATER, ALCOHOL, AMMONIA, AMINES, ALKALIS AND ACIDS, THE REACTION WITH WATER IS SLOW UNDER 50°C, BUT IS ACCELERATED AT HIGHER TEMPERATURE AND IN THE PRESENCE OF ALKALIS, TERTIARY AMINES, AND METAL COMPOUNDS. SOME REACTIONS CAN BE VIOLENT. MATERIAL CAN REACT WITH STRONG OXIDIZING AGENTS.

CONDITIONS TO AVOID: HEAT, HIGH TEMPERATURE, OPEN FLAME, SPARKS, AND MOISTURE. CONTACT WITH INCOMPATIBLE MATERIALS IN A CLOSED SYSTEM WILL CAUSE LIBERATION OF CARBON DIOXIDE AND BUILDUP OF PRESSURE.

HAZARDOUS REACTIONS/POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS BUT UNDER HIGH TEMPERATURES ABOVE 204°C, IN THE PRESENCE OF MOISTURES, ALKALIS, TERTIARY AMINES, AND METAL COMPOUNDS WILL ACCELERATE POLYMERIZATION. POSSIBLE EVOLUTION OF CARBON DIOXIDE GAS MAY RUPTURE CLOSED CONTAINERS.

HAZARDOUS DECOMPOSITION PRODUCTS: CARBON DIOXIDE, CARBON MONOXIDE, NITROGEN OXIDES, TRACE AMOUNTS OF HYDROGEN CYANIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION 11: TOXOLOGICAL INFORMATION

INFORMATION ON TOXICOLOGICAL EFFECTS

ACUTE TOXICITY:

NO DATA AVAILABLE

0000101-68-8 4,4'-METHYLENEDIPHENYL DIISOCYANATE

LC50 (RAT): 369-490 MG/M3 (AEROSOL) (4-HOUR EXPOSURE) (1)

LC50 (RAT): 178 MG/M3 (17.4 PPM) (DURATION OF EXPOSURE NOT REPORTED) (2)

LD50 (ORAL, RAT): GREATER THAN 10,000 MG/KG (1,2) LD50 (DERMAL, RABBIT): GREATER THAN 10,000 MG/KG (1) LD50 (ORAL, MOUSE): 2,200 MG/KG (3)

HEXAMETHYLENE DIISOCYANATE

PRIMARY IRRITANT EFFECT:

ON THE SKIN: ISOCYANATES REACT WITH SKIN PROTEIN AND MOISTURE AND CAN CAUSE IRRITATION. PROLONGED CONTACT CAN CAUSE REDDENING, SWELLING, RASH, SCALING, BLISTERING, AND, IN SOME CASES, SKIN SENSITIZATION. INDIVIDUALS WHO HAVE DEVELOPED A SKIN SENSITIZATION CAN DEVELOP THESE SYMPTOMS AS A RESULT OF CONTACT WITH VERY SMALL AMOUNTS OF LIQUID MATERIAL OR AS A RESULT OF EXPOSURE TO VAPOR.
CAUSES SKIN IRRITATION



PRODUCT IDENTIFIER: URETHANE CEMENT SL 160 PART A
DATE AND VERSION: 1 APRIL 2019 VERSION 1.0

SAFETY DATA SHEET (SDS)

ON THE EYE: LIQUID, AEROSOLS OR VAPORS ARE SEVERELY IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING. PROLONGED VAPOR CONTACT MAY CAUSE CONJUNCTIVITIS. ANY LEVEL OF CONTACT SHOULD NOT BE LEFT UNTREATED. CAUSES SERIOUS EYE IRRITATION

INHALATION: MAY CAUSE ALLERGY OR ASTHMA SYMPTOMS OR BREATHING DIFFICULTIES IF INHALED. MAY CAUSE AN ALLERGIC SKIN REACTION

CARCENOGENICITY: SUSPECTED OF CAUSING CANCER.

SPECIFIC TARGET ORGAN TOXICITY – SINGLE EXPOSURE: HIGH VAPOR CONCENTRATIONS MAY CAUSE CENTRAL NERVOUS SYSTEM (CNS) DEPRESSION AS EVIDENCED BY GIDDINESS, HEADACHE, DIZZINESS, AND NAUSEA. PERSONS WITH A PREEXISTING, NONSPECIFIC BRONCHIAL HYPERACTIVITY CAN RESPOND TO CONCENTRATIONS BELOW THE TLV WITH SIMILAR SYMPTOMS AS WELL AS ASTHMA ATTACK. EXPOSURE WELL ABOVE THE TLV MAY LEAD TO BRONCHITIS, BRONCHIAL SPASM AND PULMONARY EDEMA (FLUID IN LUNGS). AS A RESULT OF PREVIOUS REPEATED OVEREXPOSURES OR A SINGLE LARGE DOSE, CERTAIN INDIVIDUALS MAY DEVELOP ISOCYANATE SENSITIZATION (CHEMICAL ASTHMA) WHICH WILL CAUSE THEM TO REACT TO A LATER EXPOSURE TO ISOCYANATE AT LEVELS WELL BELOW THE TLV. MAY CAUSE RESPIRATORY IRRITATION

SPECIFIC TARGET ORGAN TOXICITY – REPEATED EXPOSURE: CHRONIC OVEREXPOSURE TO ISOCYANATE HAS ALSO BEEN REPORTED TO CAUSE LUNG DAMAGE (INCLUDING DECREASE IN LUNG FUNCTION) WHICH MAY BE PERMANENT. MAY CAUSE DAMAGE TO ORGANS THROUGH PROLONGED OR REPEATED EXPOSURE.

SECTION 12: ECOLOGICAL INFORMATION

TOXICITY:

NO DATA AVAILABLE

PERSISTENCE AND DEGRADABILITY:

NO DATA AVAILABLE

BIOACCUMULATIVE POTENTIAL:

NO DATA AVAILABLE

MOBILITY IN SOIL:

NO DATA AVAILABLE

SECTION 13: DISPOSAL CONSIDERATION

WASTE DISPOSAL OF SUBSTANCE:

UNDER RCRA, IT IS THE RESPONSIBILITY OF THE USER OF THE PRODUCT, TO DETERMINE A THE TIME OF DISPOSAL WHETHER THE PRODUCT MEETS RCRA CRITERIA FOR HAZARDOUS WASTE. WASTE MANAGEMENT SHOULD BE IN FULL COMPLIANCE WITH FEDERAL, STATE, AND LOCAL LAWS.

EMPTY CONTAINERS RETAIN PRODUCT RESIDUE WHICH MAY EXHIBIT HAZARDS OF MATERIAL, THEREFORE DO NOT PRESSURIZE, CUT, GLAZE, WELD OR USE FOR ANY OTHER PURPOSES. RETURN DRUMS TO RECLAMATION CENTERS FOR PROPER CLEANING AND REUSE.

SECTION 14: TRANSPORTATION INFORMATION

LAND TRANSPORT U.S. DOT:

NOT CLASSIFIED AS A DANGEROUS GOOD

SEA TRANSPORT IMDG:

NOT CLASSIFIED AS A DANGEROUS GOOD

AIR TRANSPORT IATA/ICAO:

NOT CLASSIFIED AS A DANGEROUS GOOD



PRODUCT IDENTIFIER: URETHANE CEMENT SL 160 PART A
DATE AND VERSION: 1 APRIL 2019 VERSION 1.0

SAFETY DATA SHEET (SDS)

SECTION 15: REGULATORY INFORMATION

CAS	CHEMICAL NAME	% BY WEIGHT	REGULATION LIST
0000101-68-8	4,4'- METHYLENEDIPHENYL DIISOCYANATE	64% - 100%	DSL,CERCLA,HAPS,SARA312,SARA313,VHAPS,VOC,TSCA
0026447-40-5	MDI (MONOMER)	1.7% - 3%	DSL,SARA312,VOC,TSCA

SECTION 16: OTHER INFORMATION

HMIS RATING:

NOTE: AS PER GHS, CATEGORY 1 IS THE GREATEST LEVEL OF HAZARD WITHIN EACH CLASS.

GLOSSARY:

ACGIH- AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS; ANSI- AMERICAN NATIONAL STANDARDS INSTITUTE; CANADIAN TDG- CANADIAN TRANSPORTATION OF DANGEROUS GOODS; CAS- CHEMICAL ABSTRACT SERVICE; CHEMTREC- CHEMICAL TRANSPORTATION EMERGENCY CENTER (US); CHIP- CHEMICAL HAZARD INFORMATION AND PACKAGING; DSL- DOMESTIC SUBSTANCES LIST; EC- EQUIVALENT CONCENTRATION; EH40 (UK)- HSE GUIDANCE NOTE EH40 OCCUPATIONAL EXPOSURE LIMITS; EPCRA- EMERGENCY PLANNING AND COMMUNITY RIGHT-TO-KNOW ACT; ESL- EFFECTS SCREENING LEVELS; HMIS- HAZARDOUS MATERIAL INFORMATION SERVICE; LC- LETHAL CONCENTRATION; LD- LETHAL DOSE; NFPA- NATIONAL FIRE PROTECTION ASSOCIATION; OEL- OCCUPATIONAL EXPOSURE LIMITS; OSHA- OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION, US DEPARTMENT OF LABOR; PEL- PERMISSIBLE EXPOSURE LIMIT; SARA (TITLE III)- SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT; SARA 313- SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT, SECTION 313; SCBA- SELF-CONTAINED BREATHING APPARATUS; STEL- SHORT TERM EXPOSURE LIMIT; TCEQ - TEXAS COMMISSION ON ENVIRONMENTAL QUALITY; TLV- THRESHOLD LIMIT VALUE; TSCA- TOXIC SUBSTANCES CONTROL ACT PUBLIC LAW 94-469; TWA - TIME WEIGHTED VALUE; US DOT- US DEPARTMENT OF TRANSPORTATION; WHMIS- WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM.

DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE. HOWEVER, NEITHER THE ABOVE NAMED SUPPLIER NOR ANY OF ITS SUBSIDIARIES ASSUMES ANY LIABILITY WHATSOEVER FOR THE ACCURACY OR COMPLETENESS OF THE INFORMATION CONTAINED HEREIN. FINAL DETERMINATION OF SUITABILITY OF ANY MATERIAL IS THE SOLE RESPONSIBILITY OF THE USER. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST. THE ABOVE INFORMATION PERTAINS TO THIS PRODUCT AS CURRENTLY FORMULATED AND IS BASED ON THE INFORMATION AVAILABLE AT THIS TIME. ADDITION OF REDUCERS OR OTHER ADDITIVES TO THIS PRODUCT MAY SUBSTANTIALLY ALTER THE COMPOSITION AND HAZARDS OF THE PRODUCT. SINCE CONDITIONS OF USE ARE OUTSIDE OUR CONTROL, WE MAKE NO WARRANTIES, EXPRESS OR IMPLIED, AND ASSUME NO LIABILITY IN CONNECTION WITH ANY USE OF THIS INFORMATION.

END OF SDS

SDS PREPARED BY: MVP COATINGS, INC.

SDS PREPARED ON: 4/1/2019