MODEL	NUMBER of ROWS	ROW SPACING	NUMBER of TIRES	FOLD // FLEX	OPEN WIDTH(A) // FOLDED WIDTH(B)	OPEN LENGTH ^(C) // FOLDED LENGTH ^(D)	HITCH TYPE	TIRE POSITION
PB2015FR	15	15"	1-2-1	4-7-4	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	FRONT RUNNING [†]
PB2020FR	12	20"	1-2-1	3-6-3	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	FRONT RUNNING [†]
PB2030FR	8	30"	1-2-1	2-4-2	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	FRONT RUNNING [†]
PB2030BR	8	30"	1-2-1	2-4-2	19' 4" // 103"	13' // 19' 6"	HAMMER BALL & SOCKET	BACK RUNNING [‡]
PB3015FR(1)	23	15"	1-4-1	6-11-6	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]
PB3020FR ⁽¹⁾	18	20"	1-4-1	5-8-5	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]
PB3022FR ⁽¹⁾	16	22"	1-4-1	4-8-4	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]
PB3030FR ⁽¹⁾	12	30"	1-4-1	3-6-3	30' 10" // 164 ¼"	15' 2" // 23' 10"	HAMMER*	FRONT RUNNING [†]
PB3030BR	12	30"	1-4-1	4-4-4 // 3-6-3	30' 10" // 128"	15' 2" // 23' 10"	HAMMER*	BACK RUNNING [‡]
PB3030BRT	12	30"	1-4-1	4-4-4 // 3-6-3	30' 10" // 128"	15' 2" // 23' 10"	2PT (CAT3)	BACK RUNNING [‡]
PB4015FR ⁽¹⁾	31	15"	2-4-2	10-11-10	41' // 164 ¼"	18' 11" // 27' 6"	HAMMER*	FRONT RUNNING [†]
PB4020FR ⁽¹⁾	24	20"	2-4-2	8-8-8	41' // 164 ¼"	18' 11" // 27' 6"	HAMMER*	FRONT RUNNING [†]
PB4030FR	16	30"	2-4-2	5-6-5	41' // 164 ¼"	18' 11" // 27' 6"	HAMMER*	FRONT RUNNING [†]
PB4030BR	16	30"	2-4-2	6-4-6 // 5-6-5	41' // 128"	18' 11" // 27' 6"	HAMMER*	BACK RUNNING [‡]
PB4030BRT	16	30"	2-4-2	6-4-6 // 5-6-5	41' // 128"	18' 11" // 27' 6"	2PT (CAT3)	BACK RUNNING [‡]
PB4422FR ⁽²⁾	24	22"	2-4-2	8-8-8	43' 6" // 164 ¼"	19' 11" // 29' 6"	HAMMER*	FRONT RUNNING [†]
PB6015FR(3,4)	47	15"	2-4-2	18-11-18	59' 10" // 164 ¼"	24' 7" // 39' 6"	HAMMER*	FRONT RUNNING [†]
PB6020FR ⁽⁴⁾	36	20"	2-4-2	14-8-14	59' 10" // 164 ¼"	24' 7" // 39' 6"	HAMMER*	FRONT RUNNING [†]
PB6020FR ULTRAFLEX(4)	36	20"	2-4-2	14-8-14 // 7-7-8-7-7	59' 10" // 164 ¼"	24 7" // 39 6"	HAMMER*	FRONT RUNNING [†]
PB6030FR	24	30"	2-4-2	9-6-9	59' 10" // 164 ¼"	24 7" // 39 6"	HAMMER*	FRONT RUNNING [†]
PB6030BR	24	30"	2-4-2	10-4-10 // 9-6-9	59' 10" // 128"	24 7" // 39 6"	HAMMER*	BACK RUNNING [‡]
PB6030BRT	24	30"	2-4-2	10-4-10 // 9-6-9	59 10 // 128	24' 7" // 39' 6"	2PT (CAT 3)	BACK RUNNING [‡]

(MODEL)1 Right hand wing tire located on outside of right wing outer row unit

(MODEL)² Requires wing stub tube to be added to PB4030FR

(MODEL)³ CSD model only Requires 3 vac fans FRONT RUNNING[†] BACK BUNNING

BULL PULL[™] brand hammer strap hitch


Tire: 20' & 30': Bartread // 40' & up: 420 55R 22.5 on center, Bartread on wings.


Tire: 30' & up: 255 70R 22.5

Narrow row tracks are available on 40' & 60' front running models.

MANY MORE ROW SPACINGS CAN BE CONFIGURED. CAN FACITILITATE TWIN ROW WITH NARROW LASERPROIN UNITS.

RIGID POWERPLANT PLOT BARS AVAILABLE IN 10' - 20' WIDTHS





401 W 20TH STREET · STORM LAKE, IA 50588

TEL: 712.213.5100 · TOLL: 888.218.5373 · FAX: 712.213.5109 WWW.HARVEST-INTERNATIONAL.COM





HARVEST INTERNATIONAL INC











CUSTOM PLANTERS BUILT FOR PRECISION



DESIGNED TO BE CUSTOMIZED, READY FOR PRECISION PLANTING

FROM BARE BAR TO FULLY OUTFITTED H-I SETUP, THE ULTRAPLANT WILL WORK FOR YOU


ULTRAPLANT SERIES | Model Shown: PB4020FR w/ CSD, 300 Gal Tank, Row Markers, & LaserPro1 Row Units


PRECISION ENGINEERING
FULLY INTEGRATED LASER TECHNOLOGY

TRI-FLEX WING FOLD DESIGN
FLEXIBLE SPAN. NARROW TRANSPORT

POWDER COAT PLUS™
BETTER COATING & LONGER LASTING

• For NON-CSD planters, 1000 Gal Tank option or deck for Montag box is available for on board storage






PB4015FR w/ Central Seed Delivery (CSD) System
Stepbacks allow for excellent trashflow with parrow row spacing



Digital In-cab Control ConsoleConvenient control of all toolbar functions: 3 plug in-cab connection



Intra-Airway™ vacuum port located inside 9x5 tube
Keeps bar free of extra lines & clean for maintenance & service



All hydraulic functions controlled by three manifolds
Better serviceability: Stainless steel M12 & weather-pack connectors



60' UltraPlant & LaserPro1 units 24 row 30' spacing: CSD, 500 gal liquid, vDrive insecticide mount



UltraPlant Model: PB6030BR Draft tube adjustments w/ nut keeper

Located next to the wing to eliminate potential tire-turning damage.



500 Gallon Liquid Tank option