

APC by Schneider Electric Back UPS Pro BX 1500VA, 10 Outlets, AVR, LCD interface, LAM 60Hz - Tower - AVR - 1...

Categoría Power/Rack Equipment > Power Equipment >

\$250.00

- Adjustable voltage sensitivity Provides the ability to adapt the UPS for optimal performance in specific power environments or generator applications.
- Audible alarms Provides notification of changing utility power and UPS power conditions
- Automatic self-test Periodic battery self-test ensures early detection of a battery that needs to be replaced.

Acerca de este producto

Overview

The Back-UPS Pro family offers guaranteed power protection for high performance computer systems, routers/modems, external storage devices, game consoles and other electronics in your home or business. These UPSs supply electronics with abundant battery backup during outages and stabilize unsafe voltage levels. They also provide power protection from damaging surges and spikes, and allow the use of management software so you get the most out of your UPS. Premium features of this family may include Automatic Voltage Regulation (AVR), an LCD display, Smart Outlets, energy saving functions that reduce electricity use, network manageability, Watchdog, or configurable outlets. Together with the rest of the Back-UPS Pro's standard features, they are the perfect choice to protect your data and keep your system available.

- Adjustable voltage sensitivity Provides the ability to adapt the UPS for optimal performance in specific power environments or generator applications.
- Audible alarms Provides notification of changing utility power and UPS power conditions
- Automatic self-test Periodic battery self-test ensures early detection of a battery that needs to be replaced.
- Automatic Voltage Regulation (AVR) -Automatically steps up low voltage and steps down high voltage to levels that are suitable for your equipment.
- Battery backup and surge protection Outlets provide abundant runtime for network gateway equipment and other critical low-power devices, allowing for hours of internet access during a power outage.
- Battery failure notification Provides earlywarning fault analysis on batteries enabling timely preventive maintenance





- Battery replacement without tools Enables fast battery replacement, lowering Mean Time to Repair (MTTR).
- Building Wiring Fault Indicator This LED informs users of potentially dangerous wiring problems in the wall circuit.
- Cold-start capable Provides temporary battery power when the utility power is out.
- Dataline surge protection Provides protection of connected equipment from power surges on the data lines.

Tech Specs

Specs			
Controls/Indicators		Depth	15"
Status Indicators	Multifunction LCD status	Product Color	Black
		Color Family	Black
Interfaces/Ports		General Information	
USB (HID Compliant) Port	Yes	Product Type	Line-interactive UPS
Management		Manufacturer Part Number	BX1500M-LM60
Alarm	Low Battery	Manufacturer Website	http://www.schneider-
7.10111	On Battery	Address	electric.com
	Overload	Manufacturer	Schneider Electric SA
Battery Information	Overredu	Product Name	Back UPS Pro BX 1500VA, 10
Battery Chemistry	Lead Acid		Outlets, AVR, LCD interface, LAM 60Hz
Battery Energy	619.2 kJ	Product Line	Back-UPS Pro
Replaceable Battery	Yes	Product Series	BX
Typical Battery			
Recharge Time	16 Hour	Power Description	APC by Schneider Electric
Environmental Conditions			120 V AC
Maximum Operating	104°F (40°C)	Input Voltage Output Voltage	120 V AC
Temperature	104 1 (40 0)	. 3	789 J
Maximum Operating Elevation Maximum Storage	10000 ft	Surge Energy Rating	
		Waveform Type	Stepped Approximated Sine Wave
Elevation	50000 ft	Input Voltage Range	88 V AC - 139 V AC
Sound Emission (A-	45 dB(A)	Output Frequency	60 Hz
Weighted)		Input Frequency	60 Hz
Miscellaneous		Load Capacity (VA)	1500 VA
Package Contents	Back UPS Pro BX 1500VA, 10 Outlets, AVR, LCD interface, LAM 60Hz	Load Capacity (Watt)	900 W
		Technical Information	
	USB cable	Application/Usage	Computer System
0 1177 11 0	User manual		Router
Certifications & Standards	FCC part 15 class BNOM		Modem
	TUV C-US certified		External Hard Drive
Environmentally	Yes		Gaming Console
Friendly		Dataline Protection	Coax
Environmental Compliance	Restriction of Hazardous Substances (RoHS)		RJ-45
Compliance	Registration, Evaluation, Authorization and Restriction of Chemicals (REACH)	Plug/Connector Type	NEMA 5-15P
		Receptacle Type	NEMA 5-15R
		AVR	Yes
Physical Characteristics		Number of Battery &	10
Weight (Approximate)	24.25 lb	Surge Outlets	
Form Factor	Tower	Number of Surge-only Outlets	5
Height	9.8"	Transfer Time	8 ms

Transfer Time

8 ms

Width 3.9" Receptacle Detail 10 x NEMA 5-15R

Warranty & Additional Information

Información adicional

Ancho del

Largo del Producto 14.47 Producto 9.48 Producto 19.77 Embalaje 39.75 inches Inches pounds

Peso de