

# XMPLAR

## TIRE CATALOG



# TIRE CATALOG



PRODUCT NUMBER	SIZE	LOAD INDEX	LOAD RANGE	PLY RATING
841623164751	11R22.5	146/143	H	16
841623164768	11R24.5	149/146	H	16
TBD	225/70R19.5	128/126	G	14
TBD	245/70R19.5	143/141	H	16
841623164775	255/70R22.5	140/137	H	16
841623164805	285/75R24.5	144/143	G	14
841623164812	295/75R22.5	146/143	H	16
SPEED RATING (mph)	RIM WIDTH RANGE (in.)	TREAD DEPTH (32nd)	MAX LOAD INFLATION (lbs.)	MAX INFLATION (psi.)
M(81 mph)	7.50-8.25	17	6610 6005	120
M(81 mph)	7.50-8.25	17	7160 6610	120
M(81 mph)	6.00-6.75-6.75RW	17	3970 3750	110
K(68 mph)	6.75-7.50	17	6005 5675	130
M(81 mph)	6.75-7.50-8.25	17	5510 5070	120
M(81 mph)	7.50-8.25-9.00	17	6175 5675	110
M(81 mph)	8.25-9.00	17	6610 6005	120
TIRE SECTION WIDTH (in.)	TIRE OUTSIDE DIAMETER (in.)	WEIGHT (lbs)		
11.0	41.5	112.2		
11.0	43.5	121.0		
8.9	31.9	65.5		
12.3	31.0	63.9		
10.0	36.6	85.3		
11.1	41.3	113.5		
11.7	39.9	109.3		



PRODUCT NUMBER	SIZE	LOAD INDEX	LOAD RANGE	PLY RATING
841623164782	11R22.5	146/143	H	16
841623164799	11R24.5	149/146	H	16
841623164720	285/75R24.5	144/141	G	14
841623164737	295/75R22.5	146/143	H	16
SPEED RATING (mph)	RIM WIDTH RANGE (in.)	TREAD DEPTH (32nd)	MAX LOAD INFLATION (lbs.)	MAX INFLATION (psi.)
M(81 mph)	7.50-8.25	27	6610 6005	120
M(81 mph)	7.50-8.25	27	7160 6610	120
M(81 mph)	7.50-8.25-9.00	27	6175 5675	110
L(75 mph)	8.25-9.00	27	6610 6005	120
TIRE SECTION WIDTH (in.)	TIRE OUTSIDE DIAMETER (in.)	WEIGHT (lbs)		
11.0	41.9	121.1		
11.0	43.9	131.4		
11.1	41.8	124.1		
11.7	40.3	119.9		

This data can be changed by manufacturer without prior notice.



PRODUCT NUMBER	SIZE	LOAD INDEX	LOAD RANGE	PLY RATING	SPEED RATING (mph)	RIM WIDTH RANGE (in)
841623164706	11R22.5	146/143	H	16	M(81 mph)	7.50-8.25
841623164713	11R24.5	149/146	H	16	M(81 mph)	7.50-8.25
TBD	225/70R19.5	128/126	G	14	M(81 mph)	6.00-6.75-6.75RW
TBD	245/70R19.5	135/133	H	16	M(81 mph)	6.75-7.50-7.50RW
TREAD DEPTH (32nds)	MAX LOAD INFLATION (lbs)	MAX INFLATION (psi)	TIRE SECTION WIDTH (in)	TIRE OUTSIDE DIAMETER (in)	WEIGHT (lbs)	
27	6610 6005	120	11.0	41.9	122.8	
27	7160 6610	120	11.0	43.5	132.1	
17	3970 3750	110	9.0	31.9	65.9	
17	4805 4540	120	9.8	33.0	78.3	



PRODUCT NUMBER	SIZE	LOAD INDEX	LOAD RANGE	PLY RATING	SPEED RATING (mph)	RIM WIDTH RANGE (in)
841623164836	11R22.5	146/143	H	16	N(87 mph)	7.50-8.25
841623164843	11R24.5	149/146	H	16	N(87 mph)	7.50-8.25
TBD	315/80R22.5	157/154	L	20	N(87 mph)	9.00-9.75
TBD	385/65R22.5	160	L	20	M(81 mph)	11.75-12.25
TBD	425/65R22.5	165	L	20	N(87 mph)	12.25-13.00
TREAD DEPTH (32nds)	MAX LOAD INFLATION (lbs)	MAX INFLATION (psi)	TIRE SECTION WIDTH (in)	TIRE OUTSIDE DIAMETER (in)	WEIGHT (lbs)	
17	6610 6005	120	11.0	41.5	116.6	
17	7160 6610	120	11.0	43.5	124.8	
20	9090 8270	130	12.3	42.4	144.8	
19	9920 /	130	15.3	42.2	150.1	
21	11400 /	120	16.6	44.3	202.8	



PRODUCT NUMBER	SIZE	LOAD INDEX	LOAD RANGE	PLY RATING	SPEED RATING (mph)	RIM WIDTH RANGE (in)
841623164850	11R22.5	144/142	G	14	M(81 mph)	7.50-8.25
841623164867	295/75R22.5	144/141	G	14	L(75 mph)	8.25-9.00
TREAD DEPTH (32nds)	MAX LOAD INFLATION (lbs)	MAX INFLATION (psi)	TIRE SECTION WIDTH (in)	TIRE OUTSIDE DIAMETER (in)	WEIGHT (lbs)	
13	6175 5840	105	11.0	41.5	104.7	
13	6175 5675	110	11.7	39.9	99.2	

# XMPLAR



**CONFIA**  
TIRES

INFO@CONFIAIRES.COM  
CONFIAIRES.COM