

WALL PACK (WP06)



Features

- Sealed die-casting profile for indoor and outdoor applications. Voltage is 120-277V, 1-10V dimmable.
- Lumen output from 3300-15100lm with efficacy up to 113lm/W.
- Polycarbonate optical lens with UV stabilizers
- Photocell and Motion Sensor optional and supports Emergency Battery
- Replacing 100W MH and 400W MH.
- Operating temperature is -40°C to 40°C (-40°F to 104°F).
- UL/cUL wet location and DLC qualified.

Medium Size: 30W/45W/70W



Large Size: 90W/135W



Housing
Suitable for both indoor and outdoor application, also suitable for J-BOX mounting and surface mounting.

Lens
Polycarbonate optical lens with UV stabilizers no yellow shading or deterioration over years

PIR Sensor
Optional PIR Sensor allows for security and energy saving

Photocell
Optional photocell allows for security and energy saving

1/2inch threaded hole
Three entries can support wires coming out from the hole for easier wire connections

Emergency Switch
8W 900lm 90min



PERFORMANCE DATA

PERFORMANCE DATA		4000K(70CRI)		5000K(70CRI)	
RATED WATTS	VOLTAGE	LUMENS	LPW	LUMENS	LPW
30W	120-277VAC	3300lm	110 lm/W	3400lm	113 lm/W
45W	120-277VAC	4900lm	109 lm/W	4900lm	109 lm/W
70W	120-277VAC	7800lm	111 lm/W	7800lm	111 lm/W
90W	120-277VAC	9900lm	110 lm/W	9900lm	110 lm/W
135W	120-277VAC	15100lm	112 lm/W	15100lm	112 lm/W




ELECTRICAL DATA

Number Of Drivers	Driver Current (mA)	Nominal Power (W)	INPUT VOLTAGE (V)	CURRENT (Amps)
1	720	30	120	0.25
		30	208	0.14
		30	240	0.13
		30	277	0.11
1	1100	45	120	0.38
		45	208	0.22
		45	240	0.19
		45	277	0.16
1	1750	70	120	0.58
		70	208	0.34
		70	240	0.29
		70	277	0.25
1	2200	90	120	0.75
		90	208	0.43
		90	240	0.38
		90	277	0.32
2	3500	135	120	1.13
		135	208	0.65
		135	240	0.56
		135	277	0.49

DIMENSION




unit: inch/mm

Medium Size



Weight: 7.396lb

Large Size




Weight: 11.62lb

PHOTOMETRICS

Medium size


Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 103.0°

Large size

Luminous Intensity Distribution Curve



Average Diffuse Angle(50%): 93.0°

ORDERING GUIDE

Fixture Type	Wattage	Voltage	CCT	Finish	Sensor (Option)	Photocell (Option)	Emergency Battery (Option)
<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>	<input type="checkbox"/>
WP06	30 30W 45 45W 70 70W 90 90W 135 135W	27V 100-277V	40K 4000K 50K 5000K	D Dark Bronze B Black W White	M With Sensor Blank Without Sensor	P1 120V Photocell P0 277V Photocell Blank Without Photocell	B Emergency Battery Blank Without Emergency Battery