



Prime Supply 1
12146 Severn Way
Riverside, CA 92503

Tel: 866-452-4525
Land Line :951-427-5711
Fax: 888-847-7756

SPECIFICATION

Typical Physical Properties

Pro Platinum Plus

Typical Properties	Test Method	
Material		Polypropylene
Color		Black with lines every 12"
Construction		15 x 10
Weight (Oz/Sq Yd)	ASTM D-3776	5.0 oz/sy (avg)
Tensile Strength (lbs)	ASTM D-4632	100 x 60
Burst (psi)	ASTM D-3786	285
Trapezoid Tear (lbs)	ASTM D-4533	70 x 70
Water Permeability (gal/min/SF)	ASTM D-4491	12
Ultraviolet Exposure (% Strength Retained)	ASTM D-4355	>70% after 2500 hrs Xenon Arc exposure
Thickness (mils)	ASTM D-1777	30

1/2011

The information contained herein is furnished without charge or obligation and the recipient assumes all responsibility for its use. Because conditions of use and handling may vary and are beyond our control, we make no representation about, and are not responsible or liable for, the accuracy or reliability of said information or the performance of any product. Any specification, properties or applications listed herein are provided as information only and in no way modify, amend, enlarge or create any warranty. Nothing contained herein is to be construed as permission or as a recommendation to infringe any patent.