



RIPA C20 INTELLIGENT MEETING ORCHESTRATOR

Version v5.5

Data Sheet

RipaTech Pty Ltd

CONTENTS

Product Summary	2
Feature Highlights.....	2
Technical Specifications.....	2
Product Demension	6
Product Image Library	6
Ordering Guide	7

PRODUCT SUMMARY

Ripa C20 Intelligent Meeting Orchestrator is an industry standard video and audio CODEC. It is designed to process high quality 4K video and high-quality audio. The intelligent firmware and high spec CPU make this CODEC the most cost effective in the industry.

C20 is ideally used in the meeting room where a dual display panel and single camera is present for huddle and medium room to communicate with remote meeting participants.



Figure 1: C20 Intelligent Meeting Orchestrator

FEATURE HIGHLIGHTS

C20 offers a mature list of SIP/H.323 CODEC features:

- **SIP and H.323 protocols:** supports both SIP and H.323 protocols.
- **Audio Processing:** support Automatic Echo Cancellation (AEC), Automatic Gain Control (AGC), Automatic Noise Suppression (ANS)
- **Multiple Video Compression Standard:** It supports H.263/H.264 video compression.
- **Chromas key:** support to display an image as your background during a meeting, which can provide you with more privacy or a consistent. This feature must be purchased separately on initial order.
- **Subtle Gesture Control:** It supports Subtle Gesture Control – Mute/Hide
- **Camera Options:** It can be used with has all Ripa 4K, 1080p and table 360 cameras.

TECHNICAL SPECIFICATIONS

Technical Specifications



Ripa C20 Intelligent Meeting Orchestrator

Package includes:		
+ RIPA C20 Codec		
+ RIPA camera		
+ RIPA Microphone Array		
+ Remote control		
+ Cable bundle		
Module	Function	Description
System Interface	Support system interface customization	
Resolution	Video Resolution Encode	Up to 4K; Content Frame Rate: Up to 30fps
	Content Video Resolution	Up to 4K; Content Frame Rate: Up to 30fps
Feature Highlights	<ul style="list-style-type: none"> • Allow HDMI input for content sharing or as camera input, including video and audio. • Displays the near-end camera in full-screen mode during the meetings. • Allows automatic or manual start content sharing. • Supports camera presets via remote control and web-based management. • Power on/off button available on the device chassis. • Power on/off control via remote control. • Allows changing the meeting room background. • Supports IP camera connectivity (Video over IP). 	
Audio	Audio Processing	Auto Echo Cancellation (AEC) Auto Gain Control (AGC) Auto Noise Suppression (ANS)
	Audio Codec	G.711(a/μ), G.719, G.722, G.722.1, G.722.1C, AAC, OPUS. Frequency range: 7kHz-to 48 kHz
Codec	Format	H.261, H.263, H.263+, H.264, H.264 High Profile, H.239, BFCP (Content Sharing)
Controller	Remote Control	Infrared Remote Control
	Web UI	Manage via Web Interface
Network	IPv4 & IPv6, Bandwidth: up to 4Mbps. Lost Packet Recovery	
Security	Algorithms: AES (128 – 256 bit) for Media SIP and H.323, Authenticated access, TLS	
Interface	Camera Input	2x USB 1x HDMI Video over IP
	Video Output	2x HDMI
	Audio Input	1x LINE IN Input, 3-pin Phoenix terminal 1x USB 1 x HDMI
	Audio Output	1 x HDMI 1 x 3.5mm stereo line-out 1x USB
	Image Interface	2x HDMI OUT



Ripa C20 Intelligent Meeting Orchestrator

	Content Interface	1x HDMI IN
	USB	2x USB (for Camera or Audio System) 1x Micro USB
	Audio Jack	1x 3.5mm linear output 1x LINE IN Input, 3-pin Phoenix terminal 1x MIC IN Input, 3-pin Phoenix terminal (with phantom power)
	Network Port	Support IPV4 & IPV6, 1x 10/100 Ethernet, Bandwidth (H323/SIP) up to 4 Mbps
	Power Interface	HEC3800 Power Socket (DC12V)
	Wall Mount Bracket	Wall/Ceiling Mount Brackets (Optional)
Camera	R30-12	R30-20
Parameters		
Image Sensor	1/2.8-inch high quality HD CMOS sensor	
Effective Pixel	2.07M, 16:9	
Video Format	<ul style="list-style-type: none"> - HDMI: 4KP30, 1080P60/50/30/25/59.94/29.97, 1080I60/50/59.94, 720P60/50/59.94/ - U3: 1)U3: 4KP30, 1920X1080P60/50/30/25, 1280X720P60/50/30/25, 960X540P30, 640X360P30, 640X480P30, 352X288P30, 800*600P30 2)U3 compatible with U2: 960X540P30, 640X360P30, 1280X720P10/15, 720X576P50, 720X480P60, 640X480P30, 352X288P30, 800*600P30. - U2: 320x240 / 352x288 / 640x480 / 704x576 / 720x480 / 720x576 / 640x360 / 800x448 / 800x600 / 960x540 / 1024x576 / 1024x768 / 1280x720 / 1920x1080P30/25/20/15/10/5 	
Optical Lens	12X f=4.1~49.2mm	20X f=5.05~101mm
Viewing Angle	6.57° (N) 70.28° (W)	3.45° (N) 60.04° (W)
Iris	F1.8 – F2.68	F1.8 – F2.9
Digital Zoom	10X	
Minimum Illumination	0.5Lux (F1.8, AGC ON)	
DNR	2D & 3D	
White Balance	Auto / Manual / One-push / 3000K / 3500K / 4000K / 4500K / 5000K / 5500K / 6000K / 6500K / 7000K	
Focus	Auto / Manual / One-push	
Iris	Auto / Manual	
Electronic Shutter	Auto / Manual	
BLC (Backlight Compensation)	On / Off	




Ripa C20 Intelligent Meeting Orchestrator

Dynamic Range	Off / Dynamic level adjustment
Video Adjustment	Brightness, Contrast, Sharpness, Horizontal Flip, Vertical Flip, Black and White Mode, Gamma Curve, Electronic Zoom, DCI, Ultra Low Light Mode
SNR	>55dB
Interface	
Interface	HDMI, LAN, RS232, A-IN, U2, U3
Video Output	HDMI, USB 3.0, LAN, USB 2.0
Image Streaming	Dual streaming output
Video Compression Formats	H.265, H.264 USB 2.0: MJPG, H264, H.265, YUY2, NV12
Audio IN Jack	A-IN: Dual audio channel 3.5mm linear input
Audio Compression Format	AAC, MP3, G.711A
Network Jack	100M (10/100BASE-TX)
Network Protocols	RTSP, RTMP, ONVIF, GB/T28181; Support network VISCA control protocols, remote upgrade, remote restart, and remote reset.
Control Jacks	RS232 (loop in/out)
Control Protocols	Protocols: VISCA/Pelco-D/Pelco-P; Baud Rate: 115200 / 38400 / 9600 / 4800 / 2400
Power Jack	HEC3800 power socket (DC12V)
Power Adapter	Input: AC100V~AC240V, 50~60 Hz. Automatic voltage detection Output: DC12V/2A
Input Voltage	DC12V±10%
Input Current	1A (Max)
Power Consumption	12W(Max)
PTZ	
Pan	-170°~+170°
Tilt	-30°~+90°
Pan Speed	0.1 ~ 60°/s
Tilt Speed	0.1~30°/s
Preset Speed	Pan: 60°/s, Tilt: 30°/s
Preset Quantity	User can set 255 presets (10 via IR remote control)



Ripa C20 Intelligent Meeting Orchestrator

PRODUCT DEMENSION



PRODUCT IMAGE LIBRARY



Figure 2: C20 Front



Figure 3: C20 Back



Ripa C20 Intelligent Meeting Orchestrator



Figure 4: Camera

ORDERING GUIDE

RipaTech product code: RP-C20- 00680