

# **RIPA CONFERENCE SPEAKERPHONE A10 R2**

Version 1

## Data Sheet

## RipaTech Pty Ltd

CONTENTS	
Product Summary	2
Feature Highlights	2
Technical Specifications	3
Ordering Guide	3



#### **PRODUCT SUMMARY**

Ripa Conference Speakerphone A10 R2: The A10 R2 is a conference omnidirectional microphone that supports secondary cascading. It contains 8 array microphones, supports omnidirectional pickup within a range of 3 meters, and is equipped with proprietary audio algorithms, providing excellent pickup experience in conference scenarios. The omnidirectional microphone supports secondary cascading, serving as both a primary microphone and an expansion microphone, allowing flexible configurations for different-sized conference rooms. Additionally, the A10 R2 is equipped with a 5W high-power speaker for clearer vocals and an immersive experience.



Figure 1: Conference Speakerphone A10 R2

## **FEATURE HIGHLIGHTS**

- 8 microphone beamforming, 3 meters omnidirectional pickup
- Built-in echo and noise cancellation algorithms
- Supports one-way USB-C to USB-C secondary cascading, master- slave reuse
- Single 5W full-range speaker
- Three-color LED indicator bar for status display
- Built-in Bluetooth 5.1 adapter, supports up to 10 meters transmission Supports Kensington physical theft prevention
- USB plug-and-play, compatible with Windows/Mac OS/Android/Linux

Note: The machine is equipped with Dongle without battery



# TECHNICAL SPECIFICATIONS

Specifications				
Model	A10 R2			
Name	Ripa Conference Speakerphone A10 R2			

ITEM	FUNCTIONS	DESCRIPTION		
	Pickup	8-array microphones, 3-meter pickup radius, 360° pickup		
	Frequency Response	10-10kHz		
	SNR	≥64dB		
	Directivity	Omnidirectional		
	Sensitivity	-40.5dB(V/Pa)		
	Full duplex audio	Support		
Speaker	Power	1x 5W Full-Range Speaker		
	Volume	85dB SPL,5w (at 1m distance)		
	Echo Cancellation	Support		
Audio	Noise Suppression	Support		
Processing	Automatic Gain	Support		
	Control Host			
	Host	1x USB-C Port, USB 2.0, Connectable to terminal devices		
Interfaces	Cascade port	1x USB-C Port, USB 2.0, Can be cascaded with another A10 R2		
	Power supply	1x USB-C Power Input Port		
	Lock	1x Kensingto		
Vovs	Power Key / Answer Key / Volume Down Key / Mute Key / Volume Up Key /			
Keys	Hang Up (Bluetooth) Key			
Bluetooth	Bluetooth 5.1			
Cascading	Supports cascading with another A10 R2 for use			
Indicator Light Strip	The body is equipped with a tri-color LED light strip (red, green, blue) for displaying status.			
Battery	not support			
Power Supply Method	Powered by a power adapter			
System	Windows 7/8/10; macOS10.10 or later; Linux ((requires UAC system support); Android			
Compatibility	(universal, may perform differently on each system integration)			
	Storage Temperature : -10°C~+70°C			
	Storage Humidity: 20% $\sim$ 95%			
Operating	Working Temperature : -10°C∼+50°C			
Conditions	Working Humidity: 20% $\sim$ 80%			
	Environment : Indoors			
Accessories	1x 12V/1.5A USB-C Power Adapter			
	1x 5m USB-C to USB-C data cable			
	1x 3m USB-C to USB-C data cable			
	1x Bluetooth USB Dongle			
Dimension	150mm x 155mm x 44mm			

# ORDERING GUIDE

RipaTech product code: RP-A10- R2