





# PROMOSOLV<sup>™</sup> 9000

MOTION FILM CLEANING
USED IN DEDICATED EQUIPMENT
VERY LOW GWP

# **BENEFITS**

PROMOSOLV 9000 is a colorless, low odor fluid dedicated for motion film cleaning applications.

It is developed as a drop-in replacement for trichlorethylene, NPB and other solvents with a high Health, Safety & Environmental impact. While reducing substantially the HSE impact, the cleaning power is at an equivalent level. Besides, it's a substitute for the phased out Novec<sup>TM</sup> 8200 as it has the same proportion of components and same properties.

PROMOSOLV 9000 is compatible with all metals and alloys, including very sensitive ones. It also has good compatibility with most plastics & elastomers, however it is necessary to test before use.

PROMOSOLV 9000 is formulated with safety in mind, which resulted in a product that is non-flammable and has no flash point.

PERFORMANCE	<ul> <li>Thermally and chemically stable in use</li> <li>Excellent compatibility with film substrates</li> <li>Short cleaning, rinsing and drying times</li> </ul>
COST	<ul> <li>Continuous recycling in equipment for a long bath-life</li> <li>Can be returned for recycling and re-use</li> <li>The relative high boiling point reduces risk of solvent drag, so limiting consumption</li> </ul>
HSE	<ul> <li>Very low toxicity</li> <li>Very low Global Warming Potential (GWP)</li> <li>No Ozon depletion potential (ODP)</li> <li>Non-flammable</li> <li>No flashpoint</li> <li>Low environmental impact: GREENWAY product</li> </ul>

# **SPECIFICATIONS**

SPECIFICATIONS	VALUES	METHODS	
Aspect	Colorless, clear	Visual	
Purity (%)	>99,0	BRY-MO-121	

# **CHARACTERISTICS**

CHARACTERISTICS	VALUES		
Boiling point (°C/°F)	76°C/169°F		
Freezing point (°C/°F)	-138°C/-216°F		
Flash point	No		
Density (g/cm³ @25°C)	1.43		
Surface tension (dynes/cm @20°C)	13.6		
Vapor pressure (mm Hg @25°C)	109		
Dynamic viscosity (mPa.s @20°C)	0.61		
Latent heat of vaporization (cal/g@bp)	30		
Specific heat (kJ/Kg.K @25°C)	1,21		

PROMOSOLV 9000

### PROCESS RECOMMENDATION

The best process will depend on factors such as operating conditions, equipment, desired cleaning time and the nature of contaminants. Our team is ready to advise you.

Compatibility report with different materials is available on request.

#### PROCESS EXAMPLE

Vapor phase: Motion film cleaning

PROMOSOLV 9000 PROMOSOLV 9000 DRYING ZONE Conc: 100% 9000 vapor Temp: 76C/169°F Temp: 60°C/140°F Temp: 76°C/169°F Time: 5-60 sec **CLEANING RINSING DRYING** 

# PACKAGING, STORAGE & SHELF LIFE

- Keep products in closed original packaging and store at room temperature.
- Shelf life is minimum 18 months from production date when kept in recommended conditions.
- The packaging is designed for easy connection to specialized motion picture cleaning equipment.

#### **AVAILABLE PACKAGING**



30 Kg DRUM

Please verify the packaging details, including volume and availability, with your sales representative, as they may vary depending on the production facility where the product is manufactured.

## **HEALTH, SAFETY & ENVIRONMENT**

PROMOSOLV 9000 is a GREENWAY product. More info on our Greenway concept via this link.



#### MAIN CONTRIBUTORS WHICH REDUCE IMPACT:

#### **HUMAN HEALTH & SAFETY**

- Non-flammable & no flashpoint: 100% safe for storage and when used in equipment
- Non-toxic, no corrosive impact & no S risk phrases

## **ENVIRONMENT PROTECTION & RESOURCES SAVINGS**

- Low environmental impact: no H labelling regarding environment
- Can be returned for recycling and re-use: ECOPROGRAM
- Reduce consumption of product, consumables, water & energy

PROPERTIES	PROMOSOLV 9000	1,1,1-TCA	PERC
Ozone Depleting Potential (ODP)	0,00	0,1	0,006
Global Warming Potential (GWP)	55	140	n.a.
Atmospheric lifetime (years)	0,77	4,8	n.a.
VOC	yes	yes	yes
Flashpoint	no	no	no

Contains no Reach Substances (on Candidate list, Annex XIV & XVII) / Contains no persistent organic pollutant (EC 850/2004) / Contains no Import/Export Hazardous substances (EU 649/2012).

Used polluted product can be returned to us for recycling if regulations permit. Please contact your local sales contact for more details on our ECOPROGRAM.



PROMOSOLV 9000 PDS2024-04 EN $^{\prime}$ 

Please refer always to the Safety Data Sheet (SDS or MSDS) prior to use. Our SDS can be downloaded at <a href="www.quickfds.com">www.quickfds.com</a>. We will request to provide your email address, so we can automatically send you a new version of the SDS when a future update would occur.

## TECHNICAL SUPPORT & FREE-OF-CHARGE TESTING

Inventec has a worldwide dedicated Technical Support team to help you along the various stages of our cooperation.

Depending on your request, we provide online or onsite support

- to select the right product based on your specific needs.
- to assist you in your product qualification process.
- to guide you with the initial set up of your process at all your worldwide manufacturing facilities.
- to provide fast response on technical issues which could occur at any time during mass production.

Customers are also welcome in our CLEANING CENTERS to see the process in action and to get convinced by our solutions. We cover water- and solvent based processes.

Contact our technical support via <a href="mailto:contact@inventec.dehon.com">contact@inventec.dehon.com</a> or your local sales representative.

# **ABOUT INVENTEC**

Inventec is a global provider of SOLDERING, CLEANING, COATING, COOLING materials for Electronic, Semiconductor and Industrial applications. For over 60 years we have shown leadership in innovation by putting HEALTH IMPACT, SUSTAINABILITY and RELIABILITY at the core of our product development.

With ISO 9001 & 14001 production sites in France, Switzerland, USA, Mexico, Malaysia and China we can guarantee a smooth and cost-effective supply chain.

We supply to many industries but the excellent performance of our products in applications which demand high reliability, leads us to focus especially on the AUTOMOTIVE, AEROSPACE, SEMICONDUCTOR, ENERGY and MEDICAL industry.

www.inventec.dehon.com



SOLDERING
CLEANING
COATING
COOLING

In accordance with the Annex II of Directive 2011/65/UE (RoHS), including its amendments, we certify that this product does not contains quantities above 0.1% of Hg, Pb, Cr VI, PBB, PBDE, DEHP, BBP, DBP, DIBP and above 0.01% of Cd

This data is based on information that the manufacturer believes to be reliable and offered in good faith. In no event will INVENTEC PERFORMANCE CHEMICALS be responsible for special, incidental and consequential damages. The user is responsible to the Administrative Authorities (regulations for the protection of the Environment) for the conformity of his installation.

Inventec Performance Chemicals – 26 rue de Coulons. 94360 Bry-sur-Marne, France Limited company with capital of 600 000€ - 964 500 706 RCS Créteil

