



PI8000



---

Quick Reference

---

Keys - Overview



Wrist strap connector

Device ON/OFF	
Medium push (2s)	Power ON / OFF
Very Long push (8s)	Reboot device
During measurement	
Short push	Arming the probe – start / resume measurement
Short push	Disarming the probe – stop measurement



Flat Tip Sensor



Bluetooth dongle

Battery

USB-C

Hammers

Low frequency hammer




High frequency hammer (3 types)  
7.5mm, 10mm and 15mm



Ball Diameter, mm	Approximate Contact Time, $\mu$ s	Maximum Useable Frequency, kHz	Minimum Measurable * Depth, mm
5	22	47	43
6	26	39	52
7	30	33	60
8	34	29	69
9	39	26	77
10	43	23	86
12	52	19	103
15	65	16	129
20	86	12	172

\*This is the minimum thickness of a structural element than can be measured  
\*It also refers to the minimum depth of a flaw that can be detected. All flaws above this depth will not be visible



**i** Select the smaller hammer for thinner elements, and the bigger hammer for wider elements

# LED - Behaviour



LED behaviour		
Battery Status (when turning on the device)	Green: single quick blink: >20%	
	Red: single quick blink: <20%	
Turn on, awaiting Bluetooth connection	Green pulsing	
Connected, awaiting arming (disarmed) <ul style="list-style-type: none"><li>Paused</li><li>Stopped</li></ul>	Blue pulsing	
Armed <ul style="list-style-type: none"><li>Resumed</li></ul>	Blue Solid	
While measuring (rod/wheels)	Blue Solid	
Errors		
Error	Red pulsing	
Device in boot loader mode	Red-Green alternate pulsing	
Battery Charging		
While Charging	Green pulsing 0.5Hz	
Charged done	Green solid	
Error <ul style="list-style-type: none"><li>batteries not charging / not inserted</li><li>Overvoltage / overheated</li></ul>	Red solid	

## One Sensor – Two Applications

### Pile Integrity Test

Deep Foundations:

- Cast in place piles.
- Driven piles.

Detection:

- Piles with free end.
- Piles with toe in bedrock.
- Short piles.
- Necking.
- Bulging.
- Cracks and voids.



### Impact Echo Test

Concrete elements:

- Slab on grade.
- Foundation slab.
- Roof, floors.
- Beams and columns.
- Concrete pavement.
- Walls.
- Tunnels.

Detection:


- Plate thickness and backwall.
- Cracks and voids.
- Delamination.
- Honeycombs.
- Debonding areas.
- PT duct voids.



## Contact Solution – Coupling material


### Pile Integrity Test

- Clean the surface from dirt and debris.
- Grind the surface to make it smoother.
- Place a small portion of putty (coupling material) in the sensor tip.
- Change the portion of putty once it gets dirty.
- Perform minimum 5-10 impacts per spot.




### Impact Echo Test

- Clean the surface from dirt and debris.
- Grind the surface to make it smoother.
- DRY CONTACT SOLUTION: Place a silicon sticker (coupling material) in the sensor tip and use it as many times as wanted.
- Once it is broken, replace it with a new sticker and clean the sensor tip with the cleaning pen.
- If coupling is not achieved, use putty.
- Perform minimum 5-10 impacts per spot.




## Technical Principle

### Pile Integrity Test



### Impact Echo Test



## First calibration of speed

### Pile Integrity Test

- Select Pile Integrity Mode **(0)**.
- Input the expected length of the pile **(1)**.
- Perform 5-10 impacts at the top of the pile.
- Press the calibration button **(2)**.
- Revise that the length shown on the app **(3)** matches with the expected one.

\* If the length of the element is not known, estimate a wave velocity of 4.000m/s.



### Impact Echo Test

- Select Impact Echo Spot / Grid mode **(0)**.
- Input the expected thickness of the concrete element **(1)**.
- Perform 5-10 impacts in the surface far away from the sides (lateral faces, construction joints, etc).
- Press the calibration button **(2)**.
- Revise that the thickness shown in the frequency peak **(3)** matches with the expected one.

\* If the thickness of the element is not known, estimate a wave velocity of 4.000m/s







## A few examples

### Pile Integrity Test


Pile with free end




Toe in bedrock



Short pile



Necking – reduction in diameter



Bulging – increase in diameter




\*These examples are shown as a reference only and are valid theoretically. However, the signal from a real case scenario can differ and it is the responsibility of the inspector to correctly identify and interpret it.


## A few examples

### Impact Echo Test


#### Cracks & Delamination




#### Honeycomb



#### Voids in post tensioning duct



#### Plates in contact with soil




\*These examples are shown as a reference only and are valid theoretically. The signal from a real case scenario can differ and it is the responsibility of the inspector to correctly identify and interpret it.

SWISS  MADE

For more information on the product use of the product,  
please refer to the Product Name PI8000 documentation

It is available for download on



<https://www.screeningeagle.com/en/products/pundit-pi8000>

**For safety and liability information, please download at <https://www.screeningeagle.com/en/about-us/gtc-and-certificates>**  
Subject to change. Copyright © 2023 by Proceq SA, Schwerzenbach. All rights reserved.

**ASIA-PACIFIC**

Proceq Asia Pte Ltd.  
1 Fusionopolis Way  
Connexis South Tower #20-02  
Singapore 138632  
T +65 6382 3966

**CHINA**

Proceq Trading Shanghai Co., Limited  
Room 701, 7th Floor, Golden Block  
407-1 Yishan Road, Xuhui District  
200032 Shanghai | China  
T +86 21 6317 7479

**EUROPE**

Proceq AG  
Ringstrasse 2  
8603 Schwerzenbach  
Zurich | Switzerland  
T +41 43 355 38 00

**UK**

Screening Eagle UK Limited  
Bedford i-lab, Stannard Way  
Priory Business Park  
MK44 3RZ Bedford  
London | United Kingdom  
T +44 12 3483 4645

**MIDDLE EAST AND AFRICA**

Proceq Middle East and Africa  
Sharjah Airport International  
Free Zone | P.O.Box: 8365  
United Arab Emirates  
T +971 6 5578505

**USA, CANADA & CENTRAL AMERICA**

Screening Eagle USA Inc.  
14205 N Mopac Expressway Suite 533  
Austin, TX 78728 | United States

Screening Eagle USA Inc.  
117 Corporation Drive  
Aliquippa, PA 15001 | United States  
T +1 724 512 0330

**SOUTH AMERICA**

Proceq SAO Equipamentos  
de Medição Ltda.  
Rua Paes Leme 136  
Pinheiros, Sao Paulo  
SP 05424-010 | Brasil  
T +55 11 3083 3889

