



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

1. Identification

Product identifier

Product Identity

GEORGIA STEEL RINSE AGENT

Other means of identification

(Product code: RP355-G, -GC, -F, -D)

Relevant identified uses of the substance or mixture and uses advised against

Personal protective equipment and safety eyewear
rinse agent/spot preventer

Details of the supplier of the safety data sheet

Company Name

Georgia Steel & Chemical Co., Inc.
9515 Gerwig Lane, Suite 111
Columbia, MD 21046

Emergency

Customer Service: Georgia Steel & Chemical Co., Inc. +1(301) 317-5502

2. Hazard(s) identification

Classification of the substance or mixture

The substance is not classified according to the WHMIS regulations.

Label elements

The substance is not classified according to the WHMIS regulations.

[Prevention]

No GHS prevention statements

[Response]

No GHS response statements

[Storage]

No GHS storage statements

[Disposal]

No GHS disposal statements



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

3. Composition/information on ingredients

This product contains the following substances that present a hazard within the meaning of the Hazardous Products Regulations.

Ingredient/Chemical Designations	Weight %	GHS Classification	Notes
Polyethylene-polypropylene glycol CAS Number: 0009003-11-6 Synonyms: PEG/PPG-17/6 Copolymer	3 - 7	Not Classified	----
Dipropylene glycol methyl ether CAS Number: 0034590-94-8 Synonyms: (2-methoxymethylethoxy)propanol	3 - 7	Not Classified	----

The actual concentration or concentration range is withheld as a trade secret.

*PBT/vPvB - PBT-substance or vPvB-substance.

The full texts of the phrases are shown in Section 16.

Section 4. First aid measures

Description of first aid measures

General	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air, keep patient warm and at rest. If breathing is irregular or stopped, give artificial respiration. If unconscious, place in the recovery position and obtain immediate medical attention. Give nothing by mouth.
Eyes	Irrigate copiously with clean water for at least 15 minutes, holding the eyelids apart and seek medical attention.
Skin	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a recognized skin cleanser.
Ingestion	If swallowed obtain immediate medical attention. Keep at rest. Do NOT induce vomiting.
Most important symptoms and effects, both acute and delayed	
Overview	No specific symptom data available. Treat symptomatically. See section 2 for further details.
Eyes	Causes serious eye irritation.

Section 5. Fire-fighting measures

Extinguishing media

Suitable Extinguishing Media: Not applicable. Product is not a fire hazard.

Unsuitable Extinguishing Media: High pressure water jet.

Special hazards arising from the substance or mixture

Hazardous decomposition: No hazardous decomposition data available.



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

Advice for fire-fighters

As with all fires, wear positive pressure, self-contained breathing apparatus, (SCBA) with a full face piece and protective clothing. Persons without respiratory protection should leave area. Wear SCBA during clean-up immediately after fire. No smoking.

Fire fighters should wear appropriate protective equipment, including self-contained breathing apparatus and impervious clothing.

ERG Guide No. ---

Section 6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Remove sources of ignition, do not turn lights or unprotected electrical equipment on or off. In case of a major spill or spillage in a confined space evacuate the area and check that solvent vapour levels are below the Lower Explosive Limit before re-entering.

Environmental precautions

Do not allow spills to enter drains or waterways.

Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

Methods and material for containment and cleaning up

Small spills may be wiped up and rinsed with water. For larger spills, contain spill with inert material (sand, clay). Transfer material to labeled containers for recovery or proper disposal. After removal, flush area with water. Follow good industrial hygiene practices.

Section 7. Handling and storage

Precautions for safe handling

Handle containers carefully to prevent damage and spillage.

Read label before use. Avoid contact with skin or eyes. Wash hands, face and any skin contact thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves, eye protection, face protection. Use only according to label directions. If unsure about safe use, contact your supervisor.

See section 2 for further details. - [Prevention]

Conditions for safe storage, including any incompatibilities

Keep out of reach of children. Do not contaminate water, food or feed by storage and disposal. Store in tightly closed, original container in a cool (10° - 30°C), dry area.

Incompatible materials: No data available.

See section 2 for further details. - [Storage]

Specific end use(s)

No data available.

Section 8. Exposure controls / personal protection



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
 (Product code: RP355-G, -GC, -F, -D)

Revision
 Date: 05/18/2022

Control parameters

Exposure

CAS No.	Ingredient	Source	Value
0009003-11-6	Polyethylene-polypropylene glycol	ACGIH	No Established Limit
		Alberta	No Established Limit
		British Columbia	No Established Limit
		Manitoba	No Established Limit
		New Brunswick	No Established Limit
		Newfoundland and Labrador	No Established Limit
		Nova Scotia	No Established Limit
		Northwest Territories	No Established Limit
		Nunavut	No Established Limit
		Ontario	No Established Limit
		Prince Edward Island	No Established Limit
		Quebec	No Established Limit
		Saskatchewan	No Established Limit
		Yukon	No Established Limit
0034590-94-8	Dipropylene glycol methyl ether	ACGIH	TWA: 100 ppm STEL: 150 ppm
		Alberta	100 ppm TWA; 606 mg/m ³ TWA 150 ppm STEL; 909 mg/m ³ STEL
		British Columbia	100 ppm TWA 150 ppm STEL
		Manitoba	100 ppm TWA 150 ppm STEL
		New Brunswick	100 ppm TWA; 606 mg/m ³ TWA 150 ppm STEL; 909 mg/m ³ STEL
		Newfoundland and Labrador	100 ppm TWA 150 ppm STEL
		Nova Scotia	100 ppm TWA 150 ppm STEL
		Northwest Territories	100 ppm TWA 150 ppm STEL
		Nunavut	100 ppm TWA 150 ppm STEL
		Ontario	100 ppm TWA 150 ppm STEL
		Prince Edward Island	100 ppm TWA 150 ppm STEL
		Quebec	100 ppm TWAEV; 606 mg/m ³ TWAEV 150 ppm STEV; 909 mg/m ³ STEV
		Saskatchewan	100 ppm TWA 150 ppm STEL
		Yukon	No Established Limit



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

Exposure controls

Respiratory	If workers are exposed to concentrations above the exposure limit they must use the appropriate, certified respirators.
Eyes	Protective safety glasses recommended
Skin	Overalls which cover the body, arms and legs should be worn. Skin should not be exposed. All parts of the body should be washed after contact. Protective gloves recommended.
Engineering Controls	Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and any vapour below occupational exposure limits suitable respiratory protection must be worn.
Other Work Practices	Use good personal hygiene practices. Wash hands before eating, drinking, smoking or using toilet. Promptly remove soiled clothing and wash thoroughly before reuse.

See section 2 for further details.

Section 9. Physical and chemical properties

Appearance	Red Liquid
Odour	None
Odour threshold	Not determined
pH	(Neat) 4.0 - 6.0 (RTU) – 5.0 - 6.0
Melting point / freezing point	Freezing Point : 32°F
Initial boiling point and boiling range	212°F
Flash Point	Not Available
Evapouration rate (Ether = 1)	Similar to water
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	Lower Explosive Limit: Not Available Upper Explosive Limit: Not Available
Vapour pressure (Pa)	Not Available
Vapour Density	Not Available
Relative Density	Not Available
Solubility in Water	Complete
Partition coefficient n-octanol/water (Log Kow)	Not Available
Auto-ignition temperature	Not Available
Decomposition temperature	Not Available
Viscosity (cSt)	Water thin
VOC Content	< 1 (Excluding exempt material)
Relative Density	1.020 %
Other information	No other relevant information.

Section 10. Stability and reactivity



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
 (Product code: RP355-G, -GC, -F, -D)

Revision
 Date: 05/18/2022

Reactivity

Hazardous Polymerization will not occur.

Chemical stability

Stable under normal circumstances.

Possibility of hazardous reactions

No data available.

Conditions to avoid

Temperatures above 50°C or below 10°C.

Incompatible materials

No data available.

Hazardous decomposition products

No hazardous decomposition data available.

Section 11. Toxicological information

Acute toxicity

Note: When no route specific LD50 data is available for an acute toxin, the converted acute toxicity point estimate was used in the calculation of the product's ATE (Acute Toxicity Estimate).

Ingredient	Oral LD50, mg/kg	Skin LD50, mg/kg	Inhalation vapour LC50, mg/L/4hr	Inhalation Dust/Mist LC50, mg/L/4hr	Inhalation Gas LC50, ppm
Polyethylene-polypropylene glycol - (9003-11-6)	11,200.00, Rat - Category: NA	5,600.00, Rabbit - Category: NA	No data available	No data available	No data available
Dipropylene glycol methyl ether - (34590-94-8)	> 5,000.00, Rat - Category: NA	> 20.00, Rat - Category: NA	No data available	No data available	No data available

Carcinogen Data

CAS No.	Ingredient	Source	Value
0009003-11-6	Polyethylene-polypropylene glycol	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit
0034590-94-8	Dipropylene glycol methyl ether	IARC	Group 1: No; Group 2a: No; Group 2b: No; Group 3: No; Group 4: No;
		ACGIH	No Established Limit

Classification	Category	Hazard Description
Acute toxicity (oral)	---	Not Applicable
Acute toxicity (dermal)	---	Not Applicable
Acute toxicity (inhalation)	---	Not Applicable
Skin corrosion/irritation	---	Not Applicable
Serious eye damage/irritation	2A	Causes serious eye irritation.
Respiratory sensitization	---	Not Applicable
Skin sensitization	---	Not Applicable



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

Germ cell mutagenicity	---	Not Applicable
Carcinogenicity	---	Not Applicable
Reproductive toxicity	---	Not Applicable
STOT-single exposure	---	Not Applicable
STOT-repeated exposure	---	Not Applicable
Aspiration hazard	---	Not Applicable

Possible routes of entry: No data available.

Symptoms and effects, both acute and delayed:

No specific symptom data available.

Treat symptomatically.

Eyes Causes serious eye irritation.

Section 12. Ecological information

Toxicity

No additional information provided for this product. See Section 3 for chemical specific data.

Aquatic Ecotoxicity

Ingredient	96 hr LC50 fish, mg/L	48 hr EC50 crustacea, mg/L	ErC50 algae, mg/L
Polyethylene-polypropylene glycol - (9003-11-6)	Not Available	Not Available	Not Available
Dipropylene glycol methyl ether - (34590-94-8)	10,000.00, Pimephales promelas	1,919.00, Daphnia magna	969.00 (72 hr), Algae

Persistence and degradability

There is no data available on the preparation itself.

Bioaccumulative potential

Not Available

Mobility in soil

No data available.

Results of PBT and vPvB assessment

This product contains no PBT/vPvB chemicals.

Other adverse effects

No data available.

Section 13. Disposal considerations



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

Waste treatment methods

Observe all federal, provincial and local regulations when disposing of this substance.

Section 14. Transport information

Classification Method: Classified as per Part 2, Sections 2.1 - 2.8 of the Transportation of Dangerous Goods Regulations.

	TDG (Domestic Surface Transportation)	IMO / IMDG (Ocean Transportation)	ICAO/IATA
UN number	Not Regulated	Not Regulated	Not Regulated
UN proper shipping name	Not Regulated	Not Regulated	Not Regulated
Transport hazard class(es)	TDG Hazard Class: Not Applicable Sub Class: Not Applicable	IMDG: Not Applicable Sub Class: Not Applicable	Air Class: Not Applicable Sub Class: Not Applicable
Packing group	Not Applicable	Not Applicable	Not Applicable
Environmental hazards			
IMDG	Marine Pollutant: No;		
Special precautions for user	Not Applicable		

Section 15. Regulatory information

This product has been classified in accordance with the hazard criteria Hazardous Products Regulations (SOR/2015-17) and the SDS contains all of the information required by those regulations.

Canadian Domestic Substance List (DSL):

Dipropylene glycol methyl ether
Polyethylene-polypropylene glycol
Water

Canadian Non-Domestic Substance List (NDSL):

To the best of our knowledge, there are no chemicals at levels which require reporting under this statute.

Section 16. Other information



Safety Data Sheet
GEORGIA STEEL RINSE AGENT
(Product code: RP355-G, -GC, -F, -D)

Revision
Date: 05/18/2022

Revision Date 05/18/2022

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations, and orders.

The full text of the phrases appearing in section 3 is:

Not Applicable

Disclaimer: The information presented herein is supplied as a guide to those who handle or use this product. Safe work practices must be employed when working with any materials. It is important that the end user makes a determination regarding the adequacy of the safety procedures employed during the use of this product.

End of Document