

ALPINE Z-1 MID-HORN

Material: 24mm Baltic Birch Plywood

Covering: Polyurea


Horn Loaded AMT Tweeter covering 10k Hz - 20k Hz



- 8" Full Range Driver (<u>No Crossover</u>) covering 125Hz – 10k Hz

Front horn

Full Range back-loaded horn



1'-5 5/16"
[439mm]

3'-10 5/8"
[1184mm]

1'-9 3/4"
[553mm]

Mouth View

Perspective View

Main Driver: Tang Band W8-2145 8" Paper Cone Full Range Driver 8 Ohm The W8-2145 full range driver uses an underhung motor to deliver linear response with minimal 2nd and 3rd order THD. The bamboo fiber reinforced paper cone uses a whizzer cone for improved high frequency and off axis response.

## Key Features:

Aluminum phase plug also acts as a shorting ring for lower distortion
Underhung voice coil improves control for lower distortion
Whizzer cone design increases high frequency response
Unique surround and large spider keeps cone linear well beyond the rated xmax
High Frequency driver: AMT-HR4

## Key Features:

Low mass Kapton diaphragm with aluminum conductor delivers high efficiency and accuracy. Utilizing Air Motion Transformer (AMT) technology delivering exceptional sound quality with less effort, resulting in a broad, immersive soundstage.

Folded Back and Front Loaded Horn Bandwidth: 125 Hz-20,000Hz

Efficiency: 101.5dB @ 1 Watt (Calculated)

Power Handling: 40w Rms

Material: 24mm" Baltic Birch Plywood

Covering: Polyurea WWW.Vanzylaudio.com

SCALE: 1" = 1'