



***MHC KENWORTH - ROCKY MOUNT***

*7418 NC Highway - 4*

*Battleboro, NC 27809*

*(252)212-5600*

<https://www.mhc.com/locations/mhc-kenworth-rocky-mount>



1. *TOTAL SPECIFICATIONS (Driver Side)*

- a. *Total Length.....404" (33.7')*
- b. *Wheelbase.....350" (29')*
- c. *Gross Vehicle Weight Rating.....57,500 lbs.*
- d. *Tare Weight (Estimated & Max Weight Preferred)....20,000 lbs. [Est.] 22,000 lbs. [Max.]*
- e. *13,200 lbs Front Steer Axle Center Hub Location (Front to Rear).....30" (2.5')*
- f. *Kenworth W900L Stainless Steel Tool Box Step Location (Front to Rear).....99" to 129"*
- g. *Thermo King Diesel APU TriPac Evolution Location (Front to Rear).....130" to 157"*
- h. *150-Gallon Fuel Tank (Front to Rear).....159" to 227"*
- i. *86" Studio Sleeper Location (Front to Rear).....128" to 214"*
- j. *Kenworth W900L Side Fairing (66" x 21"):.....,215" to 236"*
- k. *Brunner Fabrication Enclosed Three Door Aluminum Rack w/Side Door Location (Front to rear + Height bottom to top) .....215" to 227" [43" to 115" Top Height)*
- l. *Holland Aluminum FWAL 5th Wheel Stationary (Front to Rear).....332" to 368"*
- m. *Aluminum Step Box w/Step Bracket By Brunner Fabrication (22"H x 24"H x 22"D):.....237" to 261"*
- n. *Kenworth AG400L 40,000 lbs. Tandem Drive Axle Hub Location (Front to Rear).....323" to 377"*



**1. TOTAL SPECIFICATIONS (Passenger Side)**

- a. Total Length.....404" (33.7')
- b. Wheelbase.....350" (29')
- c. Gross Vehicle Weight Rating.....57,500 lbs.
- d. Tare Weight (Estimated & Max Weight Preferred)....20,000 lbs. [Est.] 22,000 lbs. [Max.]
- e. 13,200 lbs Front Steer Axle Center Hub Location (Front to Rear).....30" (2.5')
- f. Kenworth W900L Stainless Steel Tool Box Step Location (Front to Rear).....99" to 129"
- g. DEF Tank Location (Front to Rear).....135" to 153"
- h. 150-Gallon Fuel Tank (Front to Rear).....159" to 227"
- i. 86" Studio Sleeper Location (Front to Rear).....128" to 214"
- j. Kenworth W900L Side Fairing (66" x 21"):.....,215" to 236"
- k. Brunner Fabrication Enclosed Three Door Aluminum Rack w/Side Door Location (Front to rear + Height bottom to top) .....215" to 227" [43" to 115" Top Height)
- l. Holland Aluminum FWAL 5th Wheel Stationary (Front to Rear).....332" to 368"
- m. Aluminum Step Box w/Step Bracket By Brunner Fabrication (22"H x 24"H x 22"D):.....237" to 261"

- n. Kenworth AG400L 40,000 lbs. Tandem Drive Axle Hub Location (Front to Rear).....323” to 377”



1. TOTAL SPECIFICATIONS (Exterior Height)

- a. Total Height (10” Chrome Monster Exhaust Stacks) .....156” (13’)
- b. Holland Aluminum Fifth Wheel Height.....52” (4.3’)
- c. Double Frame Height.....47” (3.9’)
- d. Kenworth AG400L 40,000 lbs. Air Suspension Lowest 5th Wheel and Highest Height....41” [Lowest]. 47” [Highest]
- e. Kenworth MotoMirrow Plus Dual Heated & Motorized (Bottom to top).....84” to 113”(9.4’)
- f. Kenworth W900L Studio 86” Mid-Rise Sleeper Height (Bottom to Top).....43” to 120” (10’)
- g. Giraffe G& Truck Protection System Overhead Height Sensor Set at 13.5’ Height Mounted on Headache Rack Height.....118” (9.8’)
- h. Road Pro 54” Oil Coil Center Loaded CB Antenna Mounted on Back of Sleeper Height.....144” (12’)
- i. Universal Heavy Duty Wired Backup Camera System w/4 Rooftop Camera 360 View Height .....138” (11.5’)

*j. 8 LED Mini Square Double Face Turn Signal Mounted on Mirror Height.....110”  
(9.1’)*