



TLG PETERBILT - DAY CAB TRACTOR

1185 Sadler Road

Dunn, NC 28334

(910)900-8846

<https://tlgtrucks.com/>



2024 PETERBILT 567 TRIAXLE DAY CAB TRACTOR

1. TOTAL SPECIFICATIONS (Driver Side)

- a. Total Length.....374” (31.2)
- b. Wheelbase.....297” (24.75’)
- c. Gross Vehicle Weight Rating.....56,500 lbs.
- d. Tare Weight (Estimated & Max Weight Preferred)....20,500 lbs. [Est.] 22,000 lbs. [Max.]
- e. 23,000 lbs Front Steer Axle Center Hub Location (Front to Rear).....31” (2.5’)
- f. Peterbilt 567 Stainless Steel Tool Box Step Location (Front to Rear).....91” to 121”
- g. Thermo King Diesel APU TriPac Evolution Location (Front to Rear).....125 to 152”
- h. 150-Gallon Fuel Tank (Front to Rear).....155” to 223”
- i. Brunner Fabrication Enclosed Three Door Aluminum Rack w/Side Door Location (Front to rear + Height bottom to top)123” to 135” [43” to 115” Top Height)
- j. Hendrickson 20,000 lbs. Steerable Lift Axle Hub Location (Front to Rear).....216” (18’)
- k. Holland FW35 72” Air Sliding Fifth Wheel Location (Front to Rear).....240” to 335”
- l. Peterbilt 46,000 lbs. Tandem Drive Axle Hub Location (Front to Rear).....270” & 324”



1. TOTAL SPECIFICATIONS (Passenger Side)

- a. Total Length.....374" (31.2)
- b. Wheelbase.....297" (24.75')
- c. Gross Vehicle Weight Rating..... 56,500 lbs.
- d. Tare Weight (Estimated & Max Weight Preferred)....20,500 lbs. [Est.] 22,000 lbs. [Max.]
- e. 23,000 lbs Front Steer Axle Center Hub Location (Front to Rear).....31" (2.5')
- f. Peterbilt 567 Stainless Steel Tool Box Step Location (Front to Rear).....91" to 121"
- g. DEF Tank Location (Front to Rear).....123" to 141"
- h. 150-Gallon Fuel Tank (Front to Rear).....155" to 223"
- i. Brunner Fabrication Enclosed Three Door Aluminum Rack w/Side Door Location (Front to rear + Height bottom to top)123" to 135" [43" to 115" Top Height)
- j. Hendrickson 20,000 lbs. Steerable Lift Axle Hub Location (Front to Rear).....216" (18')
- k. Holland FW35 72" Air Sliding Fifth Wheel Location (Front to Rear).....240" to 335"
- l. Peterbilt 46,000 lbs. Tandem Drive Axle Hub Location (Front to Rear).....270" & 324"



1. TOTAL SPECIFICATIONS (Exterior Height)

- a. Total Height (10" Chrome Monster Exhaust Stacks)156" (13')
- b. Fontaine H7 Fifth Wheel Height.....52" (4.3')
- c. Double Frame Height.....42" (3.5')
- d. Peterbilt Air Trac 46,000 lbs. Air Suspension Lowest 5th Wheel and Highest Height....44" [Lowest]. 52" [Highest]
- e. Peterbilt MotoMirrow Plus Dual Heated & Motorized (Bottom to top).....84" to 113"(9.4')
- f. Whelen LED Light Bar (Miller Industries Offering) (Bottom to Top).....120" to 124"
- g. Giraffe G\$ Truck Protection System Overhead Height Sensor Set at 13' Height Mounted on Headache Rack Height.....118" (9.8')
- h. Universal Heavy Duty Wired Backup Camera System w/4 Rooftop Camera 360 View HeightOptional
- i. 8 LED Mini Square Double Face Turn Signal Mounted on Mirror Height.....110" (9.1')