



TLG PETERBILT

1185 Sadler Road

Dunn, NC 28334

(910)900-8846

<https://tlgtrucks.com/>



1. TOTAL SPECIFICATIONS (Driver Side)

- a. Total Length.....440" (36.6')***
- b. Wheelbase.....382" (31.8')***
- c. Gross Vehicle Weight Rating.....62,500 lbs.***
- d. Tare Weight (Estimated & Max Weight Preferred)....25,500 lbs. [Est.] 27,000 lbs. [Max.]***
- e. 20,000 lbs Front Steer Axle Center Hub Location (Front to Rear).....31" (2.5')***
- f. Peterbilt 389 Stainless Steel Tool Box Step Location (Front to Rear).....99" to 129"***

- g. Thermo King Diesel APU TriPac Evolution Location (Front to Rear).....130" to 157"
- h. 150-Gallon Fuel Tank (Front to Rear).....159" to 227"
- i. 63" Flattop Sleeper Location (Front to Rear).....130" to 193"
- j. Brunner Fabrication Enclosed Three Door Aluminum Rack w/Side Door Location (Front to rear + Height bottom to top)229" to 241" [43" to 115" Top Height)
- k. Hendrickson 20,000 lbs. Steerable Lift Axle Hub Location (Front to Rear).....301" (25')
- l. Holland FW35 60" Air Sliding Fifth Wheel Location (Front to Rear).....295" to 378"
- m. Peterbilt 46,000 lbs. Tandem Drive Axle Hub Location (Front to Rear).....355" & 409"



2. TOTAL SPECIFICATIONS (Passenger Side)

- a. Total Length.....440" (36.6')
- b. Wheelbase.....382" (31.8')
- c. Gross Vehicle Weight Rating.....62,500 lbs.
- d. Tare Weight (Estimated & Max Weight Preferred)....25,500 lbs. [Est.] 27,000 lbs. [Max.]
- e. 20,000 lbs Front Steer Axle Center Hub Location (Front to Rear).....31" (2.5')
- f. Peterbilt 389 Stainless Steel Tool Box Step Location (Front to Rear).....99" to 129"
- g. DEF Tank Location (Front to Rear).....135" to 153"

- h. 150-Gallon Fuel Tank (Front to Rear).....159" to 227"
- i. 63" Flattop Sleeper Location (Front to Rear).....130" to 193"
- j. Brunner Fabrication Enclosed Three Door Aluminum Rack w/Side Door Location (Front to rear + Height bottom to top)229" to 241" [43" to 115" Top Height)
- k. Hendrickson 20,000 lbs. Steerable Lift Axle Hub Location (Front to Rear).....301" (25')
- l. Holland FW35 60" Air Sliding Fifth Wheel Location (Front to Rear).....295" to 378"
- m. Peterbilt 46,000 lbs. Tandem Drive Axle Hub Location (Front to Rear).....355" & 409"



3. TOTAL SPECIFICATIONS (Exterior Height)

- a. Total Height (10" Chrome Monster Exhaust Stacks)144" (12')
- b. Fontaine H7 Fifth Wheel Height.....52" (4.3')
- c. Double Frame Height.....42" (3.5')
- d. Peterbilt Air Trac 46,000 lbs. Air Suspension Lowest 5th Wheel and Highest Height....44" [Lowest]. 52" [Highest]
- e. Peterbilt MotoMirrow Plus Dual Heated & Motorized (Bottom to top).....84" to 113"(9.4')
- f. Whelen LED Light Bar (Miller Industries Offering) (Bottom to Top).....120" to 124"
- g. Peterbilt 72" Flattop Sleeper Height (Bottom to Top).....43" to 133" (11')

- h. Giraffe G\$ Truck Protection System Overhead Height Sensor Set at 13' Height Mounted on Headache Rack Height.....118" (9.8')*
- i. Road Pro 54" Oil Coil Center Loaded CB Antenna Mounted on Back of Sleeper Height.....144" (12')*
- j. Universal Heavy Duty Wired Backup Camera System w/4 Rooftop Camera 360 View Height138" (11.5')*
- k. 8 LED Mini Square Double Face Turn Signal Mounted on Mirror Height.....110" (9.1')*