

Leica Flexacam i5 and c5 Technical Specifications

Characteristics	Values
Weight (camera only)	Flexaxam i5 (Stereo): 0.55 kg Flexaxam i5 (Compound): 0.75 kg Flexacam c5: 0.4 kg
Live image on an HDMI monitor	up to 60 fps (3,840 x 2,160 pixels)
Full-screen image capture	at 12 MP
Sensor diagonal	7.81 mm (type 1/2.3" CMOS)
Pixel size	1.55 µm x 1.55 µm
Input	5 V DC / 3 A
Power consumption	15 W
Supported software	Enersight (OSD, Mobile, Desktop)
Color filter	IR-cut coating 650 nm, not replaceable
File formats	JPG, TIF, BMP, MJPGE; for overlays also PNG
Compatibility	USB 3.0, standard USB type C
High-definition connector	HDMI 2.0a, HDMI plug type A
USB connectors	Flexacam i5 (Stereo): 4x USB 2 connectors, type A Flexacam i5 (Compound): 2x USB 2 connectors, type A Flexacam c5: 4x USB 2 connectors, type A
ON / OFF button	1x (on rear side of the camera)
Multicolor status LED	1x (on rear side of the camera)
Operating temperature	10 °C to 40 °C (50 °F to 104 °F)