## North Beach Infrastructure



Council Presentation October 29, 2019



### Overview

- North Beach Drainage issue is an Elevation issue
- Drainage problems can be solved by elevating roads and private property
- Tidal Flooding vs. Storm Water Flooding

Cost of Initial Solutions	
Navigable Ditch	\$41 Million
Raise Streets	\$35 Million




## Tidal Flooding




10/20 = 2.59' and 10/28 = 1.3 ft

10/20 = 2.59' and 10/28 = 1.3 ft





## Observed Tidal Flooding Oct 18, 2019






### Elevations 2.5ft and Below






### Elevations 2.5ft and Below






### **Elevation Profiles**





### Sandbar Ave Elevation






## Sandbar Ave Elevation





### Beach Ave Elevation






### Beach Ave Elevation





## Gulfspray Ave Elevation






## Gulfspray Ave Elevation





### Surfside Park Elevation






### Surfside Park Elevation





## Bridgeport Ave Elevation






## Bridgeport Ave Elevation






### Breakwater Ave Elevation





### Street Improvements Needed

- The preliminary estimate to raise the is approximately \$35 M.
- Listed below are our assumptions:
  - Approximate length of street to be raised is 25,000 lf.
  - Used Laguna Shores street typical x-section (one 12' lane in each direction and a 4' shoulder in each direction with no curb and gutter (C&G). Total Paved width is 32')
  - Unit cost per lf of street is around \$ 1000.00.
  - Added 40% contingency for engineering, survey, design etc.




#### SPECIFICATIONS:

- 2" HOT MIX ASPHALTIC COURSE, HOT LAID ASPHALTIC CONCRETE (TYPE D)
   14" FLEXIBLE BASE (TYPE A, GR 1-2) PLACED IN MAX. 8" LIFTS AND COMPACTED
  - GEOGRID TX-5
- SELECT FILL EMBANKMENT. FILL SHALL BE PLACED IN NO GREATER THAN 8" LIFTS A
  COMPACTED TO A WIN. OF 95% STANDARD PROCTOR DENSITY AT OPTIMUM MOISTURE
  CONTROL VARIES IN DEPTH.




## North Beach Utility Projects 2007 - 2019





# Decrease in Sanitary Sewer Overflows in North Beach





### Stormwater Infrastructure

- Storm water trunk lines size 24 in. to 54 in.
- 110 total storm water inlets
  - 5 full of sand or debris (Still drained)
  - 6 restricted flow
- 59 manholes
- Inspected and cleaned inlets 4 separate occasions in past 24 months




### **Fund Sources**

- General Obligation Bonds
- Type B Funding
- Revenue Bonds
- TIRZ
- Pay-As-You Go



## Total Buildings = 200; Elevated = 107





## Flood Insurance Rate Map



## North Beach Drainage Analysis



Council Presentation October 29, 2019




### Introduction

- Urban Engineering was given a Small A/E Contract to study options to solve the drainage issues on North Beach
- The study started in July and a Final Draft was provided to staff early last week
- The report provides
  - Review of the existing conditions
  - Three proposed options
  - Cost estimates of the options
  - Conclusions and Recommendations



### Study Area

- It includes approximately 195 acres between the beach and HWY 181
- It did not include HWY 181
  - HWY 181 design is complete
  - Construction of drainage improvements are nearly complete






### **Existing Conditions**

North Beach struggles with drainage for the following reasons

- Low Elevation
  - Areas from 0' to 6' above sea level
  - Streets from 2' to 5' above sea level
  - Some property is lower than the adjacent street
- Rising Sea Level of 5.4 mm/yr (.21 in/yr) = 10.5" over the next 50 years
- Undersized storm system that requires regular maintenance




### Relative Sea Level Rise



<sup>\*</sup> HIGHEST WATER NOT AFFECTED BY A TROPICAL STORM OR HURRICANE



### Tidal Inundation (North End)



Dark Blue = 3.25' and below Light Blue = 4.11' and below



### Tidal Inundation (South End)



Dark Blue = 3.25' and below

Light Blue = 4.11' and below



### Tidal Inundation (Continued)















### **Existing Drainage**





### Existing Drainage (Continued)

- Inlets accumulate sand and need regular maintenance
- System is undersized per 2018 HDR Report
- Long submerged lines with almost no slope







### Two Part Solution

### 1: Provide a Better Way for Storm Water to Get Out

- More Capacity (New System)
- Shorter Lines with More Slope
- Don't Submerge Storm Lines Where Possible
- Clean & Reshape Street Ditches on East/West Streets


### 2: Raise Property

- Raise the Streets City
- Raise Individual Properties Property Owners



#### Drainage Concept

- Provide a centrally located trunk line that is within 2 blocks of any property
- Recommend open system to allow for easier maintenance such as a ditch or channel
- Provide larger outfalls to the bay (possible navigable connection)
- Raise streets above high tide and slope towards Timon & Surfside Blvd






## **Drainage Options**

## Option 1: Closed Conduit System

- Expensive
- Difficult to maintain
- Least beneficial hydraulic improvement






## Drainage Options (Continued)

## Option 2: Open Ditch


- Most Cost Effective
- Easy to Maintain
- Good hydraulic improvement





# **Drainage Options**

# Options 1 & 2: Layout






### Drainage Options (Continued)

## Option 3: Navigable Channel


- Cost more than ditch
- Easy to Maintain
- Best hydraulic improvement





# **Drainage Options**

# Option 3: Layout





#### **Utilities**

All three options will require replacing or relocating some existing utilities

- Water, Sewer and Gas lines crossing east to west will need to be lowered under the Box, Ditch or Channel
- Most utilities with in Timon & Surfside Blvd will need to be relocated to make way for the Box, Ditch or Channel



#### **Cost Estimates**

Option 1: Closed Conduit System \$82,635,608

Option 2: Open Ditch System \$36,119,137

Option 3: Navigable Channel \$41,242,560

**Added to All Options** 

Raise Streets \$32,000,000



#### Conclusions

- The permanent drainage solution for North Beach needs to include significant additional drainage improvements
- Raising all streets on North Beach needs to be part of the solution. This
  needs to be programmed over multiple years.
- North Beach needs fill dirt as much as it needs more drainage infrastructure. Securing sources of fill material beyond the ditch/channel would be beneficial.



#### Recommendations

- Raising all streets on North Beach needs to be considered as part of the long-range cost of fixing North Beach
- Pursue Options 2 or 3 as viable options to solve the drainage issues for North Beach



# QUESTIONS

# Backup Slides




# Stormwater Funded Capital Improvements

Funding Source	Numbers	Amount (\$)
Stormwater CIP 2019-2020	6	\$10,600,000
Stormwater Funding from Street/Bond 2018	98	\$32,208,404
Stormwater Funding from Street/Bond 2016	1	\$350,000
	Total	\$43,158,404




# Manhole Sediment Levels





# Inlet Blockages






# Total Buildings = 200





# North Beach Drainage






# North Beach Utility Projects 2007 - 2019





# North Beach Utility Projects 2007 - 2019





# Industrial Canal Crossing





# North Beach Lift Station Improvements

- Construction contract awarded to Associated Construction Partners, LTD. to Implement Lift Station Repairs Citywide in May 2018
  - Repairs to Rincon North, Rincon South, and North Beach B Lift Stations with a total amount of \$272,000
- Condition Assessment of 20 Lift Stations including the remaining three lift stations in North Beach began in 2019 and is anticipated to be completed in February 2020



# Decrease in Inflow & Infiltration

