



HD DINGHIES



Standard Features	1.6mm Pressed sides & 1.6/2.0mm bottom sheets	Fully welded construction	Foam filled thwart seats	Basic flotation
	Anchor shelf	Bow grab handles	Transom grab handles	Transducer bracket
	Bulge pump bracket	Solid corners	Bow eye	Anchor rope tie point
	Side pockets	Rowlocks	Plate flat foredeck	Checker plate foredeck (3.8WB/4.0)
	Keel and chines	Drain bung	Decals	Moulded anchor well (3.8WB/4.0)
	Drop in floor (3.8WB/4.0)	Fuel tank rack (3.8WB/4.0)	Cross bollard (3.8WB/4.0)	Motor pad

Model	Length Overall	Beam mm	Hull Depth mm	Weight kg	Max HP	Bottom Sheets	Top Sides	People	Transom Height	Flotation
360 Rascal	3.60m	1600	665	80	20	1.6	1.6	3	Short/Long	Basic
380 Varmint	3.80m	1600	665	95	25	1.6	1.6	4	Short/Long	Basic
380 Varmint WB	3.85m	1830	760	110	30	2.0	1.6	4	Long	Basic
400 Outlaw	4.00	1850	760	115	30	2.0	1.6	4	Long	Basic



* Specifications subject to change without notice