

BAUER INDUSTRIAL EQUIPMENT LTD.

(Office) #109 - 8678 Greenall Ave, Burnaby, B.C. Canada V5J 3M6
(Warehouse) 5758 Beresford St., Burnaby, B.C. Canada
Tel: (604) 438-1121, (877) 438-1121 Fax: (604) 438-1122
Email: solutions@bauerltd.ca Web: www.bauerltd.ca

Celebrating quality products
at competitive prices since 1973!



newall



TRAK CNC

Kent (USA) Model ML-1740T/1760T

High Precision, Heavy Duty, Gap-type Engine Lathe

FEATURES

- 7.5 HP spindle motor, 12-speeds
- 3.13" spindle through hole
- Solid full length cast base w/front loading chip tray for easier cleaning
- Adjustable over-load feed clutches
- Quick reversal feed from apron
- Full-length safety foot brake
- Spindle jog button control
- One-shot lubrication for apron, carriage & bedways
- Multi-position adjustable feed position stops
- Dual inch/metric tailstock quill w/knockout tang
- Heavy duty two speed tailstock
- Dual inch/metric dials w/quick-change sleeve



SPECIFICATIONS

Swing - over bed	17"	Width of bed	12"
over cross slide	10.9"	Feed range - longitudinal	.0015 - .04"/rev
in gap	24.5"	cross	.00075 - .02"/rev
Distance between centers	44" / 57"	Thread range - metric	0.2 - 14 mm (39 kinds)
Spindle nose	D1-6 camlock	inch	2 - 72 TPI (45 kinds)
Spindle bore	3.13"	Tailstock quill diameter	2.3"
Spindle taper	MT#7 - MT #4	Tailstock quill taper	MT #4
Spindle speeds (12 steps)	36 - 1800 RPM	Tailstock quill travel	5"
Travel - compound	4.75"	Main motor	7.5 HP
cross slide	10.6"	Weight (net)	3900 / 4550 lbs.

STANDARD ACCESSORIES

3-jaw chuck (10")	Steady rest	Follow rest	4-position tool post
Halogen worklight	Thread chasing dial	Full-length splash guard	Chuck cover
Toolbox w/standard tools	Coolant system	3-position carriage stop	

OPTIONAL ACCESSORIES

Newall DRO system (5 yr warr., 3 yr no-fault warr.)
Taper turning attachment
4-jaw independent chuck (10")
Face plate (12")
Micro carriage stop

Please feel free to contact us for pricing or if you have any questions.