



PARTS

SERVICE

SELF-CONTAINED














SHOWER, EYEWASH & FACEWASH PRODUCTS





Catalog Contents

Catalog Conter
Combination Eyewash/Facewash Showe
Galvanized Piping
Stainless Steel Piping
PVC Piping
Corrosion-Resistant Coating
Vertical & Horizontal Showers
Freeze – Resistant Showers
Freeze & Scald Protection Valves
Subsurface Showers & Eye/Facewash
Through-Wall Shower & Eyewash
Self-Contained
Aquarion [®]
Helios®
Gravity Fed
Standard Pressurized Portable Eyewash
Large Pressurized Portable Evewash

Accessories & Parts	
Alarm Systems & Lighting	43
Awareness 100™ Signage	4
Awareness® & Awareness 360°™ Signage	40
Emergency Signs	47
Shower Accessories & Test Units	48
Assemblies - Heads & Nozzles	50
Bowls & Covers	5
Self-Contained	5
Activation Kits & Valves	52
Protection Valves & Fittings	53
Alarms	5
Curtains & Testing Accessories	5.

Self-Contained	
Aquarion®	20
Helios [®]	21
Gravity Fed	22
Standard Pressurized Portable Eyewash	23
Large Pressurized Portable Eyewash	24
Personal Flushing Stations	25

Representative Performance Data	54
Limited Warranty Statement	54
Numerical Parts Index	55

Eyewash & Facewash			
Wall Mount	27		
Supply Mount	29		
Pedestal Mount	31		

Key	
ABS BCP	Acrylonitrile Butadiene Styrenes Brass Chrome-Plated
CP	Chrome-Plated
DH	Drench Hose
FTR	Foot Treadle
PVC	Poly Vinyl Chloride
SS	Stainless Steel

Freeze-Protected Showers		
Therma-Flow® Freeze-Protected Showers	34	
Therma-Flow® PLUS Freeze-Protected		

Tempered Water Systems	
Electrically Heated & Blended	39
Air Driven	40
Steam Heated & Blended	41
Saf-T-Flo® Fail-Safe Blending	42

Shower Enclosures





Our emergency combination shower and eyewash are built to Encon's or to the exact customer's specifications from a wide choice of materials and coatings for unmatched performance and durability. We use premium materials and heavier gauge steel so our customers can count on Encon® when seconds matter.

- Stay-open ball valves (1" / 2.5 cm Shower, $\frac{1}{2}$ " / 1.3 cm Eyewash)
- Stainless steel valve stems and actuators (Pull Rod Shower, Push Plate Eyewash)
- Actuation graphics
- Self-adjusting regulators
- Shower Heads and Bowls available in high visibility yellow plastic or 304 stainless steel
- Eye and Facewash heads include hinged covers or floatoff covers secured with stainless steel bead chain
- 11/4" / 3.2 cm NPT Supply and Waste connections (waste connection not included on no bowl models)

ACCESSORY OPTIONS AVAILABLE ON MOST MODELS

- Bowl Cover: Available in yellow ABS plastic or 304 stainless steel. Cover is opened by push plate and manually closed.
- Drench Hose: For partial body flushing. 6' / 1.8 m synthetic rubber hose assembly, mounting bracket, yellow ABS single stream head with float-off cover, self-closing lock-open squeeze handle actuator.
- Foot Treadle: Yellow ABS plastic step-on treadle with stainless steel chain for eye/facewash activation.

Galvanized Piping

PIPING AND VALVE CHOICES

- Schedule 80 hot dip galvanized steel piping
- Chrome-plated bronze ball valves & ball

SHIP WEIGHT

Shower — 59 lb / 26.76 kg Shower with FTR — 61 lb / 27.66 kg Shower with DH — 62 lb / 21.12 kg

Model 01050260 20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl® Model 01050216 30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®

Note: ABS Facewash assembly, 8 gpm / 30.3 lpm Head available with BCP Wye. See model on page 7.



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112892. See signs on page 47.

Model 01050251

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®

Model 01050207

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®



Note: ABS Eyewash assembly, 3.2 gpm /



Model 01050217P20

20 gpm / 75.7 lpm Shower, Eyewash with Acetal Heads & BCP Wye, Yello-Bowl®

Model 01050217

30 gpm / 113.6 lpm Shower, Eyewash with Acetal Heads & BCP Wye, Yello-Bowl®



Note: Acetal eyewash & BCP Wye, 2.4 gpm / 9.1 lpm. Bowl covers available on models with BCP Wye. See bowl covered model on page 6.



Galvanized Piping

Model 01050209P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Strainer, Yello-Bowl®

Model 01050209

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Strainer, Yello-Bowl®





Model 01050288P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads, & Wye, Drench Hose, Yello-Bowl®

Model 01050288

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads, & Wye, Drench Hose, Yello-Bowl®





Model 01050290P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Foot Treadle, Yello-Bowl®

Model 01050290

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Foot Treadle, Yello-Bowl®



Note: Foot Treadle



Model 01050217P20PBC

20 gpm / 75.7 lpm Shower, Eyewash with Acetal Heads & BCP Wye, Plastic Bowl Cover, Yello-Bowl®

Model 01050217PBC

30 gpm / 113.6 lpm Shower, Eyewash with Acetal Heads & BCP Wye, Plastic Bowl Cover, Yello-Bowl®



Note: Low profile Eyewash assembly



Showers & Combination Showers

Combination Showers Eyewash/Facewash

Galvanized Piping

Model 01050266P20PBC

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, Strainer, Plastic Bowl Cover, Yello-Bowl®

Model 01050266PBC

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, Strainer, Plastic Bowl Cover, Yello-Bowl®



Note: Low profile BCP Wye assembly and Plastic bowl cover

Model 01050230P20 20 gpm / 75.7 lpm Sho

20 gpm / 75.7 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl

Model 01050230

30 gpm / 113.6 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl



Note: Stainless Steel Bowl



Model 01050234P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl

Model 01050234

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl



Model 01050281P20

20 gpm / 75.7 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl, Foot Treadle

Model 01050281

30 gpm / 113.6 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl, Foot Treadle



Galvanized Piping

Model 01050293P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl, Foot Treadle

Model 01050293

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl, Foot Treadle



Model 01050230P20PBC

20 gpm / 75.7 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl, Plastic **Bowl Cover**

Model 01050230PBC

30 gpm / 113.6 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl, Plastic **Bowl Cover**



Model 01050234P20PBC

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl, Plastic Bowl Cover

Model 01050234PBC

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl, Plastic Bowl Cover



Note: Stainless Steel bowl with Plastic



Model 01050234P20SBC

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl & Bowl Cover

Model 01050234SBC

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl & Bowl Cover





Galvanized Piping

Model 01050471S20SBC

20 gpm / 75.7 lpm SS Shower Head, Eyewash with Acetal Heads & BCP Wye, SS Bowl & Bowl Cover

Model 01050471SBC

30 gpm / 113.6 lpm SS Shower Head, Eyewash with Acetal Heads & BCP Wye, SS Bowl & Bowl Cover



Note: Stainless Steel bowl and cover



Model 01050221P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & Wye, No Bowl

Model 01050221

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & Wye, No Bowl



Note: 8 gpm / 30.3 lpm Facewash assembly with no bowl



Model 01050205P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, No Bowl

Model 01050205

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, No Bowl



Note: 3.2 gpm / 12.1 lpm Eyewash assembly with no bowl



Model 01050224P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, No Bowl

Model 01050224

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, No Bowl



Stainless Steel Piping

PIPING AND VALVE CHOICES

- Schedule 40, 304 Stainless Steel piping
- Stainless Steel ball valves & ball

SHIP WEIGHT

Shower — 59 lb / 26.76 kg Shower with FTR — 61 lb / 27.66 kg Shower with DH — 62 lb / 21.12 kg

Model 01050219P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®

Model 01050219

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®




Model 01050223P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®

Model 01050223

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®



20 gpm / 75.7 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl

Model 01050232

30 gpm / 113.6 lpm Shower, Eyewash with Acetal Heads & BCP Wye, SS Bowl





Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112892. See signs on page 47.



Showers & Combination Showers

Combination Showers Eyewash/Facewash

Stainless Steel Piping

Model 01050236P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl

Model 01050236

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl



Model 01050236P20SBC

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl, SS Bowl Cover

Model 01050236SBC

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & BCP Wye, SS Bowl, SS Bowl Cover



Model 01050264S20

20 gpm / 75.7 lpm SS Shower Head, Eyewash with SS Heads & Wye, SS Bowl

Model 01050264

30 gpm / 113.6 lpm SS Shower Head, Eyewash with SS Heads & Wye, SS Bowl



Note: 2.5 gpm / 9.5 lpm Stainless Steel Eyewash assembly



Model 01050470S20

20 gpm / 75.7 lpm SS Shower Head, Eyewash with SS Heads & Wye, SS Bowl, Foot Treadle

Model 01050470

30 gpm / 113.6 lpm SS Shower Head, Eyewash with SS Heads & Wye, SS Bowl, Foot Treadle



PVC Piping

PIPING AND VALVE CHOICES

- Schedule 80 corrosion-resistant PVC piping with socket weld joints
- Corrosion-resistant coated bronze ball valves with chrome plated ball

SHIP WEIGHT Shower — 34 lb / 15.42 kg

Model 01060022 20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®, Free Standing Model 01060021 30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®, Free Standing Note: Supported overhead section for free-stand mounting. **Note:** Every model in this section includes $a 7'' \times 11'' / 17.7 cm$ × 27.9 cm sign, part number 01112892. See signs on page 47.

Model 01060007P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®, Wall Flange Support

Model 01060007

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®, Wall Flange Support



Model 01060009P20

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®, Wall Flange Support

Model 01060009

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®, Wall Flange Support





Corrosion-Resistant Coating

PIPING AND VALVE CHOICES

- Schedule 80, hot dipped galvanized steel piping with high visibility yellow corrosion-resistant coating
- Chrome plated bronze ball valves & ball

SHIP WEIGHT

Shower — 59 lb / 26.76 kg

Model 01050276

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®

Model 01050210

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®




Model 01050277

20 gpm / 75.7 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®

Model 01050228

30 gpm / 113.6 lpm Shower, Facewash with ABS Heads & Wye, Yello-Bowl®



20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®, Foot Treadle

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Yello-Bowl®, Foot Treadle



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112892. See signs on page 47.



Vertical & Horizontal Showers

PIPING

- Mounts directly onto overhead pipe
- Available with galvanized or stainless steel piping (standard ball valve included assembly with actuation graphic

SHIP WEIGHT

Horizontal Shower 1" / 2.5 cm supply — 8 lb / 3.62 kg Vertical Shower 1" / 2.5 cm supply — 6 lb / 2.72 kg Shower 11/4" / 3.2 cm supply — 11 lb / 4.98 kg



Model 01052522

20 gpm / 75.7 lpm Shower, 1" / 2.5 cm Horizontal Pipe Mount

Model 01052501

30 gpm / 113.6 lpm Shower, 1"/ 2.5 cm Horizontal Pipe Mount





Model 01052524

20 gpm / 75.7 lpm Shower, 1" / 2.5 cm Vertical Pipe Mount

Model 01052502

30 gpm / 113.6 lpm Shower, 1" / 2.5 cm Vertical Pipe Mount



Model 01053001

Model 01053001P20

30 gpm / 113.6 lpm Shower, 11/4" / 3.2 cm Horizontal Pipe Mount

20 gpm / 75.7 lpm Shower, 11/4" /

3.2 cm Horizontal Pipe Mount



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112891. See signs on page 47.





Encon® offers a complete line of freeze-resistant showers and eyewash products designed to withstand subfreezing temperatures for brief periods. Our freeze-resistant products utilize temperature-sensitive valves to circulate water during freezing periods and our subsurface models feature underground self-drain systems to prevent freezing of exposed piping.

- Schedule 80 hot dipped galvanized steel piping or schedule 40, 304 stainless steel piping
- Stay-open ball valves
- Stainless steel valve stems and actuators
- Actuation graphics
- Self-adjusting regulators
- Heads and Bowls available in high visibility yellow plastic or 304 stainless steel
- Eye and Facewash heads include hinged covers or floatoff covers secured with stainless steel beads

ACCESSORY OPTIONS AVAILABLE ON MOST MODELS

- Bowl Cover: Available in yellow ABS plastic or 304 stainless steel
- Drench Hose for partial body flushing
- Step-on foot treadle for eye/facewash activation

Freeze-Resistant Showers

Freeze & Scald Protection Valves

FREEZE & SCALD VALVE OPTIONS

- Freeze Protection Valve: Opens automatically when internal temperature reaches 35°F /2°C and closes at 40°F / 4.5°C
- Scald Protection Valve: Opens automatically when internal temperature reaches 105°F / 40.6°C and closes at 94°F / 34.4°C

SHIP WEIGHT Automatic — 60 lb / 27.22 kg



Model 01050362P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Auto. Freeze & Scald Protection Valves, Galvanized Pipe

Model 01050362

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Auto. Freeze & Scald Protection Valves, Galvanized Pipe





Model 01050314P20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Auto. Freeze Protection Valve, Drench Hose, Galvanized Pipe

Model 01050314

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Auto. Freeze Protection Valve, Drench Hose, Galvanized Pipe





Freeze-Resistant Showers

Subsurface Showers & Eye/Facewash

AUTOMATIC DRAIN

Water drains from exposed piping to help prevent freezing.

SHIP WEIGHT


Subsurface Combination Shower — 115 lb / 52.16 kg Subsurface Shower — 75 lb / 34.02 kg Subsurface Eyewash — 40 lb / 18.14 kg

Model 01050201P20

20 gpm / 75.7 lpm Shower, Galvanized Pipe

Model 01050201

30 gpm / 113.6 lpm Shower, Galvanized Pipe




Model FRSSC-GP20

20 gpm / 75.7 lpm Shower, Eyewash with ABS Heads & Wye, Galvanized Pipe

Model FRSSC-G

30 gpm / 113.6 lpm Shower, Eyewash with ABS Heads & Wye, Galvanized Pipe




Model 01030104

Eyewash with ABS Heads & Wye, Galvanized Pipe

Model 01035604

Facewash, ABS Heads & Wye & Galvanized Pipe





Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112892. See signs on page 47.

Freeze-Resistant Showers

Freeze-Resistant Showers

Through-Wall Shower & Eyewash


AUTOMATIC DRAIN


Water drains from exposed piping to help prevent freezing

SHIP WEIGHT

Shower — 38 lb / 17.24 kg

Eye/Facewash — 9 lb / 4.08 kg





Model 01035606

Facewash with ABS Heads, Wye & Galvanized Pipe

Model 01030106

Eyewash, ABS Heads, Galvanized Pipe



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112891. See signs on page 47. NOTE: Allow minimum of 16" / 40.6 cm lateral clearance between shower and eyewash target areas for actuator arm movement.







Extend your safety perimeter. For areas where plumbed potable water is not readily available, Encon® offers a wide array of choices for self-contained emergency eyewash stations, including pressurized, gravity-fed, and sealed-cartridge units. Encon's self-contained eyewash stations meet ANSI Z358.1-2014 requirements for emergency eyewash equipment. Additionally, the Firstep® FirstFlush® station and the 5 Gallon / 22 Liter pressurized self-contained unit meet ANSI Z358.1-2014 standard for personal flushing equipment.

GRAVITY FEDS

- Durable Polyethylene body
- 0.4 gpm / 1.5 L ABS plastic dual-stream eyewash nozzles
- Pull-down tray for eyewash nozzle activation
- Instructions located on front graphics. Available in English, Spanish, and French/Canadian where noted
- CSA approved heated models with UL & FM components

PRESSURIZED PORTABLES

- 304 stainless steel ASME rated, CRN registered vessel
- ½" / 1.3 cm brass chrome-plated piping with stay-open ball valve
- Stainless steel valve stem and actuator
- Actuation graphics
- Self-adjusting regulator
- Brass relief valve opens at 115 PSI
- Custom face pressure gauge
- Drench Hose option available with self-closing, lock-open handle

ACCESSORY OPTIONS AVAILABLE ON MOST MODELS

- Insulating jacket and thermostat controlled heater
- Transport cart: Yellow tubular steel (gravity fed) or yellow polyethylene with strap (pressurized portable)
- Waste receptacle

Aquarion®

The Aquarion® offers the sealed flexible cartridge that completely self-evacuates without external forces being applied, providing reliable performance when you need it most.

- High visibility yellow ABS removable cover
- Tinted translucent ABS side windows for internal visual inspection
- Black ABS base slides onto the Back Plate
- Gray retracting tray to protect the enclosed eyewash nozzles from the environment
- Preserved saline solution in individual bags

SHIP WEIGHT

23 lb / 12.7 kg Unit

75 lb / 34.02 kg AQ120 fluid cartridges 37 lb / 16.78 kg AQ110 fluid cartridges

TRANSPORT CART (Optional)

Yellow tubular steel with wheels

Weight — 66 lb / 22.94 kg

WASTE RECEPTACLE (Optional)

Weight — 14 lb / 6.35 kg

AQUARION

Model AQ120

Preserved Saline Solution Fluid Cartridaes*

Model AQ110

Sterile Saline Solution Fluid Cartridges**

Model AQ111

User Fillable **Cartridges**



Note: *Not available in Canada & Mexico **Available only in Canada

Model AQ100

Aquarion® Self-Contained Eyewash

Model AQ100S

Aquarion® Self-Contained Eyewash - Spanish





Model AQ100H130 Heated Aguarion® Self-Contained Eyewash

Helios® Gravity Fed

Helios® has one of the sleekest profile of selfcontained products available allowing simple installation and use in a tighter, smaller area close to facility hazards.

- High visibility yellow polyethylene tank
- Internal, rotating actuating valve integral to the eye wash tray
- Eyewash Heads inset directly into the black pulldown tray offering protection from airborne particulate
- Molded eyelet hangers for mounting
- Mounting bracket available. See page 51.

SHIP WEIGHT 15 lb / 6.8 kg



Model HS100

Helios® Gravity Fed Eyewash - Spanish

Model HF100

Helios® Gravity Fed Eyewash - French






Model HE100

Helios® Gravity Fed Eyewash





A case reorder of Hydrosep® includes four 8 oz. / 236.6 mL bottles.



Gravity Fed

With its fillable tank design, the Self-Contained Gravity Fed has proven to be a reliable safety eyewash unit.

- High visibility yellow polyethylene tank; two carrying handles.
- Enclosed eyewash heads integral to hinged drain

SHIP WEIGHT 32 lb / 14.52 kg

TRANSPORT CART (Optional) Yellow tubular steel with wheels Weight — 66 lb / 22.94 kg

WASTE RECEPTACLE (Optional) Weight — 14 lb / 6.35 kg

Model 01104070

Hazardous Area C1D2 Gp. BCD Heated Gravity Fed Eyewash





Model 01104050

Self-Contained Gravity Fed Eyewash

Model 01104050S

Self-Contained Gravity Fed Eyewash - Spanish

Model 01104050C

Self-Contained Gravity Fed Eyewash - French

> Model 01104055 Gravity Fed

Eyewash with Transport Cart and Waste Receptacle

Model 00015006

Receptacle Lid



Standard Pressurized Portable Eyewash

The large water fill opening, convenient air fill stem and customized fill indicator pressure gauge makes the standard pressurized portables easy to maintain.

- 13 Gallon / 57.2 Liter capacity; ASME, Div. VIII, Section 1 rated, and CRN registered vessel
- Heated option maintained at a temperature between 60-90°F / 15.5-32.2°C

SHIP WEIGHT 32 lb / 14.52 kg 34 lb / 15.42 kg with Drench Hose

YELLOW CART (Optional) Yellow polyethylene w/wheels & strap Weight — 26.8 lb / 12.16 kg

Model 01103004

13 Gallon / 57.2 Liter, Socket Mount Eyewash with 8' / 2.4 m Hose, Heated 120 VAC

Model 01103006

13 Gallon / 57.2 Liter, Socket Mount Eyewash with 8' / 2.4 m Hose, Heated 120 VAC, C1D2 Gr. **BCD**





Model 01104002

13 Gallon / 57.2 Liter. Fixed Eyewash with handheld 8' / 2.4 m Drench Hose

Model 01103002

13 Gallon / 57.2 Liter, Socket Mount Eyewash with 8' / 2.4 m Hose





Model 01103008

Transport cart only (Eyewash station not included)





Large Pressurized Portable Eyewash

The large 37 Gallon / 162.9 Liter tank allows you the freedom to set up a dependable pressurized eyewash and drench station where you need it most.

• 37 Gallon / 162.9 Liter is ASME, Div. VIII, Section 1 rated, and CRN registered vessel

SHIP WEIGHT 160 lb / 72.6 kg

DOLLY CART

Green tubular steel with wheels and retaining chains Weight — 30 lb / 13.61 kg

Model 01106002

37 Gallon / 162.9 Liter Eyewash & Drench Hose





Model 01106001

37 Gallon / 162.9 Liter Eyewash with Drench Hose & Dolly cart



Model 01106004 37 Gallon / 162.9 Liter Eyewash with Drench Hose, Insulation & Heat Reflective Jacket





Personal Flushing Stations

Firstep® Firstflush®

- 32 oz. / 946 mL Sterile buffered isotonic saline solution
- Highly visible yellow ABS plastic holder with operational instructions; vibration and UV resistant
- HDPE, durable, non-resealable bottle

SHIP WEIGHT

Single — 20 lb / 9.07 kg Dual — 20 lb / 9.07 kg

Personal Pressurized Portable

• 5 Gallon / 22 Liter capacity; $25'' \times 81/4''$ / 63 cm × 21 cm with carrying handles

SHIP WEIGHT 15 lb / 6.8 kg

Model 01103001

5 Gallon / 22 Liter Personal Pressurized Portable, Socket Mount Nozzles, 8' / 2.4 m Coil Hose



Model 01110786S

Firstep® FirstFlush® Single Station Units

Model 01110793S

Firstep® FirstFlush® Dual Station Units



Model 01101001

5 Gallon / 22 Liter Personal Pressurized Portable, 8' / 2.4 m Coiled Drench Hose





The Eyewash & Facewash station is most appropriate in areas where hazards to the eyes and face are most common. Our Eyewash & Facewash units are designed for ease of installation to your facility's plumbed water supply. We offer installation options to a wall, a supply-pipe, or a pedestal to facilitate installations nearest to those areas where exposure can occur. Don't forget a bowl cover to keep dirt and debris away from the eye/facewash.

- \bullet ½" / 1.3 cm Stay-open ball valve
- Stainless steel valve stem and Push Plate actuator
- Actuation graphics
- Self-adjusting regulator
- Heads and Bowls available in high visibility yellow plastic or 304 stainless steel
- Eye and Facewash heads include hinged covers or floatoff covers secured with stainless steel beads
- \bullet $\frac{1}{2}$ " / 1.3 cm NPT Supply connection

ACCESSORY OPTIONS AVAILABLE ON MOST MODELS

- Bowl Cover: Available in yellow ABS plastic or 304 stainless steel.
 Cover is opened by push plate and manually closed.
- Drench Hose: For partial body flushing. 6' / 1.8 m synthetic rubber hose assembly, mounting bracket, yellow ABS single stream head with float-off cover, self-closing lock-open squeeze handle actuator.
- Foot Treadle: Yellow ABS plastic step-on treadle with stainless steel chain for eye/facewash activation.

Wall Mount

BOWL WASTE CHOICES

- Yello-Bowl® 1¼" x 6" / 3.2 cm x
 15.2 cm slip joint tailpiece
- 304 SS Bowl 11/4" / 3.2 cm NPT connection
- P-trap 11/4" / 3.2 cm tube connection

SHIP WEIGHT

Wall Mount SS Bowl — 9 lb / 4.08 kg Wall Mount Yello-Bowl[®] — 6 lb / 2.72 kg



Model 01030403

Eyewash, ABS Heads & Wye, Yello-Bowl®, Wall Bracket, BCP Pipe & Valve, Strainer

Model 01035503

Facewash, ABS Heads & Wye, Yello-Bowl®, Wall Bracket, BCP Pipe & Valve, Strainer



Note: Strainer

Model 01030401

Eyewash, ABS Heads and Wye, BCP Pipe & Valve, Yello-Bowl[®], Wall Bracket

Model 01035501

Facewash, ABS Heads and Wye, BCP Pipe & Valve, Yello-Bowl®, Wall Bracket



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112893. See signs on page 47.

Model 01030416

Eyewash, Acetal Heads, BCP Wye, Yello-Bowl®, Wall Bracket, BCP Pipe & Valve, Strainer

Model 01035511

Facewash, ABS Heads, BCP Wye, Yello-Bowl®, Wall Bracket, BCP Pipe & Valve, Strainer



Note: 2.4 gpm / 9.1 lpm Acetal eyewash heads. Bowl covers are available on models with BCP Wye. See bowl covered model on page 28.

Wall Mount



Model 01045001

Eyewash, Acetal Heads & BCP Wye, BCP Pipe & Valve, SS Bowl, Wall Bracket

Model 01045501

Facewash, ABS Heads & BCP Wye, BCP Pipe & Valve, SS Bowl, Wall Bracket



Model 01045501PBC

Facewash, ABS Heads, BCP Wye, SS Bowl, Plastic Bowl Cover, Wall Bracket



Model 01045001SBC

Eyewash, Acetal Heads, BCP Wye, SS Bowl & Bowl Cover, Wall Bracket



Facewash, ABS Heads, BCP Wye, SS Bowl, Wall Bracket, BCP Pipe & Valve, P-Trap

Supply Pipe Mount

BOWL WASTE CHOICES

- Yello-Bowl® $1\frac{1}{4}$ " × 6" / 3.2 cm × 15.2 cm slip joint tailpiece
- 304 SS Bowl 11/4" / 3.2 cm tube connection

SHIP WEIGHT

Supply Mount Yello-Bowl® — 6 lb / 2.72 kg Supply Mount SS Bowl — 9 lb / 4.08 kg



Model 01045505

Facewash, ABS Heads & BCP Wye, BCP Pipe & Valve, SS Bowl

Model 01045005

Eyewash, Acetal Heads, BCP Wye, SS Bowl, BCP Pipe & Valve



Model 01030301

Eyewash, ABS Heads & Wye, BCP Pipe & Valve, Yello-Bowl®

Model 01035401

Facewash, ABS Heads & Wye, BCP Pipe & Valve, Yello-Bowl®



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112893. See signs on page 47.



Eyewash, ABS Heads & Wye, Yello-Bowl®, PVC Pipe & Valve

Model 01038801

Facewash, ABS Heads & Wye, Yello-Bowl®, PVC Pipe & Valve



Supply Pipe Mount



Model 01030101

Eyewash, ABS Heads & Wye, No Bowl, BCP Pipe & Valve



Model 01030103

Eyewash, ABS Heads & Wye, No Bowl, BCP Pipe & Valve, Strainer



Model 01045601

Facewash, ABS Heads & BCP Wye, No Bowl, BCP Pipe & Valve

Model 01040103

Eyewash, Acetal Heads, BCP Wye, No Bowl, BCP Pipe & Valve



Model 01040135

Eyewash, SS Heads & Wye, No Bowl, SS Pipe & Valve

Model 01114021

Facewash, SS Heads & Wye, No Bowl, SS Pipe & Valve

Pedestal Mount

Schedule 80 galvanized pedestal.

WASTE

• 11/4" / 3.2 cm NPT connection

SHIP WEIGHT

Pedestal Mount — 25 lb / 11.34 kg



Model 01045002

Eyewash, Acetal Heads, BCP Wye, SS Bowl, BCP Pipe & Valve

Model 01045502

Facewash, ABS Heads, BCP Wye, SS Bowl, BCP Pipe & Valve



Model 01030302

Eyewash with ABS Heads & Wye, BCP Pipe & Valve, Yello-Bowl®

Model 01035402

Facewash with ABS Heads & Wye, BCP Pipe & Valve, Yello-Bowl®



Note: Every model in this section includes a 7" × 11" / 17.7 cm × 27.9 cm sign, part number 01112893. See signs on page 47.

Model 01045002SBC

Eyewash, Acetal Heads, BCP Wye, SS Bowl & Bowl Cover, BCP Pipe & Valve

Model 01045502SBC

Facewash, ABS Heads, BCP Wye, SS Bowl & Bowl Cover, BCP Pipe & Valve



Pedestal Mount



Model 01030316PBC

Eyewash, Acetal Heads, BCP Wye, Yello-Bowl®, Plastic Bowl Cover, BCP Pipe & Valve

Model 01035415PBC

Facewash, ABS Heads, BCP Wye, Yello-Bowl®, Plastic Bowl Cover, BCP Pipe & Valve

Model 01045006

Eyewash, Acetal Heads, BCP Wye, SS Bowl, BCP Pipe & Valve, Foot Treadle

Model 01045506

Facewash, ABS Heads, BCP Wye, SS Bowl, BCP Pipe & Valve, Foot Treadle





Model 01045008

Eyewash, Acetal Heads, BCP Wye, SS Bowl, BCP Pipe & Valve, Strainer

Model 01045514

Facewash, ABS Heads, BCP Wye, SS Bowl, BCP Pipe & Valve, Strainer

Model 01035410

Facewash, ABS Heads & Wye, Yello-Bowl®, BCP Pipe & Valve, Drench Hose

Model 01030310

Eyewash, ABS Heads & Wye, Yello-Bowl®, BCP Pipe & Valve, Drench Hose







Built to withstand winter extremes! Encon® offers models that resist freezing as low as -40°F / -40°C. Internal water temperatures are maintained using a thermostat controlled self-limiting heating cable on Therma-Flow® showers and a radiant heater or heating cable in the Therma-Flow® Plus shower enclosures. Encon® offers a customized model selection, allowing you to design a product that meets the specific needs of your facility.

- Thermostat controlled electric freeze protection options
 - Therma-Flow: Self-limiting heat trace cable
 - Therma-Flow® Plus: Radiant heater or self-limiting heat trace cable
- Schedule 80 hot dipped galvanized piping or schedule 40, 304 stainless steel piping
- Stay-open ball valves (11/4" / 3.2 cm shower, 1/2" / 1.3 cm self-draining eyewash), bronze or stainless steel
- Stainless steel valve extension stems and actuators (pull rod shower, push plate eyewash)
- Self-adjusting regulators
- Heads available in high visibility yellow ABS plastic
- Eyewash heads include float-off covers secured with stainless steel bead chain
- Top and bottom inlet connection options
- 120 or 240 VAC compatible models
- High visible colors and durable materials
- CSA approved models with UL & FM components
- Suitable for installation in general purpose and/or hazardous electrically classified areas
- Shipped pre-assembled and individually serialized

ACCESSORY OPTIONS AVAILABLE ON MOST MODELS

- Remote and local alarm capabilities with flow or MAP® switch activation
- Drench Hose
- Freeze and scald protection valves
- Area lighting and heat trace indication
- Freeze protected underground extension or additional heat tracing cable at the water inlet connection

Freeze-Protected Showers


Therma-Flow® Freeze-Protected Showers

- Shower piping is heat traced and insulated, and includes high visibility covers
- Freeze protected to -40°F / -40°C in most applications
- Covers are field removable for field maintenance

Model TF36B2000302 20 gpm / 75.7 lpm Shower, Eyewash, C1D2 Gp. BCD, Heat Trace Indicator, MAP® Switch, Remote Alarm, Green covers

Model TF35B5376300

20 gpm / 75.7 lpm Shower, Eyewash, C1D2 Gp. BCD, Green Area Light, Heat Trace Indicator, Freeze & Scald Protection Valves, Red Alarm Light & Horn, MAP® Switch, Yellow covers



20 gpm / 75.7 lpm Shower, Eyewash, C1D2 Gp. BCD, Heat Trace Indicator, Freeze & Scald Protection Valves, Orange covers



Note: Every model in this section includes a $16\frac{1}{5}$ " × 6" / 41.1 cm \times 15.2 cm sign, part number 35001810. See signs on page 46.





Freeze-Protected Showers

CUSTOM DESIGN YOUR THERMA-FLOW® SYSTEM

Create your model to meet the specific needs of your facility.

Position 3 Position 5 Position 7 Position 9 Position 11 **ELEC. CLASS / DELIVERY SAFETY VALVES & LIGHT COLORS UNDERGROUND VOLTAGE THERMOMETER EXTENSION & SYSTEM EXTRA CABLE** 30 gpm / 113.6 lpm 1 - NEMA 4 / 120V 0 - None 0 - None Shower, EW - 20 gpm / 75.7 lpm 2 - NEMA 4 / 240V 1 - Freeze Protection Valve 1 - One Light Only - Clear 0 - None Shower, EW 1 - 2' / 0.6 m Underground 30 gpm / 113.6 lpm 3 - Class 1 Div. 2, Gp. 2 - Scald Protection Valve 2 - One Light Only - Red Shower, EW, DH Extension B,C,D / 120V; Class 2 Div. 2, Gp. 20 gpm / 75.7 lpm 3 - Freeze & Scald 2½' / 0.8 m 3 - One Light Only - Green F & G Shower, EW, DH Protection Valves Underground Extension 3 - 3' / 0.9 m Underground 30 gpm / 113.6 lpm 4 - Class 1 Div. 2, Gp. 4 - Thermometer 4 - One Light Only - Blue Shower, DH Extension B,C,D / 240V; Class 2 Div. 2, Gp. 20 gpm / 75.7 lpm - Thermometer / Freeze 5 - Area Light - Clear 3½′ / 1.1 m F&G Shower, DH Alarm Light - Red Protection Valve **Underground Extension** EW = Eyewash 6 - Thermometer / Scald 6 - Area Light - Green 5 - 4' / 1.2 m Underground * Class 1, Div. 1 Gp. D DH = Drench Hose Protection Valve Alarm Light - Red Extension option is available on 7 - Thermometer / Freeze some models. Price A - 10' / 3 m Heating Cable 7 - Area Light - Blue & Scald Protection on application. Alarm Light - Red Valves B - 20' / 6.1 m Heating Cable C - 30' / 9.1 m Heating Cable D - 40' / 12.2 m Heating Cable E - 50' / 15.2 m Heating Cable TIF Position 4 Position 6 Position 8 Position 10 Position 12 **WATER INLET AREA LIGHT ALARM SYSTEM ALARM COVER COLOR** & CONTROLS **ACTIVATION** 0 - None 0 - 11/4" / 3.2 cm Top 0 - None 0 - Not Required 0 - Yellow 2 - 11/4" / 3.2 cm Bottom 1 - Side Area Light 1 - Light 1 - Orange 1 - Flow Switch Top Connection 2 - Heat Trace Indicator 2 - Bell 2 - Green 4 - 1½" / 3.8 cm Top 5 - 11/2" / 3.8 cm Bottom 3 - Top Area Light 3 - Piezo Annunciator 2 - Flow Switch 6 - 1½" / 3.8 cm Top & **Bottom Connection** 4 - Horn - Side Area Light / Bottom* Heat Trace Indicator 5 - Light / Bell *Top & Bottom water inlet 3 - MAP® Switch requires special design Shower, EW 5 - Top Area Light / 6 - Light / Piezo Annunciator and model number if Heat Trace Indicator extra cable is required. 7 - Light / Horn 4 - MAP® Switch Top & Bottom inlet Shower, DH locations can cause undesired alarm activation if Flow Switch 5 - MAP® Switch is the selected alarm Shower, EW, DH activation method.

NOTES:

Position 8 - Options 3,6: The piezo annunciator (intermittent signal) is suitable for electrical classification up to Class 1 Div. 2 Gp. B only, not for use in

Class 1, Div. 1 applications. Includes reset button on audible alarm. Position 11 - Underground Extension dimensions references length of pipe below grade.





Freeze-Protected Showers

Therma-Flow® PLUS Freeze-Protected Shower Enclosures

- Fully enclosed shower and eyewash
- Freeze protection provided by internal radiant heater or Therma-Flow® shower and eyewash
- Enclosure includes fire-retardant fiberglass reinforced plastic and urethane foam walls, chemical resistant UV inhibited gel coat finish, and adjustable double swinging doors with weather



Model TP21323230

Therma-Flow® 20 gpm / 75.7 lpm Shower, Eyewash, C1D2 Gp. BCD, Drench Hose, Red Lights & Bell, Green Area Light, Room Heater, Flow Switch



Fountain Section detail



Overhead Section detail







Freeze-Protected Showers

CUSTOM DESIGN YOUR SYSTEM

Create your model to meet the specific needs of your facility.

Position 3 Position 5 Position 7 Position 9 **DELIVERY SYSTEM VOLTAGE / ELECTRICAL AREA LIGHT BUILDING DRAIN & GRAPHICS CLASS** 1 - Gal. 20 gpm / 75.7 lpm Shower, 1 - 120V / NEMA 4* 1 - Drain Right - English 0 - None Eye/Facewash, DH 2 - 120V / NEMA 4 / NEMA 4X* 2 - Gal. 20 gpm / 75.7 lpm Shower, Eye/ 1 - Clear 2 - Drain Right - English & French Facewash, DH, Freeze & Scald Protec-2 - Blue 3 - Drain Left - English 3 - 120V / Class 1 Div. 2, Gp. B,C,D; Class 2 Div. 2, Gp. F & G* 4 - Drain Left - English & French 3 - Green 3 - Gal. 20 gpm / 75.7 lpm Shower, Eye/ 4 - 120V / Class 1 Div. 2, Gp. B,C,D; / 5 - Drain Center - English Facewash, DH, Treadle* NEMA 4X* 4 - Gal. 20 gpm / 75.7 lpm Shower, Eye/ 5 - 120V / Class 1 Div. 1, Gp. D 6 - Drain Center - English & French Facewash, DH, Treadle*, Freeze & 6 - 240V / NEMA 4* 7 - Drain Right - English & Spanish Scald Protection Valves 5 - SS 20 gpm / 75.7 lpm Shower, 7 - 240V / Class 1 Div. 2, Gp. B,C,D* 8 - Drain Left - English & Spanish Eye/Facewash, DH 8 - 240V / Class 1 Div. 1, Gp. D 6 - SS 20 gpm / 75.7 lpm Shower, Eye/ 9 - Drain Center - English & Spanish Facewash, DH, Freeze & Scald Protec-* CSA Approved Models tion Valves 7 - TF 20 gpm / 75.7 lpm Shower, Eye/ Facewash, DH 8 - TF 20 gpm / 75.7 lpm Shower, Eye/ Facewash, DH, Freeze & Scald Protection Valves EW = Eye/Facewash SS = Stainless Steel DH = Drench Hose TF = Therma-Flow® Position 8 Position 4 Position 6 Position 10 **BUILDING HEATER ALARM SYSTEM WATER INLET** UNDERGROUND **EXTENSION / EXTRA CABLE** 1 - 1¼" / 3.2 cm Top 0 - None 0 - None 1 - Flow Switch - Red Light 2 - 11/4" / 3.2 cm Bottom 0 - None 1 - Yes 3 - 11/4" / 3.2 cm Top & 1 - 21/2' / 0.8 m Underground Extension 2 - Flow Switch - Red Light & Bell Bottom* 3 - Flow Switch - Red Light & Horn 4 - 11/2" / 3.8 cm Top 2 - 3' / 0.9 m Underground Extension 3 - 31/2' / 1.1 m Underground Extension 4 - Flow Switch - Red Light & Piezo Annunciator 5 - 11/2" / 3.8 cm Bottom 6 - 1½" / 3.8 cm Top & 5 - MAP® Switch - Red Light 4 - 4' / 1.2 m Underground Extension Bottom* 6 - MAP® Switch - Red Light & Bell *Top & Bottom water inlet 5 - 25' / 7.6 m Heating Cable requires special design 7 - MAP® Switch - Red Light & Horn 6 - 50' / 15.2 m Heating Cable and model number if extra cable is required. Top & 8 - MAP® Switch - Red Light & Piezo Annunciator Underground Extension available on Bottom inlet locations can bottom water inlet selection only. cause undesired alarm


NOTES:

Position 3 - *Foot Treadle shall activate Eye/Facewash only.

Position 6 - Options 4, 8: The piezo annunciator (intermittent signal) is suitable for electrical classification up to Class

1 Div. 2 Gp. B only, not for use in Class 1, Div. 1 applications. Includes reset button on audible alarm.

Position 10 - Underground Extension dimensions references length of pipe below grade.





activation if Flow Switch is the selected alarm activation method.



Tempered Water Systems from Encon® are deployed all over the world, from the frigid Canadian Oil Sands, to the salt-water soaked North Sea Oil Platforms, and in the scorching heat of the Texas Gulf Coast. Our systems are custom built and designed to provide water at temperatures and flow levels consistent with current requirements for tepid potable water. The central element of our tempered water systems is a blending system that is used to manage tepid water delivery and developed with fail-safe mechanisms for use in emergency shower and eyewash equipment. Our systems are turnkey delivered to the specific needs of your facility and can be optioned for electrical or steam heated water and then blended and driven with the addition of electrical water pumps or pressurized air if required.

- Systems provide tempered water according to standard requirements
- Various tempering and delivery system options available
- Fail-safe designs
- Indoor and freeze-protected outdoor models
- Schedule 80 hot dipped galvanized piping
- Available with shower and eyewash station included, or without to provide tempered water to separate stations in the facility loop
- Suitable for installation in general purpose and hazardous electrically classified areas
- CSA approved models with FM, UL, and CSA approved components
- Custom ordering system
- Ships pre-assembled and individually serialized

OPTIONS AVAILABLE ON MOST MODELS

- Freeze protection by thermostat controlled radiant heater for enclosed models
- Various local and remote alarm capabilities and alarm activation devices
- Custom engineered pump packages
- Corrosion-resistant coating for exposed piping and metal components
- High visibility color and signage options
- Area lighting
- Freeze-protected underground extension at the water inlet connection

Tempered Water Systems

Tempered Water Systems

Electrically Heated & Blended

- 120 Gallon, 30 gpm / 454.2 Liter, 113.6 lpm blending or 300 Gallon, 60 gpm / 1135.6 Liter, 227.1 lpm blending models
- Water delivered from electrically heated vessel and mixed with cold water through electrically controlled fail-safe blending system
- Target 85°F / 29.4°C outlet water
- Plumbed from local facility cold water supply

Custom Design Your System

Create your model to meet the specific needs of your facility



120 Gallon, 30 gpm / 454.2 liter, 113.6 lpm electric blending system, Yellow corrosion-resistant coating, alarm, skid mounted



300 Gallon, 60 gpm / 1135.6 liter, 227.1 lpm electric blending system, Dual recirculation and booster pumps, skid mounted

Wondering if customization is right for you? Call Encon Customer Service Representative with your questions or to place an order at 1-800-283-6266.

Tempered Water Systems

Air Driven

- 400 Gallon / 1514.2 Liter self-contained system
- Designed for areas where plumbed potable water is not always available
- Water delivered from electrically heated vessel at pressure supplied from compressed air cylinders, facility instrument or clean utility air
- Treated water stored at 85°F / 29.4°C
- Uses water from portable transport, temporary supply, or plumbed lines with insufficient volume and pressure



Create your model to meet the specific needs of your facility







Air driven 400 Gallon / 1514.2 Liter, Shower & Eyewash, Grey corrosion-resistant coating, Stainless Steel Eyewash Bowl, Heat reflective tank cover, skid mounted



01110802 32 oz. / 946.4 mL Hydrosep® included with air-driven unit. Reorder in case of 12. See page 51.



Air driven 400 Gallon / 1514.2 Liter, Horizontal tank, Stainless Steel Shower and Eyewash heads, Alarm Light and Horn

Wondering if customization is right for you? Call Encon Customer Service Representative with your questions or to place an order at 1-800-283-6266.

Tempered Water Systems

Tempered Water Systems


Steam Heated & Blended

- Water heated and delivered through a steam heat exchanger and mixed with cold water through a blending valve
- Redundant blending system included for failsafe operation
- Target 85°F / 29.4°C outlet water
- Plumbed from local facility cold water supply and facility steam source

Custom Design Your System

Create your model to meet the specific needs of your facility







Wondering if customization is right for you? Call Encon Customer Service Representative with your questions or to place an order at 1-800-283-6266.


Fail-Safe Blending

Saf-T-Flo® Fail-Safe Blending

- 30 and 60 gpm / 113.6 and 227.1 lpm models
- Target 85°F / 29.4°C outlet water
- Redundant solenoid valves for tempering control
- Fail-safe to cold-water bypass
- Temperature gauge included
- 120 or 240 VAC compatible models
- Bracket or corrosion-resistant case for wall mounting
- Heated wall case option available

PIPING CHOICES

- Galvanized with brass valves
- Polyurethane coated galvanized pipe and brass
- Copper with brass valves
- Stainless steel with stainless steel valves (available for 30 gpm / 113.6 lpm units only)



Model STF60WB120G

60 gpm / 227.1 lpm, Wall Bracket, Galvanized Pipe, Brass Valves, 120V



Model STF30WP120C

30 gpm / 113.6 lpm, Wall Case, Copper Pipe, Brass Valves, 120V







Alarm Systems & Lighting

STANDARD IN ALL SYSTEMS

Installation

For existing or new Shower stations to alert local and/or remote locations when in use

Remote Capability

Spare NO/NC "dry" contacts available on all alarm products; 120V, 3 amp rating on relay remote

WALL/SHOWER MOUNT

- NEMA 3 rated
- Displays red blinking alarm light and rings bell when activated

SHOWER MOUNT OPTIONS

Light & Audio Alarm with Reset Switch

• Provides intermittent pulsing signal when activated; local reset button to silence the audible alarm

Visual Alarm

• Displays red blinking alarm light when activated

Area Light

• Provides constant illumination to emergency station when area vision is compromised; choice of clear, blue or green globe light

ACTIVATION DEVICE OPTIONS

Flow Switch*

• Detects flow through piping when emergency assembly activated; suitable for Class 1 Div. 2 Gp. B, C & D areas

MAP® Switch (Magnetic Activated Proximity Switch)

• Senses shower pull rod and/or push plate activation; Yello-Bowl®, SS bowl, or no bowl options available




Model 02111000

Audible Alarm, Red Alarm Light, contacts for remote, Flow Switch



Shower Mount Model Number Generator



Model #: 02--00

> *Flow switch systems include flexible conduit for top water entry systems. Midpoint or lower-water entry systems require additional conduit and field assembly by others.



Alarm Systems & Lighting




Model 02200000

Remote alarm contacts only, MAP® switch



Model 02100000


Remote alarm contacts only, flow switch





Model 02000300







Audible Alarm, Red Alarm Light, remote contacts, MAP® switch, Green Area Light





Model 02311000 240

Audible Alarm, Red Alarm Light, remote contacts, MAP® switch

AWARENESS 100™ Signage

High visibility graphics and reflective strip on chemical resistant ABS plastic shell.

MOUNTING CHOICES

- Pipe Mount Includes plastic snap rivets for easy and secure mounting on piping stanchion.
- Wall Mount
 Suitable for wall mounting above fountains or below shower (hardware not included).

GRAPHIC CHOICES

- Shower/Eyewash Icons
- Shower/Shower Icons
- Eyewash/Eyewash Icons

DIMENSIONS

• $6\frac{1}{2}$ " × 4" × 20" / 16.5 cm × 10.1 cm × 50.8 cm

SHIP WEIGHT 5 lb / 2.27 kg



Model 00113001

AWARENESS 100™ Sign Yellow, Black Shower/Eyewash, Pipe Mount

Model 00113007

AWARENESS 100™ Sign Green, White Shower/Eyewash, Pipe Mount

Model 00113004

AWARENESS 100™ Sign Orange, Black Shower/Eyewash, Pipe Mount



Model 00113003

AWARENESS 100™ Sign Orange, Black Shower/Shower, Pipe Mount

Model 00113000

AWARENESS 100™ Sign Yellow, Black Shower/Shower, Pipe Mount

Model 00113006

AWARENESS 100™ Sign Green, White Shower/Shower, Pipe Mount



Model 00113017

AWARENESS 100™ Sign Green, White Eyewash/Eyewash, Wall Mount

Model 00113011

AWARENESS 100™ Sign Yellow, Black Eyewash/Eyewash, Wall Mount

Model 00113014

AWARENESS 100[™] Sign Orange, Black Eyewash/Eyewash, Wall Mount



AWARENESS® & AWARENESS 360°™ Signage

AWARENESS® 360°™

High visibility graphics on chemical resistant ABS plastic shell.

MOUNTING

Mounts directly onto shower piping above shower hood.

DIMENSIONS

• $16\frac{1}{5}$ " × 6" / 41.1 cm × 15.2 cm

SHIP WEIGHT 5 lb / 2.27 kg

AWARENESS® SIGNS

High visibility graphics on chemical resistant ABS plastic shell.

MOUNTING CHOICES

Includes tie wraps & trim strip for shower piping stanchion mount.

- For top/bottom entry showers.
- For midpoint entry showers.
- On walls above fountains or below shower.

LANGUAGE CHOICES

- English
- French
- Spanish
- Others upon request

DIMENSIONS

• $9\frac{1}{4}$ " × 8" × 40" / 23.5 cm × 20.3 cm × 101.6 cm

SHIP WEIGHT 5 lb / 2.27 kg

Model 01112911

AWARENESS® Sign Yellow, Shower/Eyewash, Black Letters, Top/Bottom

Model 01112953

AWARENESS® Sign Green, Shower/Eyewash, White Letters, Top/Bottom

Model 01112951

AWARENESS® Sign Orange, Shower/Eyewash, Black Letters, Top/Bottom

Note: Sign with Shower/Shower graphic is also available





Model 35001810 AWARENESS 360° Sign Green, White Shower/Eyewash graphics

Model 01112942

AWARENESS® Sign Orange, Eyewash/ Eyewash, Black Letters, Wall Mount

Model 01112912

AWARENESS® Sign Yellow, Eyewash/Eyewash, Black Letters, Wall Mount

Model 01112946

AWARENESS® Sign Green, Eyewash/Eyewash, White Letters, Wall Mount



Emergency Signs

White placard sign with green letters and graphics.

Suitable for wall mounting or pipe mounting (hardware not included.)

DIMENSIONS

• 7" × 11" & 8" × 18" / 17.8 cm × 27.9 cm & 20.3 cm × 45.7 cm

Model 01112892

Emergency Shower/ Eyewash Sign, 7" × 11" / 17.8 cm × 27.9 cm

Model 01112847

Emergency Shower/ Eyewash Sign, 8" x 18" / 20.3 cm x 45.7 cm



Model 01112893

Emergency Eyewash Sign, 7" × 11" / 17.8 cm × 27.9 cm

Model 01112848

Emergency Eyewash Sign, $8" \times 18" / 20.3 \text{ cm} \times 45.7 \text{ cm}$



Model 01112891

Emergency Shower Sign, $7'' \times 11'' / 17.8 \text{ cm} \times 27.9 \text{ cm}$

Model 01112846

Emergency Shower Sign, $8'' \times 18'' / 20.3$ cm $\times 45.7$ cm



Model 01112900

Drench Hose Station, 7" × 11" / 17.8 cm × 27.9 cm



Shower Accessories & Test Units

MODESTY CURTAIN ASSEMBLY

Provides immediate privacy; easily mounts to most floor mounted shower stations.

Includes ABS plastic blocks, SS rod & support bracket with SS U-bolts to hold assembly in place. Large hooks included.

- $70'' \times 145'' / 177.8 \text{ cm} \times 368.3 \text{ cm}$ high visibility yellow
- Water-resistant PVC nylon-coated heavy duty material with weighted bottom
- Clean Room Option for electronic clean room; highly fluid repellent; $70'' \times 145'' / 177.8 \text{ cm} \times 368.3 \text{ cm}$

SHIP WEIGHT 15 lb / 6.80 kg

SHOWER SHELTER

3-sided wind break structure

- SS clamp & hardware,
- Galvanized steel pipe supports & flanges
- Fiberglass panels and molded roof
- 111" × 45" × 51" / 281.9 cm × 114.3 cm × 129.5 cm

SHIP WEIGHT 345 lb / 156.49 kg

SHOWER TEST UNIT

Light weight, durable and portable PVC-coated nylon test chute for volume flow testing of shower. Large opening with drawstring secures around shower head & hemmed bottom to neatly direct water into bucket

MOBILITY CHOICES

- Cart High visibility yellow with 10" / 25.4 cm semipneumatic back wheels and 6" / 15.2 cm locking front casters
- Dolly A wheel castered square dolly; twist on/off receptacle

SHIP WEIGHT 81 lb / 36.74 kg



Model 01080024 **Shower Shelter** (shower not included)

Model 01052149

Modesty Curtain Assembly (shower not included)



Model 01052187 **Modesty Curtain** Replacement Kit





Model STU1

Shower testing mobile cart with receptacle and chute (shower not included)

Shower Accessories & Test Units

TREADLE KIT ASSEMBLY

ABS foot treadle with chain usable for indoor applications

SHIP WEIGHT 1 lb / 0.45 kg

RETROFIT DRENCH HOSE KITS

- ½" / 1.3 cm Tee connection with squeeze valve and lock open handle
- ½" / 1.3 cm Tee connection with push plate and stay-open chrome plated ball valve
- 6' / 1.8 m Neoprene® rubber hose, yellow ABS head with float off cover, support bracket

SHIP WEIGHT 1 lb / 0.45 kg

DRAIN PAN

- $36'' \times 36'' / 91.4 \text{ cm} \times 91.4 \text{ cm}$ high visibility yellow gel coating, 6" / 15.2 cm depth fiberglass shower catch basin
- Attaches to 1" / 2.5 cm structural open grates in multi-level process areas
- PVC slip joint 2" / 5.1 cm inside, 3" / 7.6 cm
- SS nuts, bolts & washer; galvanized steel clips


SHIP WEIGHT 50 lb / 22.67 kg





Model 01090098

6' / 1.8 m Drench hose with ABS Head & Self-Close Locking BCP Valve, 1/2" / 1.3 cm Tee Connection




Model 01052232 Drain pan assembly,

 $36'' \times 36'' / 91.4 \text{ cm} \times 91.4 \text{ cm}$



Model 01090017

6' / 1.8 m Drench hose with ABS Head, Push Plate CP Valve



Assemblies - Heads & Nozzels



Model 01052123

Eyewash Assembly, ABS Heads & Wye w/Flip Lids, ½" / 1.3 cm Inlet, 3.2 gpm / 12.1 lpm

Model 01052185

Eyewash Assembly, ABS Heads & Wye w/Flip Lids, 3/8" / 1 cm Inlet, 3.2 gpm / 12.1 lpm



Model 01052132

Eyewash Assembly, Acetal Heads w/Hinged Covers, BCP Wye, 1/2" / 1.3 cm Inlet, 2.4 gpm / 9.1 lpm

Model 01052129

Eyewash Assembly, Acetal Heads w/Hinged Covers, BCP Wye, 3/8" / 1 cm Inlet, 2.4 gpm / 9.1 lpm



Model 01052208

Eyewash Assembly, Low Profile, Acetal Heads w/Hinged Covers, BCP Wye, 3/8" / 1 cm Inlet, 2.4 gpm / 9.1 lpm



Model 01052263

Eyewash Assembly, SS Heads & Wye, w/Hinged Covers, 1/2" / 1.3 cm Inlet, 2.5 gpm / 9.5 lpm



Model 01052045

Eyewash Head, Plastic 1/4" / 0.6 cm NPT 1.2 gpm / 4.5 lpm Regulated w/Hinge Cap Model 01052037

Eyewash Head, Plastic 1/4" / 0.6 cm NPT 1.4 gpm / 5.3 lpm Regulated w/Hinge Cap



Model 01052122

Facewash Assembly, ABS Heads & Wye w/Covers, SS Bead Chain, 1/2" / 1.3 cm Inlet, 8 gpm / 30.3 lpm Model 01052189

Facewash Assembly, ABS Heads & Wye w/Covers, SS Bead Chain, 3/4" / 1 cm Inlet, 8 gpm / 30.3 lpm



Model 01052133

Facewash Assembly, ABS Heads & BCP Wye w/Covers, SS Bead Chain, 1/2" / 1.3 cm Inlet, 8 gpm / 30.3 lpm

Model 01052130

Facewash Assembly, ABS Heads & BCP Wye w/Covers, SS Bead Chain, 3%" / 1 cm Inlet, 8 gpm / 30.3 lpm



Model 01052040

Facewash Head only, 1/4" / 0.6 cm NPT Model 01052041

Drench Hose Head only, 3/8" / 1 cm NPT





Model 01054005

Shower Head Assembly, Yellow ABS, integral 20 gpm / 75.7 lpm regulator, 1" / 2.5 cm connection



Model 01054003

Shower Head Assembly, Yellow ABS, integral 30 gpm / 113.6 lpm regulator, 1" / 2.5 cm connection



Model 01055007

Shower Head Assembly, SS, integral 30 gpm / 75.7 lpm regulator, 1" / 2.5 cm connection Model 01055005

Shower Head Assembly, SS, integral 20 gpm / 113.6 lpm regulator, 1" / 2.5 cm connection



Model 01120002

ABS Bowl Cover Kit for Encon Eyewash Yello-Bowl®



Bowls & Covers



Model 01120001 ABS Bowl Cover Kit for Encon Facewash Yello-Bowl®



Model 01110462 Encon Yello-Bowl®, ABS



Model 01110096 Bowl, Stainless Steel



Model 01052020 Facewash Cover with 10" / 25.4 cm SS Bead Chain

Self-Contained



Model 01052113 Eyewash Cover with 8" / 20.3 cm SS Bead Chain



Model 01110764 Hydrosep® water additive - 4pk



Model 01110802 Hydrosep® QT water additive -12/case



Model 01110803 Hydrosep® GL water additive -Four, 1-gallon jugs per case



Model 01110738 Gravity Fed Eyewash "J Hook" mounting bracket



Model 01110741 Mounting bracket for Helios®



Model 00015003 Gravity Fed Eyewash Receptacle, 28 gal / 106 L, grey plastic



Model 01110700 Transport Cart & Receptacle - For Gravity Fed and Aquarion® only Model 01110302 Transport Cart only - For Gravity Fed and Aquarion® only



Model 00014314 Air Gauge for Pressurized Portable



Model 00014337 Hose, $\frac{1}{4}$ " × 8' / 0.6 cm × 243.8 cm Red recoil



Model 01052124 Nozzel assembly, for 00011406 portable drenching hose, 0.4 gpm / 1.5 lpm



Model 01052131 Eyewash head cover, with 8" / 20.3 cm SS bead chain, for 01052111A

51



Model 01105001 Relief valve retrofit kit for selfcontained portable, 115 psi



Model 00011077 Relief valve only, 115 psi



Model 01105005 Drench Hose Assembly



Model 01052111 Eyewash Assembly with ABS Heads, Wye & Covers, SS bead chain, ½" / 1.3 cm Inlet, 0.4 gpm / 1.5 lpm, for self contained portable

Activation Kits & Valves



Model 01052103 Ball Valve Kit for Shower, 11/4" / 3.2 cm BCP, with Nut

Model 01052104 Ball Valve Kit, Shower, 11/4" / 3.2 cm SS with Nut



Model 01052120 Ball Valve Kit, 1" / 2.5 cm for **Emergency Showers**

Model 01052197 Ball Valve Kit, 1" / 2.5 cm horizontal, SS with actuator arm



Model 01052018 Push Plate, SS with Decal



Model 01052101 Ball Valve Kit for Eyewash, $\frac{1}{2}$ " / 1.3 cm BCP, with Nut, Push Plate



Model 01052114 Ball Valve Kit for Eyewash, 1/2" / 1.3 cm Self-drain, with Push Plate



Model 01052001 Pull Rod, SS with Graphic & Pin Fastener, 29" / 73.7 cm



Model 01052065 Ball Valve Kit, 11/4" / 3.2 cm BCP, with 29" / 73.7 cm SS Pull Rod Actuator

Model 01052086 Ball Valve Kit, 1" / 2.5 cm BCP, with 29" / 73.7 cm SS Pull Rod Actuator



Model 01110142 Extension Stem 21/4" / 5.7 cm for ½" / 1.3 cm Ball Valve Freeze Protection



Model 01110147 Extension Stem for 11/4" / 3.2 cm or 1½" / 3.8 cm Ball Valve Freeze Protection



Protection Valves & Fittings



Model 00011082 Freeze Protection Valve, ½" / 1.3 cm opens at 35°F / 2°C



Model 03900006 Freeze Protection Valve Assembly, for exterior drain at 35°F / 2°C



Model 00011081 Scald Protection Valve $\frac{1}{2}$ " / 1.3 cm opens at 95°F / 35°C



Model 03900003 Scald Protection Valve Assembly, for exterior drain at 95°F / 35°C

Alarms



Model 01052098 Strainer Tee Assembly, BCP, ½" / 1.3 cm, 16 Mesh



Model 00013460 Clear Light Globe



Model 00013582 Blue Light Globe



Model 00013571 Green Light Globe



Model 00014606 Red Light Globe



Model 00014685 Flow Switch Assembly, 2 gpm / 7.6 lpm, 1" / 2.5 cm



Model 00014683 Flow Switch Bonnet, 2 gpm / 7.6



Model 00013319M MAP® Switch & Magnet

Curtains & Testing Accessories




Model 01110447 Hook for Modesty Curtain, Zinc Plated



Model 01110593 Hook for Mod Curtain, Stainless Steel



Model 01112894 Shower eyewash inspection tag, yellow



Model 01110469 Eye/Facewash Test Gauge to ANSI Z358.1



Model 02570001 Shower Tester Chute

Representative Performance Data & Limited Warranty Statement

Encon utilizes self-adjusting flow regulators to deliver a constant, even flow under varying hydraulic conditions. ANSI Standard Z358.1 requires a minimum dynamic (flowing) pressure of 30 psi. It is important to include dynamic pressure drops through the potable water system when calculating system hydraulic requirements. Dynamic pressure above 80 psi to shower and eyelfacewash equipment is not recommended.

	Dynamic Pressure	GPM / LPM Output		
Eyewash Dual-stream Heads	30	3.2 / 12.1		
•	40	3.4 / 12.9		
	50	3.5 / 13.2		
	60	3.6 / 13.6		
	70	3.7 / 14		
Eye/Facewash Dual-stream Heads	30	7.0 / 26.5		
	40	7.5 / 28.4		
	50	8.0 / 30.3		
	60	8.5 / 32.2		
	70	9.0 / 34.1		
Regulated Showers on Combination Units				
with 20 gpm / 75.7 lpm shower & 8 gpm / 30.3 lpm FV	V 40	28 / 106		
with 30 gpm / 113.6 lpm shower & 8 gpm / 30.3 lpm F	W 30	38 / 143.8		
with 20 gpm / 75.7 lpm shower & 3.5 gpm / 13.2 lpm	EW 40	23.5 / 89		
with 30 gpm / 113.6 lpm shower & 3.5 gpm / 13.2 lpm	EW 30	33.5 / 126.8		
Hand-held Drench Hose with squeeze	30	3.6 / 13.6		
valve, black-braided hose (Nylon recoil	40	4.5 / 17		
hose requires minimum 45 psi)	50	4.8 / 18.2		
·	60	4.9 / 18.5		
	70	5.0 / 18.9		
Hand-held Drench Hose with stay-open	30	5.3 / 20.1		
valve, black-braided hose (Nylon recoil	40	6.0 / 22.7		
hose requires minimum 45 psi)	50	6.9 / 26.1		
•	60	7.5 / 28.4		
	70	7.8 / 29.5		

WITH RESPECT TO EMERGENCY SHOWERS (THE "EQUIPMENT") ENCON SAFETY PRODUCTS HEREBY DISCLAIMS ALL WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTY OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE, EXCEPT AS HEREAFTER PROVIDED.

ENCON warrants the Equipment to be free of defects in material and workmanship if properly installed, cared for, and operated under normal conditions, with competent supervision, and in accordance with ENCON installation, operating, and maintenance instructions. With respect to the Equipment, ENCON's only obligation under this warranty is to repair or replace such components of the Equipment:

As prove defective and ENCON is so advised within one year after shipment, and shall appear to ENCON's satisfaction to have been defective in material or workmanship. However, in no event shall ENCON be liable under this Warranty unless ENCON is provided an opportunity to inspect such material or workmanship and, at its option, allowed to repair or replace such material or workmanship.

No warranty is given in connection with any portion of the Equipment, which is altered or rebuilt without ENCON's express written consent.

ENCON shall not be liable for loss, damage, or expense, arising directly, or indirectly, as a consequence of use of the Equipment with other products, or from any other cause, other than ENCON's obligation to repair or replace defective components of the Equipment as expressly provided in this warranty statement.

THE CUSTOMER'S PURCHASE AND ACCEPTANCE OF THE EQUIPMENT SHALL BE DEEMED TO BE ITS AGREEMENT TO BE BOUND BY THE TERMS AND PROVISIONS OF THIS WARRANTY.

Under no circumstances will ENCON ever be liable for indirect or consequential loss or damage arising out of the ownership or use of the Equipment.

The terms of this warranty shall apply to any replacement parts installed on, or furnished in connection with, the Equipment.

The equipment was designed using information and specifications supplied by the customer and sized and fitted, using common piping elements, accordingly. ENCON is not liable for the correctness of any design, materials or construction criteria furnished or specified in the equipment performance specification documents.



Numerical Parts Index

Part No.	<u>Page No.</u>	Part No.	<u>Page No.</u>	Part No.	<u>Page No.</u>	Part No.	<u>Page No.</u>
00011077		01050207			52	01110700	
00011081		01050209			53	01110738	51
00011082 00013319M		01050209P20. 01050210			52	01110741	51
00013317111		01050216			52	01110764	21
00013571		01050217			52	01110764	51
00013582		01050217P20.			51	01110786S .	
00014314		01050217P20P			52	011107935 .	
00014337		01050217PBC.			52		
00014606 00014683		01050219 01050219P20 .			50	01110802	
00014685		01050217720.			51	01110803	
00015003		01050221P20.			50	01112846	
00015006		01050223		01052130	50	01112847	47
00113000		01050223P20.			51	01112848	47
00113001		01050224			50	01112891	47
00113003 00113004		01050224P20.			50		47
00113004		01050228 01050230			43		47
00113007		01050230P20.			50		53
00113011		01050230P20P			48		
00113014		01050230PBC.			50		47
00113017		01050232			52	01112911	
01030101 01030103		01050232P20 . 01050234			50	01112912	46
01030103		01050234 01050234P20 .			50	01112942	46
01030104		01050234P20P			49	01112946	46
01030301		01050234P20S			14	01112951	46
01030302		01050234PBC.			14	01112953	46
01030310		01050234SBC.			14	01114021	
01030316PBC. 01030401		01050236 01050236P20 .			14	01120001	
01030401		01050236P203			14		
01030416		010502367 203			50	01120002	
01035401	29	01050251		01054005	50		44
01035402		01050260			50	02000300	
01035410		01050264			50	02100000	
01035415PBC. 01035501		01050264S20 . 01050266P20P			12) 12	02111000	43
01035503		01050266PBC.			12	02200000	44
01035511		01050276) 12	02211300	44
01035601		01050277			12	02311000 240	44
01035603		01050281			12	02570001	
01035604 01035606		01050281P20 .			48		53
01035606		01050288 01050288P20 .			49	03900006.	
01038801			6	01101001			
01040103	30	01050290P20.	6	01103001	25		46
01040135		01050293			23	AQ100	
01045001		01050293P20.			23	AQ100H130.	
01045001PBC. 01045001SBC.		01050294 01050294P20 .			23	AQ100S	
0104500156C.		01050294F20.			23	AQ110	20
01045002SBC.		01050314P20.			22	AQ111	20
01045005		01050317	16		22	AQ120	20
01045006		01050317P20.			22	FRSSC-G	17
01045008 01045010		01050362			22	FRSSC-GP20	
01045010		01050362P20. 01050376			52	HE100	
01045501PBC.		01050370			52		
01045501SBC.		01050470			24	HF100	
01045502	31	01050470S20.	11		24	HS100	
01045505		01050471S20S			24		i 42
01045506 01045502SBC.		01050471SBC. 01052001			51		: 42
010455025BC. 01045510		01052001			52	STF60WB1200	i 42
01045514		01052020			21	STU1	48
01045601	30	01052037	50	01110302	51	TF34B230000	1 34
01050201		01052040			53	TF35B5376300) 34
01050201P20.		01052041			51	TF36B200030	
01050205 01050205P20.		01052045 01052065			53	TP21323230	
3 10302031 ZU.		3100 <u>2</u> 003		01110373		11 2 1020200	

SAFETY



SOLUTIONS







6825 West Sam Houston Pkwy. North, Houston, TX 77041 Toll Free: 1(800) AT ENCON 1(800) 283-6266 Fax: (713) 466-1703 customerservice@enconsafety.com www.enconsafety.com ESEWFULL-08-25-2017

WALL CASES









PARTS



ENGINEERED





QUALITY