

Pebble Lights - 24V

RGB+360Peb-24v / RGB+180Peb-24v

Lens: clear, frosted

Pitch: 4-, 6-, 12-inch, custom


View Angle: 360-, 180-degs.

Bulb Count: 5-, 10-, 25-light, custom

Wire Color: black, green, white, clear

Ends: thru-connect, terminated

Output	
LED Type	SMD5050
LED Channels	R-G-B
Greyscale	16-bit, 65,536 dimming levels*
LED Quantity	2 / pixel
Viewing Angle	360-degrees (or 180-deg., option)
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 200L (to be verified)
Max Distance before Power Injection	approx. 180-feet (to be verified)
Electrical & Safety	
Input Voltage	24 VDC
Current	0.015 Amps
Power	0.36 Watts
Wire	20 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+4A-24v
Certifications	(c)UL listed, IP 65, CE
Physical	
Size	2.0 x 0.875 x 0.5" [^]
Weight	approx. 0.256 oz. per bulb
Housing	polycarbonate
Mounting bracket	yes, 2-screw hole adjustable clip, add-on
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



Distributed by:
Minleon USA
5267 Simpson Ferry Road
Mechanicsburg, PA
(717) 763-1055
www.MinleonUSA.com



* 8-bit via DDP. ^180Peb-24v size is similar to RGB+Peb12v.
Specifications as of January 2020 and are subject to change.

