



TrikLit 100's RGB+Trik100

Pitch: 4-, 6-, 12-inch, custom

Bulb Count: 5-, 10-, 25-light, custom

Wire Color: black, green, white

Ends: thru-connect, terminated

Output	
LED Type	SMD5050
LED Channels	R-G-B
Greyscale	16-bit, 65,536 dimming levels*
LED Quantity	8
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 30L
Max Distance before Power Injection	approx. 25-feet
Electrical & Safety	
Input Voltage	12 VDC
Current	0.112 Amps
Power	1.344 Watts
Wire	22 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB +5A-12V
Certifications	(c)UL listed, IP 65
Physical	
Diameter	100mm
Weight	approx. 3.2 oz. per bulb
Housing	polycarbonate
Bulb Style	frosted
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



Distributed by:
Minleon USA
 5267 Simpson Ferry Road
 Mechanicsburg, PA
 (717) 763-1055
www.MinleonUSA.com

* 8-bit via DDP.

Specifications as of February 2020 and are subject to change.

