

**Pitch:** 4-, 6-, 12-inch, custom

**Bulb Count:** 5-, 10-, 25-light, custom

**Wire Color:** black, green, white, clear

**Ends:** thru-connect, terminated, eye-hole loop

Output	
LED Type	SMD5050
LED Channels	RGB or RGBW (warm white)
Greyscale	16-bit, 65,536 dimming levels*
LED Quantity	2
Viewing Angle	360-degrees
Control	
Individually Addressable	yes
Control Systems	NDB+ (ArtNet, E1.31), WEC+, MC+
Max Lights before power injection	approx. 125L
Max Distance before Power Injection	approx. 100-feet
Electrical & Safety	
Input Voltage	12 VDC
Current	0.028 Amps
Power	0.336 Watts
Wire	22 AWG, 3C, UV protected
Inline power injection	via Minleon Power T+'s & RGB+5A-12V
Certifications	(c)UL listed, IP 65, CE
Physical	
Diameter	42mm
Weight	approx. 1.2 oz. per bulb
Housing	polycarbonate
Bulb Style	frosted
Connector Type	LLT twist-lock
Operating Temperature	Neg -20 to +50 Cel. / Neg -4 to +122 Far.



**Distributed by:**  
**Minleon USA**  
 5267 Simpson Ferry Road  
 Mechanicsburg, PA  
 (717) 763-1055  
[www.MinleonUSA.com](http://www.MinleonUSA.com)

\* 8-bit via DDP.

Specifications as of February 2020 and are subject to change.

