

Interior Glow Kit

Installation Instructions

www.DCSLighting.com



Like and Follow us on Facebook and Instagram @dcslighting

Thanks for choosing a DCS product that is designed and manufactured in the USA!

Installation Time: 20-30 Minutes

Tools Needed: Wire strippers/crimpers.

Step 1: Locate a flat metal surface underneath each front seat and attach the lights (Fig 1). Make sure lights and wire are mounted in a manner that it will not be affected by seat movement. Run wires along either side of center console, below the carpet and under the dash. All wires will go to the same location in front of shifter under the dash (Fig 2)

Step 2: On 4 door kits, repeat step 1 on the rear seats using the lights marked "REAR". If seats fold down be sure to route wire will it will not be affected by movement. We encourage slowly folding seat down while checking wires to be sure. Route wire under carpet and along center console until it is grouped with other connectors.

Step 3: Locate a flat metal surface under both driver and passenger side of the dash and attach lights. Route wire towards center of dash until it is grouped with

other connectors. Be careful not to route wire in a manner where it will affect the brake, gas, and clutch pedals.

Step 4: Plug all connections into the main harness. Attach black ground wire to a chassis ground. On Jeep JK Wranglers a good chassis ground can be found to the left of the pedal assembly in the form of a stud with a 10mm nut. Red positive wire should be connected to a relay/fuse protected power source.

Note: Once lights are on move them around under seats and dash to see what placement yields the best illumination results. Once the desired lighting is achieved be sure that the location will not be affected by seat movement.



Figure 1



Figure 2