



# HINO SPECIFICATION SHEET

	Hino 300 614 SWB MT	Hino 300 614 SWB AT	Hino 300 614 LWB MT	Hino 300 714 SWB MT	Hino 300 714 SWB AT	Hino 300 714 LWB MT	Hino 300 714 LWB CC AT	Hino 300 816 SWB MT	Hino 300 816 SWB AT	Hino 300 816 LWB CC AT	Hino 300 916 LWB MT	Hino 300 916 LWB AT	Hino 300 916 LWB CC AT
<b>Engine</b>													
Bore x Stroke (mm)	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118	104 X 118
Piston Displacement (cc)	4009	4009	4009	4009	4009	4009	4009	4009	4009	4009	4009	4009	4009
Compression Ratio	18:1	18:1	18:1	18:1	18:1	18:1	18:1	18:1	18:1	18:1	18:1	18:1	18:1
Configuration	In-line Cylinder	In-line Cylinder	In-line Cylinder	In-line Cylinder	In-line	In-line Cylinder	In-line Cylinder	In-line	In-line	In-line	In-line	In-line	In-line
Engine Oil Cooler	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes
Euro Emission Status	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3	Euro 3
Firing Order	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2	1 - 3 - 4 - 2
Max Eng. Speed (rpm)	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100
No. of Main Bearings	5	5	5	5	5	5	5	5	5	5	5	5	5
Number of Cylinders	4	4	4	4	4	4	4	4	4	4	4	4	4
Number of Valves per Cylinder	4	4	4	4	4	4	4	4	4	4	4	4	4
Power (EEC/ISO NET) (kW @ rpm)	100 @ 2500	100 @ 2500	100 @ 2500	100 @ 2500	100 @ 2500	100 @ 2500	100 @ 2500	110 @ 2800	110 @ 2800	110 @ 2800	110 @ 2800	110 @ 2800	110 @ 2800
Torque (Nm @ rpm)	392 @ 1600	392 @ 1600	392 @ 1600	392 @ 1600	392 @ 1600	392 @ 1600	392 @ 1600	420 @ 1400	420 @ 1400	420 @ 1400	420 @ 1400	420 @ 1400	420 @ 1400
Type of Cylinders	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners	Dry Liners
Valve Configuration	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead	Overhead
<b>Mass Data (kg)</b>													
A - Front	2300	2300	2300	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100
A - Rear	4360	4360	4360	5100	5100	5100	5100	5500	5500	5500	6200	6200	6200
Approx. Body + Payload Allowance	3365	3325	3295	4030	3990	4010	3760	4980	4950	4715	5915	5885	5665
D/T	7300	7300	7300	8300	8300	8300	8300	9300	9300	9300	10300	10300	10300
GA - Front	2600	2600	2600	3100	3100	3100	3100	3100	3100	3100	3100	3100	3100
GA - Rear	4400	4400	4400	5100	5100	5100	5100	5500	5500	5500	6200	6200	6200
GCM	7300	7300	7300	8300	8300	8300	8300	9300	9300	9300	10300	10300	10300





# HINO SPECIFICATION SHEET

	Hino 300 614 SWB MT	Hino 300 614 SWB AT	Hino 300 614 LWB MT	Hino 300 714 SWB MT	Hino 300 714 SWB AT	Hino 300 714 LWB MT	Hino 300 714 LWB CC AT	Hino 300 816 SWB MT	Hino 300 816 SWB AT	Hino 300 816 LWB CC AT	Hino 300 916 LWB MT	Hino 300 916 LWB AT	Hino 300 916 LWB CC AT
<b>Fuel Tank</b>													
Capacity (ℓ)	80	80	100	100	100	100	100	100	100	100	150	150	100
<b>Safety and Security</b>													
Airbags	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger
Seatbelt Pre-tensioner	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger
Transponder Key Immobiliser	•	•	•	•	•	•	•	•	•	•	•	•	•
Daytime Running Lights	•	•	•	•	•	•	•	•	•	•	•	•	•
Side Impact Beams	•	•	•	•	•	•	•	•	•	•	•	•	•
Microdot Vehicle Identification	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>Comfort and Convenience</b>													
Air Conditioner	•	•	•	•	•	•	•	•	•	•	•	•	•
Key Activated Central Locking	•	•	•	•	•	•	•	•	•	•	•	•	•
Electric Windows	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger	Driver & Passenger
AM / FM Radio with CD Player, USB, AUX, Bluetooth	•	•	•	•	•	•	•	•	•	•	•	•	•
Storage Facilities	•	•	•	•	•	•	•	•	•	•	•	•	•
<b>Service and Maintenance Plans</b>													
Service Intervals*	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km	20 000 km
Warranty	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km	24 Months Unlimited km
<b>Advalorem Tariff Headings</b>													
	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)	8704.22.90(0)
* Please refer to Hino Care Disclaimer													