

Numerical

Q1. Sound was measured at 80 DBA and 76dBA in the operator's cabin on a tractor. What is the RMS sound pressures correspond to both the sound pressure level [GATE 1998]

Q2. Sound was measured at 80 DB in the operator's cabin on a tractor. What is the RMS sound pressure and also determine the resultant sound pressure in decibels, if the sound pressure is increased eight times [GATE 2001]

Q3. The measures value of the acceleration at the cab floor of the tractor is 2 m/s^2 . If the ratio of the frequency of the tractor chassis and the underamped natural frequency of the set is 2 and the damping ratio is zero. Find out the vibration intensity experienced by the operator (A) 0.4 M/S^2 (B) 0.66 M/S^2 (C) 0.88 M/S^2 (D) 1.16 M/S^2 [GATE2006]

Q4. The differential equation of motion for a single degree of freedom mass-spring damped system is $8 \frac{D^2x}{Dt^2} + 5 \frac{Dx}{Dt} + 12x = 0$. If the units of mass, length and time are Kg, m and sec respectively. The natural frequency of the vibration is in

(A) 0.42 rad /sec (B) 0.52 rad /sec (C) 1.22 rad /sec (D) 1.83 rad /sec [GATE2006]

Q5. A tractor seat suspension system with a seat and operator mass of 90 kg has a seat suspension damping rate of 350 N s m^{-1} . If the spring rate of the system is 5 N mm^{-1} , the damping ratio of the system is [GATE 2009]

(A) 0.13 (B) 0.26 (C) 0.39 (D) 0.52

Q6. The tractor seat vibrates with a frequency of 1 Hz when there is no damping, when damping is provided the frequency of damped vibration is reduced by 10%. The damping factor is [GATE 2010]

(A) 0.21 (B) 0.39 (C) 0.44 (D) 0.93

Q7. The range of frequency of vertical vibration of tractor most harmful to the operator's body at a root mean square acceleration of 1.0 m/s^2 in Hertz [GATE 2011]

(A) 0.4 — 0.8 (B) 4.0 — 8.0 (C) 400 — 800 (D) 4000 — 8000

Q8. During a test, sound level was measured as 90 dB in the operator's cabin on a tractor. Taking reference sound pressure as $2 \times 10^{-5} \text{ N m}^{-2}$, the measured RMS sound pressure in N m^{-2} is [GATE 2013]

(A) 6.32 (B) 6.32×10^{-1} (C) 1.8×10^{-3} (D) 6.32×10^{-10}

Q9. For a reference sound pressure of 2×10^{-5} N m⁻², the sound level measured at the operator's workspace of a tractor was 80 dB. If the RMS sound pressure is increased by eight times, the resulting sound pressure level in dB, will be _____. [GATE 2015]

Q10. Natural frequency of an undamped operator seat is 5 Hz, and combined weight of the seat and the operator is 880 N. If there are four springs fitted in parallel below the operator seat, the spring rate (or stiffness) of each spring in kN m⁻¹ is _____. [GATE 2016]

GateForAll (Coaching Institute of GATE Agriculture Engineering, BankAFO, ARS & ICAR)