

TH-200CE O2 Auto-dispenser (general type) will feed and cut oxygen absorbers or desiccant pouches from a continuous strip on a reel or belt. It handles pouches up to 2 inches wide and 0.39-inch-thick at a speed up to 130 cuts per minute. An electronic sensor accurately registers cut position, to ensure highly reliable cuts. It would stop cutting if detecting possible false cut with danger of opening the sachet. Configuration is easily set up through a touch panel. This unit can be a master or a slave to an existing line. It is ideal for narrow, limited space applications.

The table below shows some technical specification of the machine:

MODEL	GENERAL TYPE
Cutting rates (max.)	130 cuts per minute for a 35 mm pouch
Min web width	30 mm / 1.2 in.
Max web width	50 mm / 2 in.
Min. packet length	35 mm / 1.4 in.
Max packet length	80 mm / 3.15 in.
Max web thickness	10 mm / 0.39 in.
Machine dimension ⁽¹⁾ (L x W x H)	830 x 600 x 504 (mm) / 32.7 x 23.6 x 19.8 (in.)
Machine weight	80 -100kgs / 176-220 lbs.
Power consumption	600 w
Power supply	AC 110V 60Hz (Optional 220v 60HZ)
Operating environment	Indoor temperature: 0°C~40°C, without condensate
Materials	Stainless steel and aluminum alloy
Interface language	English
Critical components	PLC Interface screen Servo motor and controller Photoelectric sensor switching device
Alarm system	Alarm lamp and buzzer alarm
Delivery Time	8-11 Days
FOB	San Bernardino, CA 92408
Payment Terms	50% down and balance, 30-days after delivery.

Additional Features



- Open Exit Chute Virtually Jam Free
- Color Touch Screen for Easy Operator Setup
- Cantilever Design offers Complete Access and a Full View of Feeding Process
- Portable an Adjustable Height Stand*
- Easy to Mount over or Alongside a Production Line
- A sensor to prevent false cuts that may cause a sachet to open and contaminate the production line.

This unit can be a master or a slave to an existing line. A sensor will trigger when to dispense or can receive a cutting signal from your packing machine.

*Note: support.

A supporting frame supplied with the machine will allow the adjustment of height between 700-1000 mm.

