

## FEATURES & BENEFITS

Meets or exceeds the following requirements:

- Optimum cold-weather performance & start-up protection.
- Superior wear protection for all engine types.
- Unique high film strength technology for modern motoring.
- Exceptional oxidation resistance.

**CANMORE FULLY SYNTHETIC MOTOR OIL** is formulated with ultra-pure synthetic blend base oils and superior additive technology.

**CANMORE FULLY SYNTHETIC BLEND MOTOR OIL** exceeds the stringent requirements of API SP and surpasses the stricter limits defined by foreign and domestic automakers for some of their high-est-performing engines.

Full Synthetic motor oil contains unique film strength additives to enhance the protective barrier between critical engine components. It is also designed to resist the oxidative break-down and shearing loss associated with operation at higher temperatures maintaining a strong and durable film for maximum engine protection.

## SPECIFICATIONS

- API SP
- API SN PLUS, SN

## TYPICAL RESULTS

SAE GRADE	5W-40
DENSITY @ 15°C kg/L (D4052)	0.85
VISCOSITY (D445)	
cSt @ 40°C	90.3
cSt @ 100°C	14.7
VISCOSITY INDEX (D2270)	171
POUR POINT (D5949), °C	-46
FLASH POINT (D7094), °C	203
CCS VISCOSITY (D5293), cP	5668 @ -30°C

## ORDER CODE

Size	5W-40
1 LITRE	FWW0003915
5 LITRE	FWW0003930

You should always consult your Owners Manual when selecting any lubricant product. Check with your sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice.

**CANMORE Petroleum**  
1502 Cyrville Road,  
Gloucester, Ontario, Canada  
[www.canmorepetroleum.com](http://www.canmorepetroleum.com)  
**1-613 800 1214**

