

FEATURES & BENEFITS

- Optimum cold-weather performance & start-up protection
- Superior wear protection for all engine types.
- Unique high film strength technology for modern motoring
- Exceptional oxidation resistance for severe-service & turbocharged applications

SPECIFICATIONS

- API SP
- API SN PLUS, SN
- ILSAC GF-6A
- Chrysler MS-6395
- Ford WSS-M2C962-A1, WSS-M2C947-B1 (0W-20)
- Ford WSS-M2C961-A1, WSS-M2C946-B1 (5W-30)

CANMORE FULL SYNTHETIC MOTOR OIL is formulated with ultra-pure synthetic blend base oils and superior additive technology.

CANMORE FULL SYNTHETIC MOTOR OIL exceeds the stringent requirements of API SP and surpasses the stricter limits defined by foreign and domestic automakers for some of their highest-performing engines. Full Synthetic motor oil contains unique film strength additives to enhance the protective barrier between critical engine components. It is also designed to resist the oxidative break-down and shearing loss associated with operation at higher temperatures maintaining a strong and durable film for maximum engine protection.

TYPICAL RESULTS

TESTING PARAMETERS	0W-20	5W-30
DENSITY @ 15°C kg/L (D4052)	0.84	0.85
VISCOSITY (D445)		
cSt @ 40°C	42.2	60.7
cSt @ 100°C	8.0	10.8
VISCOSITY INDEX (D2270)	165	171
POUR POINT (D97), °C	-42	-39
FLASH POINT (D93A), °C	203	204
CCS VISCOSITY (D5293), cP	5250 @ -35°C	3680 @ -30°C

ORDER CODE

SIZE	0W-20	5W-30
1 LITRE	FWW0004015	FWW0004115
5 LITRE	N/A	FWW0004130

You should always consult your Owners Manual when selecting any lubricant product. Check with your sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice.

CANMORE Petroleum
1502 Cyrville Road,
Gloucester, Ontario, Canada
www.canmorepetroleum.com
1-613 800 1214

