

CANMORE HDD HEAVY DUTY CONVENTIONAL 40 MONOGRADE MOTOR OIL

CANMORE HEAVY DUTY 40 MONOGRADE OIL is blended from select high viscosity base stocks and low-ash additives with sufficient detergent to ensure excellent engine cleanliness, minimize ring-sticking, reduce liner-scuffing, prevent sludge formation, reduce bearing corrosion and cut back on engine rusting.

CANMORE HEAVY DUTY 40 MONOGRADE OIL was developed to meet the needs of mixed fleet operators in order to reduce inventory. CANMORE HEAVY DUTY 40 MONOGRADE OIL can be used in high speed diesel engines, construction and certain marine diesel applications.

FEATURES & BENEFITS

- Combats corrosion and moisture
- Promotes engine cleanliness
- Excellent resistance to high temperature
- Low ash less than 1%

SPECIFICATIONS

Meets the Following Industry Standards

- API CF / CF-2
- API SF
- Allison C4
- CAT TO-2
- Detroit Diesel DFS 93K222



TYPICAL RESULTS

TEST METHOD	40
Density (D4052) @15°C kg/L	0.89
Viscosity (D445) cSt @40°C	138.5
Viscosity (D445) cSt @100°C	14.3
Viscosity Index (D2270)	101
Pour Point (D97) °C	-18
Flash Point (D93) °C	204
Total Base Number (D2896) mgKOH/g	7.1

ORDER CODE

SIZE	40
1 LITRE	FWW0002715
5 LITRE	FWW0002730
18.9 LITRE	FWW0002740
205 L	FWW0002750

