

### FEATURES & BENEFITS

- Superior cold start-up protection
- Exceptional wear protection
- Resists degradation due to heat and oxidation
- High-temperature volatility resistance
- Reduces deposit and sludge formation



**CANMORE SYNTHETIC BLEND MOTOR OIL** is formulated with ultra-pure synthetic blend base oils and advanced additive technology.

**CANMORE SYNTHETIC BLEND MOTOR OIL** exceeds the stringent requirements of API SP and surpasses the stricter limits defined by foreign and domestic automakers for some of their highest-performing engines.

Synthetic blends help reduce high-temperature volatility and burn-off, which can cause conventional oils to break down and evaporate. The unique detergent package helps prevent the formation of high-temperature deposits and sludge, maintaining engine performance and durability when it matters most.

### SPECIFICATIONS

- API SP (5W-20, 5W-30, 10W-30, 10W-40)
- API SN PLUS, SN (5W-20, 5W-30, 10W-30, 10W-40)
- API SN (20W-50)
- ILSAC GF-6A (5W-20, 5W-30, 10W-30)
- Ford WSS-M2C960-A1, WSS-M2C945-B1 (5W-20)
- Ford WSS-M2C961-A1, WSS-M2C946-B1 (5W-30)

You should always consult your Owners Manual when selecting any lubricant product. Check with your sales Representative for latest product approvals. Please note, these are typical performance indicators and can change without notice.

**CANMORE Petroleum**  
1502 Cyrville Road,  
Gloucester, Ontario, Canada  
[www.canmorepetroleum.com](http://www.canmorepetroleum.com)  
**1-613 800 1214**



### TYPICAL RESULTS

SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W-50
DENSITY @ 15°C kg/L (D4052)	0.85	0.85	0.86	0.86	0.87
VISCOSITY (D445) cSt @ 40°C	45.1	56.2	58.2	89.4	152.3
VISCOSITY (D445) cSt @ 100°C	8.1	9.8	9.6	13.7	18.2
VISCOSITY INDEX (D2270)	154	161	149	157	133
POUR POINT (D5949), °C	-48	-47	-45	-42	-27
FLASH POINT (D7094), °C	203	204	205	206	203
v	4390 @ -30°C	4763 @ -30°C	3718 @ -25°C	5007 @ -25°C	5705 @ -15°C

### ORDER CODE

SAE GRADE	5W-20	5W-30	10W-30	10W-40	20W-50
1 LITRE	FWW0003315	FWW0003415	FWW0003515	FWW0003615	FWW0002415
5 LITRE	FWW0003330	FWW0003430	FWW0003530	FWW0003630	FWW0002430
205 LITRE	N/A	N/A	N/A	FWW0003650	N/A

You should always consult your Owners Manual when selecting any lubricant product.  
Check with your sales Representative for latest product approvals.  
Please note, these are typical performance indicators and can change without notice.

**CANMORE Petroleum**  
1502 Cyrville Road,  
Gloucester, Ontario, Canada  
[www.canmorepetroleum.com](http://www.canmorepetroleum.com)  
**1-613 800 1214**

