

BSR-V

Series

性能資料

PERFORMANCE DATA

INVERTER SCREW REFRIGERANT COMPRESSOR

變頻式螺旋冷媒壓縮機

P-BSR-V-990702

復盛股份有限公司

Fu Sheng Industrial Co., Ltd.

Toll-Free Number: 080-0881953



BSR-V R-134a Water Cooled Performance Data(70Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	53.9	17.7	67.6	18.3	85.1	18.8	104.3	19.8	117.2	20.5	126.6	21.2	0.0	0.0	0.0	0.0
	38	47.1	20.4	60.2	21.0	75.5	21.7	94.9	22.0	107.1	22.6	116.2	22.9	140.9	24.1	169.6	25.6
	50	37.3	25.0	49.2	26.0	63.0	27.0	79.2	28.0	90.1	28.8	98.3	29.1	122.4	29.8	148.6	31.1
	60	0.0	0.0	38.6	31.4	51.0	32.7	65.6	33.9	75.3	34.7	82.9	35.1	103.1	36.2	128.6	36.6
BSR216	30	66.3	21.6	83.2	22.4	104.6	23.1	128.2	24.3	144.1	25.2	155.7	26.0	0.0	0.0	0.0	0.0
	38	58.0	25.0	73.9	25.8	92.8	26.5	116.6	27.0	131.6	27.7	142.8	28.1	173.3	29.6	208.5	31.4
	50	45.9	30.7	60.4	31.9	77.4	33.1	97.4	34.4	110.7	35.2	120.9	35.7	150.4	36.5	182.6	38.1
	60	0.0	0.0	47.5	38.5	62.6	40.0	80.7	41.6	92.5	42.6	101.9	43.0	126.7	44.3	158.1	44.8
BSR311	30	83.4	26.8	104.6	27.8	131.5	28.6	161.2	30.1	181.2	31.2	195.8	32.3	0.0	0.0	0.0	0.0
	38	72.9	31.0	93.0	32.0	116.7	32.9	146.7	33.5	165.6	34.3	179.6	34.8	217.9	36.6	262.2	38.9
	50	57.7	38.0	76.0	39.6	97.4	41.1	122.5	42.6	139.3	43.7	152.0	44.2	189.2	45.3	229.7	47.2
	60	0.0	0.0	59.7	47.7	78.8	49.6	101.5	51.5	116.4	52.8	128.2	53.3	159.4	55.0	198.8	55.6
BSR314	30	105.9	33.1	132.8	34.3	167.0	35.3	204.7	37.2	230.1	38.5	248.7	39.8	0.0	0.0	0.0	0.0
	38	92.6	38.2	118.1	39.4	148.2	40.6	186.3	41.3	210.2	42.3	228.1	43.0	276.7	45.2	333.0	48.1
	50	73.2	46.9	96.5	48.8	123.7	50.7	155.6	52.6	176.8	53.9	193.0	54.6	240.3	55.9	291.7	58.2
	60	0.0	0.0	75.8	58.9	100.1	61.2	128.8	63.6	147.8	65.1	162.7	65.8	202.4	67.8	252.4	68.6
BSR316	30	124.8	38.6	156.5	40.1	196.8	41.2	241.2	43.4	271.1	44.9	293.0	46.5	0.0	0.0	0.0	0.0
	38	109.1	44.6	139.2	46.0	174.6	47.4	219.5	48.2	247.7	49.4	268.7	50.2	326.0	52.8	392.3	56.1
	50	86.3	54.7	113.7	57.0	145.7	59.1	183.3	61.4	208.4	62.9	227.5	63.7	283.1	65.2	343.7	67.9
	60	0.0	0.0	89.4	68.7	117.9	71.5	151.8	74.2	174.1	76.0	191.7	76.7	238.5	79.1	297.5	80.0
BSR321	30	136.7	42.3	171.4	43.9	215.6	45.1	264.2	47.5	297.0	49.2	320.9	50.9	0.0	0.0	0.0	0.0
	38	119.5	48.9	152.4	50.4	191.2	51.9	240.4	52.8	271.3	54.1	294.4	55.0	357.2	57.8	429.8	61.4
	50	94.5	59.9	124.6	62.4	159.6	64.8	200.8	67.2	228.2	68.9	249.2	69.7	310.1	71.4	376.5	74.4
	60	0.0	0.0	97.9	75.3	129.2	78.3	166.3	81.3	190.8	83.3	210.0	84.0	261.2	86.7	325.8	87.7

BSR-V R-134a Water Cooled Performance Data(70Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR323	30	161.4	49.8	202.4	51.7	254.4	53.1	311.8	55.9	350.5	57.9	378.8	59.9	0.0	0.0	0.0	0.0
	38	141.0	57.5	179.9	59.3	225.7	61.1	283.7	62.1	320.3	63.6	347.4	64.7	421.6	68.0	507.3	72.3
	50	111.6	70.5	147.0	73.5	188.4	76.3	237.0	79.1	269.4	81.1	294.1	82.1	366.1	84.1	444.3	87.6
	60	0.0	0.0	115.5	88.6	152.4	92.1	196.3	95.6	225.2	98.0	247.9	98.9	308.3	102.0	384.6	103.2
BSR324	30	179.0	55.2	224.5	57.2	282.2	58.8	345.9	62.0	388.8	64.2	420.2	66.3	0.0	0.0	0.0	0.0
	38	156.4	63.7	199.6	65.7	250.4	67.7	314.7	68.8	355.3	70.5	385.4	71.7	467.6	75.4	562.7	80.1
	50	123.8	78.1	163.1	81.4	209.0	84.5	262.9	87.6	298.8	89.8	326.2	90.9	406.1	93.1	492.9	97.0
	60	0.0	0.0	128.2	98.2	169.1	102.1	217.7	106.0	249.8	108.5	275.0	109.6	342.0	113.0	426.6	114.3
BSR326	30	192.8	59.0	241.8	61.2	304.0	62.9	372.6	66.3	418.8	68.6	452.6	71.0	0.0	0.0	0.0	0.0
	38	168.5	68.2	215.0	70.3	269.7	72.4	339.0	73.6	382.7	75.4	415.2	76.7	503.7	80.6	606.1	85.7
	50	133.3	83.6	175.7	87.1	225.1	90.4	283.2	93.8	321.9	96.1	351.4	97.3	437.4	99.6	531.0	103.8
	60	0.0	0.0	138.1	105.0	182.2	109.2	234.5	113.3	269.1	116.1	296.2	117.2	368.4	120.9	459.6	122.3
BSR413	30	234.2	70.7	293.7	73.3	369.2	75.3	452.6	79.4	508.7	82.2	549.8	85.0	0.0	0.0	0.0	0.0
	38	204.7	81.7	261.1	84.2	327.6	86.7	411.8	88.2	464.8	90.4	504.3	91.8	611.8	96.6	736.2	102.6
	50	161.9	100.2	213.4	104.3	273.4	108.3	344.0	112.3	391.0	115.1	426.8	116.6	531.3	119.3	644.9	124.4
	60	0.0	0.0	167.7	125.8	221.2	130.8	284.9	135.8	326.8	139.1	359.8	140.4	447.5	144.8	558.2	146.5
BSR415	30	261.2	78.5	327.5	81.4	411.8	83.7	504.7	88.2	567.3	91.3	613.1	94.5	0.0	0.0	0.0	0.0
	38	228.2	90.7	291.2	93.6	365.3	96.3	459.3	98.0	518.4	100.4	562.4	102.0	682.3	107.3	821.0	114.0
	50	180.6	111.2	238.0	115.8	304.9	120.2	383.7	124.8	436.0	127.9	476.0	129.5	592.5	132.5	719.2	138.1
	60	0.0	0.0	187.0	139.8	246.7	145.3	317.7	150.8	364.4	154.5	401.3	156.0	499.0	160.9	622.5	162.7
BSR421	30	297.3	89.1	372.8	92.5	468.7	95.0	574.5	100.1	645.8	103.7	697.9	107.2	0.0	0.0	0.0	0.0
	38	259.8	103.0	331.5	106.2	415.8	109.3	522.7	111.2	590.0	113.9	640.1	115.8	776.6	121.8	934.5	129.4
	50	205.5	126.3	270.9	131.5	347.1	136.5	436.7	141.6	496.3	145.2	541.8	146.9	674.4	150.5	818.6	156.8
	60	0.0	0.0	212.8	158.7	280.8	164.9	361.6	171.2	414.8	175.4	456.7	177.1	568.0	182.6	708.5	184.7

BSR-V R-134a Water Cooled Performance Data(70Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR423	30	327.9	98.1	411.2	101.7	517.0	104.5	633.7	110.2	712.3	114.0	769.8	117.9	0.0	0.0	0.0	0.0
	38	286.6	113.3	365.6	116.8	458.6	120.3	576.6	122.3	650.8	125.3	706.1	127.4	856.7	133.9	1030.8	142.4
	50	226.7	138.9	298.8	144.7	382.8	150.2	481.7	155.8	547.4	159.7	597.6	161.7	743.9	165.5	903.0	172.5
	60	0.0	0.0	234.8	174.5	309.8	181.4	398.9	188.3	457.6	193.0	503.8	194.8	626.5	200.9	781.5	203.2
BSR424	30	365.0	108.7	457.7	112.7	575.4	115.8	705.3	122.1	792.8	126.4	856.8	130.7	0.0	0.0	0.0	0.0
	38	318.9	125.6	407.0	129.5	510.5	133.3	641.8	135.6	724.4	138.9	785.8	141.2	953.5	148.5	1147.3	157.8
	50	252.3	154.0	332.6	160.4	426.1	166.5	536.1	172.7	609.3	177.0	665.2	179.2	827.9	183.5	1005.0	191.2
	60	0.0	0.0	261.3	193.5	344.8	201.1	443.9	208.8	509.3	213.9	560.7	215.9	697.4	222.7	869.8	225.3
BSR426	30	408.5	117.3	512.3	121.7	634.4	126.9	777.7	133.8	874.1	138.5	944.6	143.2	0.0	0.0	0.0	0.0
	38	357.0	135.5	455.5	139.8	571.4	143.9	707.6	148.5	798.6	152.2	866.4	154.6	1051.3	162.6	1265.0	172.8
	50	282.5	166.2	372.2	173.0	477.0	179.6	600.1	186.3	682.0	191.0	744.5	193.4	912.9	200.9	1108.1	209.4
	60	0.0	0.0	292.5	208.8	385.9	217.0	496.9	225.3	570.0	230.8	627.7	233.0	780.6	240.3	959.1	246.7

BSR-V R-134a Water Cooled Performance (60Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	52.6	17.9	66.0	18.6	83.0	19.1	101.7	20.1	114.3	20.8	123.6	21.6	0.0	0.0	0.0	0.0
	38	46.0	20.7	58.7	21.4	73.6	22.0	92.5	22.4	104.5	22.9	113.3	23.3	137.5	24.5	165.4	26.0
	50	36.4	25.4	48.0	26.4	61.4	27.4	77.3	28.5	87.9	29.2	95.9	29.5	119.4	30.3	144.9	31.5
	60	0.0	0.0	37.7	31.9	49.7	33.2	64.0	34.4	73.4	35.3	80.9	35.6	100.6	36.7	125.4	37.1
BSR216	30	64.7	22.0	81.1	22.8	102.0	23.4	125.0	24.7	140.5	25.5	151.9	26.4	0.0	0.0	0.0	0.0
	38	56.5	25.4	72.1	26.2	90.5	26.9	113.8	27.4	128.4	28.1	139.3	28.5	169.0	30.0	203.4	31.9
	50	44.7	31.1	59.0	32.4	75.5	33.6	95.0	34.9	108.0	35.8	117.9	36.2	146.8	37.1	178.2	38.6
	60	0.0	0.0	46.3	39.1	61.1	40.6	78.7	42.2	90.3	43.2	99.4	43.6	123.6	45.0	154.2	45.5
BSR311	30	81.4	27.2	102.1	28.2	128.3	29.0	157.3	30.6	176.8	31.7	191.1	32.8	0.0	0.0	0.0	0.0
	38	71.1	31.5	90.7	32.5	113.8	33.4	143.1	34.0	161.5	34.8	175.2	35.4	212.6	37.2	255.8	39.5
	50	56.3	38.6	74.2	40.2	95.0	41.7	119.6	43.3	135.9	44.4	148.3	44.9	184.6	46.0	224.1	47.9
	60	0.0	0.0	58.3	48.5	76.9	50.4	99.0	52.3	113.6	53.6	125.0	54.1	155.5	55.8	194.0	56.4
BSR314	30	103.3	33.6	129.6	34.9	162.9	35.8	199.7	37.8	224.5	39.1	242.6	40.4	0.0	0.0	0.0	0.0
	38	90.3	38.8	115.2	40.0	144.5	41.2	181.7	41.9	205.1	43.0	222.5	43.7	270.0	45.9	324.9	48.8
	50	71.4	47.6	94.2	49.6	120.6	51.5	151.8	53.4	172.5	54.7	188.3	55.4	234.4	56.7	284.6	59.1
	60	0.0	0.0	74.0	59.8	97.6	62.2	125.7	64.5	144.2	66.1	158.8	66.8	197.5	68.8	246.3	69.6
BSR316	30	121.8	39.2	152.7	40.7	192.0	41.8	235.3	44.1	264.5	45.6	285.8	47.2	0.0	0.0	0.0	0.0
	38	106.4	45.3	135.8	46.7	170.3	48.1	214.1	48.9	241.7	50.1	262.2	50.9	318.1	53.6	382.8	56.9
	50	84.2	55.5	110.9	57.8	142.2	60.0	178.9	62.3	203.3	63.9	221.9	64.6	276.2	66.2	335.3	69.0
	60	0.0	0.0	87.2	69.8	115.0	72.6	148.1	75.3	169.9	77.2	187.1	77.9	232.7	80.3	290.2	81.3
BSR321	30	133.4	43.0	167.3	44.6	210.3	45.8	257.8	48.3	289.7	50.0	313.1	51.7	0.0	0.0	0.0	0.0
	38	116.6	49.6	148.7	51.2	186.6	52.7	234.5	53.6	264.7	54.9	287.2	55.8	348.5	58.7	419.3	62.4
	50	92.2	60.8	121.5	63.4	155.7	65.8	195.9	68.2	222.7	70.0	243.1	70.8	302.6	72.5	367.3	75.5
	60	0.0	0.0	95.5	76.5	126.0	79.5	162.2	82.5	186.1	84.5	204.9	85.3	254.9	88.0	317.9	89.0

BSR-V R-134a Water Cooled Performance (60Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR323	30	157.4	50.6	197.4	52.4	248.2	53.9	304.2	56.8	342.0	58.8	369.6	60.8	0.0	0.0	0.0	0.0
	38	137.6	58.4	175.5	60.2	220.2	62.0	276.8	63.1	312.4	64.6	339.0	65.7	411.3	69.1	494.9	73.4
	50	108.8	71.6	143.4	74.6	183.8	77.4	231.2	80.3	262.8	82.3	286.9	83.3	357.1	85.3	433.5	88.9
	60	0.0	0.0	112.7	90.0	148.7	93.5	191.5	97.1	219.7	99.5	241.9	100.4	300.8	103.6	375.2	104.8
BSR324	30	174.6	56.0	219.0	58.1	275.3	59.7	337.5	62.9	379.3	65.1	409.9	67.4	0.0	0.0	0.0	0.0
	38	152.6	64.7	194.7	66.7	244.3	68.7	307.1	69.9	346.6	71.6	376.0	72.7	456.2	76.5	549.0	81.3
	50	120.7	79.3	159.1	82.6	203.9	85.8	256.5	89.0	291.5	91.2	318.3	92.3	396.2	94.5	480.9	98.5
	60	0.0	0.0	125.0	99.7	165.0	103.6	212.4	107.6	243.7	110.2	268.3	111.2	333.7	114.7	416.2	116.1
BSR326	30	188.1	59.9	235.9	62.1	296.6	63.8	363.5	67.3	408.6	69.7	441.6	72.1	0.0	0.0	0.0	0.0
	38	164.4	69.2	209.8	71.4	263.1	73.5	330.8	74.8	373.4	76.6	405.0	77.8	491.4	81.8	591.4	87.0
	50	130.1	84.9	171.4	88.4	219.6	91.7	276.3	95.2	314.0	97.6	342.8	98.8	426.7	101.1	518.0	105.4
	60	0.0	0.0	134.7	106.6	177.7	110.9	228.8	115.1	262.5	117.9	289.0	119.0	359.4	122.7	448.3	124.2
BSR413	30	228.5	71.8	286.5	74.4	360.2	76.5	441.5	80.6	496.3	83.5	536.4	86.3	0.0	0.0	0.0	0.0
	38	199.7	82.9	254.8	85.5	319.6	88.0	401.7	89.6	453.5	91.7	492.0	93.2	596.9	98.0	718.2	104.2
	50	158.0	101.7	208.2	105.9	266.8	109.9	335.6	114.0	381.4	116.9	416.4	118.3	518.3	121.2	629.2	126.2
	60	0.0	0.0	163.6	127.8	215.8	132.8	277.9	137.9	318.8	141.2	351.0	142.6	436.6	147.0	544.5	148.8
BSR415	30	254.8	79.7	319.5	82.7	401.7	85.0	492.4	89.6	553.5	92.7	598.2	95.9	0.0	0.0	0.0	0.0
	38	222.7	92.1	284.1	95.0	356.4	97.8	448.1	99.5	505.7	101.9	548.7	103.6	665.7	108.9	801.0	115.7
	50	176.2	112.9	232.2	117.6	297.5	122.1	374.3	126.7	425.4	129.8	464.4	131.4	578.0	134.6	701.7	140.2
	60	0.0	0.0	182.4	141.9	240.7	147.5	309.9	153.1	355.6	156.9	391.5	158.4	486.9	163.3	607.3	165.2
BSR421	30	290.0	90.5	363.7	93.9	457.3	96.4	560.5	101.7	630.0	105.2	680.8	108.8	0.0	0.0	0.0	0.0
	38	253.5	104.6	323.4	107.8	405.7	111.0	510.0	112.9	575.6	115.7	624.5	117.6	757.7	123.6	911.7	131.4
	50	200.5	128.2	264.3	133.5	338.6	138.6	426.0	143.8	484.2	147.4	528.6	149.2	657.9	152.8	798.7	159.2
	60	0.0	0.0	207.7	161.1	274.0	167.4	352.8	173.8	404.7	178.1	445.6	179.8	554.2	185.4	691.2	187.5

BSR-V R-134a Water Cooled Performance (60Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR423	30	319.9	99.6	401.2	103.3	504.4	106.1	618.2	111.8	694.9	115.8	751.0	119.7	0.0	0.0	0.0	0.0
	38	279.6	115.0	356.7	118.6	447.5	122.1	562.5	124.2	634.9	127.2	688.8	129.3	835.8	136.0	1005.7	144.5
	50	221.2	141.0	291.5	146.9	373.5	152.4	469.9	158.2	534.1	162.1	583.0	164.1	725.7	168.0	881.0	175.1
	60	0.0	0.0	229.0	177.2	302.2	184.2	389.1	191.2	446.4	195.9	491.5	197.7	611.3	203.9	762.5	206.3
BSR424	30	356.1	110.4	446.5	114.5	561.4	117.6	688.1	124.0	773.5	128.3	835.9	132.7	0.0	0.0	0.0	0.0
	38	311.2	127.5	397.0	131.5	498.0	135.3	626.1	137.7	706.7	141.1	766.7	143.4	930.2	150.7	1119.3	160.2
	50	246.2	156.3	324.4	162.8	415.7	169.0	523.0	175.3	594.4	179.7	648.9	181.9	807.8	186.3	980.5	194.1
	60	0.0	0.0	254.9	196.4	336.4	204.2	433.1	212.0	496.9	217.2	547.1	219.2	680.3	226.1	848.6	228.7
BSR426	30	398.6	119.1	499.8	123.5	619.0	128.8	758.7	135.8	852.8	140.6	921.6	145.4	0.0	0.0	0.0	0.0
	38	348.3	137.6	444.4	141.9	557.5	146.0	690.3	150.8	779.2	154.5	845.3	157.0	1025.6	165.1	1234.1	175.5
	50	275.6	168.7	363.2	175.7	465.3	182.3	585.5	189.2	665.4	193.9	726.4	196.3	890.6	204.0	1081.1	212.6
	60	0.0	0.0	285.4	211.9	376.5	220.3	484.8	228.7	556.1	234.3	612.4	236.5	761.5	243.9	935.7	250.5

BSR-V R-134a Water Cooled Performance (50Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	51.3	18.2	64.3	18.9	80.9	19.4	99.2	20.4	111.5	21.2	120.5	21.9	0.0	0.0	0.0	0.0
	38	44.8	21.0	57.2	21.7	71.8	22.3	90.2	22.7	101.8	23.3	110.5	23.6	134.1	24.9	161.3	26.4
	50	35.5	25.8	46.8	26.8	59.9	27.9	75.4	28.9	85.7	29.6	93.5	30.0	116.4	30.7	141.3	32.0
	60	0.0	0.0	36.7	32.4	48.5	33.7	62.4	34.9	71.6	35.8	78.8	36.1	98.0	37.3	122.3	37.7
BSR216	30	63.1	22.3	79.1	23.1	99.5	23.8	121.9	25.1	137.0	25.9	148.1	26.8	0.0	0.0	0.0	0.0
	38	55.1	25.8	70.3	26.6	88.2	27.3	110.9	27.8	125.2	28.5	135.8	29.0	164.8	30.5	198.3	32.4
	50	43.6	31.6	57.5	32.9	73.6	34.1	92.7	35.4	105.3	36.3	115.0	36.8	143.1	37.6	173.7	39.2
	60	0.0	0.0	45.2	39.7	59.6	41.3	76.7	42.8	88.0	43.9	96.9	44.3	120.5	45.7	150.3	46.2
BSR311	30	79.4	27.6	99.5	28.7	125.1	29.5	153.4	31.1	172.4	32.1	186.3	33.2	0.0	0.0	0.0	0.0
	38	69.3	31.9	88.5	32.9	111.0	33.9	139.5	34.5	157.5	35.3	170.9	35.9	207.3	37.8	249.5	40.1
	50	54.9	39.2	72.3	40.8	92.6	42.3	116.6	43.9	132.5	45.0	144.6	45.6	180.0	46.7	218.5	48.6
	60	0.0	0.0	56.8	49.2	75.0	51.1	96.5	53.1	110.7	54.4	121.9	54.9	151.6	56.6	189.1	57.3
BSR314	30	100.8	34.1	126.3	35.4	158.9	36.3	194.7	38.3	218.9	39.7	236.5	41.0	0.0	0.0	0.0	0.0
	38	88.1	39.4	112.3	40.6	140.9	41.8	177.2	42.6	200.0	43.6	216.9	44.3	263.2	46.6	316.7	49.5
	50	69.7	48.3	91.8	50.3	117.6	52.2	148.0	54.2	168.2	55.6	183.6	56.2	228.6	57.6	277.5	60.0
	60	0.0	0.0	72.1	60.7	95.2	63.1	122.6	65.5	140.6	67.1	154.8	67.8	192.5	69.9	240.1	70.7
BSR316	30	118.7	39.8	148.9	41.3	187.2	42.4	229.4	44.7	257.9	46.3	278.7	47.9	0.0	0.0	0.0	0.0
	38	103.7	46.0	132.4	47.4	166.0	48.8	208.7	49.7	235.6	50.9	255.6	51.7	310.1	54.4	373.2	57.8
	50	82.1	56.4	108.2	58.7	138.6	60.9	174.4	63.2	198.2	64.8	216.4	65.6	269.3	67.2	326.9	70.0
	60	0.0	0.0	85.0	70.8	112.2	73.6	144.4	76.4	165.7	78.3	182.4	79.1	226.8	81.5	282.9	82.5
BSR321	30	130.0	43.6	163.1	45.2	205.0	46.5	251.3	49.0	282.5	50.7	305.3	52.4	0.0	0.0	0.0	0.0
	38	113.6	50.4	145.0	52.0	181.9	53.5	228.7	54.4	258.1	55.7	280.0	56.6	339.7	59.6	408.8	63.3
	50	89.9	61.8	118.5	64.3	151.8	66.8	191.0	69.3	217.1	71.0	237.0	71.9	295.0	73.6	358.1	76.7
	60	0.0	0.0	93.1	77.6	122.9	80.7	158.2	83.7	181.5	85.8	199.8	86.6	248.5	89.3	309.9	90.4

BSR-V R-134a Water Cooled Performance (50Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR323	30	153.5	51.3	192.5	53.2	242.0	54.7	296.6	57.7	333.4	59.7	360.3	61.7	0.0	0.0	0.0	0.0
	38	134.1	59.3	171.1	61.1	214.7	62.9	269.9	64.0	304.6	65.6	330.5	66.7	401.0	70.1	482.5	74.5
	50	106.1	72.7	139.9	75.7	179.2	78.6	225.5	81.5	256.2	83.6	279.7	84.6	348.2	86.6	422.7	90.3
	60	0.0	0.0	109.9	91.3	145.0	94.9	186.7	98.6	214.2	101.0	235.8	101.9	293.3	105.1	365.8	106.3
BSR324	30	170.3	56.8	213.5	59.0	268.4	60.6	329.0	63.9	369.9	66.1	399.7	68.4	0.0	0.0	0.0	0.0
	38	148.8	65.7	189.8	67.7	238.1	69.7	299.4	70.9	337.9	72.7	366.6	73.8	444.8	77.6	535.2	82.5
	50	117.7	80.5	155.1	83.9	198.8	87.0	250.1	90.3	284.2	92.6	310.3	93.7	386.3	95.9	468.9	100.0
	60	0.0	0.0	121.9	101.2	160.8	105.2	207.1	109.2	237.6	111.9	261.6	112.9	325.3	116.4	405.8	117.8
BSR326	30	183.4	60.8	230.0	63.1	289.2	64.8	354.5	68.3	398.4	70.7	430.6	73.1	0.0	0.0	0.0	0.0
	38	160.3	70.3	204.5	72.5	256.5	74.6	322.5	75.9	364.0	77.7	394.9	79.0	479.2	83.1	576.6	88.3
	50	126.8	86.1	167.1	89.7	214.1	93.1	269.4	96.6	306.2	99.0	334.3	100.2	416.1	102.6	505.1	107.0
	60	0.0	0.0	131.3	108.2	173.3	112.5	223.1	116.8	255.9	119.7	281.8	120.8	350.4	124.6	437.1	126.0
BSR413	30	222.8	72.9	279.4	75.6	351.2	77.6	430.5	81.9	483.9	84.7	522.9	87.6	0.0	0.0	0.0	0.0
	38	194.7	84.2	248.4	86.8	311.6	89.4	391.7	90.9	442.1	93.1	479.7	94.6	582.0	99.5	700.3	105.8
	50	154.0	103.2	203.0	107.5	260.1	111.6	327.2	115.7	371.9	118.7	406.0	120.1	505.4	123.0	613.4	128.1
	60	0.0	0.0	159.5	129.7	210.4	134.8	271.0	139.9	310.8	143.4	342.3	144.7	425.6	149.2	530.9	151.0
BSR415	30	248.4	80.9	311.5	83.9	391.7	86.2	480.1	90.9	539.7	94.1	583.2	97.3	0.0	0.0	0.0	0.0
	38	217.1	93.5	277.0	96.4	347.5	99.2	436.8	101.0	493.1	103.4	534.9	105.1	649.0	110.5	781.0	117.5
	50	171.8	114.6	226.4	119.4	290.1	123.9	364.9	128.6	414.8	131.8	452.8	133.4	563.6	136.6	684.1	142.3
	60	0.0	0.0	177.9	144.0	234.7	149.7	302.2	155.4	346.7	159.2	381.7	160.7	474.7	165.8	592.1	167.7
BSR421	30	282.8	91.9	354.6	95.3	445.8	97.9	546.5	103.2	614.3	106.8	663.8	110.5	0.0	0.0	0.0	0.0
	38	247.1	106.1	315.3	109.5	395.5	112.7	497.2	114.6	561.2	117.4	608.9	119.3	738.7	125.5	888.9	133.4
	50	195.5	130.1	257.7	135.5	330.1	140.7	415.4	145.9	472.1	149.6	515.4	151.4	641.5	155.0	778.7	161.6
	60	0.0	0.0	202.5	163.5	267.1	170.0	344.0	176.4	394.6	180.7	434.5	182.5	540.3	188.2	674.0	190.4

BSR-V R-134a Water Cooled Performance (50Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR423	30	311.9	101.1	391.1	104.8	491.8	107.7	602.8	113.5	677.6	117.5	732.2	121.5	0.0	0.0	0.0	0.0
	38	272.6	116.8	347.8	120.4	436.3	123.9	548.5	126.1	619.1	129.2	671.6	131.3	814.9	138.0	980.5	146.7
	50	215.7	143.1	284.2	149.1	364.2	154.7	458.2	160.5	520.7	164.6	568.5	166.6	707.6	170.6	858.9	177.7
	60	0.0	0.0	223.3	179.9	294.7	187.0	379.4	194.1	435.2	198.8	479.2	200.7	596.0	207.0	743.4	209.4
BSR424	30	347.2	112.0	435.4	116.2	547.4	119.4	670.9	125.8	754.1	130.3	815.0	134.7	0.0	0.0	0.0	0.0
	38	303.4	129.4	387.1	133.5	485.6	137.4	610.4	139.8	689.0	143.2	747.5	145.5	907.0	153.0	1091.3	162.6
	50	240.0	158.7	316.3	165.2	405.3	171.5	510.0	178.0	579.6	182.4	632.7	184.7	787.6	189.1	956.0	197.0
	60	0.0	0.0	248.6	199.4	328.0	207.3	422.3	215.1	484.4	220.4	533.4	222.5	663.3	229.5	827.4	232.1
BSR426	30	388.6	120.9	487.3	125.4	603.5	130.7	739.7	137.8	831.5	142.7	898.6	147.6	0.0	0.0	0.0	0.0
	38	339.6	139.6	433.3	144.0	543.5	148.2	673.0	153.1	759.7	156.8	824.2	159.4	1000.0	167.6	1203.3	178.1
	50	268.7	171.2	354.1	178.3	453.7	185.1	570.8	192.0	648.7	196.9	708.2	199.2	868.3	207.1	1054.0	215.8
	60	0.0	0.0	278.2	215.1	367.1	223.6	472.7	232.1	542.2	237.8	597.0	240.1	742.5	247.6	912.3	254.2

BSR-V R-134a Water Cooled Performance (40Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	50.0	18.5	62.7	19.1	78.8	19.7	96.6	20.7	108.6	21.5	117.4	22.2	0.0	0.0	0.0	0.0
	38	43.7	21.3	55.8	22.0	69.9	22.6	87.9	23.0	99.2	23.6	107.7	24.0	130.6	25.2	157.2	26.8
	50	34.6	26.2	45.6	27.2	58.4	28.3	73.4	29.3	83.5	30.1	91.1	30.4	113.4	31.2	137.7	32.5
	60	0.0	0.0	35.8	32.9	47.2	34.2	60.8	35.5	69.8	36.3	76.8	36.7	95.5	37.8	119.2	38.3
BSR216	30	61.5	22.6	77.1	23.5	96.9	24.1	118.8	25.4	133.5	26.3	144.3	27.2	0.0	0.0	0.0	0.0
	38	53.7	26.1	68.5	27.0	86.0	27.8	108.1	28.2	122.0	28.9	132.3	29.4	160.6	30.9	193.2	32.9
	50	42.5	32.1	56.0	33.4	71.8	34.7	90.3	35.9	102.6	36.9	112.0	37.3	139.4	38.2	169.3	39.8
	60	0.0	0.0	44.0	40.3	58.1	41.9	74.8	43.5	85.8	44.5	94.4	44.9	117.4	46.4	146.5	46.9
BSR311	30	77.3	28.1	97.0	29.1	121.9	29.9	149.4	31.5	168.0	32.6	181.5	33.7	0.0	0.0	0.0	0.0
	38	67.6	32.4	86.2	33.4	108.1	34.4	136.0	35.0	153.5	35.9	166.5	36.4	202.0	38.3	243.1	40.7
	50	53.5	39.7	70.5	41.4	90.3	43.0	113.6	44.6	129.1	45.7	140.9	46.2	175.4	47.4	212.9	49.3
	60	0.0	0.0	55.4	49.9	73.0	51.9	94.0	53.9	107.9	55.2	118.8	55.7	147.7	57.5	184.3	58.1
BSR314	30	98.2	34.6	123.1	35.9	154.8	36.9	189.7	38.9	213.3	40.3	230.5	41.6	0.0	0.0	0.0	0.0
	38	85.8	40.0	109.5	41.2	137.3	42.5	172.6	43.2	194.8	44.2	211.4	45.0	256.5	47.3	308.6	50.3
	50	67.9	49.0	89.5	51.1	114.6	53.0	144.2	55.0	163.9	56.4	178.9	57.1	222.7	58.4	270.3	60.9
	60	0.0	0.0	70.3	61.6	92.7	64.0	119.4	66.5	137.0	68.1	150.8	68.8	187.6	70.9	234.0	71.7
BSR316	30	115.7	40.4	145.1	41.9	182.4	43.0	223.5	45.4	251.3	47.0	271.5	48.6	0.0	0.0	0.0	0.0
	38	101.1	46.7	129.0	48.1	161.8	49.5	203.4	50.4	229.6	51.6	249.1	52.5	302.2	55.2	363.6	58.6
	50	80.0	57.2	105.4	59.6	135.0	61.8	169.9	64.2	193.1	65.8	210.8	66.6	262.4	68.2	318.5	71.0
	60	0.0	0.0	82.8	71.9	109.3	74.7	140.7	77.6	161.4	79.5	177.7	80.2	221.0	82.7	275.7	83.7
BSR321	30	126.7	44.2	158.9	45.9	199.8	47.1	244.9	49.7	275.2	51.5	297.5	53.2	0.0	0.0	0.0	0.0
	38	110.7	51.1	141.3	52.7	177.2	54.3	222.8	55.2	251.5	56.5	272.8	57.5	331.0	60.4	398.3	64.2
	50	87.6	62.7	115.5	65.3	147.9	67.7	186.1	70.3	211.5	72.1	230.9	72.9	287.5	74.7	348.9	77.8
	60	0.0	0.0	90.7	78.7	119.7	81.9	154.1	85.0	176.8	87.1	194.7	87.9	242.1	90.6	302.0	91.7

BSR-V R-134a Water Cooled Performance (40Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR323	30	149.6	52.1	187.5	54.0	235.8	55.5	289.0	58.5	324.9	60.6	351.1	62.6	0.0	0.0	0.0	0.0
	38	130.7	60.2	166.8	62.0	209.2	63.9	263.0	65.0	296.8	66.6	322.0	67.6	390.7	71.1	470.1	75.6
	50	103.4	73.8	136.3	76.8	174.6	79.7	219.7	82.7	249.7	84.8	272.6	85.8	339.3	87.9	411.8	91.6
	60	0.0	0.0	107.1	92.7	141.3	96.3	181.9	100.0	208.7	102.5	229.8	103.4	285.8	106.7	356.4	107.9
BSR324	30	165.9	57.7	208.0	59.8	261.6	61.5	320.6	64.8	360.4	67.1	389.5	69.4	0.0	0.0	0.0	0.0
	38	145.0	66.6	185.0	68.7	232.0	70.7	291.7	72.0	329.3	73.7	357.2	74.9	433.4	78.8	521.5	83.7
	50	114.7	81.7	151.2	85.1	193.7	88.3	243.7	91.6	277.0	93.9	302.4	95.1	376.3	97.4	456.8	101.5
	60	0.0	0.0	118.8	102.7	156.7	106.7	201.8	110.8	231.5	113.5	254.9	114.6	317.0	118.2	395.4	119.5
BSR326	30	178.7	61.7	224.1	64.0	281.8	65.8	345.4	69.3	388.2	71.8	419.5	74.2	0.0	0.0	0.0	0.0
	38	156.2	71.3	199.3	73.5	250.0	75.7	314.2	77.0	354.7	78.9	384.8	80.2	466.9	84.3	561.8	89.6
	50	123.6	87.4	162.8	91.0	208.6	94.5	262.5	98.0	298.3	100.5	325.7	101.7	405.4	104.2	492.1	108.5
	60	0.0	0.0	128.0	109.8	168.8	114.2	217.4	118.5	249.4	121.4	274.6	122.6	341.5	126.4	425.9	127.9
BSR413	30	217.1	73.9	272.2	76.7	342.2	78.8	419.5	83.1	471.5	86.0	509.5	88.9	0.0	0.0	0.0	0.0
	38	189.7	85.4	242.0	88.1	303.6	90.7	381.7	92.2	430.8	94.5	467.4	96.0	567.1	101.0	682.3	107.3
	50	150.1	104.7	197.8	109.1	253.4	113.2	318.8	117.5	362.4	120.4	395.6	121.9	492.4	124.8	597.7	130.0
	60	0.0	0.0	155.4	131.6	205.1	136.8	264.0	142.0	302.9	145.5	333.5	146.8	414.7	151.4	517.3	153.2
BSR415	30	242.1	82.1	303.6	85.2	381.7	87.5	467.8	92.3	525.8	95.5	568.3	98.8	0.0	0.0	0.0	0.0
	38	211.5	94.9	269.9	97.8	338.6	100.7	425.6	102.5	480.4	105.0	521.2	106.7	632.4	112.2	761.0	119.2
	50	167.4	116.3	220.6	121.1	282.6	125.7	355.6	130.5	404.1	133.7	441.2	135.4	549.1	138.6	666.6	144.4
	60	0.0	0.0	173.3	146.2	228.7	151.9	294.4	157.7	337.8	161.6	371.9	163.1	462.5	168.2	576.9	170.2
BSR421	30	275.5	93.2	345.5	96.7	434.4	99.3	532.5	104.7	598.5	108.4	646.8	112.1	0.0	0.0	0.0	0.0
	38	240.8	107.7	307.2	111.1	385.4	114.3	484.5	116.3	546.8	119.1	593.3	121.1	719.8	127.3	866.1	135.3
	50	190.5	132.0	251.1	137.5	321.7	142.7	404.7	148.1	460.0	151.8	502.1	153.7	625.0	157.3	758.7	163.9
	60	0.0	0.0	197.3	165.9	260.3	172.5	335.1	179.0	384.5	183.4	423.3	185.1	526.5	190.9	656.7	193.2

BSR-V R-134a Water Cooled Performance (40Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR423	30	303.9	102.5	381.1	106.4	479.2	109.3	587.3	115.2	660.2	119.2	713.5	123.3	0.0	0.0	0.0	0.0
	38	265.6	118.5	338.9	122.2	425.1	125.8	534.4	127.9	603.2	131.1	654.4	133.2	794.0	140.1	955.4	148.9
	50	210.1	145.3	276.9	151.3	354.8	157.0	446.4	162.9	507.4	167.0	553.9	169.0	689.4	173.1	836.9	180.4
	60	0.0	0.0	217.6	182.5	287.1	189.7	369.7	196.9	424.1	201.8	466.9	203.7	580.7	210.0	724.3	212.5
BSR424	30	338.3	113.7	424.2	117.9	533.3	121.1	653.7	127.7	734.8	132.2	794.1	136.7	0.0	0.0	0.0	0.0
	38	295.6	131.3	377.2	135.4	473.1	139.4	594.8	141.8	671.4	145.3	728.3	147.7	883.7	155.3	1063.4	165.0
	50	233.9	161.0	308.2	167.7	394.9	174.1	496.9	180.6	564.7	185.1	616.5	187.4	767.4	191.9	931.5	199.9
	60	0.0	0.0	242.2	202.3	319.6	210.3	411.5	218.3	472.0	223.7	519.7	225.8	646.3	232.8	806.2	235.6
BSR426	30	378.6	122.7	474.8	127.2	588.0	132.7	720.7	139.9	810.1	144.8	875.5	149.7	0.0	0.0	0.0	0.0
	38	330.9	141.7	422.2	146.1	529.6	150.4	655.8	155.3	740.2	159.1	803.0	161.7	974.3	170.1	1172.4	180.7
	50	261.8	173.7	345.0	180.9	442.1	187.8	556.2	194.9	632.1	199.8	690.1	202.2	846.1	210.1	1027.0	219.0
	60	0.0	0.0	271.1	218.3	357.7	226.9	460.6	235.6	528.3	241.3	581.7	243.6	723.5	251.2	888.9	258.0

BSR-V R-134a Water Cooled Performance (30Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	48.7	18.7	61.0	19.4	76.8	20.0	94.1	21.0	105.8	21.8	114.3	22.5	0.0	0.0	0.0	0.0
	38	42.5	21.6	54.3	22.3	68.1	23.0	85.6	23.4	96.6	23.9	104.8	24.3	127.2	25.6	153.0	27.2
	50	33.7	26.5	44.4	27.6	56.8	28.7	71.5	29.8	81.3	30.5	88.7	30.9	110.4	31.6	134.1	32.9
	60	0.0	0.0	34.9	33.3	46.0	34.7	59.2	36.0	67.9	36.9	74.8	37.2	93.0	38.4	116.0	38.8
BSR216	30	59.8	23.0	75.0	23.8	94.4	24.5	115.7	25.8	130.0	26.7	140.5	27.6	0.0	0.0	0.0	0.0
	38	52.3	26.5	66.7	27.4	83.7	28.2	105.2	28.6	118.8	29.3	128.9	29.8	156.3	31.4	188.1	33.3
	50	41.4	32.5	54.5	33.9	69.9	35.2	87.9	36.5	99.9	37.4	109.1	37.8	135.8	38.8	164.8	40.4
	60	0.0	0.0	42.8	40.9	56.5	42.5	72.8	44.1	83.5	45.2	91.9	45.6	114.4	47.0	142.6	47.6
BSR311	30	75.3	28.5	94.4	29.5	118.7	30.3	145.5	32.0	163.5	33.1	176.7	34.2	0.0	0.0	0.0	0.0
	38	65.8	32.9	83.9	33.9	105.3	34.9	132.4	35.5	149.4	36.4	162.1	37.0	196.7	38.9	236.7	41.3
	50	52.1	40.3	68.6	42.0	87.9	43.6	110.6	45.2	125.7	46.4	137.2	46.9	170.8	48.0	207.3	50.1
	60	0.0	0.0	53.9	50.7	71.1	52.7	91.6	54.7	105.0	56.0	115.7	56.5	143.8	58.3	179.4	59.0
BSR314	30	95.6	35.1	119.9	36.4	150.7	37.4	184.7	39.5	207.6	40.8	224.4	42.2	0.0	0.0	0.0	0.0
	38	83.5	40.6	106.6	41.8	133.7	43.1	168.1	43.8	189.7	44.9	205.8	45.6	249.7	48.0	300.5	51.0
	50	66.1	49.8	87.1	51.8	111.6	53.8	140.4	55.8	159.6	57.2	174.2	57.9	216.8	59.3	263.2	61.8
	60	0.0	0.0	68.4	62.5	90.3	65.0	116.3	67.5	133.4	69.1	146.9	69.8	182.6	71.9	227.8	72.8
BSR316	30	112.6	41.0	141.2	42.5	177.6	43.7	217.7	46.0	244.7	47.7	264.4	49.3	0.0	0.0	0.0	0.0
	38	98.4	47.3	125.6	48.8	157.5	50.3	198.0	51.1	223.5	52.4	242.5	53.2	294.2	56.0	354.1	59.5
	50	77.9	58.0	102.6	60.4	131.5	62.7	165.4	65.1	188.0	66.7	205.3	67.6	255.5	69.2	310.1	72.1
	60	0.0	0.0	80.6	72.9	106.4	75.8	137.0	78.7	157.2	80.6	173.0	81.4	215.2	83.9	268.4	84.9
BSR321	30	123.4	44.9	154.7	46.6	194.5	47.8	238.4	50.4	268.0	52.2	289.6	54.0	0.0	0.0	0.0	0.0
	38	107.8	51.9	137.6	53.5	172.6	55.1	216.9	56.0	244.9	57.4	265.7	58.3	322.3	61.3	387.8	65.2
	50	85.3	63.6	112.4	66.2	144.0	68.7	181.2	71.3	206.0	73.1	224.9	74.0	279.9	75.8	339.7	78.9
	60	0.0	0.0	88.3	79.9	116.6	83.1	150.1	86.2	172.2	88.3	189.6	89.2	235.7	91.9	294.0	93.0

BSR-V R-134a Water Cooled Performance (30Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR323	30	145.6	52.8	182.6	54.8	229.6	56.3	281.4	59.4	316.3	61.4	341.8	63.5	0.0	0.0	0.0	0.0
	38	127.3	61.0	162.4	63.0	203.7	64.8	256.1	65.9	289.0	67.5	313.5	68.6	380.4	72.2	457.8	76.7
	50	100.7	74.8	132.7	77.9	170.0	80.9	213.9	83.9	243.1	86.0	265.4	87.1	330.3	89.2	401.0	92.9
	60	0.0	0.0	104.3	94.0	137.6	97.8	177.1	101.5	203.2	104.0	223.7	104.9	278.2	108.2	347.1	109.5
BSR324	30	161.5	58.5	202.6	60.7	254.7	62.4	312.2	65.8	350.9	68.1	379.2	70.4	0.0	0.0	0.0	0.0
	38	141.2	67.6	180.1	69.7	225.9	71.8	284.0	73.0	320.6	74.8	347.8	76.0	422.0	79.9	507.8	85.0
	50	111.7	82.9	147.2	86.3	188.6	89.6	237.3	93.0	269.7	95.3	294.4	96.5	366.4	98.8	444.8	102.9
	60	0.0	0.0	115.7	104.2	152.6	108.3	196.5	112.4	225.4	115.2	248.2	116.2	308.6	119.9	385.0	121.3
BSR326	30	174.0	62.6	218.2	64.9	274.3	66.7	336.3	70.3	378.0	72.8	408.5	75.3	0.0	0.0	0.0	0.0
	38	152.1	72.3	194.0	74.6	243.4	76.8	306.0	78.1	345.4	80.0	374.7	81.3	454.6	85.5	547.0	90.9
	50	120.3	88.7	158.6	92.4	203.2	95.9	255.6	99.5	290.5	102.0	317.1	103.2	394.7	105.7	479.2	110.1
	60	0.0	0.0	124.6	111.4	164.4	115.8	211.7	120.2	242.8	123.2	267.3	124.4	332.5	128.2	414.7	129.7
BSR413	30	211.3	75.0	265.0	77.8	333.2	79.9	408.4	84.3	459.1	87.2	496.1	90.2	0.0	0.0	0.0	0.0
	38	184.7	86.7	235.7	89.4	295.6	92.0	371.6	93.6	419.5	95.9	455.1	97.4	552.1	102.5	664.4	108.9
	50	146.1	106.3	192.6	110.6	246.7	114.9	310.4	119.2	352.8	122.2	385.2	123.7	479.4	126.6	582.0	131.9
	60	0.0	0.0	151.3	133.5	199.7	138.8	257.1	144.1	294.9	147.6	324.7	149.0	403.8	153.6	503.7	155.4
BSR415	30	235.7	83.3	295.6	86.4	371.6	88.8	455.5	93.6	512.0	96.9	553.3	100.2	0.0	0.0	0.0	0.0
	38	206.0	96.3	262.8	99.3	329.7	102.2	414.4	103.9	467.8	106.5	507.5	108.2	615.8	113.8	740.9	121.0
	50	163.0	118.0	214.8	122.9	275.2	127.6	346.2	132.4	393.5	135.7	429.6	137.3	534.7	140.6	649.1	146.5
	60	0.0	0.0	168.8	148.3	222.7	154.1	286.7	160.0	328.9	163.9	362.1	165.5	450.4	170.7	561.8	172.7
BSR421	30	268.3	94.6	336.4	98.1	423.0	100.8	518.5	106.2	582.8	110.0	629.8	113.7	0.0	0.0	0.0	0.0
	38	234.4	109.3	299.1	112.7	375.2	116.0	471.7	118.0	532.5	120.9	577.6	122.8	700.9	129.2	843.3	137.3
	50	185.5	134.0	244.5	139.5	313.2	144.8	394.1	150.2	447.9	154.0	488.9	155.9	608.6	159.6	738.8	166.3
	60	0.0	0.0	192.1	168.3	253.4	175.0	326.3	181.6	374.3	186.1	412.2	187.8	512.6	193.7	639.4	196.0

BSR-V R-134a Water Cooled Performance (30Hz)

	TE	-15		-10		-5		0		3		5		10		15	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR423	30	295.9	104.0	371.1	107.9	466.6	110.9	571.9	116.9	642.8	121.0	694.7	125.1	0.0	0.0	0.0	0.0
	38	258.6	120.2	330.0	124.0	413.9	127.6	520.3	129.8	587.3	133.0	637.2	135.1	773.1	142.1	930.2	151.0
	50	204.6	147.4	269.6	153.5	345.5	159.3	434.7	165.3	494.0	169.4	539.3	171.5	671.3	175.6	814.9	183.0
	60	0.0	0.0	211.9	185.2	279.6	192.5	359.9	199.8	412.9	204.7	454.7	206.6	565.4	213.1	705.3	215.6
BSR424	30	329.4	115.3	413.0	119.6	519.3	122.9	636.5	129.6	715.5	134.1	773.2	138.7	0.0	0.0	0.0	0.0
	38	287.8	133.2	367.2	137.4	460.7	141.4	579.1	143.9	653.7	147.4	709.2	149.8	860.5	157.5	1035.4	167.4
	50	227.7	163.4	300.1	170.1	384.5	176.6	483.8	183.2	549.9	187.8	600.3	190.1	747.2	194.7	907.0	202.8
	60	0.0	0.0	235.8	205.3	311.2	213.4	400.6	221.5	459.6	226.9	506.0	229.1	629.3	236.2	785.0	239.0
BSR426	30	368.7	124.4	462.3	129.1	572.5	134.6	701.8	141.9	788.8	146.9	852.5	151.9	0.0	0.0	0.0	0.0
	38	322.2	143.8	411.1	148.3	515.7	152.6	638.5	157.6	720.7	161.4	781.9	164.1	948.7	172.5	1141.6	183.4
	50	254.9	176.3	335.9	183.6	430.4	190.5	541.6	197.7	615.5	202.7	671.9	205.1	823.8	213.2	1000.0	222.1
	60	0.0	0.0	264.0	221.5	348.3	230.2	448.4	239.0	514.4	244.9	566.4	247.2	704.4	254.9	865.5	261.8

BSR-V R-134a Air Cooled Performance Data(70Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	53.9	17.7	67.6	18.3	85.1	18.8	104.3	19.8	117.2	20.5	126.6	21.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	47.1	20.4	60.2	21.0	75.5	21.7	94.9	22.0	107.1	22.6	116.2	22.9	140.9	24.1	169.6	25.6	202.7	27.5
	50	37.3	25.0	49.2	26.0	63.0	27.0	79.2	28.0	90.1	28.8	98.3	29.1	122.4	29.8	148.6	31.1	178.8	32.5
	60	0.0	0.0	38.6	31.4	51.0	32.7	65.6	33.9	75.3	34.7	82.9	35.1	103.1	36.2	128.6	36.6	156.3	37.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	51.0	40.7	59.4	41.8	66.2	42.2	84.1	43.9	105.2	45.6	129.7	47.8
BSR216	30	66.3	21.6	83.2	22.4	104.6	23.1	128.2	24.3	144.1	25.2	155.7	26.0	0.0	0.0	0.0	0.0	0.0	0.0
	38	58.0	25.0	73.9	25.8	92.8	26.5	116.6	27.0	131.6	27.7	142.8	28.1	173.3	29.6	208.5	31.4	249.1	33.7
	50	45.9	30.7	60.4	31.9	77.4	33.1	97.4	34.4	110.7	35.2	120.9	35.7	150.4	36.5	182.6	38.1	219.8	39.8
	60	0.0	0.0	47.5	38.5	62.6	40.0	80.7	41.6	92.5	42.6	101.9	43.0	126.7	44.3	158.1	44.8	192.2	45.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	62.7	49.9	73.0	51.2	81.4	51.7	103.4	53.9	129.3	55.9	159.4	58.5
BSR311	30	83.4	26.8	104.6	27.8	131.5	28.6	161.2	30.1	181.2	31.2	195.8	32.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	72.9	31.0	93.0	32.0	116.7	32.9	146.7	33.5	165.6	34.3	179.6	34.8	217.9	36.6	262.2	38.9	313.4	41.7
	50	57.7	38.0	76.0	39.6	97.4	41.1	122.5	42.6	139.3	43.7	152.0	44.2	189.2	45.3	229.7	47.2	276.5	49.3
	60	0.0	0.0	59.7	47.7	78.8	49.6	101.5	51.5	116.4	52.8	128.2	53.3	159.4	55.0	198.8	55.6	241.7	56.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	78.9	61.9	91.8	63.5	102.4	64.1	130.1	66.8	162.6	69.4	200.5	72.6
BSR314	30	105.9	33.1	132.8	34.3	167.0	35.3	204.7	37.2	230.1	38.5	248.7	39.8	0.0	0.0	0.0	0.0	0.0	0.0
	38	92.6	38.2	118.1	39.4	148.2	40.6	186.3	41.3	210.2	42.3	228.1	43.0	276.7	45.2	333.0	48.1	397.9	51.5
	50	73.2	46.9	96.5	48.8	123.7	50.7	155.6	52.6	176.8	53.9	193.0	54.6	240.3	55.9	291.7	58.2	351.1	60.8
	60	0.0	0.0	75.8	58.9	100.1	61.2	128.8	63.6	147.8	65.1	162.7	65.8	202.4	67.8	252.4	68.6	306.9	70.1
	70	0.0	0.0	0.0	0.0	0.0	0.0	100.2	76.4	116.6	78.4	130.0	79.1	165.2	82.4	206.5	85.6	254.6	89.5
BSR316	30	124.8	38.6	156.5	40.1	196.8	41.2	241.2	43.4	271.1	44.9	293.0	46.5	0.0	0.0	0.0	0.0	0.0	0.0
	38	109.1	44.6	139.2	46.0	174.6	47.4	219.5	48.2	247.7	49.4	268.7	50.2	326.0	52.8	392.3	56.1	468.8	60.1
	50	86.3	54.7	113.7	57.0	145.7	59.1	183.3	61.4	208.4	62.9	227.5	63.7	283.1	65.2	343.7	67.9	413.6	71.0
	60	0.0	0.0	89.4	68.7	117.9	71.5	151.8	74.2	174.1	76.0	191.7	76.7	238.5	79.1	297.5	80.0	361.6	81.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	118.1	89.1	137.4	91.4	153.2	92.3	194.7	96.1	243.3	99.8	300.0	104.5

BSR-V R-134a Air Cooled Performance Data(70Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR321	30	136.7	42.3	171.4	43.9	215.6	45.1	264.2	47.5	297.0	49.2	320.9	50.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	119.5	48.9	152.4	50.4	191.2	51.9	240.4	52.8	271.3	54.1	294.4	55.0	357.2	57.8	429.8	61.4	513.6	65.8
	50	94.5	59.9	124.6	62.4	159.6	64.8	200.8	67.2	228.2	68.9	249.2	69.7	310.1	71.4	376.5	74.4	453.1	77.8
	60	0.0	0.0	97.9	75.3	129.2	78.3	166.3	81.3	190.8	83.3	210.0	84.0	261.2	86.7	325.8	87.7	396.1	89.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	129.3	97.6	150.5	100.1	167.8	101.1	213.2	105.3	266.5	109.4	328.6	114.4
BSR323	30	161.4	49.8	202.4	51.7	254.4	53.1	311.8	55.9	350.5	57.9	378.8	59.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	141.0	57.5	179.9	59.3	225.7	61.1	283.7	62.1	320.3	63.6	347.4	64.7	421.6	68.0	507.3	72.3	606.2	77.5
	50	111.6	70.5	147.0	73.5	188.4	76.3	237.0	79.1	269.4	81.1	294.1	82.1	366.1	84.1	444.3	87.6	534.8	91.5
	60	0.0	0.0	115.5	88.6	152.4	92.1	196.3	95.6	225.2	98.0	247.9	98.9	308.3	102.0	384.6	103.2	467.6	105.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	152.7	114.9	177.6	117.9	198.1	119.0	251.7	124.0	314.5	128.7	387.9	134.7
BSR324	30	179.0	55.2	224.5	57.2	282.2	58.8	345.9	62.0	388.8	64.2	420.2	66.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	156.4	63.7	199.6	65.7	250.4	67.7	314.7	68.8	355.3	70.5	385.4	71.7	467.6	75.4	562.7	80.1	672.4	85.8
	50	123.8	78.1	163.1	81.4	209.0	84.5	262.9	87.6	298.8	89.8	326.2	90.9	406.1	93.1	492.9	97.0	593.2	101.4
	60	0.0	0.0	128.2	98.2	169.1	102.1	217.7	106.0	249.8	108.5	275.0	109.6	342.0	113.0	426.6	114.3	518.7	116.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	169.3	127.3	197.0	130.6	219.7	131.9	279.2	137.3	348.9	142.6	430.2	149.2
BSR326	30	192.8	59.0	241.8	61.2	304.0	62.9	372.6	66.3	418.8	68.6	452.6	71.0	0.0	0.0	0.0	0.0	0.0	0.0
	38	168.5	68.2	215.0	70.3	269.7	72.4	339.0	73.6	382.7	75.4	415.2	76.7	503.7	80.6	606.1	85.7	724.3	91.8
	50	133.3	83.6	175.7	87.1	225.1	90.4	283.2	93.8	321.9	96.1	351.4	97.3	437.4	99.6	531.0	103.8	639.0	108.5
	60	0.0	0.0	138.1	105.0	182.2	109.2	234.5	113.3	269.1	116.1	296.2	117.2	368.4	120.9	459.6	122.3	558.7	124.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	182.4	136.1	212.2	139.7	236.7	141.1	300.8	146.9	375.9	152.6	463.5	159.6
BSR413	30	234.2	70.7	293.7	73.3	369.2	75.3	452.6	79.4	508.7	82.2	549.8	85.0	0.0	0.0	0.0	0.0	0.0	0.0
	38	204.7	81.7	261.1	84.2	327.6	86.7	411.8	88.2	464.8	90.4	504.3	91.8	611.8	96.6	736.2	102.6	879.8	110.0
	50	161.9	100.2	213.4	104.3	273.4	108.3	344.0	112.3	391.0	115.1	426.8	116.6	531.3	119.3	644.9	124.4	776.2	130.0
	60	0.0	0.0	167.7	125.8	221.2	130.8	284.9	135.8	326.8	139.1	359.8	140.4	447.5	144.8	558.2	146.5	678.6	149.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	221.5	163.1	257.8	167.3	287.5	169.0	365.3	176.0	456.5	182.8	562.9	191.2

BSR-V R-134a Air Cooled Performance Data(70Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR415	30	261.2	78.5	327.5	81.4	411.8	83.7	504.7	88.2	567.3	91.3	613.1	94.5	0.0	0.0	0.0	0.0	0.0	0.0
	38	228.2	90.7	291.2	93.6	365.3	96.3	459.3	98.0	518.4	100.4	562.4	102.0	682.3	107.3	821.0	114.0	981.2	122.2
	50	180.6	111.2	238.0	115.8	304.9	120.2	383.7	124.8	436.0	127.9	476.0	129.5	592.5	132.5	719.2	138.1	865.6	144.3
	60	0.0	0.0	187.0	139.8	246.7	145.3	317.7	150.8	364.4	154.5	401.3	156.0	499.0	160.9	622.5	162.7	756.8	166.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	247.1	181.2	287.5	185.9	320.6	187.7	407.4	195.5	509.1	203.0	627.8	212.4
BSR421	30	297.3	89.1	372.8	92.5	468.7	95.0	574.5	100.1	645.8	103.7	697.9	107.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	259.8	103.0	331.5	106.2	415.8	109.3	522.7	111.2	590.0	113.9	640.1	115.8	776.6	121.8	934.5	129.4	1116.8	138.7
	50	205.5	126.3	270.9	131.5	347.1	136.5	436.7	141.6	496.3	145.2	541.8	146.9	674.4	150.5	818.6	156.8	985.2	163.9
	60	0.0	0.0	212.8	158.7	280.8	164.9	361.6	171.2	414.8	175.4	456.7	177.1	568.0	182.6	708.5	184.7	861.4	188.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	281.2	205.6	327.2	211.0	364.9	213.1	463.7	221.9	579.5	230.4	714.5	241.1
BSR423	30	327.9	98.1	411.2	101.7	517.0	104.5	633.7	110.2	712.3	114.0	769.8	117.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	286.6	113.3	365.6	116.8	458.6	120.3	576.6	122.3	650.8	125.3	706.1	127.4	856.7	133.9	1030.8	142.4	1231.8	152.5
	50	226.7	138.9	298.8	144.7	382.8	150.2	481.7	155.8	547.4	159.7	597.6	161.7	743.9	165.5	903.0	172.5	1086.8	180.2
	60	0.0	0.0	234.8	174.5	309.8	181.4	398.9	188.3	457.6	193.0	503.8	194.8	626.5	200.9	781.5	203.2	950.2	207.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	310.2	226.2	360.9	232.1	402.5	234.4	511.5	244.1	639.2	253.5	788.2	265.2
BSR424	30	365.0	108.7	457.7	112.7	575.4	115.8	705.3	122.1	792.8	126.4	856.8	130.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	318.9	125.6	407.0	129.5	510.5	133.3	641.8	135.6	724.4	138.9	785.8	141.2	953.5	148.5	1147.3	157.8	1371.1	169.1
	50	252.3	154.0	332.6	160.4	426.1	166.5	536.1	172.7	609.3	177.0	665.2	179.2	827.9	183.5	1005.0	191.2	1209.6	199.8
	60	0.0	0.0	261.3	193.5	344.8	201.1	443.9	208.8	509.3	213.9	560.7	215.9	697.4	222.7	869.8	225.3	1057.5	230.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	345.3	250.8	401.7	257.3	448.0	259.8	569.3	270.6	711.4	281.0	877.2	294.0
BSR426	30	408.5	117.3	512.3	121.7	634.4	126.9	777.7	133.8	874.1	138.5	944.6	143.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	357.0	135.5	455.5	139.8	571.4	143.9	707.6	148.5	798.6	152.2	866.4	154.6	1051.3	162.6	1265.0	172.8	1511.7	185.2
	50	282.5	166.2	372.2	173.0	477.0	179.6	600.1	186.3	682.0	191.0	744.5	193.4	912.9	200.9	1108.1	209.4	1333.6	218.8
	60	0.0	0.0	292.5	208.8	385.9	217.0	496.9	225.3	570.0	230.8	627.7	233.0	780.6	240.3	959.1	246.7	1166.0	252.1
	70	0.0	0.0	0.0	0.0	0.0	0.0	386.5	270.6	449.7	277.6	501.5	280.4	637.2	292.0	796.3	303.2	981.9	317.2

BSR-V R-134a Air Cooled Performance Curve (60Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	52.6	17.9	66.0	18.6	83.0	19.1	101.7	20.1	114.3	20.8	123.6	21.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	46.0	20.7	58.7	21.4	73.6	22.0	92.5	22.4	104.5	22.9	113.3	23.3	137.5	24.5	165.4	26.0	197.7	27.9
	50	36.4	25.4	48.0	26.4	61.4	27.4	77.3	28.5	87.9	29.2	95.9	29.5	119.4	30.3	144.9	31.5	174.4	32.9
	60	0.0	0.0	37.7	31.9	49.7	33.2	64.0	34.4	73.4	35.3	80.9	35.6	100.6	36.7	125.4	37.1	152.5	38.0
	70	0.0	0.0	0.0	0.0	0.0	0.0	49.8	41.3	57.9	42.4	64.6	42.8	82.1	44.6	102.6	46.3	126.5	48.5
BSR216	30	64.7	22.0	81.1	22.8	102.0	23.4	125.0	24.7	140.5	25.5	151.9	26.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	56.5	25.4	72.1	26.2	90.5	26.9	113.8	27.4	128.4	28.1	139.3	28.5	169.0	30.0	203.4	31.9	243.1	34.2
	50	44.7	31.1	59.0	32.4	75.5	33.6	95.0	34.9	108.0	35.8	117.9	36.2	146.8	37.1	178.2	38.6	214.4	40.4
	60	0.0	0.0	46.3	39.1	61.1	40.6	78.7	42.2	90.3	43.2	99.4	43.6	123.6	45.0	154.2	45.5	187.5	46.5
	70	0.0	0.0	0.0	0.0	0.0	0.0	61.2	50.7	71.2	52.0	79.4	52.5	100.9	54.7	126.1	56.8	155.5	59.4
BSR311	30	81.4	27.2	102.1	28.2	128.3	29.0	157.3	30.6	176.8	31.7	191.1	32.8	0.0	0.0	0.0	0.0	0.0	0.0
	38	71.1	31.5	90.7	32.5	113.8	33.4	143.1	34.0	161.5	34.8	175.2	35.4	212.6	37.2	255.8	39.5	305.7	42.4
	50	56.3	38.6	74.2	40.2	95.0	41.7	119.6	43.3	135.9	44.4	148.3	44.9	184.6	46.0	224.1	47.9	269.7	50.1
	60	0.0	0.0	58.3	48.5	76.9	50.4	99.0	52.3	113.6	53.6	125.0	54.1	155.5	55.8	194.0	56.4	235.8	57.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	77.0	62.8	89.6	64.5	99.9	65.1	126.9	67.8	158.6	70.4	195.6	73.7
BSR314	30	103.3	33.6	129.6	34.9	162.9	35.8	199.7	37.8	224.5	39.1	242.6	40.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	90.3	38.8	115.2	40.0	144.5	41.2	181.7	41.9	205.1	43.0	222.5	43.7	270.0	45.9	324.9	48.8	388.2	52.3
	50	71.4	47.6	94.2	49.6	120.6	51.5	151.8	53.4	172.5	54.7	188.3	55.4	234.4	56.7	284.6	59.1	342.5	61.8
	60	0.0	0.0	74.0	59.8	97.6	62.2	125.7	64.5	144.2	66.1	158.8	66.8	197.5	68.8	246.3	69.6	299.4	71.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	97.8	77.5	113.7	79.5	126.9	80.3	161.2	83.7	201.4	86.9	248.4	90.9
BSR316	30	121.8	39.2	152.7	40.7	192.0	41.8	235.3	44.1	264.5	45.6	285.8	47.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	106.4	45.3	135.8	46.7	170.3	48.1	214.1	48.9	241.7	50.1	262.2	50.9	318.1	53.6	382.8	56.9	457.4	61.0
	50	84.2	55.5	110.9	57.8	142.2	60.0	178.9	62.3	203.3	63.9	221.9	64.6	276.2	66.2	335.3	69.0	403.5	72.1
	60	0.0	0.0	87.2	69.8	115.0	72.6	148.1	75.3	169.9	77.2	187.1	77.9	232.7	80.3	290.2	81.3	352.8	83.0
	70	0.0	0.0	0.0	0.0	0.0	0.0	115.2	90.5	134.0	92.8	149.5	93.7	189.9	97.6	237.3	101.4	292.7	106.1

BSR-V R-134a Air Cooled Performance Curve (60Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR321	30	133.4	43.0	167.3	44.6	210.3	45.8	257.8	48.3	289.7	50.0	313.1	51.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	116.6	49.6	148.7	51.2	186.6	52.7	234.5	53.6	264.7	54.9	287.2	55.8	348.5	58.7	419.3	62.4	501.1	66.8
	50	92.2	60.8	121.5	63.4	155.7	65.8	195.9	68.2	222.7	70.0	243.1	70.8	302.6	72.5	367.3	75.5	442.1	79.0
	60	0.0	0.0	95.5	76.5	126.0	79.5	162.2	82.5	186.1	84.5	204.9	85.3	254.9	88.0	317.9	89.0	386.5	90.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	126.2	99.1	146.8	101.7	163.7	102.7	208.0	106.9	260.0	111.0	320.6	116.2
BSR323	30	157.4	50.6	197.4	52.4	248.2	53.9	304.2	56.8	342.0	58.8	369.6	60.8	0.0	0.0	0.0	0.0	0.0	0.0
	38	137.6	58.4	175.5	60.2	220.2	62.0	276.8	63.1	312.4	64.6	339.0	65.7	411.3	69.1	494.9	73.4	591.4	78.6
	50	108.8	71.6	143.4	74.6	183.8	77.4	231.2	80.3	262.8	82.3	286.9	83.3	357.1	85.3	433.5	88.9	521.7	92.9
	60	0.0	0.0	112.7	90.0	148.7	93.5	191.5	97.1	219.7	99.5	241.9	100.4	300.8	103.6	375.2	104.8	456.2	107.0
	70	0.0	0.0	0.0	0.0	0.0	0.0	148.9	116.6	173.3	119.7	193.3	120.8	245.6	125.8	306.9	130.7	378.4	136.7
BSR324	30	174.6	56.0	219.0	58.1	275.3	59.7	337.5	62.9	379.3	65.1	409.9	67.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	152.6	64.7	194.7	66.7	244.3	68.7	307.1	69.9	346.6	71.6	376.0	72.7	456.2	76.5	549.0	81.3	656.0	87.1
	50	120.7	79.3	159.1	82.6	203.9	85.8	256.5	89.0	291.5	91.2	318.3	92.3	396.2	94.5	480.9	98.5	578.8	102.9
	60	0.0	0.0	125.0	99.7	165.0	103.6	212.4	107.6	243.7	110.2	268.3	111.2	333.7	114.7	416.2	116.1	506.0	118.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	165.2	129.2	192.2	132.6	214.4	133.9	272.4	139.4	340.4	144.8	419.7	151.5
BSR326	30	188.1	59.9	235.9	62.1	296.6	63.8	363.5	67.3	408.6	69.7	441.6	72.1	0.0	0.0	0.0	0.0	0.0	0.0
	38	164.4	69.2	209.8	71.4	263.1	73.5	330.8	74.8	373.4	76.6	405.0	77.8	491.4	81.8	591.4	87.0	706.7	93.2
	50	130.1	84.9	171.4	88.4	219.6	91.7	276.3	95.2	314.0	97.6	342.8	98.8	426.7	101.1	518.0	105.4	623.5	110.1
	60	0.0	0.0	134.7	106.6	177.7	110.9	228.8	115.1	262.5	117.9	289.0	119.0	359.4	122.7	448.3	124.2	545.1	126.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	178.0	138.2	207.1	141.8	230.9	143.2	293.4	149.1	366.7	154.9	452.2	162.0
BSR413	30	228.5	71.8	286.5	74.4	360.2	76.5	441.5	80.6	496.3	83.5	536.4	86.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	199.7	82.9	254.8	85.5	319.6	88.0	401.7	89.6	453.5	91.7	492.0	93.2	596.9	98.0	718.2	104.2	858.3	111.7
	50	158.0	101.7	208.2	105.9	266.8	109.9	335.6	114.0	381.4	116.9	416.4	118.3	518.3	121.2	629.2	126.2	757.2	131.9
	60	0.0	0.0	163.6	127.8	215.8	132.8	277.9	137.9	318.8	141.2	351.0	142.6	436.6	147.0	544.5	148.8	662.0	152.0
	70	0.0	0.0	0.0	0.0	0.0	0.0	216.1	165.6	251.5	169.9	280.5	171.6	356.4	178.7	445.4	185.5	549.2	194.1

BSR-V R-134a Air Cooled Performance Curve (60Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR415	30	254.8	79.7	319.5	82.7	401.7	85.0	492.4	89.6	553.5	92.7	598.2	95.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	222.7	92.1	284.1	95.0	356.4	97.8	448.1	99.5	505.7	101.9	548.7	103.6	665.7	108.9	801.0	115.7	957.2	124.0
	50	176.2	112.9	232.2	117.6	297.5	122.1	374.3	126.7	425.4	129.8	464.4	131.4	578.0	134.6	701.7	140.2	844.5	146.5
	60	0.0	0.0	182.4	141.9	240.7	147.5	309.9	153.1	355.6	156.9	391.5	158.4	486.9	163.3	607.3	165.2	738.3	168.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	241.1	183.9	280.5	188.7	312.8	190.6	397.5	198.5	496.7	206.1	612.5	215.6
BSR421	30	290.0	90.5	363.7	93.9	457.3	96.4	560.5	101.7	630.0	105.2	680.8	108.8	0.0	0.0	0.0	0.0	0.0	0.0
	38	253.5	104.6	323.4	107.8	405.7	111.0	510.0	112.9	575.6	115.7	624.5	117.6	757.7	123.6	911.7	131.4	1089.5	140.8
	50	200.5	128.2	264.3	133.5	338.6	138.6	426.0	143.8	484.2	147.4	528.6	149.2	657.9	152.8	798.7	159.2	961.2	166.3
	60	0.0	0.0	207.7	161.1	274.0	167.4	352.8	173.8	404.7	178.1	445.6	179.8	554.2	185.4	691.2	187.5	840.4	191.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	274.4	208.8	319.2	214.2	356.0	216.3	452.4	225.3	565.3	233.9	697.1	244.8
BSR423	30	319.9	99.6	401.2	103.3	504.4	106.1	618.2	111.8	694.9	115.8	751.0	119.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	279.6	115.0	356.7	118.6	447.5	122.1	562.5	124.2	634.9	127.2	688.8	129.3	835.8	136.0	1005.7	144.5	1201.8	154.9
	50	221.2	141.0	291.5	146.9	373.5	152.4	469.9	158.2	534.1	162.1	583.0	164.1	725.7	168.0	881.0	175.1	1060.3	183.0
	60	0.0	0.0	229.0	177.2	302.2	184.2	389.1	191.2	446.4	195.9	491.5	197.7	611.3	203.9	762.5	206.3	927.0	210.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	302.6	229.7	352.1	235.6	392.7	238.0	499.0	247.8	623.6	257.4	768.9	269.3
BSR424	30	356.1	110.4	446.5	114.5	561.4	117.6	688.1	124.0	773.5	128.3	835.9	132.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	311.2	127.5	397.0	131.5	498.0	135.3	626.1	137.7	706.7	141.1	766.7	143.4	930.2	150.7	1119.3	160.2	1337.6	171.7
	50	246.2	156.3	324.4	162.8	415.7	169.0	523.0	175.3	594.4	179.7	648.9	181.9	807.8	186.3	980.5	194.1	1180.1	202.9
	60	0.0	0.0	254.9	196.4	336.4	204.2	433.1	212.0	496.9	217.2	547.1	219.2	680.3	226.1	848.6	228.7	1031.7	233.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	336.8	254.6	391.9	261.2	437.1	263.8	555.4	274.7	694.1	285.3	855.8	298.5
BSR426	30	398.6	119.1	499.8	123.5	619.0	128.8	758.7	135.8	852.8	140.6	921.6	145.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	348.3	137.6	444.4	141.9	557.5	146.0	690.3	150.8	779.2	154.5	845.3	157.0	1025.6	165.1	1234.1	175.5	1474.8	188.0
	50	275.6	168.7	363.2	175.7	465.3	182.3	585.5	189.2	665.4	193.9	726.4	196.3	890.6	204.0	1081.1	212.6	1301.1	222.2
	60	0.0	0.0	285.4	211.9	376.5	220.3	484.8	228.7	556.1	234.3	612.4	236.5	761.5	243.9	935.7	250.5	1137.5	255.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	377.0	274.7	438.7	281.9	489.3	284.6	621.7	296.4	776.9	307.8	958.0	322.1

BSR-V R-134a Air Cooled Performance Curve (50Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	51.3	18.2	64.3	18.9	80.9	19.4	99.2	20.4	111.5	21.2	120.5	21.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	44.8	21.0	57.2	21.7	71.8	22.3	90.2	22.7	101.8	23.3	110.5	23.6	134.1	24.9	161.3	26.4	192.8	28.3
	50	35.5	25.8	46.8	26.8	59.9	27.9	75.4	28.9	85.7	29.6	93.5	30.0	116.4	30.7	141.3	32.0	170.1	33.4
	60	0.0	0.0	36.7	32.4	48.5	33.7	62.4	34.9	71.6	35.8	78.8	36.1	98.0	37.3	122.3	37.7	148.7	38.5
	70	0.0	0.0	0.0	0.0	0.0	0.0	48.5	42.0	56.5	43.1	63.0	43.5	80.0	45.3	100.0	47.0	123.3	49.2
BSR216	30	63.1	22.3	79.1	23.1	99.5	23.8	121.9	25.1	137.0	25.9	148.1	26.8	0.0	0.0	0.0	0.0	0.0	0.0
	38	55.1	25.8	70.3	26.6	88.2	27.3	110.9	27.8	125.2	28.5	135.8	29.0	164.8	30.5	198.3	32.4	237.0	34.7
	50	43.6	31.6	57.5	32.9	73.6	34.1	92.7	35.4	105.3	36.3	115.0	36.8	143.1	37.6	173.7	39.2	209.1	41.0
	60	0.0	0.0	45.2	39.7	59.6	41.3	76.7	42.8	88.0	43.9	96.9	44.3	120.5	45.7	150.3	46.2	182.8	47.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	59.7	51.4	69.4	52.8	77.4	53.3	98.4	55.5	123.0	57.6	151.6	60.3
BSR311	30	79.4	27.6	99.5	28.7	125.1	29.5	153.4	31.1	172.4	32.1	186.3	33.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	69.3	31.9	88.5	32.9	111.0	33.9	139.5	34.5	157.5	35.3	170.9	35.9	207.3	37.8	249.5	40.1	298.1	43.0
	50	54.9	39.2	72.3	40.8	92.6	42.3	116.6	43.9	132.5	45.0	144.6	45.6	180.0	46.7	218.5	48.6	263.0	50.8
	60	0.0	0.0	56.8	49.2	75.0	51.1	96.5	53.1	110.7	54.4	121.9	54.9	151.6	56.6	189.1	57.3	229.9	58.5
	70	0.0	0.0	0.0	0.0	0.0	0.0	75.1	63.8	87.3	65.4	97.4	66.1	123.8	68.8	154.7	71.5	190.7	74.8
BSR314	30	100.8	34.1	126.3	35.4	158.9	36.3	194.7	38.3	218.9	39.7	236.5	41.0	0.0	0.0	0.0	0.0	0.0	0.0
	38	88.1	39.4	112.3	40.6	140.9	41.8	177.2	42.6	200.0	43.6	216.9	44.3	263.2	46.6	316.7	49.5	378.5	53.1
	50	69.7	48.3	91.8	50.3	117.6	52.2	148.0	54.2	168.2	55.6	183.6	56.2	228.6	57.6	277.5	60.0	333.9	62.7
	60	0.0	0.0	72.1	60.7	95.2	63.1	122.6	65.5	140.6	67.1	154.8	67.8	192.5	69.9	240.1	70.7	291.9	72.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	95.3	78.7	110.9	80.7	123.7	81.5	157.2	84.9	196.4	88.2	242.2	92.3
BSR316	30	118.7	39.8	148.9	41.3	187.2	42.4	229.4	44.7	257.9	46.3	278.7	47.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	103.7	46.0	132.4	47.4	166.0	48.8	208.7	49.7	235.6	50.9	255.6	51.7	310.1	54.4	373.2	57.8	446.0	61.9
	50	82.1	56.4	108.2	58.7	138.6	60.9	174.4	63.2	198.2	64.8	216.4	65.6	269.3	67.2	326.9	70.0	393.5	73.2
	60	0.0	0.0	85.0	70.8	112.2	73.6	144.4	76.4	165.7	78.3	182.4	79.1	226.8	81.5	282.9	82.5	344.0	84.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	112.3	91.8	130.7	94.2	145.7	95.1	185.2	99.1	231.4	102.9	285.3	107.6

BSR-V R-134a Air Cooled Performance Curve (50Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR321	30	130.0	43.6	163.1	45.2	205.0	46.5	251.3	49.0	282.5	50.7	305.3	52.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	113.6	50.4	145.0	52.0	181.9	53.5	228.7	54.4	258.1	55.7	280.0	56.6	339.7	59.6	408.8	63.3	488.5	67.8
	50	89.9	61.8	118.5	64.3	151.8	66.8	191.0	69.3	217.1	71.0	237.0	71.9	295.0	73.6	358.1	76.7	431.0	80.1
	60	0.0	0.0	93.1	77.6	122.9	80.7	158.2	83.7	181.5	85.8	199.8	86.6	248.5	89.3	309.9	90.4	376.8	92.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	123.0	100.6	143.1	103.2	159.6	104.2	202.8	108.5	253.5	112.7	312.6	117.9
BSR323	30	153.5	51.3	192.5	53.2	242.0	54.7	296.6	57.7	333.4	59.7	360.3	61.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	134.1	59.3	171.1	61.1	214.7	62.9	269.9	64.0	304.6	65.6	330.5	66.7	401.0	70.1	482.5	74.5	576.6	79.8
	50	106.1	72.7	139.9	75.7	179.2	78.6	225.5	81.5	256.2	83.6	279.7	84.6	348.2	86.6	422.7	90.3	508.7	94.3
	60	0.0	0.0	109.9	91.3	145.0	94.9	186.7	98.6	214.2	101.0	235.8	101.9	293.3	105.1	365.8	106.3	444.8	108.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	145.2	118.4	169.0	121.5	188.4	122.7	239.4	127.7	299.2	132.7	368.9	138.8
BSR324	30	170.3	56.8	213.5	59.0	268.4	60.6	329.0	63.9	369.9	66.1	399.7	68.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	148.8	65.7	189.8	67.7	238.1	69.7	299.4	70.9	337.9	72.7	366.6	73.8	444.8	77.6	535.2	82.5	639.6	88.4
	50	117.7	80.5	155.1	83.9	198.8	87.0	250.1	90.3	284.2	92.6	310.3	93.7	386.3	95.9	468.9	100.0	564.3	104.5
	60	0.0	0.0	121.9	101.2	160.8	105.2	207.1	109.2	237.6	111.9	261.6	112.9	325.3	116.4	405.8	117.8	493.4	120.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	161.1	131.1	187.4	134.5	209.0	135.9	265.6	141.5	331.9	146.9	409.2	153.7
BSR326	30	183.4	60.8	230.0	63.1	289.2	64.8	354.5	68.3	398.4	70.7	430.6	73.1	0.0	0.0	0.0	0.0	0.0	0.0
	38	160.3	70.3	204.5	72.5	256.5	74.6	322.5	75.9	364.0	77.7	394.9	79.0	479.2	83.1	576.6	88.3	689.0	94.6
	50	126.8	86.1	167.1	89.7	214.1	93.1	269.4	96.6	306.2	99.0	334.3	100.2	416.1	102.6	505.1	107.0	607.9	111.8
	60	0.0	0.0	131.3	108.2	173.3	112.5	223.1	116.8	255.9	119.7	281.8	120.8	350.4	124.6	437.1	126.0	531.5	128.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	173.5	140.3	201.9	143.9	225.2	145.4	286.1	151.4	357.5	157.2	440.8	164.5
BSR413	30	222.8	72.9	279.4	75.6	351.2	77.6	430.5	81.9	483.9	84.7	522.9	87.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	194.7	84.2	248.4	86.8	311.6	89.4	391.7	90.9	442.1	93.1	479.7	94.6	582.0	99.5	700.3	105.8	836.9	113.3
	50	154.0	103.2	203.0	107.5	260.1	111.6	327.2	115.7	371.9	118.7	406.0	120.1	505.4	123.0	613.4	128.1	738.3	133.9
	60	0.0	0.0	159.5	129.7	210.4	134.8	271.0	139.9	310.8	143.4	342.3	144.7	425.6	149.2	530.9	151.0	645.5	154.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	210.7	168.1	245.2	172.4	273.5	174.1	347.5	181.4	434.2	188.3	535.4	197.0

BSR-V R-134a Air Cooled Performance Curve (50Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR415	30	248.4	80.9	311.5	83.9	391.7	86.2	480.1	90.9	539.7	94.1	583.2	97.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	217.1	93.5	277.0	96.4	347.5	99.2	436.8	101.0	493.1	103.4	534.9	105.1	649.0	110.5	781.0	117.5	933.3	125.9
	50	171.8	114.6	226.4	119.4	290.1	123.9	364.9	128.6	414.8	131.8	452.8	133.4	563.6	136.6	684.1	142.3	823.4	148.7
	60	0.0	0.0	177.9	144.0	234.7	149.7	302.2	155.4	346.7	159.2	381.7	160.7	474.7	165.8	592.1	167.7	719.9	171.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	235.0	186.7	273.5	191.5	305.0	193.4	387.5	201.4	484.3	209.2	597.2	218.9
BSR421	30	282.8	91.9	354.6	95.3	445.8	97.9	546.5	103.2	614.3	106.8	663.8	110.5	0.0	0.0	0.0	0.0	0.0	0.0
	38	247.1	106.1	315.3	109.5	395.5	112.7	497.2	114.6	561.2	117.4	608.9	119.3	738.7	125.5	888.9	133.4	1062.3	142.9
	50	195.5	130.1	257.7	135.5	330.1	140.7	415.4	145.9	472.1	149.6	515.4	151.4	641.5	155.0	778.7	161.6	937.2	168.8
	60	0.0	0.0	202.5	163.5	267.1	170.0	344.0	176.4	394.6	180.7	434.5	182.5	540.3	188.2	674.0	190.4	819.4	194.5
	70	0.0	0.0	0.0	0.0	0.0	0.0	267.5	211.9	311.3	217.4	347.1	219.6	441.1	228.7	551.2	237.5	679.7	248.4
BSR423	30	311.9	101.1	391.1	104.8	491.8	107.7	602.8	113.5	677.6	117.5	732.2	121.5	0.0	0.0	0.0	0.0	0.0	0.0
	38	272.6	116.8	347.8	120.4	436.3	123.9	548.5	126.1	619.1	129.2	671.6	131.3	814.9	138.0	980.5	146.7	1171.8	157.2
	50	215.7	143.1	284.2	149.1	364.2	154.7	458.2	160.5	520.7	164.6	568.5	166.6	707.6	170.6	858.9	177.7	1033.8	185.7
	60	0.0	0.0	223.3	179.9	294.7	187.0	379.4	194.1	435.2	198.8	479.2	200.7	596.0	207.0	743.4	209.4	903.8	213.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	295.1	233.1	343.3	239.2	382.9	241.5	486.5	251.5	608.0	261.2	749.7	273.3
BSR424	30	347.2	112.0	435.4	116.2	547.4	119.4	670.9	125.8	754.1	130.3	815.0	134.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	303.4	129.4	387.1	133.5	485.6	137.4	610.4	139.8	689.0	143.2	747.5	145.5	907.0	153.0	1091.3	162.6	1304.2	174.3
	50	240.0	158.7	316.3	165.2	405.3	171.5	510.0	178.0	579.6	182.4	632.7	184.7	787.6	189.1	956.0	197.0	1150.6	205.9
	60	0.0	0.0	248.6	199.4	328.0	207.3	422.3	215.1	484.4	220.4	533.4	222.5	663.3	229.5	827.4	232.1	1005.9	237.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	328.4	258.4	382.1	265.1	426.2	267.7	541.5	278.8	676.7	289.6	834.5	303.0
BSR426	30	388.6	120.9	487.3	125.4	603.5	130.7	739.7	137.8	831.5	142.7	898.6	147.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	339.6	139.6	433.3	144.0	543.5	148.2	673.0	153.1	759.7	156.8	824.2	159.4	1000.0	167.6	1203.3	178.1	1437.9	190.8
	50	268.7	171.2	354.1	178.3	453.7	185.1	570.8	192.0	648.7	196.9	708.2	199.2	868.3	207.1	1054.0	215.8	1268.6	225.5
	60	0.0	0.0	278.2	215.1	367.1	223.6	472.7	232.1	542.2	237.8	597.0	240.1	742.5	247.6	912.3	254.2	1109.1	259.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	367.6	278.8	427.7	286.1	477.0	288.9	606.1	300.9	757.5	312.4	934.0	326.9

BSR-V R-134a Air Cooled Performance Curve (40Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	50.0	18.5	62.7	19.1	78.8	19.7	96.6	20.7	108.6	21.5	117.4	22.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	43.7	21.3	55.8	22.0	69.9	22.6	87.9	23.0	99.2	23.6	107.7	24.0	130.6	25.2	157.2	26.8	187.8	28.7
	50	34.6	26.2	45.6	27.2	58.4	28.3	73.4	29.3	83.5	30.1	91.1	30.4	113.4	31.2	137.7	32.5	165.7	33.9
	60	0.0	0.0	35.8	32.9	47.2	34.2	60.8	35.5	69.8	36.3	76.8	36.7	95.5	37.8	119.2	38.3	144.9	39.1
	70	0.0	0.0	0.0	0.0	0.0	0.0	47.3	42.6	55.0	43.7	61.4	44.1	78.0	46.0	97.5	47.7	120.2	49.9
BSR216	30	61.5	22.6	77.1	23.5	96.9	24.1	118.8	25.4	133.5	26.3	144.3	27.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	53.7	26.1	68.5	27.0	86.0	27.8	108.1	28.2	122.0	28.9	132.3	29.4	160.6	30.9	193.2	32.9	230.9	35.2
	50	42.5	32.1	56.0	33.4	71.8	34.7	90.3	35.9	102.6	36.9	112.0	37.3	139.4	38.2	169.3	39.8	203.7	41.6
	60	0.0	0.0	44.0	40.3	58.1	41.9	74.8	43.5	85.8	44.5	94.4	44.9	117.4	46.4	146.5	46.9	178.1	47.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	58.1	52.2	67.7	53.6	75.5	54.1	95.9	56.3	119.8	58.5	147.7	61.2
BSR311	30	77.3	28.1	97.0	29.1	121.9	29.9	149.4	31.5	168.0	32.6	181.5	33.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	67.6	32.4	86.2	33.4	108.1	34.4	136.0	35.0	153.5	35.9	166.5	36.4	202.0	38.3	243.1	40.7	290.5	43.6
	50	53.5	39.7	70.5	41.4	90.3	43.0	113.6	44.6	129.1	45.7	140.9	46.2	175.4	47.4	212.9	49.3	256.3	51.6
	60	0.0	0.0	55.4	49.9	73.0	51.9	94.0	53.9	107.9	55.2	118.8	55.7	147.7	57.5	184.3	58.1	224.0	59.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	73.1	64.7	85.1	66.4	94.9	67.1	120.6	69.8	150.7	72.5	185.8	75.9
BSR314	30	98.2	34.6	123.1	35.9	154.8	36.9	189.7	38.9	213.3	40.3	230.5	41.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	85.8	40.0	109.5	41.2	137.3	42.5	172.6	43.2	194.8	44.2	211.4	45.0	256.5	47.3	308.6	50.3	368.8	53.8
	50	67.9	49.0	89.5	51.1	114.6	53.0	144.2	55.0	163.9	56.4	178.9	57.1	222.7	58.4	270.3	60.9	325.4	63.6
	60	0.0	0.0	70.3	61.6	92.7	64.0	119.4	66.5	137.0	68.1	150.8	68.8	187.6	70.9	234.0	71.7	284.5	73.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	92.9	79.9	108.1	81.9	120.5	82.7	153.1	86.2	191.4	89.5	236.0	93.6
BSR316	30	115.7	40.4	145.1	41.9	182.4	43.0	223.5	45.4	251.3	47.0	271.5	48.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	101.1	46.7	129.0	48.1	161.8	49.5	203.4	50.4	229.6	51.6	249.1	52.5	302.2	55.2	363.6	58.6	434.5	62.8
	50	80.0	57.2	105.4	59.6	135.0	61.8	169.9	64.2	193.1	65.8	210.8	66.6	262.4	68.2	318.5	71.0	383.4	74.2
	60	0.0	0.0	82.8	71.9	109.3	74.7	140.7	77.6	161.4	79.5	177.7	80.2	221.0	82.7	275.7	83.7	335.2	85.5
	70	0.0	0.0	0.0	0.0	0.0	0.0	109.4	93.2	127.3	95.6	142.0	96.5	180.4	100.5	225.5	104.4	278.0	109.2

BSR-V R-134a Air Cooled Performance Curve (40Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR321	30	126.7	44.2	158.9	45.9	199.8	47.1	244.9	49.7	275.2	51.5	297.5	53.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	110.7	51.1	141.3	52.7	177.2	54.3	222.8	55.2	251.5	56.5	272.8	57.5	331.0	60.4	398.3	64.2	476.0	68.8
	50	87.6	62.7	115.5	65.3	147.9	67.7	186.1	70.3	211.5	72.1	230.9	72.9	287.5	74.7	348.9	77.8	420.0	81.3
	60	0.0	0.0	90.7	78.7	119.7	81.9	154.1	85.0	176.8	87.1	194.7	87.9	242.1	90.6	302.0	91.7	367.2	93.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	119.9	102.1	139.5	104.7	155.6	105.8	197.6	110.1	247.0	114.4	304.6	119.7
BSR323	30	149.6	52.1	187.5	54.0	235.8	55.5	289.0	58.5	324.9	60.6	351.1	62.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	130.7	60.2	166.8	62.0	209.2	63.9	263.0	65.0	296.8	66.6	322.0	67.6	390.7	71.1	470.1	75.6	561.8	81.0
	50	103.4	73.8	136.3	76.8	174.6	79.7	219.7	82.7	249.7	84.8	272.6	85.8	339.3	87.9	411.8	91.6	495.7	95.7
	60	0.0	0.0	107.1	92.7	141.3	96.3	181.9	100.0	208.7	102.5	229.8	103.4	285.8	106.7	356.4	107.9	433.4	110.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	141.5	120.1	164.6	123.3	183.6	124.5	233.3	129.6	291.5	134.6	359.5	140.8
BSR324	30	165.9	57.7	208.0	59.8	261.6	61.5	320.6	64.8	360.4	67.1	389.5	69.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	145.0	66.6	185.0	68.7	232.0	70.7	291.7	72.0	329.3	73.7	357.2	74.9	433.4	78.8	521.5	83.7	623.2	89.7
	50	114.7	81.7	151.2	85.1	193.7	88.3	243.7	91.6	277.0	93.9	302.4	95.1	376.3	97.4	456.8	101.5	549.8	106.0
	60	0.0	0.0	118.8	102.7	156.7	106.7	201.8	110.8	231.5	113.5	254.9	114.6	317.0	118.2	395.4	119.5	480.7	122.1
	70	0.0	0.0	0.0	0.0	0.0	0.0	156.9	133.1	182.6	136.5	203.7	137.9	258.8	143.6	323.4	149.1	398.8	156.0
BSR326	30	178.7	61.7	224.1	64.0	281.8	65.8	345.4	69.3	388.2	71.8	419.5	74.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	156.2	71.3	199.3	73.5	250.0	75.7	314.2	77.0	354.7	78.9	384.8	80.2	466.9	84.3	561.8	89.6	671.3	96.0
	50	123.6	87.4	162.8	91.0	208.6	94.5	262.5	98.0	298.3	100.5	325.7	101.7	405.4	104.2	492.1	108.5	592.3	113.4
	60	0.0	0.0	128.0	109.8	168.8	114.2	217.4	118.5	249.4	121.4	274.6	122.6	341.5	126.4	425.9	127.9	517.8	130.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	169.1	142.4	196.7	146.1	219.4	147.5	278.7	153.6	348.4	159.5	429.5	166.9
BSR413	30	217.1	73.9	272.2	76.7	342.2	78.8	419.5	83.1	471.5	86.0	509.5	88.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	189.7	85.4	242.0	88.1	303.6	90.7	381.7	92.2	430.8	94.5	467.4	96.0	567.1	101.0	682.3	107.3	815.4	115.0
	50	150.1	104.7	197.8	109.1	253.4	113.2	318.8	117.5	362.4	120.4	395.6	121.9	492.4	124.8	597.7	130.0	719.4	135.9
	60	0.0	0.0	155.4	131.6	205.1	136.8	264.0	142.0	302.9	145.5	333.5	146.8	414.7	151.4	517.3	153.2	628.9	156.5
	70	0.0	0.0	0.0	0.0	0.0	0.0	205.3	170.5	238.9	175.0	266.5	176.7	338.6	184.0	423.1	191.1	521.7	200.0

BSR-V R-134a Air Cooled Performance Curve (40Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR415	30	242.1	82.1	303.6	85.2	381.7	87.5	467.8	92.3	525.8	95.5	568.3	98.8	0.0	0.0	0.0	0.0	0.0	0.0
	38	211.5	94.9	269.9	97.8	338.6	100.7	425.6	102.5	480.4	105.0	521.2	106.7	632.4	112.2	761.0	119.2	909.4	127.7
	50	167.4	116.3	220.6	121.1	282.6	125.7	355.6	130.5	404.1	133.7	441.2	135.4	549.1	138.6	666.6	144.4	802.3	150.9
	60	0.0	0.0	173.3	146.2	228.7	151.9	294.4	157.7	337.8	161.6	371.9	163.1	462.5	168.2	576.9	170.2	701.4	173.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	229.0	189.4	266.5	194.4	297.2	196.3	377.6	204.4	471.9	212.3	581.8	222.1
BSR421	30	275.5	93.2	345.5	96.7	434.4	99.3	532.5	104.7	598.5	108.4	646.8	112.1	0.0	0.0	0.0	0.0	0.0	0.0
	38	240.8	107.7	307.2	111.1	385.4	114.3	484.5	116.3	546.8	119.1	593.3	121.1	719.8	127.3	866.1	135.3	1035.0	145.0
	50	190.5	132.0	251.1	137.5	321.7	142.7	404.7	148.1	460.0	151.8	502.1	153.7	625.0	157.3	758.7	163.9	913.2	171.3
	60	0.0	0.0	197.3	165.9	260.3	172.5	335.1	179.0	384.5	183.4	423.3	185.1	526.5	190.9	656.7	193.2	798.4	197.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	260.7	215.0	303.3	220.6	338.2	222.8	429.8	232.0	537.1	241.0	662.3	252.1
BSR423	30	303.9	102.5	381.1	106.4	479.2	109.3	587.3	115.2	660.2	119.2	713.5	123.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	265.6	118.5	338.9	122.2	425.1	125.8	534.4	127.9	603.2	131.1	654.4	133.2	794.0	140.1	955.4	148.9	1141.7	159.5
	50	210.1	145.3	276.9	151.3	354.8	157.0	446.4	162.9	507.4	167.0	553.9	169.0	689.4	173.1	836.9	180.4	1007.3	188.5
	60	0.0	0.0	217.6	182.5	287.1	189.7	369.7	196.9	424.1	201.8	466.9	203.7	580.7	210.0	724.3	212.5	880.6	217.1
	70	0.0	0.0	0.0	0.0	0.0	0.0	287.5	236.5	334.5	242.7	373.1	245.1	474.0	255.3	592.4	265.1	730.5	277.3
BSR424	30	338.3	113.7	424.2	117.9	533.3	121.1	653.7	127.7	734.8	132.2	794.1	136.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	295.6	131.3	377.2	135.4	473.1	139.4	594.8	141.8	671.4	145.3	728.3	147.7	883.7	155.3	1063.4	165.0	1270.7	176.8
	50	233.9	161.0	308.2	167.7	394.9	174.1	496.9	180.6	564.7	185.1	616.5	187.4	767.4	191.9	931.5	199.9	1121.1	208.9
	60	0.0	0.0	242.2	202.3	319.6	210.3	411.5	218.3	472.0	223.7	519.7	225.8	646.3	232.8	806.2	235.6	980.2	240.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	320.0	262.2	372.3	269.1	415.3	271.7	527.6	283.0	659.4	293.8	813.1	307.4
BSR426	30	378.6	122.7	474.8	127.2	588.0	132.7	720.7	139.9	810.1	144.8	875.5	149.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	330.9	141.7	422.2	146.1	529.6	150.4	655.8	155.3	740.2	159.1	803.0	161.7	974.3	170.1	1172.4	180.7	1401.1	193.7
	50	261.8	173.7	345.0	180.9	442.1	187.8	556.2	194.9	632.1	199.8	690.1	202.2	846.1	210.1	1027.0	219.0	1236.1	228.8
	60	0.0	0.0	271.1	218.3	357.7	226.9	460.6	235.6	528.3	241.3	581.7	243.6	723.5	251.2	888.9	258.0	1080.7	263.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	358.2	282.9	416.8	290.3	464.8	293.2	590.6	305.3	738.1	317.1	910.1	331.7

BSR-V R-134a Air Cooled Performance Curve (30Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
	TC	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power	Capacity	Power
BSR213	30	48.7	18.7	61.0	19.4	76.8	20.0	94.1	21.0	105.8	21.8	114.3	22.5	0.0	0.0	0.0	0.0	0.0	0.0
	38	42.5	21.6	54.3	22.3	68.1	23.0	85.6	23.4	96.6	23.9	104.8	24.3	127.2	25.6	153.0	27.2	182.9	29.1
	50	33.7	26.5	44.4	27.6	56.8	28.7	71.5	29.8	81.3	30.5	88.7	30.9	110.4	31.6	134.1	32.9	161.3	34.4
	60	0.0	0.0	34.9	33.3	46.0	34.7	59.2	36.0	67.9	36.9	74.8	37.2	93.0	38.4	116.0	38.8	141.1	39.7
	70	0.0	0.0	0.0	0.0	0.0	0.0	46.1	43.2	53.6	44.3	59.8	44.8	75.9	46.6	94.9	48.4	117.0	50.7
BSR216	30	59.8	23.0	75.0	23.8	94.4	24.5	115.7	25.8	130.0	26.7	140.5	27.6	0.0	0.0	0.0	0.0	0.0	0.0
	38	52.3	26.5	66.7	27.4	83.7	28.2	105.2	28.6	118.8	29.3	128.9	29.8	156.3	31.4	188.1	33.3	224.8	35.7
	50	41.4	32.5	54.5	33.9	69.9	35.2	87.9	36.5	99.9	37.4	109.1	37.8	135.8	38.8	164.8	40.4	198.3	42.2
	60	0.0	0.0	42.8	40.9	56.5	42.5	72.8	44.1	83.5	45.2	91.9	45.6	114.4	47.0	142.6	47.6	173.4	48.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	56.6	53.0	65.9	54.3	73.5	54.9	93.3	57.1	116.7	59.3	143.8	62.1
BSR311	30	75.3	28.5	94.4	29.5	118.7	30.3	145.5	32.0	163.5	33.1	176.7	34.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	65.8	32.9	83.9	33.9	105.3	34.9	132.4	35.5	149.4	36.4	162.1	37.0	196.7	38.9	236.7	41.3	282.8	44.3
	50	52.1	40.3	68.6	42.0	87.9	43.6	110.6	45.2	125.7	46.4	137.2	46.9	170.8	48.0	207.3	50.1	249.5	52.3
	60	0.0	0.0	53.9	50.7	71.1	52.7	91.6	54.7	105.0	56.0	115.7	56.5	143.8	58.3	179.4	59.0	218.1	60.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	71.2	65.7	82.9	67.4	92.4	68.0	117.4	70.8	146.7	73.6	181.0	77.0
BSR314	30	95.6	35.1	119.9	36.4	150.7	37.4	184.7	39.5	207.6	40.8	224.4	42.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	83.5	40.6	106.6	41.8	133.7	43.1	168.1	43.8	189.7	44.9	205.8	45.6	249.7	48.0	300.5	51.0	359.1	54.6
	50	66.1	49.8	87.1	51.8	111.6	53.8	140.4	55.8	159.6	57.2	174.2	57.9	216.8	59.3	263.2	61.8	316.8	64.6
	60	0.0	0.0	68.4	62.5	90.3	65.0	116.3	67.5	133.4	69.1	146.9	69.8	182.6	71.9	227.8	72.8	277.0	74.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	90.4	81.0	105.2	83.1	117.3	83.9	149.1	87.4	186.3	90.8	229.8	95.0
BSR316	30	112.6	41.0	141.2	42.5	177.6	43.7	217.7	46.0	244.7	47.7	264.4	49.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	98.4	47.3	125.6	48.8	157.5	50.3	198.0	51.1	223.5	52.4	242.5	53.2	294.2	56.0	354.1	59.5	423.1	63.7
	50	77.9	58.0	102.6	60.4	131.5	62.7	165.4	65.1	188.0	66.7	205.3	67.6	255.5	69.2	310.1	72.1	373.3	75.3
	60	0.0	0.0	80.6	72.9	106.4	75.8	137.0	78.7	157.2	80.6	173.0	81.4	215.2	83.9	268.4	84.9	326.4	86.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	106.5	94.5	124.0	97.0	138.3	97.9	175.7	102.0	219.5	105.9	270.7	110.8

BSR-V R-134a Air Cooled Performance Curve (30Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR321	30	123.4	44.9	154.7	46.6	194.5	47.8	238.4	50.4	268.0	52.2	289.6	54.0	0.0	0.0	0.0	0.0	0.0	0.0
	38	107.8	51.9	137.6	53.5	172.6	55.1	216.9	56.0	244.9	57.4	265.7	58.3	322.3	61.3	387.8	65.2	463.5	69.8
	50	85.3	63.6	112.4	66.2	144.0	68.7	181.2	71.3	206.0	73.1	224.9	74.0	279.9	75.8	339.7	78.9	408.9	82.5
	60	0.0	0.0	88.3	79.9	116.6	83.1	150.1	86.2	172.2	88.3	189.6	89.2	235.7	91.9	294.0	93.0	357.5	95.0
	70	0.0	0.0	0.0	0.0	0.0	0.0	116.7	103.5	135.8	106.2	151.5	107.3	192.4	111.7	240.5	116.0	296.6	121.4
BSR323	30	145.6	52.8	182.6	54.8	229.6	56.3	281.4	59.4	316.3	61.4	341.8	63.5	0.0	0.0	0.0	0.0	0.0	0.0
	38	127.3	61.0	162.4	63.0	203.7	64.8	256.1	65.9	289.0	67.5	313.5	68.6	380.4	72.2	457.8	76.7	547.0	82.2
	50	100.7	74.8	132.7	77.9	170.0	80.9	213.9	83.9	243.1	86.0	265.4	87.1	330.3	89.2	401.0	92.9	482.6	97.1
	60	0.0	0.0	104.3	94.0	137.6	97.8	177.1	101.5	203.2	104.0	223.7	104.9	278.2	108.2	347.1	109.5	421.9	111.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	137.8	121.9	160.3	125.1	178.8	126.3	227.1	131.5	283.9	136.6	350.0	142.9
BSR324	30	161.5	58.5	202.6	60.7	254.7	62.4	312.2	65.8	350.9	68.1	379.2	70.4	0.0	0.0	0.0	0.0	0.0	0.0
	38	141.2	67.6	180.1	69.7	225.9	71.8	284.0	73.0	320.6	74.8	347.8	76.0	422.0	79.9	507.8	85.0	606.8	91.0
	50	111.7	82.9	147.2	86.3	188.6	89.6	237.3	93.0	269.7	95.3	294.4	96.5	366.4	98.8	444.8	102.9	535.4	107.6
	60	0.0	0.0	115.7	104.2	152.6	108.3	196.5	112.4	225.4	115.2	248.2	116.2	308.6	119.9	385.0	121.3	468.1	123.9
	70	0.0	0.0	0.0	0.0	0.0	0.0	152.8	135.0	177.8	138.5	198.3	139.9	252.0	145.7	314.9	151.3	388.3	158.3
BSR326	30	174.0	62.6	218.2	64.9	274.3	66.7	336.3	70.3	378.0	72.8	408.5	75.3	0.0	0.0	0.0	0.0	0.0	0.0
	38	152.1	72.3	194.0	74.6	243.4	76.8	306.0	78.1	345.4	80.0	374.7	81.3	454.6	85.5	547.0	90.9	653.7	97.4
	50	120.3	88.7	158.6	92.4	203.2	95.9	255.6	99.5	290.5	102.0	317.1	103.2	394.7	105.7	479.2	110.1	576.7	115.1
	60	0.0	0.0	124.6	111.4	164.4	115.8	211.7	120.2	242.8	123.2	267.3	124.4	332.5	128.2	414.7	129.7	504.2	132.6
	70	0.0	0.0	0.0	0.0	0.0	0.0	164.6	144.4	191.5	148.2	213.6	149.6	271.4	155.8	339.2	161.8	418.2	169.3
BSR413	30	211.3	75.0	265.0	77.8	333.2	79.9	408.4	84.3	459.1	87.2	496.1	90.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	184.7	86.7	235.7	89.4	295.6	92.0	371.6	93.6	419.5	95.9	455.1	97.4	552.1	102.5	664.4	108.9	793.9	116.7
	50	146.1	106.3	192.6	110.6	246.7	114.9	310.4	119.2	352.8	122.2	385.2	123.7	479.4	126.6	582.0	131.9	700.4	137.9
	60	0.0	0.0	151.3	133.5	199.7	138.8	257.1	144.1	294.9	147.6	324.7	149.0	403.8	153.6	503.7	155.4	612.4	158.8
	70	0.0	0.0	0.0	0.0	0.0	0.0	199.9	173.0	232.6	177.5	259.4	179.3	329.7	186.7	412.0	193.9	508.0	202.9

BSR-V R-134a Air Cooled Performance Curve (30Hz)

	TE	-15		-10		-5		0		3		5		10		15		20	
BSR415	30	235.7	83.3	295.6	86.4	371.6	88.8	455.5	93.6	512.0	96.9	553.3	100.2	0.0	0.0	0.0	0.0	0.0	0.0
	38	206.0	96.3	262.8	99.3	329.7	102.2	414.4	103.9	467.8	106.5	507.5	108.2	615.8	113.8	740.9	121.0	885.4	129.6
	50	163.0	118.0	214.8	122.9	275.2	127.6	346.2	132.4	393.5	135.7	429.6	137.3	534.7	140.6	649.1	146.5	781.2	153.1
	60	0.0	0.0	168.8	148.3	222.7	154.1	286.7	160.0	328.9	163.9	362.1	165.5	450.4	170.7	561.8	172.7	683.0	176.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	223.0	192.2	259.4	197.2	289.3	199.1	367.6	207.4	459.4	215.4	566.5	225.3
BSR421	30	268.3	94.6	336.4	98.1	423.0	100.8	518.5	106.2	582.8	110.0	629.8	113.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	234.4	109.3	299.1	112.7	375.2	116.0	471.7	118.0	532.5	120.9	577.6	122.8	700.9	129.2	843.3	137.3	1007.8	147.1
	50	185.5	134.0	244.5	139.5	313.2	144.8	394.1	150.2	447.9	154.0	488.9	155.9	608.6	159.6	738.8	166.3	889.1	173.8
	60	0.0	0.0	192.1	168.3	253.4	175.0	326.3	181.6	374.3	186.1	412.2	187.8	512.6	193.7	639.4	196.0	777.4	200.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	253.8	218.2	295.3	223.8	329.3	226.0	418.5	235.4	522.9	244.5	644.8	255.8
BSR423	30	295.9	104.0	371.1	107.9	466.6	110.9	571.9	116.9	642.8	121.0	694.7	125.1	0.0	0.0	0.0	0.0	0.0	0.0
	38	258.6	120.2	330.0	124.0	413.9	127.6	520.3	129.8	587.3	133.0	637.2	135.1	773.1	142.1	930.2	151.0	1111.7	161.8
	50	204.6	147.4	269.6	153.5	345.5	159.3	434.7	165.3	494.0	169.4	539.3	171.5	671.3	175.6	814.9	183.0	980.7	191.2
	60	0.0	0.0	211.9	185.2	279.6	192.5	359.9	199.8	412.9	204.7	454.7	206.6	565.4	213.1	705.3	215.6	857.5	220.3
	70	0.0	0.0	0.0	0.0	0.0	0.0	279.9	240.0	325.7	246.2	363.3	248.7	461.6	259.0	576.8	268.9	711.3	281.4
BSR424	30	329.4	115.3	413.0	119.6	519.3	122.9	636.5	129.6	715.5	134.1	773.2	138.7	0.0	0.0	0.0	0.0	0.0	0.0
	38	287.8	133.2	367.2	137.4	460.7	141.4	579.1	143.9	653.7	147.4	709.2	149.8	860.5	157.5	1035.4	167.4	1237.3	179.4
	50	227.7	163.4	300.1	170.1	384.5	176.6	483.8	183.2	549.9	187.8	600.3	190.1	747.2	194.7	907.0	202.8	1091.6	212.0
	60	0.0	0.0	235.8	205.3	311.2	213.4	400.6	221.5	459.6	226.9	506.0	229.1	629.3	236.2	785.0	239.0	954.4	244.2
	70	0.0	0.0	0.0	0.0	0.0	0.0	311.6	266.0	362.5	273.0	404.3	275.7	513.7	287.1	642.0	298.1	791.7	311.9
BSR426	30	368.7	124.4	462.3	129.1	572.5	134.6	701.8	141.9	788.8	146.9	852.5	151.9	0.0	0.0	0.0	0.0	0.0	0.0
	38	322.2	143.8	411.1	148.3	515.7	152.6	638.5	157.6	720.7	161.4	781.9	164.1	948.7	172.5	1141.6	183.4	1364.2	196.5
	50	254.9	176.3	335.9	183.6	430.4	190.5	541.6	197.7	615.5	202.7	671.9	205.1	823.8	213.2	1000.0	222.1	1203.5	232.2
	60	0.0	0.0	264.0	221.5	348.3	230.2	448.4	239.0	514.4	244.9	566.4	247.2	704.4	254.9	865.5	261.8	1052.2	267.4
	70	0.0	0.0	0.0	0.0	0.0	0.0	348.8	287.1	405.8	294.5	452.6	297.4	575.0	309.8	718.6	321.7	886.1	336.6