


COMMERCIAL

GARAGE DOORS



A SUPERIOR DOOR INSIDE & OUT

PERFORMANCE VERIFIED



The DASMA Thermal Performance Verification is a program that certifies the thermal performance of sectional doors. U-factor ratings tests the entire installed assembly whereas R-value is calculated for only a portion of section insulation.

PACKAGE UPGRADES

HARSH ENVIRONMENT


This package includes our toughest components to effectively stand up to Mother Nature.

- Corrosion-resistant rollers
- Galvanized spring wire
- Zinc-plated shafts
- Stainless steel cables
- 11-gauge heavy-duty hinges
- 4³/₈-inch shielded bearings on ends & center


HEAVY-DUTY HARDWARE

This package includes our durable heavy-duty hardware. Best of all, these components come standard on doors 30-feet-3-inches wide and larger.

- One-piece Triple End Stile hinges
- Grease zerks
- 5/8-inch rollers



MIDLAND GARAGE DOOR MFG CO ThermoGuard™ Door



Competitor's polyurethane door

WHY DO MIDLAND THERMOGUARD™ DOORS PERFORM BETTER?

The infrared images below show a side-by-side comparison of a Midland ThermoGuard™ door, next to a competitor's polyurethane door. This was observed with the doors installed next to the other in the same location. The outside temperature was 0°F and the inside temperature was 55°F. The dark areas show where energy loss occurs.

01

TRUE THERMAL BREAK

Midland door sections utilize a true thermal break that minimizes energy loss between sections

02

MINIMAL AIR INFILTRATION

A flexible commercial-grade seal between the door sections minimizes air infiltration

03

SUPERIOR FIT

Midland door sections have tighter and more consistent section gaps

04

MOISTURE RESISTANT

Closed cell end dams help to keep moisture away from insulation

05

STRUCTURAL RIGIDITY

Concealed full-height vertical center stiles and tailor-made custom end stiles provide structural rigidity

06

QUALITY STEEL

Hot dipped galvanized steel, that is conditioned and embossed with a pebble texture for maximum durability



Commercial ThermoGuard™

UNCOMPROMISING
QUALITY & STRENGTH

- Best thermal performance in the industry
- Polyurethane provides additional support and rigidity
- The thicker and denser insulation will decrease noise and vibrations




CHOOSE YOUR OPTIONS

SPECIFICATIONS

	3-Inch ThermoGuard™	2-Inch ThermoGuard™
U-Factor R-Value	0.11 26.0	0.14 18.0
Foam/Insulate	Polyurethane	Polyurethane
Thickness	3 inches	2 inches
Maximum Width	40 ft. 2 In.	32 ft. 2 in.
Exterior Steel	27 gauge <i>20 gauge upgrade, white only</i>	27 gauge <i>20 gauge upgrade, white only</i>
Interior Steel	27 gauge	27 gauge
Warranty* <i>Excludes Springs</i>	10 years	10 years

*For full warranty details contact your Midland dealer




COLORS



Color Select™

*ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.


WINDOWS



TRACK MOUNTING




Reverse Angle Mounted Track
Continuous leg-in angle to attach to steel jambs




Angle Mounted Track
Continuous leg-out angle used on larger doors to attach to wood jambs


TRACK CONFIGURATIONS



Standard Lift
For normal installations




Inclined Track
To follow pitch of roof



Hi-Lift
To put horizontal track as close to ceiling as possible



Vertical Lift
Full vertical rise where headroom is available



Low Headroom
For low-clearance installations

GLASS



Double Dark

*Tempered only. All other glass is available in both tempered and untempered.



Commercial EnergySaver™

SIMPLICITY & HEAVY-DUTY RELIABILITY

- Over 30 years of proven quality and durability
- Pre-formed polystyrene offers consistent fit and finish over time
- Closed-cell extruded polystyrene is perfect for high moisture environments



CHOOSE YOUR OPTIONS


SPECIFICATIONS

	3-Inch EnergySaver™	2-Inch EnergySaver™
U-Factor R-Value	0.15 17.05	0.22 9.25
Foam/Insulate	Extruded closed-cell polystyrene	Polystyrene
Thickness	3 inches	2 inches
Maximum Width	40 ft. 2 In.	24 ft. 2 in.
Exterior Steel	25 gauge <i>20 gauge upgrade, white only</i>	25 gauge <i>20 gauge upgrade, white only</i>
Interior Steel	25 gauge	25 gauge
Warranty* <i>Excludes Springs</i>	10 years	10 years

*For full warranty details contact your Midland dealer




WINDOWS




TRACK MOUNTING



TRACK CONFIGURATIONS



COLORS



GLASS



*Tempered only. All other glass is available in both tempered and untempered.



FullView & FullView Stylist

NATURAL LIGHT WITH STRENGTH & STABILITY

- Maximizes the amount of light in your space
- Modern, upscale style with a variety of options
- Offers optional insulated rails



CHOOSE YOUR OPTIONS

SPECIFICATIONS	Stylist	FullView Glass Panel	FullView Anodized Aluminum Panel
U-Factor	Not Tested	0.85	Not Tested
Frame	6063-T Aluminum	6063-T Aluminum	6063-T Aluminum
Thickness	2 inches	2 inches	2 inches
Glass	½ inch insulated ¾ inch insulated	½ inch insulated ¾ inch non-insulated ⅝ inch non-insulated	–
Panel	–	–	½ inch insulated
Rails	Insulated non-insulated	Insulated non-insulated	Insulated non-insulated
Air Infiltration Seal	•	•	•
Warranty* Excludes Springs	5 years	5 years	5 years

*For full warranty details contact your Midland dealer



FRAME COLORS



Color Select™

*ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.


GLASS




*Stylist is only available in Plain & Satin Stylist.

**Tempered only. All other glass is available in both tempered and untempered.


TRACK CONFIGURATIONS



Standard Lift
For normal installations




Inclined Track
To follow pitch of roof



Hi-Lift
To put horizontal track as close to ceiling as possible



Vertical Lift
Full vertical rise where headroom is available



Low Headroom
For low-clearance installations



CS20 • CS24 CS26 Ribbed

DURABLE ROLL-FORMED STEEL

- Entry level door that doesn't sacrifice quality
- Options for 20, 24, or 26 gauge thick steel to meet various project standards



CHOOSE YOUR OPTIONS

SPECIFICATIONS	CS20	CS24	CS26
Plain Steel U-Factor	Unrated	Unrated	Unrated
U-Factor R-Value: T-Bond:	0.38 7.05	0.38 7.05	0.38 7.05
Thickness	2 inches	2 inches	2 inches
Maximum Width	40 ft 2 in	24 ft 2 in	16 ft 2 in
Exterior Steel	20 gauge	24 gauge	26 gauge
Warranty* Excludes Springs	10 years	10 years	25 years

*For full warranty details contact your Midland dealer




COLORS



*ColorSelect™ uses Sherwin Williams Polane® Solar Reflective Polyurethane Enamel, providing a durable, heat-repelling coating.

WINDOWS




*Only available in 3-inch

GLASS






*Tempered only. All other glass is available in both tempered and untempered.

TRACK MOUNTING



TRACK CONFIGURATIONS



MIDLAND™

GARAGE DOOR MFG CO

WEST FARGO, ND
800.437.4056

EDEN PRAIRIE, MN
800.521.0047

SPRINGFIELD, NE
800.533.8358



© 2023 MIDLAND GARAGE DOOR MFG. CO. INC. ALL RIGHTS RESERVED.

MIDLAND GARAGE DOORS SOLD BY: