



SOONLINMAS PLYWOOD SDN BHD

Lot 10377, Block 5, Kuala Baram Land District,
C.D.T. 252, 98009 Miri, Sarawak, Malaysia

Tel: +6085 659 888, 663 399

Whatsapp: +6016 962 9590 (Jang)

PRODUCT CATALOGUE AS OF 2024



WWW.SOONLINMASPLYWOOD.COM



JANG.K@SOONLINMAS.COM

About Us

We are a leading plywood and blockboard manufacturers mainly in Malaysia and Indonesian with over 25 years experiences.

In the other hand, we also have businesses partners (suppliers) all over the world which we exchange our business with partners in China, Myanmar, Vietnam, and Thailand.



Export Businesses

We have export to over 30 countries such as USA, Thailand, Korea, Dubai, Middle East, Mexico, South Africa, Australia, Myanmar, South East Asia, Europe, East Africa, China, India etc. We open the opportunities to collaborate with more businesses from different countries and offer the best plywood and blockboard.

FULL HARDWOOD PLYWOOD



**SOONLINMAS PLYWOOD
MALAYSIA**



Property	Common Specification	Characteristic
Thickness	2.7mm - 24.0mm	<ol style="list-style-type: none"> 1. Heavy 2. High Strength 3. Expensive 4. Smooth Surface 5. Easy working 6. Red/brown/ yellow faces depends <p>Suitable for high-class furniture Interior/Exterior</p>
Sheet Size	Up to 4FT x 10FT	
Glue Type	MR / T1.5 / WBP / Phenolic	
Wood Material	Tropical Hardwood - MY, IND ex. Meranti, Keruing, Rubberwood	
Formodehyde Level	Class E1 E2 E0, CARB B2	
Documents	All necessary documents can be provided	
Grade	UTY/ UTY BTR/ BBCC/ OVL	

*Customised product requirements is available upon request

*Special certificates is available upon request

FULL FALCATA PLYWOOD



**SOONLINMAS PLYWOOD
MALAYSIA**



Property	Common Specification	Characteristic
Thickness	2.7mm - 24.0mm	1. Light Weight 2. Cheapest in Plywood 3. Easy working 4. White colour Suitable for 1. price-oriented projects 2. Interior/Exterior
Sheet Size	Up to 4FT x 10FT	
Glue Type	MR / T1.5 / WBP / Phenolic	
Wood Material	Plantation Softwood, also called Albasia/ Sengon/ Falcata. IND	
Formodehyde Level	Class E1 E2 E0, CARB B2	
Documents	All neccessary documents can be provided	
Grade	UTY/ UTY BTR/ BBCC	

*Customised product requirements is available upon request

*Special certificates is available upon request

F/B HARDWOOD CORE FALCATA PLYWOOD



**SOONLINMAS PLYWOOD
MALAYSIA**



Property	Common Specification	Characteristic
Thickness	2.7mm - 24.0mm	<p>1. Heavier than Full Falcata</p> <p>2. High Strength</p> <p>3. Affordable</p> <p>4. Red/brown/yellow faces follows hardwood colour</p> <p>Suitable for high-class furniture Interior/Exterior</p>
Sheet Size	Up to 4FT x 10FT	
Glue Type	MR / T1.5 / WBP / Phenolic	
Wood Material	Face & Back: Hardwood Core: Falcata - IND	
Formaldehyde Level	Class E1 E2 E0, CARB B2	
Documents	All necessary documents can be provided	
Grade	UTY/ UTY BTR/ BBCC/ OVL	

*Customised product requirements is available upon request

*Special certificates is available upon request

BENDING/ FLEXIBLE PLYWOOD



**SOONLINMAS PLYWOOD
MALAYSIA**



Property	Common Specification	Characteristic
Thickness	2.7mm - 8.0mm	1. High Elasticity 2. short & long grain 3. Time savings 4. Broad function available
Sheet Size	Up to 4FT x 8FT	
Glue Type	MR	
Wood Material	Falcata/ Combi (Mix) IND Full Hardwood MY	
Formdehyde Level	Available upon request	
Documents	All neccessary documents can be provided	Suitable for 1. Bending furniture/ deco furniture 2. Interior/Exterior
Grade	UTY BTR/ BBCC	

*Customised product requirements is available upon request

*Special certificates is available upon request

BLOCKBOARD

- ~ F/B MLH Core Falcata
- ~ Full Falcata



**SOONLINMAS PLYWOOD
MALAYSIA**

Property	Common Specification	Characteristic
Thickness	12 mm - 49mm	1. Light weight 2. Easy working 3. Affordable 4. Warp Resistance Suitable for Interior/Exterior Door, Cabinets, Tables...
Sheet Size	Up to 4FT x 8FT	
Glue Type	MR / T1.5 / WBP / Phenolic	
Wood Material	Depends on requirement. MLH = Mixed Hardwoods IND	
Formodehyde Level	Class E1 E2 E0, CARB B2	
Documents	All necessary documents can be provided	
Grade	UTY BTR/ BBCC	

*Customised product requirements is available upon request

*Special certificates is available upon request

TEGO FILMED/ FILMED FACED PLYWOODS



**SOONLINMAS PLYWOOD
MALAYSIA**

Logo on film available upon request

Property	Common Specification	Characteristic
Thickness	12mm - 24mm	1. Reusable 5-20 times depends on grades 2. Waterproof 3. High resistance to weather Suitable for Construction Usage
Sheet Size	Up to 4FT x 10FT	
Glue Type	MR / T1.5 / WBP / Phenolic	
Wood Material	Full Hardwoods -MY -VN Construction Plywoods	
Formaldehyde Level	Class E1 E2 E0, CARB B2	
Documents	All necessary documents can be provided	
Grade	Grade A, B, C	

*Customised product requirements is available upon request

*Special certificates is available upon request

Grading Guides

No	Visual Disability	BBCC	UTY/BTR	UTY EXPORT
1	Open Spilt	* Max width 3mm length 250mm 2 point * Nice puttied with flat surface, same colour	*Max width 3mm length 500mm 2 point *Nice puttied with flat surface, same colour	* Max width 9mm * Nice puttied with flatsurface and same colour
2	Dead Knots	* Diameter 10mm 2 pt *Nice puttied with flate surface, same colour	* Diameter 20mm 3 pt *Nice puttied with flat surface, same colour	* Diameter 20mm Max. 5 point ; a swarm of dead knots is not allowed
3	Discolouration	Not allowed	It is allowable as long as not too extreme	It is allowable
4	Ripping	Not allowed	Not allowed	Not allowed
5	Swollen	Not allowed	Not allowed	Not allowed
6	Patching	Not allowed	Max. width 10cm length 15mm 3 point and same colour	Max. width 10cm length 15mm 5 point and same colour
7	Face Join	Not allowed	Not allowed	Max. 2 point and same colour
8	Samping Kurang	* Face width 2mm length 300mm with nice puttied	* Face width 3mm length 5cm with nice puttied	* Face width 3mm with nice puttied and same colour
9	Over Sanding	Not allowed	Not allowed	Not allowed
10	Core Hole	*Max. 2mm stuffed	*Max. 3mm stuffed	*Max. 5mm stuffed
11	Core Overlap	*Max. width 2mm length 150mm, flat and smooth	*Max. width 3mm length 200mm, flat and smooth	*Max. width 5mm length 400mm, not broken

Grading Guides cont.

No	Visual Disability	BBCC	UTY/BTR	UTY EXPORT
12	Press Mark	*Max. width 2mm length 50mm nice puttied with flat surface	*Max. width 3mm length 60mm nice puttied with flat surface	width 5mm length 100mm nice puttied with flat surface
13	Cutter Mark	*Not allowed	*Max. 2-3 point polished evenly	Must be polished evenly
14	Glue Penetration	*Not allowed	*Not allowed	Slightly is acceptable but should not be stack
15	Blue Stin	*Not allowed	Max. 10cm at side	Max. 20cm at side

To enhance on quality control progresss, we hire graders to double confirm on the qualities

Send Enquiries NOW (FOB/CNF)



JANG.K@SOONLINMAS.COM



+6016 962 9590 (Jang)



**Receive Quotation in FOB / CNF
Proceed for Trial Order**



**Check goods quality before shipment:
Grading photos provided / On site gradings**



Shipment arranged. & Payment Terms:

- 1. Letter of Credit**
- 2. Deposit 30% & TT against documents**



Check documents & confirm upon goods arrivals



After Sales: Provide feedbacks



Sample request is available for some products only



SOONLINMAS PLYWOOD SDN BHD

Lot 10377, Block 5, Kuala Baram Land District,
C.D.T. 252, 98009 Miri, Sarawak, Malaysia

Tel: +6085 659 888, 663 399

Whatsapp: +6016 962 9590 (Jang)