## www.TAILGATETALKS.com

AN OCCUPATIONAL SAFETY & HEALTH TRAINING SERIES FOR HIGH HAZARD INDUSTRIES

www.TailgateTalks.com

© 2016 Courage Safety Systems, LLC., San Clemente, CA 92673 Tel: (800) 673-7569

Company Name:	Dept:	Location:	Date:	
			#207	7
Stru	ck-By: Constructi	ion Vehicles & He	eavy Machinery	
Approximately 75% of struck vehicle safety practices can	-by fatalities involve heavy increase the risk of injury. other vehicle or other equip	/ equipment such as truck Such injuries include, bei	eaths is being struck by an object. ss, cranes or backhoes. Failure to follow ing pinned between the vehicle and g backhoes, crushed beneath overturned	
apparent damage that cou  Whenever equipment is parapossible. If the machine is ground, apply the parking I  Do not operate vehicle at a sawareness and decrease so Always keep a lookout for acceptable: an automatic be braking device, which will a operator when backing up  Never move, lift or swing a sure everyone is aware that Avoid injury from rollover a serious or fatal crushing in it is evenly distributed and  Be careful working at the elements.	each shift to ensure that all ld cause failure while in us arked, the parking brake shift to be parked on an incline brake, and securely block is speeds which will endange speed when traveling over bystanders; warn them who ack-up audible alarm which apply the brake on contact can be used as well. I load over anyone. When at heavy machinery is being accidents. Wear the seatbed juries may result. Be care the load is stable, know the dge of an excavation, near elocal conditions. Read a	parts and accessories arese.  In all be set. Always park the per always lower the buckethe wheels.  In the driver, traffic or peopuneven ground. Do not the necessary. When back the can be clearly heard from the with an object. A spotter possible, clear the immediate with an object. A spotter possible, clear the immediate with an object of the immediate of the period of the machine and the open and understand of the open and the	the in safe operating condition and free of the machine on level ground where the so that the cutting lips contact the cole in the surrounding area. Increase the ransport anyone on the loader bucket, obking up, the following warning devices at som a distance of 200 feet; an automatic for flagger in clear view to direct the diate surrounding working area, or make ap clear of tripping machines because lope; avoid sharp turns, balance weight seems to the control of the	are
Meeting Conducted By	:			)
Meeting Attended By:	Print Name		Signature	
			Document Filing Reference	
Notes & Suggestions		s "Tailgate Talk" should be filed in empl	loyer's safety training records and cross-	,