

General Notes for Wall Sections

- (3) SEE EXTERIOR ELEVATIONS FOR BRICK COLOR.
- (4) GENERAL CONTRACTOR SHALL VERIFY TOP OF FINISH GRADES, TOP OF OF CONCRETE WALKS AND TOP OF CONCRETE SLABS ADJACENT TO BUILDING AND ADJUST LAYOUT OF EXTERIOR WALL FLASHING ACCORDINGLY.
- (5) PROVIDE PLASTIC NESTER WIPES AT ALL DOOR, WINDOW AND FLOOR FLASHING.
- (6) GENERAL CONTRACTOR SHALL SLOPE CONCRETE FLOOR TO FLOOR DRAINS AS SHOWN ON PLUMBING DRAWINGS.
- (7) ALL CMU CELLS BELOW FINISH FLOOR SHALL BE FILLED WITH CONCRETE.
- (8) ALL VAPOR BARRIERS UNDER FLOOR SLABS SHALL BE LAPPED 17" MINIMUM AND TAPED CONTINUOUS AT JOINTS. GENERAL CONTRACTOR SHALL REPAIR ANY DAMAGED VAPOR BARRIER PRIOR TO PLACING CONCRETE.
- (9) PROVIDE 4" MINIMUM SPRAY POLYURETHANE INSULATION IN ALL METAL STUDS EXTERIOR WALLS, SEAS AND FOUNDATIONS.
- (10) PROVIDE SPRAY POLYURETHANE INSULATION IN ALL NESTED METAL STUD WINDOW AND DOOR JAMBS, SILLS AND HEADS.
- (11) ALL INTERIOR METAL STUD/GYPSUM WALLBOARD PARTITIONS REQUIRE SOUND ATTENUATION BATT'S.
- (12) PROVIDE METAL CHAIRS UNDER ALL STEEL WIRE MATS REINFORCING STEEL FOR CONCRETE SLABS AND FOUNDATIONS.
- (13) PROVIDE GYPSUM CONTROL JOINTS AT ALL GYPSBOARD / METAL STUD WINDOW JAMBS. SEE INTERIOR ELEVATIONS.
- (14) ALL SEALANT COLORS TO BE SELECTED BY ARCHITECT.
- (15) ROOF INSULATION TAPE ALL ROOF INSULATION JOINTS, BOTH LAYERS, LAP AND TAPE VAPOR BARRIER, ARCHITECT TO FILL VERTIFY PRIOR TO METAL ROOF PANEL INSTALLATION. FORMER AT THE JOINTS.
- (16) PROVIDE PRE-FORMED THRU-WALL FLASHING CORNER MEMBERS FOR EXTERIOR WALL FORMS AT THE JOINTS.

