



**Toyota Hilux/Revo 2005-Present
Runflat Specifications
Assembly PN# HLXRF-DT**

Web: www.dimensiontek.com

Tel.: 614-638-2854

E-mail : info@dimensiontek.com

955 Caniff Rd. Columbus, OH 43221

Cage: 7HX48

Runflat Assembly Components

- ❑ 17" Runflat, FINABEL 20.A.5
- ❑ 17"x 7.5", One Piece Steel Wheel, ISO/DOT
- ❑ 265/70R17 115S All-Terrain Tire , DOT

Runflat Assembly Specifications

Runflat Specification Met: 17"

- FINABEL 20.A.5, travel a total distance of 31mi/50km on the road (desirable: 46mi/75km), without tires coming off rims or starting to burn, and without its properties of steering maneuverability, stability or speed being seriously affected under the following conditions:
- - 2mi/3km at maximum speed (escape speed),
- - 6mi/10km at uniform speed of 31mph/50km/h,
- - The rest of the distance at a uniform speed of 16mph/25km/h
- - Runflat rated: 3307 lb/1500kg



Runflat Assembly Specifications

Wheel Specifications:

- 17"x7.5" Six Lug Toyota Style One Piece Steel Wheel.
- DOT Approved, Conforming to ISO MFG. standards.
- Rated to 2646lbs./1200kgs



Runflat Assembly Specifications

Tire Specifications:

- Kenda Klever All-Terrain Tire - P265/70R17 115S
- Approval: DOT
- Ply: NA
- Load Rating: 115 2679lbs./1215kg
- Speed Rating: S 112mph/180km/h
- Exceeds OEM P265/65R17 112S Tire



Runflat Assembly Specifications

Assembly Estimated Size/Weight Each

- Size: 30.7"x 10.7" / 780mm x 272mm
- Weight: 92lbs./42kg



Dimension**tek**

Web: www.dimensiontek.com

Tel.: 614-638-2854

E-mail: info@dimensiontek.com

955 Caniff Rd.

Columbus, OH 43221

Cage: 7HX48