



**Toyota LC70 Series HD Runflat  
Specifications  
Assembly PN# LC70HDRF-DT**

Web: [www.dimensiontek.com](http://www.dimensiontek.com)

Tel.: 614-638-2854

E-mail : [info@dimensiontek.com](mailto:info@dimensiontek.com)

*955 Caniff Rd. Columbus, OH 43221*

*Cage: 7HX48*

## Runflat Assembly Components HD

- ❑ 16" Runflat, FINABEL 20.A.5
- ❑ 16"x 7", One Piece Steel Wheel, ISO/DOT
- ❑ LT265/75R16 All Terrain Tire, DOT

# *Runflat Assembly Specifications HD*

## **Runflat Specification Met: 16"**

- FINABEL 20.A.5, travel a total distance of 31mi/50km on the road (desirable: 46mi/75km), without tires coming off rims or starting to burn, and without its properties of steering maneuverability, stability or speed being seriously affected under the following conditions:
- - 2mi/3km at maximum speed (escape speed),
- - 6mi/10km at uniform speed of 31mph/50km/h,
- - The rest of the distance at a uniform speed of 16mph/25km/h
- - Runflat rated: 3307 lb/1500kg



# *Runflat Assembly Specifications HD*

## **Wheel Specifications:**

- 16"x7" Five Lug One Piece Steel Wheel.
- DOT Approved, Conforming to ISO MFG. standards.
- Rated to 4630lbs./2100kgs



# *Runflat Assembly Specifications HD*

## **Tire Specifications:**

- Kenda Klever A/T All Terrain LT265/75R16
- Approval: DOT
- Ply: 10
- Load Rating: 123 3417lbs./1550kg
- Speed Rating: Q 99mph/160km/h



# *Runflat Assembly Specifications HD*

## **Assembly Estimated Size/Weight Each**

- Size: 31.7"x 10.6" / 805mm x 269mm
- Weight: 94lbs./45kg



# Dimension**tek**

Web: [www.dimensiontek.com](http://www.dimensiontek.com)

Tel.: 614-638-2854

E-mail: [info@dimensiontek.com](mailto:info@dimensiontek.com)

955 Caniff Rd.

Columbus, OH 43221

Cage: 7HX48