

| | | | |
|--|-------------------------------|---------------------------------|---------------------------|
| MANUFACTURING PART # VPG-1310-TGTS | INNER DIAMETER 13mm | OUTER DIAMETER 17.5mm | LENGTH 10 Meter |
|--|-------------------------------|---------------------------------|---------------------------|




ACTIVFLEX PROTECTIVE TUBING

- High-Temperature, Spatter-Resistant Cable & Hose Protection
- Suitable for casting, welding and industrial applications.
- Pre-slit along length for retrofitting in field installations

| | Property | Specification | Unit | Value |
|------------------------------|---------------------|---|-------|-------|
| General | Color | | | Gray |
| | Applications | Welding, casting, industrial, general purpose | | |
| | Material | PTFE | | |
| | Coating | none | | |
| | Split Configuration | Split entire length | | |
| Mechanical | Inner Diameter | +/- 5% | mm | 13.0 |
| | Outer Diameter | +/- 5% | mm | 17.5 |
| | Wall Thickness | +/- 5% | mm | 0.85 |
| | Length | +/- 5% | m | 10.0 |
| | Bend Radius | min. | cm | 5 |
| Operating Temperature | -50 to +250 deg C | Continuous (max) | deg C | 250 |


I.D. = 13 mm



O.D. = 17.5 mm

WALL THICKNESS = 0.85 mm

OVERALL LENGTH = 10 meter



APPLICATION NOTE:

- Product intended for application within operating temperature specifications.
- Product not intended for fluid handling applications.
- Operators of the product are responsible for compliance with measures relating to the protections of persons, equipment, electrical standards and environmental regulations.