



OUR STEEL TANK RANGE IS AVAILABLE IN A VARIETY OF COLOURS, CAPACITIES AND THICKNESSES. WE CAN ACCOMMODATE ANY CUSTOMER REQUIREMENT, INCLUDING ONE-OFF AND BESPOKE SYSTEMS. FURTHERMORE, WITH OUR HIGHLY SKILLED FABRICATOR WELDERS, YOU WILL RECEIVE A STEEL PRODUCT THAT WILL OUTSHINE ANY OTHER.

<p>1100SB 1100SBFS</p> <p>Length: 1750mm Width: 1000mm Height: 1000mm Capacity: 1100 litres Weight: 500kg</p>	<p>1400SB 1400SBFS</p> <p>Length: 1830mm Width: 1100mm Height: 1100mm Capacity: 1400 litres Weight: 650kg</p>	<p>1800SB 1800SBFS</p> <p>Length: 1750mm Width: 1220mm Height: 1220mm Capacity: 1800 litres Weight: 775kg</p>	<p>2700SB 2700SBFS</p> <p>Length: 2500mm Width: 1250mm Height: 1250mm Capacity: 2700 litres Weight: 950kg</p>
<p>5000SB 5000SBFS</p> <p>Length: 3000mm Width: 1500mm Height: 1500mm Capacity: 5000 litres Weight: 2000kg</p>	<p>10000SB 10000SBFS</p> <p>Length: 3660mm Width: 1830mm Height: 1830mm Capacity: 10000 litres Weight: 2500kg</p>	<p>15000SB 15000SBFS</p> <p>Length: 3000mm Width: 2500mm Height: 2500mm Capacity: 15000 litres Weight: 5500kg</p>	<p>20000SB 20000SBFS</p> <p>Length: 4000mm Width: 2500mm Height: 2500mm Capacity: 20000 litres Weight: 6500kg</p>

*Note: dimensions exclude cabinet, weights are approximate



STEEL BUNDED TANK RANGE



Features

- All models:
- Vent
 - 1" BSP bottom outlet
 - Overfill prevention valve
 - Channel runners
 - Lifting lugs
 - Euroguard primer finish as standard (other specifications available on request)
 - Tank Pack (1" - 1/2" adaptor, ball valve and filter)

- 1100/1400/1800/2700 models:
- 2" fill point on top of the tank
 - Visual float gauge

- 5000/10000/15000/20000 models:
- 2" fill point located within the cabinet
 - Hydrostatic contents gauge
 - Small fill point cabinet with hinged door

Optional Extras

- Locking fill cap with 2 keys
- Fire Protection
- Electronic Remote Reading Gauge
- High Accuracy Contents Gauge & Bund and Overfill Alarm Unit, 240V (Tuffa FMS)
- Security Fill Point Cabinet with lockable hinged door
- Various other colours available
- 240v bund/overflow alarm
- Tank stand - manufactured to suit

STEEL DISPENSING TANK RANGE



Features

- 240V Submersible Pump (Approx 60lpm)
- 4 metres of Delivery Hose
- Automatic Shut off Nozzle
- Nozzle Parker
- Digital Flowmeter
- 10 micron Filtration - particulate only
- High Accuracy Contents Gauge & Bund and Overfill Alarm Unit (Tuffa FMS)
- Overfill Prevention Valve
- 2" Fill Point
- Ventilation
- Lockable Security Cabinet
- Channel Runners
- Lifting Lugs
- Paint specification: Euroguard Primer Finish as standard (other specifications available on request)

Optional Extras

- Walk-in Cabinet
- Key Switch
- Locking Fill Cap with 2 keys
- Extra Length Delivery Hose
- High Flow Pump (Approx. 80lpm)
- 10micron Water & Particulate Filter
- Armco
- Hose Reels
- Flowmeter Pulse Output- for connection to existing Fuel Management
- Fire Protection
- Also available: Various colours, split compartments, calibrated gauges and more
- Tank stand - manufactured to suit

Facts

- Manufactured in mild steel to BS EN/10 025
- Manufactured to BS799 Part 5
- Outer bund to contain 110% of the inner tank volume
- Serviceable life in excess of 30 years (with regular maintenance)
- Fully bunded to comply with Oil Storage Regulations
- Inner tank and outer bund pressure tested

Benefits

- We offer a unique service, whilst being a large operation we still have the groundings of a friendly, family, personal, one to one service.
- We use only premium quality equipment.
- Bespoke tanks available upon request.
- Expert technical advice at hand to assist you.
- Design versatility to suit almost every site requirement
- Size and capacities to suit clients' footprint or site limitations
- Needs only hard standing foundation

Our steel tanks are available in a range of colours, capacities and thicknesses. They are manufactured to your specification including critical dimensions and Fire Protection for both domestic and commercial applications. We also include a lock facility to ensure a high level of security is achieved. Steel bunded or plastic inner/steel outer tanks are available.





Larger bulk models available - call for more details

STEEL FIRE PROTECTED TANK RANGE

Features

900SBFP / 30
900SBFP / 60

Length: 1700mm
Width: 800mm
Height: 1250mm
Capacity: 900 litres
Weight: 550kg/650kg

1100SBFP / 30
1100SBFP / 60

Length: 2000mm
Width: 1000mm
Height: 1000mm
Capacity: 1100 litres
Weight: 600kg/700kg

1400SBFP / 30
1400SBFP / 60

Length: 2000mm
Width: 1250mm
Height: 1100mm
Capacity: 1400 litres
Weight: 700kg/800kg



Small Security cabinet available as an optional extra

1640SBFP / 30
1640SBFP / 60

Length: 1900mm
Width: 1250mm
Height: 1250mm
Capacity: 1640 litres
Weight: 750kg/850kg

2300SBFP / 30
2300SBFP / 60

Length: 2500mm
Width: 1250mm
Height: 1250mm
Capacity: 2300 litres
Weight: 950kg/1050kg



Can be installed inside for Extra Security

4500SBFP / 30
4500SBFP / 60

Length: 3000mm
Width: 1500mm
Height: 1500mm
Capacity: 4500L
Weight: 1400kg/1500kg

8700SBFP / 30
8700SBFP / 60

Length: 3600mm
Width: 1830mm
Height: 1830mm
Capacity: 8700L
Weight: 2200kg/2350kg

*Note: dimensions exclude cabinet, weights are approximate

Description

The inner tank is clad in either a 30 minute or 60 minute fire rated material, then completely enclosed in a mild steel bund making the unit weatherproof and secure. The fire rated material can be fitted to any Tuffa Tank giving a secure fire-rated oil storage solution for both the domestic and non-domestic market.

Fire protected fuel stations also available



Does it comply with Regulations?

The FireStop is designed with a 'fire barrier' to protect oil tanks where fire protection is necessary. The fire barrier is constructed from high quality fire retardant material, with the following achievements:

Independently tested to BS476: Part 22: 1987
Independently tested to BS476 (Warrington Fire Research Centre)
Meets Section J 5.4 of Building Regulations, Table 5.1 for Fire Protection for Oil Storage Tanks
LABC (Local Authority Building Control) System Approval
CE marked in accordance with EN13341 and the Construction Products Regulations.

- Fire Retardant material integrally fitted
- 2" BSP fill point complete with cap and chain
- Vent
- Clock gauge & remote reading electronic watchman sonic gauge, 240v mains.
- 1" BSP bottom outlet (top outlet available on request)
- Overfill prevention valve
- Channel runners (these will increase the tank height)
- Lifting lugs
- Paint specification: Euroguard Primer Finish as standard (other specification available on request)

Optional Extras

- Lockable fill point cabinet
- Tank pack (1" – ½" adaptor, ball valve and filter)
- Lockable fill point
- Various colours available, including Sandstone
- Full station equipment



Larger sizes available

We are able to manufacture tanks of all sizes with Fire Protection, up to a capacity of 200,000 litres.

This steel Fire Protected inner tank makes up part of a mammoth steel tank weighing in at 18 tonnes. The tank measured up at 12000mm (L) x 2700mm (W) x 2500mm (H) and consisted of 1x 47,000 litre and 1x 10,000 litre compartment suitable to store Diesel and AdBlue respectively.