



OUR RANGE OF EASY TO HANDLE ABOVE GROUND ADBLUE TANKS THAT PROVIDE HIGHLY PROFESSIONAL SOLUTIONS FOR ADBLUE STORAGE TO ALL CUSTOMER GROUPS; MANUFACTURED TO AUS32 GUIDELINES.

The Chemical characteristics of AdBlue require special storage and handling equipment. AdBlue Systems can be manufactured from 1350 litres up to a capacity of 15000 litres, plus. All AdBlue tanks incorporate specialised equipment suitable for the AdBlue aqueous solution, and are manufactured to fulfil the highest demands of quality, stability and longevity.

FIS will be very pleased to offer advice and consultation with regards to bespoke AdBlue storage tank systems to suit your particular requirements.



1350SLBFS/SKYBLUE

Dimensions: 2680mm (L) x 870mm (W) x 1665mm (H)



1400VBFS/SKYBLUE

Dimensions: 1585mm (DIA) x 1740mm (H)



2300SBFS/SKYBLUE

Dimensions: 1850mm (L) x 1250mm (W) x 2500mm



2500HBFS/SKYBLUE

Dimensions: 2840mm (L) x 1520mm (W) x 1630mm (H)



3200SBFS/SKYBLUE

Dimensions: 1850mm (L) x 1250mm (W) x 3500mm (H)



3500VBFS/SKYBLUE

Dimensions: 2034mm (DIA) x 2520mm (H)



6000VBFS/SKYBLUE

Dimensions: 2580mm (DIA) x 2610mm (H)



10000VBFS/SKYBLUE

Dimensions: 2890mm (DIA) x 2600mm (H)



15000VBFS/SKYBLUE

Dimensions: 2860mm (DIA) x 3500mm (H)

Optional Extras

- **Auto-operation Nozzle Holster** – like standard forecourt pumps, an auto-operation nozzle holster cuts off the pump when the user finishes dispensing
- **Pulsed Output Flowmeter** – allows connection to an existing fuel monitoring system
- **Temperature Control Environment Package** - for applications which are to be employed in to extreme environments
- **Liquid Monitoring Remote Management Systems** – that have the capability to control and manage the consumption of AdBlue
- **Telemetry** – Remote contents level monitoring via web
- **Hose Reel** - various lengths
- **Extra length delivery hose**

Why Buy?

- We are the UK's Largest AdBlue **Tank Manufacturer**
- A wide variety of capacities available from **1,350 litres to 15,000 litres**, and interlinking to obtain larger capacities is an option.
- Horizontal and Vertical models available
- **Plastic inner / Steel outer** (Spacesaver) models available for sites with limited space
- All AdBlue tanks incorporate **premium quality equipment**, and are of a fully bonded construction that offers integral protection from leaking and overfilling.
- The **FMS**, a combined high accuracy gauge and bund/overfill alarm unit, is fitted to all our larger models
- The refuelling equipment is easily accessible on all tanks from ground level
- Tanks are secure; all our tanks are **fully lockable**
- Manufactured to **AUS32 / DEF Guidelines**

Specification



	2" TODO Coupling	Screened Vent	Sub Pump	Digital Flowmeter	Clock Gauge	FMS Unit	4m Hose + Nozzle	Stainless 'Y' Filter	Lockable Cabinet	Lockable Flip Lid	Plastic Inner/ Steel Outer
1350	*	*	*	*	*		*	*		*	
1400	*	*	*	*	*		*	*		*	
2300	*	*	*	*		*	*	*	*		*
2500	*	*	*	*	*		*	*		*	
3200	*	*	*	*		*	*	*	*		*
3500	*	*	*	*		*	*	*	*		
6000	*	*	*	*		*	*	*	*		
10000	*	*	*	*		*	*	*	*		
15000	*	*	*	*		*	*	*	*		