

C-SERIES

C-Series Commercial 180 LPM



Ideal for heavy duty commercial environments

Suitable for HGV, large boats, locomotives and plant

Petrol, Diesel, Gas Oil, Avgas and Jet A1
W&M, ATEX, DMG14 and MID approved

0.2% meter accuracy

Single or three-phase motors

Stainless steel construction

Range of interface options

Use with above and below-ground tanks

The C-Series Commercial 180 LPM pump is a must for heavy duty, commercial environment high-speed refuelling of HGV, large boats, locomotives and heavy plant equipment.

Although a mono-only pump, the two pumping units with integral air separation are housed in our stainless steel twin cabinet with a single 1 1/2" outlet, 1 1/2" hose and ZVA 32 nozzle, or as a single pump with twin hoses. This option provides two speeds and gives the user the ability to refuel the standard vehicle fleet at 180 LPM and at 60 LPM.

The attention to detail and quality of components used to construct the C-Series range ensures you will receive a truly reliable product which provides fast, accurate and repeatable fuel dispensing, time and again.

C-SERIES



C-Series Commercial 180 LPM

Specification

- › Single-sided 25mm illuminated digital commercial displays (volume only)
- › Pumping unit with integral air separation (not included in dispenser format)
- › 0.2% meter accuracy
- › Solenoid valve
- › Approved 'latch open' nozzles with safety break
- › 3.5m Elaflex hose 1 1/2" (black colour as standard)
- › Infra-red management control
- › Stainless steel construction
- › Single or three-phase motors (115v/230v/380v)
- › Integral nozzle locking (no padlocks required)
- › Twin pick-up (2" supply work recommended)
- › Interface options include Pulse, Serial, Gilbarco 2 Wire and HL2
- › Manufactured to EN13617-1 SIRA Certificate number 05ATEX9095
- › Approved by UK Weights & Measures (attendant operated or fuel monitoring system)
- › Measuring Instrument Directive approved
- › Ministry of Defence Design and Maintenance Guide 14 (DMG14)
- › 12 months warranty

Options

- › Second side display (volume only)
- › Stainless steel under-pump plinth
- › Galvanised under-pump stool
- › GRP under-pump sump
- › Marine grade stainless steel panels available
- › Aviation hoses available
- › Avgas suitable conversions available
- › Second outlet 60 LPM

Dimensions

- › 1425mm (H) x 540mm (W) x 450mm (D) – Weight: 140kg

Checklist

- ✓ Approved for Re-sale
- ✓ Petroleum & Diesel
- ✓ Alternative Fuel
- ✓ Electronic

C-SERIES



C-Series Commercial 180 LPM

Product codes

Part no	Description
SC11EEHC	Series C Commercial Mono Suction Single Sided – Nominal 180 LPM
SC11EEHC/DISP	Series C Commercial Mono Dispenser Single Sided – Nominal 180 LPM
SC12EEHC	Series C Commercial Mono Suction with Twin hose Single Sided – Nominal 60/180 LPM

Accessories

COMDIS001	Second side Mono Commercial (Volume) Display
MS000022	Galvanised Twin Under Pump Stool
NC002082	GRP Under Pump Twin Sump
Plinthkit-Twin	Standard St/St Plinth kit for Twin