



Lumeno India

PRODUCT CATALOGUE - 2025-26

QUALITY PRODUCT IN LED LIGHTING

www.lumenoindia.com

INTRODUCTION

LUMENO is synonym to energy efficient and best quality lighting products across the length and breadth of India. Originally called as Super Lite, a household name for generations, the brand is known for its quality and after-sale services combined with an extensive network of dealers and suppliers across the country. LUMENO is a Lighting company founded by Mr. Vipin Ruwali. It is one of the most well known brand among Indian consumers. The company has been operating in India for more than 10 years and its key business areas include LED Lighting and Outdoor Lighting. Founded in 2015 as a Fancy Light Company, today LUMENO becomes the No. 1 Lighting Company in the area of Wall, Outdoor and Hanging Lighting. LUMENO is one of the fastest growing LED lighting companies in India. LUMENO is also a leader in Outdoor LED Lighting. It offers a huge collection of LED products in various categories like Hanging, Outdoor, Mirror and Wall Lights with protective technology. All products are made with higher and innovative technology. So, they are known to increase the quality of consumer's professional. LUMENO is the brand meant to produce innovative products of various types, using LED for both indoor and outdoor usage. These products are meant to be the best substitute and replacement to the lighting products that are currently being used. All "Amase" products come with in-house modules; drivers are fitted with leading brands of LEDs. All LUMENO Products are highly energy efficient, radiation free, eco friendly with excellent durability & light output. "LUMENO" has a range of products under the category of outdoor lights, wall lights, fancy lights & garden lights to meet the various light output demand.

OUT DOOR ONE WAY

LL-ODW-101



Watts : 6W
Dimension : 65mm*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-102



Watts : 12W
Dimension : 90mm*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-103



Watts : 24W
Dimension : 120mm*215mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-104



Watts : 36W
Dimension : 120mm*275mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-105-S LL-ODW-105



Watts : 6W*2 WAY
Watts : 12W*2 WAY
Dimension 6W : 65mm*150mm
Dimension 12W : 90mm*220mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-106



Watts : 24W*2
Dimension : 120mm*340mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-107



Watts : 36W*2
Dimension : 120mm*420mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-108



Watts : 12W
Dimension : 90mm*130mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-109



Watts : 18W
Dimension : 90mm*220mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR ONE WAY

LL-ODW-110



Watts : 24W
Dimension : 130mm*250mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-111



Watts : 30W
Dimension : 130mm*280mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-112



Watts : 36W
Dimension : 130mm*310mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-113



Watts : 40W
Dimension : 130mm*340mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-114



Watts : 7W*2
Dimension : 90mm*235mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-115



Watts : 12W*2
Dimension : 90mm*235mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-116



Watts : 18W*2
Dimension : 90mm*355mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-117



Watts : 24W*2
Dimension : 130mm*395mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-118



Watts : 30W*2
Dimension : 130mm*450mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR TWO WAY

LL-ODW-119



Watts : 40W*2
Dimension : 130mm*530mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-120



Watts : 7W*2
Dimension : 50*160*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-121



Watts : 12W*2
Dimension : 50*160*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-122



Watts : 5W*2
Dimension : 65mm*160mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-123



Watts : 5W
Dimension : 65mm*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-124



Watts : 2W*2
Dimension : 130*70*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY
SQ LENS

LL-ODW-125



Watts : 1W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY
SQ LENS

LL-ODW-126



Watts : 3W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY
SQ LENS

LL-ODW-127



Watts : 5W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR ONE WAY SQ LENS

LL-ODW-128



Watts : 1W*1
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY SQ LENS

LL-ODW-129



Watts : 3W*1
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY SQ LENS

LL-ODW-130



Watts : 5W*1
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY RD & SQ LENS

LL-ODW-131



Watts : 3W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY RD LENS

LL-ODW-132



Watts : 1W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY RD LENS

LL-ODW-133



Watts : 3W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY RD LENS

LL-ODW-134



Watts : 5W*2
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY RD LENS

LL-ODW-135



Watts : 1W*1
Dimension : 60*45*120mm:
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY RD LENS

LL-ODW-136



Watts : 3W*1
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR ONE WAY RD LENS

LL-ODW-137



Watts : 5W*1
Dimension : 60*45*120mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-138



Watts : 3W*2
Dimension : 55*110*175mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-139



Watts : 1W*2
Dimension : 55*110*175mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-140



Watts : 3W*2
Dimension : 80*50*50mm
Body Color : Gray, Black
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-141



Watts : 3W*1
Dimension : 80*50*50mm
Body Color : Gray, Black
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-142



Watts : 3W*2
Dimension : 85*70*55mm
Body Color : Gray, Black
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-142



Watts : 5W*2
Dimension : 120*60*80mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-143



Watts : 1W*2
Dimension : 70*60*55mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-144



Watts : 1W*2
Dimension : 55*40*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR ONE WAY

LL-ODW-145



Watts : 1W
Dimension : 55*40*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-146



Watts : 6W
Dimension : 100*100mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-147



Watts : 3W*2
Dimension : 105*100mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-148



Watts : 1W*2
Dimension : 48*65*80mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-149



Watts : 3W*2
Dimension : 75*105*55mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-150



Watts : 5W*2
Dimension : 95*50*110mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-151



Watts : 2W*2
Dimension : 115*35*45mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-152



Watts : 1W*2
Dimension : 135*50*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-153



Watts : 3W*2
Dimension : 140*80*65mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR TWO WAY

LL-ODW-154



Watts : 6W*2
Dimension : 140*80*65mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-155



Watts : 3W
Dimension : 80*75*65mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-156



Watts : 6W
Dimension : 80*75*65mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-157



Watts : 6W*2
Dimension : 115*90mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-158



Watts : 8W*2
Dimension : 175mm*90mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-159



Watts : 6W*2
Dimension : 160mm*100mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-160



Watts : 8W*2
Dimension : 175mm*110mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-161



Watts : 6W*2
Dimension : 160mm*100mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 3 WAY

LL-ODW-162



Watts : 1W*3
Dimension : 75*150*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR 4 WAY

LL-ODW-163



Watts : 1W*4
Dimension : 80*130*35mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 6 WAY

LL-ODW-164



Watts : 1W*6
Dimension : 80*165*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-165



Watts : 1W*2
Dimension : 60*100*50mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-166



Watts : 2W*4
Dimension : 130*80*350mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 6 WAY

LL-ODW-167



Watts : 30W*2
Dimension : 165*85*45mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 3 WAY

LL-ODW-168



Watts : 16W
Dimension : 180*25mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 3 WAY

LL-ODW-169



Watts : 3W*3
Dimension : 170*170*50mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-170



Watts : 1W*6
Dimension : 80*50*50mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-171



Watts : 1W*4
Dimension : 190*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR 4 WAY

LL-ODW-172



Watts : 3W*4
Dimension : 100*40mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-173



Watts : 1W*4
Dimension : 90*40mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-174



Watts : 1W*4
Dimension : 100*98mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-175



Watts : 3W*4
Dimension : 100*98mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-176



Watts : 1W*4
Dimension : 75*75*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-177



Watts : 3W*4
Dimension : 75*75*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-178



Watts : 1W*1
Dimension : 60*45mm
Body Color : Gray, White
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-179



Watts : 3W*1
Dimension : 60mm*45mm
Body Color : Gray, White
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-180



Watts : 3W*2
Dimension : 60mm*45mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR TWO WAY

LL-ODW-181



Watts : 3W*2
Dimension : 60mm*45mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-182



Watts : 1W*1
Dimension : 75mm*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-183



Watts : 3W*1
Dimension : 75mm*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-184



Watts : 1W*2
Dimension : 75*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR TWO WAY

LL-ODW-185



Watts : 3W*2
Dimension : 75*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-186



Watts : 1W*2
Dimension : 75*115mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-187



Watts : 3W*2
Dimension : 75mm*115mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-188



Watts : 1W*4
Dimension : 75mm*115mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 4 WAY

LL-ODW-189



Watts : 3W*4
Dimension : 75mm*115mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



OUT DOOR 6 WAY

LL-ODW-190



Watts : 1W*3
Dimension : 75*170mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 6 WAY

LL-ODW-191



Watts : 3W*3
Dimension : 75*170mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 6 WAY

LL-ODW-192



Watts : 1W*6
Dimension : 75*170mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 6 WAY

LL-ODW-193



Watts : 3W*6
Dimension : 75*170mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR ONE WAY

LL-ODW-194



Watts : 5W
Dimension : 65mm*85mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

OUT DOOR 2 WAY

LL-ODW-195



Watts : 10W
Dimension : 130mm*85mm
Body Color : Gray
CCT (K) : 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

180 DEGREE

LL-ODW-195



Watts : 6W
Dimension : 155*95mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

360 DEGREE

LL-ODW-196



Watts : 9W
Dimension : 120mm*165mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-101



Watts : 5W
Dimension : 65*110mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-CYSF-102



Watts : 7W
Dimension : 88*150mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-103



Watts : 12W
Dimension : 88*150mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-104



Watts : 18W
Dimension : 130*235mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-105



Watts : 24W
Dimension : 130*260mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-106



Watts : 30W
Dimension : 130mm*270mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-107



Watts : 40W
Dimension : 130mm*350mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-108



Watts : 5W
Dimension : 65mm*95mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-109



Watts : 7W
Dimension : 65mm*95mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-110



Watts : 12W
Dimension : 90mm*125mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-CYSF-111



Watts : 24W
Dimension : 120*230mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-112



Watts : 36W
Dimension : 120mm*290mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-CYSF-113



Watts : 5W
Dimension : 65mm*170mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-101



Watts : 7W
Dimension : 50mm*80mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-102



Watts : 7W
Dimension : 50mm*80mm
Body Color : Gray
CCT (K) : RED, GREEN, BLUE
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-103



Watts : 7W
Dimension : 50mm*80mm
Body Color : Gray
CCT (K) : RGB
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-104



Watts : 12W
Dimension : 60mm*90mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-105



Watts : 12W
Dimension : 60mm*90mm
Body Color : Gray
CCT (K) : RED, GREEN, BLUE
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-106



Watts : 12W
Dimension : 60mm*90mm
Body Color : Gray
CCT (K) : RGB
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-SPK-116



Watts : 5W
Dimension : 60*90mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-117



Watts : 5W
Dimension : 60mm*115mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-118



Watts : 7W
Dimension : 85*70*185mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-119



Watts : 5W
Dimension : 55mm*90mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-120



Watts : 7W
Dimension : 55mm*90mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-121



Watts : 10W
Dimension : 60mm*80mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-122



Watts : 12W
Dimension : 60mm*80mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-123



Watts : 15W
Dimension : 80mm*110mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-124



Watts : 20W
Dimension : 80mm*110mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-SPK-107



Watts : 7W
Dimension : 65*90*185mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-108



Watts : 12W
Dimension : 85*95*185mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-109



Watts : 7W
Dimension : 65*110*185mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-110



Watts : 12W
Dimension : 85*110*185mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-111



Watts : 6W
Dimension : 45mm*70mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-112



Watts : 12W
Dimension : 120mm*340mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-113



Watts : 8W
Dimension : 80*140*350mm
Body Color : Black
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-114



Watts : 12W
Dimension : 80*140*350mm
Body Color : Black
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-115



Watts : 6W
Dimension : 60*100*240mm
Body Color : Black
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-SPK-116



Watts : 7W
Dimension : 45*140mm
Body Color : Gray, Black
CCT (K) : 2700K, 6000K
Beam Angle : 15/36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-117



Watts : 12W
Dimension : 60*120mm
Body Color : Gray, Black
CCT (K) : 2700K, 6000K
Beam Angle : 15/36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-118



Watts : 20W
Dimension : 80*130mm
Body Color : Gray, Black
CCT (K) : 2700K, 6000K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-119



Watts : 30W
Dimension : 80*130mm
Body Color : Gray
CCT (K) : 2700K, 6000K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-120



Watts : 7W
Dimension : 45*110mm
Body Color : Gray
CCT (K) : 2700K, 6000K
Beam Angle : 15/36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-121



Watts : 12W
Dimension : 60mm*110mm
Body Color : Gray
CCT (K) : 2700K, 6500K
Beam Angle : 15/36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-122



Watts : 20W
Dimension : 80*140*350mm
Body Color : Gray
CCT (K) : 2700K, 6000K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-123



Watts : 30W
Dimension : 80*140*350mm
Body Color : Gray
CCT (K) : 2700K, 6500K
Beam Angle : 15/36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-124



Watts : 10W
Dimension : 75*80mm
Body Color : Black
CCT (K) : 2700K, 6500K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-SPK-125



Watts : 7W
Dimension : 75*80mm
Body Color : Black
CCT (K) : Green
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-126



Watts : 18W
Dimension : 95*100mm
Body Color : Black
CCT (K) : 3000K, 6500K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-129



Watts : 7W
Dimension : 75*70mm
Body Color : Gray
CCT (K) : 2700K, 6000K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPK-130



Watts : 12W
Dimension : 80*80mm
Body Color : Gray
CCT (K) : 2700K, 6500K
Beam Angle : 36/60
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-SPKB-101



Watts : 5W
Dimension : 60*100mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-102



Watts : 12W
Dimension : 76mm*135mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-103



Watts : 15W
Dimension : 89mm*175mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-104



Watts : 6W
Dimension : 60mm*90mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-105



Watts : 6W
Dimension : 60mm*90mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-106



Watts : 7W
Dimension : 65mm*90mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-107



Watts : 12W
Dimension : 85mm*95mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-108



Watts : 7W
Dimension : 65mm*110mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-109



Watts : 12W
Dimension : 85mm*110mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-SPKB-110



Watts : 7W
Dimension : 50*90mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-111



Watts : 7W
Dimension : 120mm*340mm
Body Color : Gray
CCT (K) : RED, GREEN, BLUE
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-112



Watts : 7W
Dimension : 120mm*340mm
Body Color : Gray
CCT (K) : RGB
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-113



Watts : 12W
Dimension : 60mm*90mm
Body Color : Gray
CCT (K) : 3000K, 6500K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-114



Watts : 12W
Dimension : 60mm*90mm
Body Color : Gray
CCT (K) : RED, GREEN, BLUE
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-115



Watts : 12W
Dimension : 60mm*90mm
Body Color : Gray
CCT (K) : RGB
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-116



Watts : 12W
Dimension : 70mm*130mm
Body Color : Gray
CCT (K) : 2700K, 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-SPKB-117




Watts : 18W
Dimension : 70mm*130mm
Body Color : Gray
CCT (K) : 2700K, 3000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-FTL-101



Watts : 3W
Dimension : 85*85*45mm
Cut Out : 80*80*45mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-102



Watts : 5W
Dimension : 115*85*55mm
Cut Out : 100*80*50mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-103



Watts : 4W
Dimension : 145*75*55mm
Cut Out : 135*65*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-104



Watts : 6W
Dimension : 160*100*80mm
Cut Out : 150*90*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-105



Watts : 9W
Dimension : 195*20*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-106



Watts : 5W
Dimension : 100*70*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-107




Watts : 8W
Dimension : 130*70mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-108



Watts : 3W
Dimension : 95*95*55mm
Cut Out : 105*75*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-109



Watts : 3W
Dimension : 90*60*40mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-FTL-110



Watts : 8W
Dimension : 150*70*40mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-111



Watts : 4W
Dimension : 105mm*105mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-112



Watts : 4W
Dimension : 115mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-113



Watts : 3W
Dimension : 100mm*20mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-114



Watts : 3W
Dimension : 95mm*60mm
Cut Out : 90mm*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-115



Watts : 3W
Dimension : 95mm*60mm
Cut Out : 90mm*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-116



Watts : 3W
Dimension : 85*80*45mm
Cut Out : 80*80*45mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-117



Watts : 3W
Dimension : 60mm*55mm
Cut Out : 50mm*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-118



Watts : 3W
Dimension : 60mm*55mm
Cut Out : 50mm*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-FTL-119



Watts : 3W
Dimension : 60mm*55mm
Cut Out : 50mm*55
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-120



Watts : 3W
Dimension : 46mm*80mm
Cut Out : 36mm*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-120



Watts : 3W
Dimension : 46mm*80mm
Cut Out : 36mm*80mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-121



Watts : 3W
Dimension : 50mm*70mm
Cut Out : 45mm*70mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-122



Watts : 6W
Dimension : 120mm*340mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-123



Watts : 2W
Dimension : 115*115*60mm
Cut Out : 110*110*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-123



Watts : 4W
Dimension : 170*115*60mm
Cut Out : 160*110*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-124



Watts : 8W
Dimension : 180*120*75mm
Cut Out : 170*110*75mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-125



Watts : 6W
Dimension : 225*115*60mm
Cut Out : 220*110*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-FTL-126



Watts : 12W
Dimension : 225*115*60mm
Cut Out : 220*110*60mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-127



Watts : 3W
Dimension : 140*70*60mm
Cut Out : 130*65mm
Body Color : Gray, White
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-128



Watts : 6W
Dimension : 140*70*60mm
Cut Out : 130*65mm
Body Color : White, Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-129



Watts : 4W
Dimension : 200*90*35mm
Body Color : Gray, White
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-130



Watts : 8W
Dimension : 200*90*35mm
Body Color : Gray, White
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-131



Watts : 3W
Dimension : 125*125*40mm
Cut Out : 110*110mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-132



Watts : 3W
Dimension : 125mm*40mm
Cut Out : 110*mm*40
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-133



Watts : 3W
Dimension : 85mm*50mm
Cut Out : 65mm*50mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-134



Watts : 3W
Dimension : 85*85*45mm
Cut Out : 70*70*45mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

Architectural Outdoor Lights



LL-FTL-135



Watts : 4W
Dimension : 130*55*30mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-136



Watts : 8W
Dimension : 170*60*30mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-137



Watts : 6W
Dimension : 145*70*55mm
Cut Out : 135*65*55mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-138



Watts : 3W
Dimension : 210mm*50mm
Cut Out : 185*35*45mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-139



Watts : 3W
Dimension : 100*60*50mm
Cut Out : 95*50*50mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-140



Watts : 6W
Dimension : 210*60*50mm
Cut Out : 200*55*50mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-141



Watts : 5W
Dimension : 90*90*70mm
Cut Out : 75*75*70mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-142



Watts : 5W
Dimension : 90mm*70mm
Cut Out : 75mm*70mm
Body Color : Gray
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

LL-FTL-143



Watts : 5W
Dimension : 60mm*20mm
Body Color : Black
CCT (K) : 2700K, 6000K
IP Rating : IP65
CRI : >90
Powered : CREE
Luminous : 80lm/Watt
Driver : 4kv Constant current Driver
Material : Dia-casting Aluminum

BURIAL LIGHT 230V/AC COB MODEL



- Model :- LLIGB101
- Watts :- 1W
- Dimension :- Ø45*70Hmm
- Cut Out :- 60MM
- Power By :- Cree , Bridgelux
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC COB MODEL



- Model :- LLIGB102
- Watts :- 3W
- Dimension :- Ø45*70Hmm
- Cut Out :- 60MM
- Power By :- Cree , Bridgelux
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 24V/DC COB MODEL



- Model :- LLIGB103
- Watts :- 3W
- Dimension :- Ø45*70Hmm
- Cut Out :- 60MM
- Power By :- CREE , BRIDGLUX
- CCT :- RGB
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB104
- Watts :- 3W
- Dimension :- 100*90mm
- Cut Out :- 95mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 24V/DC



- Model :- LLIGB105
- Watts :- 3W
- Dimension :- 100*90mm
- Cut Out :- 95mm
- Power By :- CREE , BRIDGLUX
- CCT :- RGB
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB106
- Watts :- 6W
- Dimension :- 120*90mm
- Cut Out :- 115mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 24V/DC



- Model :- LLIGB107
- Watts :- 6W
- Dimension :- 120*90mm
- Cut Out :- 115mm
- Power By :- CREE , BRIDGLUX
- CCT :- RGB
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB108
- Watts :- 9W
- Dimension :- 150*90mm
- Cut Out :- 125mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 24V/DC



- Model :- LLIGB109
- Watts :- 9W
- Dimension :- 150*90mm
- Cut Out :- 125mm
- Power By :- CREE , BRIDGLUX
- CCT :- RGB
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB110
- Watts :- 12W
- Dimension :- Ø180*90Hmm
- Cut Out :- 155mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 24V/DC



- Model :- LLIGB111
- Watts :- 12W
- Dimension :- Ø180*90Hmm
- Cut Out :- 155mm
- Power By :- CREE , BRIDGLUX
- CCT :- RGB
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB112
- Watts :- 3W
- Dimension :- Ø130*140Hmm
- Cut Out :- 120mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 15°, 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB113
- Watts :- 9W
- Dimension :- Ø180*190Hmm
- Cut Out :- 170MM
- Power By :- Cree , Bridgelux
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°
- Lumens :- 90lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC



- Model :- LLIGB114
- Watts :- 27W
- Dimension :- Ø260*270Hmm
- Cut Out :- 270MM
- Power By :- Cree , Bridgelux
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°
- Lumens :- 90lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC COB MODEL



- Model :- LLIGB115
- Watts :- 3W
- Dimension :- Ø45*70Hmm
- Cut Out :- 40mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS + ABS

BURIAL LIGHT 230V/AC COB MODEL



- Model :- LLIGB116
- Watts :- 7W
- Dimension :- Ø95*100Hmm
- Cut Out :- 85MM
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS + ABS

BURIAL LIGHT 230V/AC COB MODEL



- Model :- LLIGB117
- Watts :- 12W
- Dimension :- 115*110mm
- Cut Out :- 105mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS + ABS

BURIAL LIGHT 230V/AC PATH WAY ONE SIDE



- Model :- LLIGB118
- Watts :- 1W
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC PATH WAY ONE SIDE



- Model :- LLIGB118
- Watts :- 3W
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC PATH WAY ONE SIDE



- Model :- LLIGB118
- Watts :- 5W
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC PATH WAY TWO SIDE



- Model :- LLIGB119
- Watts :- 1W*2
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC PATH WAY TWO SIDE



- Model :- LLIGB119
- Watts :- 3W*2
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC PATH WAY THREE SIDE



- Model :- LLIGB120
- Watts :- 1W*3
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

BURIAL LIGHT 230V/AC PATH WAY FOUR SIDE



- Model :- LLIGB121
- Watts :- 1W*4
- Dimension :- 85*90mm
- Cut Out :- 75mm
- Power By :- CREE , BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 30°
- Lumens :- 80lm/W
- Material :- Aluminum + PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF3W-SS
- Watts :- 3W
- Dimension :- 85*140mm
- Power By :- Cree, Bridgelux
- CCT :- 3K, 4K, 6K,
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF3W-SS
- Watts :- 3W
- Dimension :- 85*140mm
- Power By :- Cree, Bridgelux
- CCT :- RGB, RGBW
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF6W-SS
- Watts :- 6W
- Dimension :- 120*140Hmm
- Power By :- CREE, BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF6W-SS
- Watts :- 6W
- Dimension :- 120*140Hmm
- Power By :- CREE, BRIDGLUX
- CCT :- RGB, RGBW
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF9W-SS
- Watts :- 09W
- Dimension :- 145*180mm
- Power By :- CREE, BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF9W-SS
- Watts :- 09W
- Dimension :- 145*180mm
- Power By :- CREE, BRIDGLUX
- CCT :- RGB, RGBW
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF12W-SS
- Watts :- 12W
- Dimension :- 160*215mm
- Power By :- CREE, BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUF12W-SS
- Watts :- 12W
- Dimension :- 160*215mm
- Power By :- CREE, BRIDGLUX
- CCT :- RGB, RGBW
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC




- Model :- LLUNF3W
- Watts :- 3W / 9W
- Dimension :- 125mm*50mm
- Thread ID :- 1.5"
- Power By :- CREE, BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC




- Model :- LLUNF3W
- Watts :- 3W / 9W
- Dimension :- 125mm*50mm
- Thread ID :- 1.5"
- Power By :- CREE, BRIDGLUX
- CCT :- RGB, RGBW
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUNF6W
- Watts :- 6W / 18W
- Dimension :- 125mm*50mm
- Thread ID :- 1.5"
- Power By :- CREE, BRIDGLUX
- CCT :- 3K, 4K, 6K
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

FOUNTAIN LIGHT 24V/AC/DC



- Model :- LLUNF3W
- Watts :- 6W / 18W
- Dimension :- 125*50mm
- Thread ID :- 1.5"
- Power By :- CREE, BRIDGLUX
- CCT :- RGB, RGBW
- IP Rating :- IP65 / IP68
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 80lm/W
- Material :- SS 303/ 304, PC

Architectural Wall Washer Lights



- Model :- LLWWL 101
- Watts :- 12W
- Dimension :- 300*45*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB, RGBWW
- IP Rating :- IP65
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 102
- Watts :- 24W
- Dimension :- 600*45*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB, RGBWW
- IP Rating :- IP65
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 103
- Watts :- 36W
- Dimension :- 900*45*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB, RGBWW
- IP Rating :- IP65
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 104
- Watts :- 45W
- Dimension :- 1200*45*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB, RGBWW
- IP Rating :- IP65
- Beam Angle :- 10°, 30°, 40°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 105
- Watts :- 6W
- Dimension :- 160*55*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 106
- Watts :- 12W (RGB - 20W)
- Dimension :- 300*55*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 107
- Watts :- 18W (RGB - 30W)
- Dimension :- 500*55*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 108
- Watts :- 36W (RGB - 50W)
- Dimension :- 1000*55*50mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 109
- Watts :- 12W (RGB - 20W)
- Dimension :- 160*75*70mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 110
- Watts :- 25W (RGB - 30W)
- Dimension :- 300*75*70mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 111
- Watts :- 36W (RGB - 50W)
- Dimension :- 500*75*70mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 112
- Watts :- 70W, 100W
- Dimension :- 1000*75*70mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc



- Model :- LLWWL 113
- Watts :- 12W
- Dimension :- 300*70*45mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Glass



- Model :- LLWWL 114
- Watts :- 24W
- Dimension :- 600*70*45mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Glass



- Model :- LLWWL 115
- Watts :- 36W
- Dimension :- 900*75*70mm
- Power By :- 3030 Osram
- Input Voltage :- 24V/DC, 230V/AC
- CCT :- 3K, 4K, 6K, RGB,
- IP Rating :- IP65
- Beam Angle :- 36°, 45°
- Lumens :- 90lm/W
- Material :- Aluminum + Pc

SMALL, MEDIUM, BIG SIZE

- Model :- LLWL101
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



SMALL, MEDIUM, BIG SIZE

- Model :- LLTP162
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



SMALL, BIG SIZE

- Model :- LLWL103
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



SMALL, MEDIUM, BIG SIZE

- Model :- LLWL104
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



SMALL, BIG SIZE

- Model :- LLWL105
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL106
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL107
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL108
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL109
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL110
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL111
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL112
- Wattage :- E27 - 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL113
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL114
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL115
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL116
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL117
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL117
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL118
- Wattage :- 12W*2WAY
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL120
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



Architectural Outdoor Lights



WALL LIGHT

- Model :- LLWL121
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL122
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL123
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



WALL LIGHT

- Model :- LLWL124
- Wattage :- 12W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP101
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP102
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP103
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP104
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP105
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP106
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP107
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP108
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP109
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP110
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP111
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP112
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP113
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP114
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP115
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP116
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP117
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP118
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP119
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP120
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP121
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP122
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP123
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP124
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP125
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP126
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP127
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP128
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP129
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP130
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP131
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP132
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP133
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP134
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP135
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP136
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP137
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP138
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP139
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP140
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP141
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP142
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP143
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP144
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP145
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP146
- Wattage :- 12W to 50W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP147
- Wattage :- 12W to 50W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP148
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP149
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP150
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP151
- Wattage :- 50W to 100W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP152
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

BIG SIZE & SMALL SIZE

- Model :- LLTP153
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

BIG SIZE & SMALL SIZE

- Model :- LLTP154
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP155
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP156
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

BIG SIZE & SMALL SIZE

- Model :- LLTP157
- Wattage :- E27, 12W, 15W
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP158
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

- Model :- LLTP159
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

SMALL, MEDIUM, BIG SIZE

- Model :- LLTP160
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

SMALL, MEDIUM, BIG SIZE

- Model :- LLTP161
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

SMALL, MEDIUM, BIG SIZE

- Model :- LLTP162
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

SMALL, BIG SIZE

- Model :- LLTP163
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated



CUSTOMIZE FITTING

SMALL, MEDIUM, BIG SIZE

- Model :- LLTP164
- Wattage :- E27
- Chip Brand :- CREE , BRIDGLUX
- CCT :- 3000K, 4000K, 6500K
- IP Rating :- IP65
- Lifetime :- 50,000hrs
- Dia Size :- As Per Requirement
- Material :- Aluminum & M.S Powder Coated

