

| Picture   | Size(MM)                          | Angle (°C) | Material                   | Voltage (V) | Power (W) | Luminous (LM/W) | Color |
|---|-----------------------------------|------------|----------------------------|-------------|-----------|-----------------|-------|
|    | 90MM<br>Opening: 65*H5<br>2MM     | 15°C       | Aluminum<br>+<br>Reflector | AC220V      | 3W        | 90-100          | W/WW  |
|   |                                   |            |                            |             | 5W        |                 |       |
|   | 110MM<br>Opening: 85*H5<br>5MM    | 15°C       | Aluminum<br>+<br>Reflector | AC220V      | 7W        | 90-100          | W/WW  |
|   |                                   |            |                            |             | 9W        |                 |       |
|  | 140MM,<br>Opening: 120*H<br>80MM  | 15°C       | Aluminum<br>+<br>Reflector | AC220V      | 20W       | 90-100          | W/WW  |
|   | 160MM,<br>Opening: 140*H<br>90MM  |            |                            |             | 24W       |                 |       |
|  | 165MM,<br>Opening: 150*H<br>175MM | 24°C       | Aluminum<br>+<br>Reflector | AC220V      | 30W       | 90-100          | W/WW  |
|   | 166MM,<br>Opening: 150*H<br>160MM |            |                            |             | 15W       |                 |       |

STALWART