



# 2019 CFMOTO ZFORCE 500 HO/HO EPS LX



STARTING AT  
**\$9,999\***

**Best 5 Year  
(LIMITED)  
Warranty\*\***

**CFMOTO.CA**   

**WIND  
ZONE**   
**windzone.ca**

\*Plus PDI, freight and applicable taxes. Photos are for illustrative purposes only and any accessories shown are not included. Roof accessory not included. Subject to change without notice. Details in store. \*\*5 Year limited warranty: 1 year full + balance 48 months powertrain only or 5,000-km.

# 2019 CFMOTO ZFORCE 500 HO/HO EPS LX



**Best 5 Year  
(LIMITED)  
Warranty\*\***

■ NEBULA BLACK  
■ ORANGE

## STANDARD FEATURES AND BENEFITS

### SAFETY

Passenger hold bar | Lateral mirrors | Horn  
ROPS certified Roll Cage | Hand brake  
Halogen hi & low beam | Hazard lights | Flashers

### LOOK

High quality graphics | Premium glossy paint | 2 color seats

### CONVENIENCE

Trailer connector | Adjustable & lockable steering | Cup holders  
Storage under hood | Glove compartment | Cargo bin with net  
Hitch receiver | 12V plug | LX model: Winch (3000 lbs)

### DURABILITY

Skid plate | Stainless steel exhaust system | Steel bumpers

### LCD DASHBOARD

Digital information center with brightness control, KM/MPH  
odometer and a multi-function gauge: RPM, speed, tachometer,  
gear position, temperature, engine light, fuel level, hour meter  
and a clock.

**PLUS VALUE  
OF \$2,199**

## ENGINE

TYPE	Single-Cylinder, 4-valve
DISPLACEMENT	495 cc
BORE & STROKE	91 x 76.2 mm (3.6 x 3 in)
COMPRESSION	10.3 : 1
ENGINE MANAGEMENT	BOSCH EFI & Ignition
MAXIMUM TORQUE	31.7 FT/LB @ 5800 rpm
MAXIMUM POWER OUTPUT	37.5 HP / 6800 rpm
COOLING SYSTEM	Liquid
STARTING	Electric
BATTERY	Yuasa, 30 Amp

## SIZE / WEIGHT

LENGTH x WIDTH x HEIGHT	2870 x 1310 x 1770 mm (113 x 51.6 x 69.7 in)
WHEELBASE	2040 mm (80.3 in)
SEAT HEIGHT	395 mm (15.6 in)
GROUND CLEARANCE	287 mm (11.3 in)
FUEL TANK CAPACITY	27 L (7.1 gal)
CURB WEIGHT	577 kg (1272 lb) / LX model: 587 kg (1294 lbs)
TOWING CAPACITY	To come
REAR BOX CAPACITY	100 kg (220 lbs)

## TRANSMISSION

CV-TECH IBC clutch system	Primary and secondary variable transmission Gear box: L / H / N / R / P (parking lock shift system)
POWER TRAIN	2 wheel / 4 wheel drive, electric locking differential



## WHEELS

FRONT WHEELS	Aluminium black rims (14 x 7 in)
REAR WHEELS	Aluminium black rims (14 x 8 in)
FRONT TIRES	AT 26 x 9-14 (ABUZZ CST 6 ply rating)
REAR TIRES	AT 26 x 11-14 (ABUZZ CST 6 ply rating)

## SUSPENSION AND STEERING

FRONT SUSPENSION	Double wishbone independent suspension Gas shock absorber with separate adjustable rebound & compression
TRAVEL	198 mm (7.8 in)
REAR SUSPENSION	Double wishbone independent suspension Gas shock absorber with adjustable rebound/compression
TRAVEL	165 mm (6.5 in)
STEERING	Rack and pinion / LX model: Rack and pinion, Electronic Power Steering (EPS)

## BRAKES

FRONT AND REAR BRAKE DISC SYSTEM

